

SuperView-Library ii

COLLABORATORS			
TITLE : SuperView-Library			
ACTION	NAME	DATE	SIGNATURE
WRITTEN BY		April 13, 2022	

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

SuperView-Library iii

Contents

1	Supe	erView-Library	1
	1.1	SuperView Library Documentation	1
	1.2	Copyright	3
	1.3	Disclaimer	5
	1.4	Distribution	5
	1.5	Abilities, Purposes and much more	7
	1.6	Making use of 680x0 CPUs and PPC accelerators	7
	1.7	PowerPC (powerUP) support	10
	1.8	Installation and Configuration	12
	1.9	Overview of currently available SVObjects	16
	1.10	Overview of currently available Device SVObjects	20
	1.11	Overview of currently available SVDrivers	20
	1.12	Overview of currently available SVOperators	22
	1.13	Software supporting SuperView-Library	24
	1.14	superviewnote	25
	1.15	sqopalnote	26
	1.16	superloadernote	26
	1.17	imageengineernote	26
	1.18	picmanagernote	27
	1.19	drafunote	28
	1.20	genesisnote	28
	1.21	And thanks for all the fish:	29
	1.22	How to contact the author	32
	1.23	The future of SuperView-Library	33
	1.24	Known bugs and suggestions for workarounds	34
	1.25	Harddisk MaxTransfer Problem	34
	1.26	Problems with specific applications	35
	1.27	History	38
		Printer.svobject	
	1.29	Scanner.svobject	49

SuperView-Library iv

1.30	AmiFIG.svobject	51
1.31	Degas.svobject	52
1.32	ILBM.svobject	53
1.33	PBM.svobject	54
1.34	ACBM.svobject	55
1.35	Datatypes support	55
1.36	PCX.svobject	56
1.37	Spectrum.svobject	57
1.38	SVG.svobject	58
1.39	The SVG Graphics File Format Specification	59
1.40	GPlot.svobject	60
1.41	BMP.svobject	62
1.42	AmiIcon.svobject	63
1.43	WinIcon.svobject	65
1.44	FBM.svobject	65
1.45	Limbo.svobject	66
1.46	PNM.svobject	69
1.47	PNG.svobject	70
1.48	C64.svobject	72
1.49	CDR.svobject	73
1.50	CVP.svobject	74
1.51	IMG.svobject	74
1.52	TIFF.svobject	75
1.53	EPS.svobject	77
1.54	WinIcon.svobject	78
1.55	TIM.svobject	79
1.56	GhostScript.svobject	80
1.57	Targa.svobject	83
1.58	MetaView.svobject	85
1.59	WPG.svobject	87
1.60	SunRaster.svobject	88
1.61	SGI.svobject	88
1.62	PICT.svobject	89
1.63	Pictor.svobject	90
1.64	MAC.svobject	91
1.65	JPEG.svobject	92
1.66	PCD.svobject	94
1.67	FastILBM24.svobject	96
1.68	YUVN.svobject	96

SuperView-Library v

1.69 DEEP.svobject
1.70 FAXX.svobject
1.71 RGB8.svobject
1.72 RGFX.svobject
1.73 QRT.svobject
1.74 C-Source.svobject
1.75 UXFormats
1.76 ECS.svdriver
1.77 AGA.svdriver
1.78 Window.svdriver
1.79 CgxOverlay.svdriver
1.80 CyberGraphics.svdriver
1.81 EGS7.svdriver
1.82 Picasso96.svdriver
1.83 PicassoII.svdriver
1.84 OPAL.svdriver
1.85 Retina.svdriver
1.86 MERLIN.svdriver
1.87 XOR.svoperator
1.88 24BitToHAM.svoperator
1.89 Blur.svoperator
1.90 Crop.svoperator
1.91 Dither24Bit.svoperator
1.92 HilbertDither256.svoperator
1.93 AnyTo24Bit.svoperator
1.94 ExtractGrayScales
1.95 ExtractRed
1.96 ExtractGreen
1.97 ExtractBlue
1.98 TopToBottom
1.99 LeftToRight
1.100Rotate
1.101RotateFree
1.102Scale50
1.103 Sharpen.svoperator
1.104CallPNM
1.105OptimizePalette
1.106PaletteDither.svoperator
1.107Requirements for the SuperView-Library Package

SuperView-Library vi

1.108NotesAndHints
1.109Memory Usage
1.110Displaying 24 bit graphics
1.111Converting 24 bit graphics
1.112SVPrefs
1.113SuperViewSupport-Library
1.114SuperView in the Press
1.115Books and other written stuff used during development
1.116Overview: Other Program Projects
1.117Credits
1.118ControlPad Fileformat
1.119CPInfo Fileformat
1.120ControlDod Overview

SuperView-Library 1 / 174

Chapter 1

SuperView-Library

1.1 SuperView Library Documentation

```
superview.library V22.2
```

- Freeware (Licenseware) - product-specific Licenseware

Any usage from and by other programs without an explicite license is strictly forbidden (see "Distribution").

Ask for licenses.

© 1993-99 by Andreas R. Kleinert. All rights reserved.

A PerSuaSiVe SoftWorX PRODUCT.

This program has been written under OS V3.1 and is therefore fully compatible. It needs OS V2.04+.

Actively supports PowerPC (TM) via powerUP (TM) and ppc.library.

Release Date: 20.02.1999

If you at first don't succeed, call it a public beta version...

Legal

Copyrights and legal stuff

Disclaimer

Distribution

Usage

Short: Purpose and Abilities

Requirements

Installation

68020-060/PPC support

SuperView-Library 2 / 174

```
Making use of fast CPUs
                       PowerPC (powerUP) support
What can be expected ?
                               Contact
How to contact the author
                              Archive
History
SVObject Descriptions/History
Device SVObject Descriptions/History
SVDriver Descriptions/History
SVOperator Descriptions/History
Support-Library Description/History
                            Various Topics
Supporting Software
Known bugs and workarounds
Notes and Hints
Possible future enhancements ...
Credits and even more legal stuff
Thanks and Greetings
SuperView in the Press
Bibliography
More Projects
                       ControlPad Preferences
Preferences
ControlPad Fileformat
CPInfo Fileformat
ControlPad enlistment
                   External Links in this Directory
         German ReadMe File
     Only \X/ Amiga makes it possible!
```

SuperView-Library 3 / 174

Please visit:

SuperView WWW Sites
http://home.t-online.de/home/Andreas_Kleinert/
http://wdo.de/ark/

Simon Edward's Image Engineer WWW Site http://www.amigaworld.com/support/imageengineer/ (Image Processing program produced by Simon Edwards)

Die CHAOS-Theorie:

"Dabei geht es zum Beispiel darum, den verdammten Schmetterling zu finden, dessen Flügelschläge die vielen Stürme in letzter Zeit verursacht haben." (Terry Pratchett in "Total verhext")

In English means something like:

The CHAOS theory:

"Like finding that bloody butterfly whose flapping wings cause all these storms we've been having lately and getting it to stop." (see "Witches Abroad" by Terry Pratchett)

Ahm...well:

...and thanks for all the fish.

1.2 Copyright

The superview.library and the distributed files - e.g. the \leftrightarrow documentation

files - are (C)opyright 1993-99 by Andreas R. Kleinert. All rights reserved.

(For some files there may additional or substitutive Copyrights take place, which then are stated locally within the documentation or via local reference to "Credits".)

The following usage and license conditions are announced for all parts of the distribution, which means SVObjects, SVDrivers, SVOperators and all other files.

When refering to the whole program package as such, it is called "SuperView-Library".

The usage and distribution of SuperView-Library takes place under the concept of product-specific Freeware (Licenseware).

SuperView-Library 4 / 174

For more details on distribution rules and developers restrictions, you have to see paragraph "Distribution".

Please note:

- * Should any of the listed terms and clauses within this document not be valid in conjunction with the law of certain countries this does not affect the validity of the other clauses.
- * Some of the mentioned names or products within this or other documents may be copyrighted by companies or trademarks of companies or persons.
- * This software is based in part on the work of the Independent JPEG Group (concerning JPEG.svobject).
- * The "xpkmaster.library" (part of the useful Xpk package, which can be found on Aminet) is developed under the concept of the GNU license by its authors, c/o Dirk Stöcker <stoecker@rcs.urz.tu-dresden.de>
 This freely distributable Library is needed by SVG.svobject, Unpack.svobject and and RGFX.svobject to read and decode XPK-packed files.
- * The "newicons.library" (part of the useful NewIcons package, which can be found on Aminet) is developed by the 'Team NewIcons', c/o
 Eric Sauvageau <merlin@thule.no> and Phil Vedovatti <vedovatt@u.washington. ←
 edu>

This library is needed by Amilcon.svobject to read/write Newlcons.

GIF is obsolete - you neither should use nor support it any longer. If you are doing WWW design, use PNG and JPEG instead. It's important!

This software was translated with the help of ATO, the Amiga Translators' Organization. ATO is a non-profit organization that translates for the Amiga community!

Finnish : Mika Lundell <c71829@uwasa.fi>
Linus Silvander <linus@icenet.fi>

Serbian : Ljubomir Jankovic <lurch@afrodita.rcub.bg.ac.yu>
Andrija Antonijevic <antony@oreska.dv.co.yu>

French : Julien Wilk <wilkj@esiee.fr>

Pascal Rullier <rullier@triade.fr>

Español : Dámaso D. Estévez <amidde@arrakis.es>

SuperView-Library 5 / 174

Amiga Translators' Organization: http://www.vapor.com/ato mail: ato-info@ato.vapor.com

(Also see

Thanks and Greetings for more information on translation issues and translators.)

1.3 Disclaimer

The author takes no responsibility for any results of the use of this program.

This software is provided "AS IS" and there is no warranty of any kind, so that you use this software at your own risk.

The author reserves the right to discontinue development of the program.

1.4 Distribution

Distribution in Common

The Library must not be distributed isolated, detached from any specific program package, whose author has licensed the library.

If the licensed library is included within the licensing program's program distribution, the distribution conditions of this program take place as long as these do not explicitly contradict to the disposals described in the following text.

Licensed programs are not restricted to have any special legal copying conditions, so the Library may appear together with any form of Software, like e.g. Freeware, Shareware or commercial programs, perhaps with exception of "pure" Public Domain.

Restrictions

~~~~~~~~~~~

The program SuperView-Library in this version is product-specific Freeware (Licenseware), which at first means, that a single distribution of the Library is as well forbidden as an unauthorized distribution together with programs of non-licensees.

Also, the Library MUST not:

- be included into other program's distributions without my explicitely written permission
- be copied as a single package without being directly related to a specific program
- without a license be copied and also not be used directly or - via any tricks - indirectly

SuperView-Library 6 / 174

#### Licensing

~~~~~~~

There is no way of automatic licensing via "agree-to-the-above-terms". Any license has to be given in written, non-electronic form. Interim-licenses may be promised via phone, email, etc but have to be confirmed in paper form.

The only one, who is authorized to write and send licenses or promise licensing is the author of SuperView-Library, which is Andreas R. Kleinert.

If you want to license the library, please send me the following information:

STATUS - what's the status of your planned or actually existing program ?

Main categories are Freeware, Shareware, Commercial.

WHO - what's your (or your companies') name, address and
 phone number, maybe also email address ?

WHAT - what kind is your program of ?

Not any programmer of any kind of program will get a licence.

I am not going to support programs, which may concern

my vital interests by being direct competitors of

other programs where I am involved as a participator,

depending on the success of the programs. [;-)]

On the other hand there are various ways to synchronize

programming efforts and to come to a solution, which

is acceptable for both sides.

PLANS - according to the type of your program you might also tell me something about your plans for future versions of the program as long as it does concern a fundamental change in the program's concept and function (competitor)

 $\mbox{SAMPLE}\ -\mbox{would}$ be nice to see a copy of the previous, beta or final version of the program

PAYMENT - are you gonna pay for the licence ?

Freeware authors will not have to pay anything, if they get a license. Shareware authors might. Commercial programs will perhaps.
Tell me what you think, then we'll talk about it.

Tell me what you think, then we'll talk about it. Fees aren't expensive in my opinion.

After Licensing

~~~~~~~~~~~~~~~

Each license is specific to the licensee and his wishes.

Common to all licensees is the following:

- The Right to use the unmodified library within the

SuperView-Library 7 / 174

- program or program-group it has been licensed for
- Access to not publicly documented functions
- The Right to distribute the library together with your program
- The Right to integrate the library into the concept of your program as long as no basic parts have to be changed
- The Obligation to respect the distribution conditions and to add a ReadMe file and documentation remark reflecting this to the program
- The Obligation to send me a copy of the final, registered or register-able version of the program using SuperView-Library

If there are more questions, please don't regret to ask me, because just asking doesn't cost you anything.

I may as well tell you, which programming languages currently are directly supported (C of course always).

# 1.5 Abilities, Purposes and much more

The "SuperView-Library" consists of many functions and sub-  $\hookleftarrow$  libraries,

which allow quick and easy displaying, saving, converting and processing of various picture formats, like IFF-ILBM, JPEG, PCX, Targa, PCD TIFF, PNG, BMP, ... (more than 50 altogether).

It has been designed for the purpose to display and process any common type of bitmap graphics as fast and as comfortable as possible on almost any Amiga hardware configuration.

External Loader-/Saver-Libraries (SVObjects), Graphic Card Drivers (SVDrivers) and various Operators (SVOperators) allow easy but flexible configuration, usage and expansion.

Programming documentation is available for license-takers, only.

Feature Overview

Recognized file graphic formats

Supported graphic cards and display adapters

Supported input/output devices

Available image processing operators

#### 1.6 Making use of 680x0 CPUs and PPC accelerators

SuperView-Library 8 / 174

Basically, this program does run with a plain 68000 CPU.

However, if you do own an 68020/030+68881/882 FPU or 68040/060+FPU, or maybe a dual processor board with PPC, you may wish to make use of the extra horse power.

There are certain configuration options, special libraries and/or patches available, so you perhaps should investigate into that issue a little bit deeper - but carefully.

#### PPC Support

#### \_\_\_\_\_

- 1. With CyberStorm PPC cards, it may make sense to make use of the "SetFastAvec" and "Set60nsMode" (SetMemMode) tools, which should speed up the system performance somewhat, i.e. by addressing your RAM with 60ns instead of 70ns access time. Newer versions allow to do these settings fromout the card's bootmenu. If you get random crashes, step back to 70ns.
- 2. Make sure, that you have a lot of RAM on the accelerator, so that the PPC isn't forced to make accesses to the slow motherboard RAM. If you get random crashes, make sure you followed the installation instructions, and did not configure SIMMs of different vendors for a 64 bit access bank.
- 3. This program does make use of "ppc.library". So:
   Make sure, that you a) don't have "powerpc.library" installed or b) have a version of "powerpc.library" installed, which does not conflict with "ppc.library" (V7 is said to work together with ppc.library). Don't install ppc.library without having a PPC board plugged in. Always make use of the newest 68040/68060.library plus ppc.library as available under ftp.phase5.de or Aminet.
  - (There's BTW now indirect support for powerpc.library V14 as well, so you can decide. It should work to run the PPC-Library versions under Frank Wille's ppc.library emulation for WOS.)
- 4. Read the corresponding FAQ pages for more information on PPC support and configuration - especially note, that a keyfile is required for fully functional PPC support within this datatype.

# 68020/030+68881/882 FPU and 68040/060+FPU Support

Usually, Amiga OS' mathieee-Libraries do automatically manage the coprocessor support, but for some reasons, these libraries are not used with this datatype:

- they can't be shared between processes
- they are not actually optimized for 68040/060+FPU as with OS 3.1

SuperView-Library 9 / 174

Unfortunately, the used FFP libraries don't support an FPU at all.

But there are certain patches available on Aminet, to speed up FPU support in general, add FPU support for the FFP libraries or in general allow more efficient use of the 040/060 CPUs, e.g. by avoiding unnecessary emulation of missing instructions through 68040/68060.1ibrary.

Make sure, that those patches don't conflict with certain versions of the 680x0 libraries or even are part of these already. If you've carefully read the docs you may wish to check out the following solutions:

1. Fix bugs within the math libraries

This one has nothing to do with the FFP libraries, but since there's also a bug in mathieeesingbas.library (which resides in ROM), you should install a patch for that:

- a) best solution is a newer SetPatch Version V43.x (available from ftp.amiga.de somewhere in "/pub/")
- b) if SetPatch V43 does not work with your OS version, you should try for example "SetMathPatch" (coming e.g. with GhostScript - see Aminet:gfx/show)

Those patches may conflict with some math library replacements — it seems to be logically, that a completely rewritten replacement library of course does not need to be patched any further. At least not for the same bugs...

- 2. Patching the math#? libraries for better (or introducing)
   FPU support:
  - a) FMath V40.6 Aminet:util/libs/FMath406.LHA
     FFPPatch Aminet:util/boot/ffppatch.lha
  - b) HSMathLibs Aminet:util/libs/HSMathLibs\_040.lha
    Aminet:util/libs/HSMathLibs\_060.lha
  - c) various other patches from the "util" area of Aminet

With the 68040/68060.libraries of p5, according to their docs, further patches of the math libraries are not recommended - however may work nevertheless.

3. General 040/060 speedup

For automatic speedup on 68020+ systems, this datatype makes use of utility.library.

This one has nothing to do with the FPU, but if you do own a 060 and OS 3.0 you should perhaps consider to install "Mult64Patch", which claims to implement the 64 bit integer functions UMult64/SMult64 of utility.library V39+ (which have

SuperView-Library 10 / 174

to be software emulated on the 060) two times faster than the patches done by 68060.library and four times faster than the trap emulation. A speed test program is included.

That program can be found under Aminet:util/boot/Mult64Patch.lha - however, it may already be obsolete for newer versions of your 68060.library. Do the speed check, then decide.

4. Better performance on 680x0 and PPC

Here, the following tools work quite fine on a 040/PPC board (taken in this oder from s:startup-sequence):

```
REBOOT
C:SetPatch QUIET
C:QuickRom >NIL: <NIL:</pre>
C:CMQ060 >NIL: <NIL:
Run >NIL: <NIL: C:CpuBlit</pre>
                         -> various speedups
FastExec V2.9 (Aminet)
SetPatch V43.6b (www.amiga.de) -> OS patches
QuickRom V36.08 (Aminet) -> ROM to RAM
                         -> optimizes CopyMem(Quick)
CMQ 1.2
           (Aminet)
                        -> let the CPU do blitting
CpuBlit98
            (Aminet)
```

This all runs fine in 60ns mode, together with SetFastAvec, PPCInstall and CyberGraphX V3.

# 1.7 PowerPC (powerUP) support

Concept: loadable PPC-Modules for use with ppc.library V45+ (17.11.98)

The most time-consuming routines of certain modules of SuperView-Library have been ported to native PowerPC code and perhaps will profit a lot from the presence of an installed powerUP system.

These "native modules" are located in a new subdirectory of LIBS: called "svppc/", with subdirectories for each of SuperView-Library's module types.

If any "native modules" are present, these will be used whenever applicable. Should none of these modules be available, then this does not matter, since the plain 68k code (which may be optimized for a certain 68k CPU, though) will be used instead (fallback option).

Note, that SuperView-Library's native modules won't replace any of the existing libraries or modules as such - they only do supply specialized routines in native code for certain tasks.

When running any PowerPC code, you should have made sure, that there's enough RAM on the powerUP board available - at least in an A4000 the RAM interface from the CPU card (e.g. A3640) to the mainboard is so slow, that even a 68040 could not access Fast RAM with full speed,

SuperView-Library 11 / 174

so possibly a PowerPC would suffer from the same problem.

You should take care, that there's still enough "fast" Fast RAM available, even if all the libraries and code have been loaded: usually the graphics are loaded at last - a 1024x768 graphics in 24 Bit will just take 2.4 MB and in a dithered version again around 790 K.

If there's enough "fast" Fast RAM available, you can expect high speed increases with most basic operations, especially when internal representation conversions do take place.

(See the documentation of the single modules for further information. PowerUP support usually is marked separately, on top of the module documentation.)

#### Availability

-----

NONE OF THE PPC MODULES ARE FREEWARE - THEY WON'T APPEAR ON AMINET.

54 modules (+/-) are made available in a special powerUP PPC plugin module package, which e.g. can be bought by registered SuperView/SViewNG/SViewII users or will be included with some commercial programs.

Also, there will follow some PPC modules, which will only be available for exclusive shipment with some commercial programs (as also are the concerned SV modules).

This is high end software, and its development must be financed - so you have to pay for it to help ensuring further development.

The following modules are available right now:

svdrivers (dir) svoperators (dir) 24BitToHam\_ham6.svm 24BitToHam ham8.svm AnyTo24Bit\_HAM.svm Blur 24.svm HilbertDither256 code.svm PaletteDither\_code.svm RotateFree\_8.svm Scale50\_Half.svm svobjects (dir) 24BitToHam\_ham6.svm 24BitToHam\_ham8.svm BMP\_Decode.svm BMP\_Plain.svm HJG\_Efdpef.svm ILBM\_c2p\_24.svm ILBM\_CBR\_Encode.svm JPEG code.svm PBM\_Encode.svm PCX\_Decode24.svm

24BitToHam\_ham6quick.svm 24BitToHam\_ham8quick.svm Dither24Bit\_floyd.svm Dither24Bit\_ordered.svm OptimizePalette\_code.svm RotateFree\_24.svm Scale50\_Double.svm Sharpen\_24.svm

24BitToHam\_ham6quick.svm 24BitToHam\_ham8quick.svm BMP\_Encode.svm DEEP\_Decode24.svm HJG\_Fmdpef.svm ILBM\_CBR\_Decode.svm ILBM\_p2c\_24.svm PBM\_Decode.svm PCD\_yuv.svm PCX\_Decode4.svm SuperView-Library 12 / 174

PCX\_Decode8.svm
PCX\_Encode4.svm
PICT\_code.svm
RGB8\_Decode.svm
Targa\_Decode1.svm
Targa\_Decode24.svm
TIFF\_code.svm
WPG\_Decode4.svm

svsupport\_c2p.svm

PCX\_Encode24.svm
PCX\_Encode8.svm
PNG\_code.svm
RGB8\_Encode.svm
Targa\_Decode16.svm
Targa\_Decode8.svm
WPG\_Decode1.svm
WPG\_Decode8.svm
svsupport\_p2c.svm

PLEASE NOTE, THAT NUMBER AND KIND OF THE PPC MODULES ARE SUBJECT TO CHANGES.

Picture Manager professional (PMPro) V5.5 already does include these modules, plus additionally the following exclusive PPC plugins (for SVOperators that also are exclusive to PMPro):

libs/svppc/svoperators
 Convolve\_24.svm
 EdgeDetect\_Plain.svm
 ScaleFree\_8.svm

DitherFix24\_Floyd.svm ScaleFree\_24.svm

PLEASE NOTE, THAT NUMBER AND KIND OF THE PPC MODULES ARE SUBJECT TO CHANGES.

Where to obtain from ?

The PPC plugin modules basically already are part of Picture Manager  $\leftrightarrow$  professional V5.5 (or any upgrade from earlier versions).

Additionally, the (non-exclusive) PPC modules also can be ordered by registered (as well as newly registering) users of SuperView/SViewNG/SViewII. or ImageEngineer.

For details, please see the registration form coming with SViewII.

### 1.8 Installation and Configuration

\_\_\_\_\_

Installation Options: Overview

-----

- A. Automatized Installer-based Installation
  - 1. Installer procedure
- B. Customized Installation
  - 1. Main installation procedure
  - 2. Setting Up Standard Configuration
  - 3. Plugging in 680x0 modules
  - 4. Plugging in PackerSupport
  - 5. Plugging in SQ-Operators
  - 6. Using VMEM: (Needed)
  - 7. Plugging in Ghostscript/Postscript (TM)

SuperView-Library 13 / 174

- 8. Reading GPlot (CGM), Amifig (Fig),
   AMF/WMF/CLP/DR2D/DRSF/DXF/WPG-vector
   files (MetaView)
- 9. Support for high PhotoCD resolutions
- 10. Plugging in powerUP (TM) PPC modules
- C. To Be Checked Also
  - 1. Datatypes-Support
  - 2. Other Libraries
  - 3. Additional settings
  - 4. Preferences

\_\_\_\_\_

# A. Automatized Installer-based Installation

#### 1. Installer procedure

-----

Depending on the selected skill mode (novice, intermediate, expert) you will at least be asked for some of the following:

- your basic graphics engine (ECS, AGA, various GfxCards)
- a place to install the libraries to instead of LIBS:
- a place to install the catalogs to instead of SYS:locale/catalogs
- a path to assign VMEM: to (s:user-startup will be modified)
- whether

SVPrefs

should be copied to SYS:Prefs

- whether to install the PackerSupport stuff
- whether to immediately also install the SQ-Operators
- questions about (existing) GhostScript/MetaView installations

# B. Customized Installation

1. Main installation procedure

\_\_\_\_\_

Copy "superview.library" and "superviewsupport.library" to your LIBS: directory, the SVObjects to "LIBS:svobjects/", the SVDrivers to "LIBS:svdrivers/" and the SVOperators to "LIBS:svoperators/"!

(PowerPC modules must be stored in "LIBS:svppc/" plus subdirectories - see paragraph 9.)

Be aware, that library names are case-sensitive and wrongly spelled libraries won't be recognized, though.

Installation of the libraries can be done to any directory, so that these may be installed separate from the system libraries. Adding the SuperView-Library to the system would then be managed via

Assign LIBS: [PATH] ADD

somewhere in the User-Startup.

SuperView-Library 14 / 174

#### 2. Setting Up Standard Configuration

\_\_\_\_\_

Docs/Sample\_Configs contains basic configuration settings for ENVARC: and ENV: which have to be copied there to allow the library system running without problems. env\_AGA contains plain AGA configuration and so on - see Installer script for more information.

#### 3. Plugging in 680x0 modules

\_\_\_\_\_

Owners of 68020-68060 systems should copy the turbo versions of some of the modules over the 68000 installation. Simply type "Copy libs/68030 to LIBS: all" or similar.

#### 4. Plugging in PackerSupport

-----

PackerSupport/libs/svobjects does contain the support module for XPK (includes PowerPacker PP20) compressed data. Optionally copy this to LIBS:svobjects and the config from env to ENVARC: (and ENV: as well, of course)

#### 5. Plugging in SQ-Operators

\_\_\_\_\_

Steve Quartly's great additional svoperators can be found within "SQ-Operators/". Just install those separately, as already done for PackerSupport before.

#### 6. Using VMEM: (Needed)

\_\_\_\_\_

Addionally, you should create an assignment called "VMEM:", which is intended to contain virtual memory image files or other temporary data, which may be created either by superviewsupport-library (vmem\_XXXXXXXX), JPEG.svobject (jpeg\_XXX) or other modules. It does not always make sense, to place this directory somewhere at a Ram-Disk, because most programs will perhaps only try to place files there, after they already checked, that there's no more memory available (so even your Ram-Disk would not grant more space).

It is suggested to place this Assign on a fast harddisk or partition, with a high AddBuffers value.

#### 7. Plugging in Ghostscript/Postscript (TM)

\_\_\_\_\_

If you have Ghostscript installed, you may want to use it for reading Postscript (TM) files - if not, you may consider to install it for such uses.

See

GhostScript.svobject description for more information.

 Reading GPlot (CGM), AmiFIG (FIG), AMF/WMF/CLP/DR2D/DRSF/DXF/WPG-vector files (MetaView)

-----

See

GPlot.svobject

SuperView-Library 15 / 174

AmiFIG.svobject
and

MetaView.svobject descriptions for more information on installation.

Please note, that GPlot and AmiFIG both do require Postscript support, which means: a fully working Ghostscript installation.

Alternatively, you now can redirect CGM and FIG handling to MetaView as  $\ensuremath{\hookleftarrow}$  well.

#### 9. Support for high PhotoCD resolutions

-----

Support for BASE\*4 (1536x1024) and BASE\*16 (3072x2048) requires the NetPBM-Tool "hpcdtoppm" to be installed and configured for use with PCD.svobject. See PCD.svobject description for

more information.

#### 10. Plugging in powerUP (TM) PPC modules

\_\_\_\_\_

These have to be placed to "LIBS:svppc/" into the same directories as their counterparts, thus "LIBS:svpcc/svobjects/" and so on.

#### C. To Be Checked Also

\_\_\_\_\_

### 1. Datatypes-Support

\_\_\_\_\_

"datatypes.library" V39+ is only needed, if OS3-DataTypes are wished to be supported - not available for OS2 users. For 24 Bit datatype support also picture.datatype V43 is needed to be installed (with ECS/AGA this one also needs a version of cyberncg.library, which had been removed from newer pic-dt 43 distributions - alternatively use the pic-dt 43, which is coming with the Picasso96 RTG system and which works with ECS/AGA without any other requirements).

#### 2. Other Libraries

\_\_\_\_\_

Please take care, which libraries also additionally may be needed by single SVObjects/SVDrivers/SVOperators.

#### 3. Additional Settings

\_\_\_\_\_

Directory Caching:

~~~~~~~~~~~~~~~~~

Buffer values (set via C:AddBuffers) for the used drives should at least be around 25, sometimes more may be quite useful.

Stacksize:

~~~~~~~

If you don't set this one to a reasonable value, the system

SuperView-Library 16 / 174

might crash when using some specific modules (e.g. Dither24Bit). It is strongly recommended to use values >= 32768 bytes with any programs using the library.

User-Startup:

~~~~~~~~~~~~

Add the following line somewhere to s:user-startup

SYS:Prefs/SVPrefs >NIL: <NIL: INIT

It will make sure, that ppc.library already is in memory, when the first program tries to open it via superviewsupport.library.

4. Preferences

For modifying any specific ControlPad settings, you should

SVPrefs

(optionally copied to SYS:Prefs during Installer-based installation).

Nevertheless sometimes modules do not come with the required .cpinfo files, so it would become necessary to edit ControlPad files directly at their locations ENV:SuperView-Library and ENVARC:SuperView-Library, maybe by using the descriptions inside the doc-file "ControlPads".

1.9 Overview of currently available SVObjects

Available SVObjects and/or supported file formats (mostly $\ \leftarrow$ included) :

SVObject Type Read-Support Write-Support

AMF

EXT -> MetaView 1.x (not available)

BMP (Win, OS/2)/RIFF

EXT max 8/24bit files max 8/24bit files

C64 (Koala, Doodle)

EXT max 4bit files (not yet available)

CDR (Corel Preview)

EXT (various) (not available)

CGM

EXT -> GPlot (not available)

CLP

* EXT -> MetaView 2.x (not available)

CVP

SuperView-Library 17 / 174

EXT 24bit files (not available) Degas (Atari) EXT max 4bit files (not available) DXF EXT -> MetaView 2.x (not available) EPS(F)-Header EXT (various) only from 24bit sources FBM (*nix) EXT max 8/24bit files max 8/24bit files FIG EXT -> AmiFIG (not available) Icon (Amiga) EXT 4/16 Color Icons 4/16 Color Icons Icon (W*nd*ws) EXT 16 Color Icons (not available) IFF-ACBM EXT max 8bit files max 8bit files IFF-DEEP EXT 24bit files only 24bit files IFF-DR2D EXT -> MetaView 2.x (not available) IFF-DRSD EXT -> MetaView 2.x (not available) IFF-FAXX EXT lbit files (not available) IFF-ILBM FastILBM24 EXT max 8/24bit files max 8/24bit files IFF-PBM 8bit files EXT 8bit files IFF-RGB8/N EXT 24bit files only 24bit files IFF-RGFX 8/24bit files EXT 8/24bit files IFF-YUVN EXT 24bit files only 24bit files IMG (GEM/V*nt*ra)

EXT max 8bit files (not yet available)

SuperView-Library 18 / 174

JPEG (JFIF)

EXT max 8/24bit files always as 24bit files

Limbo

* EXT -> Limbo (24 Bit via Limbo)

MAC (MacPaint)

EXT max 1bit files (not yet available)

PCD (PhotoCD)

EXT 24bit files (not available)

PCX upto V3.0

EXT max 8/24bit files max 8/24bit files

PICT-2 (Mac)

EXT always as 24bit files (not available)

Pictor/PCPaint/PIC

EXT max 8bit files (not yet available)

PNG (Network Gfx)

EXT max 8/24bit files max 8/24bit files

PNM (*nix)

EXT max 8/24bit files max 8/24bit files

Postscript/PDF

* EXT -> Ghostscript (not available)

QRT/POV

EXT 24bit files 24bit files

SGI

EXT max 8/24bit files only 24bit files

Spectrum ZX EXT max 8bit files (not available)

SunRaster (RAS)

EXT max 8/24bit files max 8/24bit files

SVG Graphics

EXT max 8/24bit files max 8/24bit files

Targa

EXT max 8/24bit files max 8/24bit files

TIFF (V5.0)

EXT max 8/24bit files max 8/24bit files

MIT

EXT max 8/24bit files (not yet \leftrightarrow available)

avallable

Utah RLE

EXT 24bit files 24bit files

SuperView-Library 19 / 174

```
WMF
                                 EXT -> MetaView 1.x
                                                              (not available)
             WPG (WP-Draw BitMap)
                 EXT max 8bit files
                                             (not yet available)
             WPG (WP-Draw Drawing)
              * EXT -> MetaView 2.x
                                            (not available)
             XWD
                                  EXT max 8/24bit files (not available)
             DataTypes
                           INT all Pictures/DTs (not available)
  * SVObjects marked with an Asterisk will only work, when
   the mentioned external programs (usually freely distributable
    software from AmiNet) also have been installed and set up as needed.
    (If not set up, these may be disabled via controlpad STATUS=DISABLED.)
There's also an Unpack.svobject in the PackerSupport-Directory,
which allows reading of packed files without explicitely unpacking
these before (supports XPK and PP20). It also supports reading of Mac-written
 .HQX files (BinHex compression) without having to extract the data fork before.
It is as well possible to save graphics as
             C or Asm-Sourcecode
  GIF is obsolete - you neither should use nor support it any longer. If
  you are doing WWW design, use PNG and JPEG instead. It's important !
  If you need to handle GIF graphics (e.g for conversion to PNG), just
  install one of the available GIF datatypes - and reading will work.
Planned SVObjects (no quarantee !) :
  - XBM
   - MTV
   - Rendition
   - various raw formats
  - more Atari formats
      (if I get my hands on some pictures ->
             send
              some, if PD !)
  - and more
      (vou mav
             send
              me gfx's and/or descriptions, if PD)
 Please ask before sending graphics via email.
```

SuperView-Library 20 / 174

1.10 Overview of currently available Device SVObjects

Available SVObjects:

SVObject Type

Printer

supports printer.device/TurboPrint3-5/Studio EXPORT

Scanner

supports scanner.device of ScanQuix IMPORT

1.11 Overview of currently available SVDrivers

Overview: Supported and Non-supported Graphics Cards

| Card Name | Kin | d of | Suppo | rt | |
|---------------------------|-----|------|------------|---------|----------|
| Card Name | | d of | Suppo | | |
| 1600GX | _ | | | | |
| A2410 TIGA | CG | EGS | | | 1 |
| BVisionPPC | CG | | | | 2 |
| CyberVision64 | | | P96 | | 3 |
| CyberVision64/3D | CG | | P96 | | 4 |
| CyberVisionPPC | CG | | | | 5 |
| DCTV | - | | | | |
| Domino | CG | EGS | P96 | | 6 |
| DraCo Altais | CG | | | | 7 |
| Firecracker | _ | | | | |
| GDA-1 | _ | | | | |
| Graffity | _ | | | | _ |
| GVP 110/24 | | EGS | | | 8 |
| GVP IV 24 | | EGS | | | 9 |
| Colormaster | 00 | EGS | | | 10 |
| Inferno (Wildfire) Merlin | CG | | P96 | ייי ענע | 11
12 |
| Meriin
OMniBus | | | P96
P96 | NAT | 13 |
| OpalVision | | | P 9 6 | NAT | 14 |
| Picasso II | CG | | P96 | NAT | 15 |
| Picasso II+ | | | | NAT | 16 |
| Picasso IV | | | | IVAI | 17 |
| Piccolo | | EGS | | | 18 |
| Piccolo SD64 | CG | | P96 | | 19 |
| Pixel64 | CG | | P96 | | 20 |
| Rain*ow II (R-II) | | EGS | | | 21 |
| Rain*ow III (R-III) | | EGS | | | 22 |
| Retina Z2 | | EGS | | NAT | 23 |
| Retina Z3 BLT | CG | | P96 | NAT | 24 |
| Spectrum | CG | EGS | P96 | | 25 |
| Visiona | | EGS | | | 26 |

SuperView-Library 21 / 174

As you can see, any reasonable graphics card for the Amiga is supported via one or more SVDrivers for emulation software, available for these. Only some strange RGB-Port adaptors or rare framebuffers are not supported.

Shortcut Explanation

CG = CyberGraphX or CyberGraphX-Clone available (CyberGraphics.svdriver)

EGS = EGS available (with EGSPlus this means: CG, too)

P96 = Picasso96 SVDriver available

NAT = native emulation software and SVDriver available, as long as not already covered by the other mentions

= nothing known about any emulation software

| Available SV | Drivers (mostly included) : | | |
|--------------|---|------------------|----------------|
| SVDriver | Requirements | BITPLANE | ONEPLANE |
| | OCS/ECS OCS/ECS* and OS V2.04 | + (V37+) (system | n) 8/24bit |
| | AGA* and OS V3.x+ | (V39+) (s | ystem) 8/24bit |
| | Window
(AGA and/or CyberGra | phX RTG) 8bit | 8/24bit |
| | CgxOverlay
(CyberGraphX RTG, Overla | y) 8bit | 8/24bit |
| | CyberGraphX
CyberGraphX** RTG System | 8bit | 8/24bit |
| | EGS 7 EGS Emulation Softw | are V7 8bit | 8/24bit |
| | Merlin Merlin*** Card Softw | are 8bit | 8/24bit |
| | OpalVision
OpalVision Card Software | 8bit | 8/24bit |
| | Picasso96
Picasso96 RTG System | 8bit | 8/24bit |
| | Picasso PicassoEmu** (Picasso | II(+)/IV) 8bit | 8/24bit |
| | Retina | | |

RetinaEmu (Retina Z2/Z3) 8bit 8/24bit

SuperView-Library 22 / 174

```
* ECS- and AGA.svdriver will both work with graphic cards, if they are configured with "BITMAPCOPY=RTG" and the GfxCard software does supply a Workbench Emulation and/or Screen Promotion. If you own a graphics card, without having an appropriate SVDriver for it, always try using AGA.svdriver at first. For handling 24 Bit, extra settings should be done (dithering, etc.)
```

- ** The APIs of these RTG/emulation systems have been "cloned" by other systems, also. Drivers possibly may work with these as well, since they are not relying on any undocumented features except maybe concerning specific system-friendly workarounds for specific bugs. If there is a "native" driver for these systems, you should not use the "cloned" API driver if not stated differently or unavoidable.
- *** With ProBench V3, use the CyberGraphX SVDriver instead.

 The native API seems to have become incompatible to its predecessors in some ways.

too limited.

1.12 Overview of currently available SVOperators

```
Available SVOperators (mostly included):

SVOperator

24BitToHAM
dithers 24 bit RGB to HAM6/HAM8

AnyTo24Bit
converts input to 24 bit

Blur
applies blur filter to graphics
```

SuperView-Library 23 / 174

CallPNM

Call preset external PNM operator Crop "crops" boxes of any size from 8/24 bit graphics Dither24Bit dithers 24 bit RGB to 2..256 Colors ExtractBlue extracts Blue values from (upto) 256 Colors or 24 bit ExtractGrayScales converts (upto) 256 Colors or 24 bit to Gray ExtractGreen extracts Green values from (upto) 256 Colors or 24 bit ExtractRed extracts Red values from (upto) 256 Colors or 24 bit HilbertDither256 dithers to Black & White LeftToRight turns left to right ... OptimizePalette reduces depth by filtering unused or redundant colors PaletteDither dithers (optionally in parts) to a user-supplied palette Rotate rotates by 90/180/270 degrees ... RotateFree rotates freely by 0..360 degrees about a given point Scale50 scales to half/double size Sharpen applies sharpen operator to graphics TopToBottom turns top to bottom ... XOR nice effects ... Just for information:

- this distribution also includes a bunch of image processing

operators by

SuperView-Library 24 / 174

Steve Quartly
 (SQOperators) like

SQBentley.svoperatorSQBlur.svoperatorSQContrast.svoperatorSQDeep_Press.svoperatorSQDiffuse.svoperatorSQEmboss.svoperatorSQHighPass.svoperatorSQMosaic.svoperatorSQMotion_Blur.svoperatorSQOilPaint.svoperatorSQSharpen.svoperatorSQSlicing.svoperatorSQThreshold.svoperatorSQTiling.svoperator

- buyers of the commercial program

Picture Manager professional

are not freely distributable (exclusively shipped with PMPro):

AddText.svoperator
AutoBorder.svoperator
Brightness.svoperator
Complement.svoperator
Convolve.svoperator
EdgeDetect.svoperator
Mosaic.svoperator
Brightness.svoperator
Contrast.svoperator
DitherFix24.svoperator
Gamma.svoperator
PagePrint.svoperator

Mosaic.svoperator PagePrint.svoperator RGBAdjust.svoperator ScaleFree.svoperator

(refering to release V5.5 - may differ from version to version)

Planned SVOperators (no guarantee !) :

- some more operators for common image processing
- and more

1.13 Software supporting SuperView-Library

o The following programs do own a license for SuperView-Library:

Program Description Status

SuperView

THE image viewer and converter for anyone SW

SqOpal

THE image viewer and processor for OpalVision SW

SuperLoader

THE loader module for OpalPaint FW

ImageEngineer

THE image processing program for anyone SW

PictureManager

THE image database program for professionals COM

SuperView-Library 25 / 174

DRAFU

THE function plotting program

SW

GenesisPro Editor

Game Level Editor

SuperView-Library Plugin

COM

FW

o The following small programs have been written by me and do also support SuperView-Library in some way:

| Program | Description, Author | Status |
|------------|---------------------------------------|--------|
| SimpleView | SuperView-Library Example Program | FW |
| MicroView | SuperView-Library Example Program | FW |
| KFracPlus | fractal generator (saves via library) | FW |
| PNG-Box | conversion "any to PNG" for WWW uses | SW |

1.14 superviewnote

ArtEffect

SuperView is a program that has been designed for the purpose, to display any kind of graphic as fast and as comfortable as possible.

Fast means not only fast in reading and displaying but also in calling and using the program.

Highest possible flexibility is implemented via the external Driver-System, consisting of the SuperView-Library, the SVObjects, SVDrivers and SVOperators.

These intentions resulted in a bundle of features and options you have access to when using SuperView and installing it to your System:

- licensed "SuperView-Library" (see directory SuperViewLibrary)
- intensive use of many special OS V2.04+ and OS V2.1+ capabilities
- support of many OS V3.x+ and AGA graphics features,
 - as e.g. support of interleaved BitMaps
- support of all SVObjects, SVDrivers and SVOperators of SuperView-Library
- "Screen-Grabbing"
- Commodity (optional)
- ARexx-Ports (optional)
- AppIcon (optional)
- AppMenu (optional)
- AppWindow (optional)
- Clipboard reading and writing
- Support of Devices, like e.g. Scanners
- Localization for OS V2.1+ (not all texts yet)
- AmigaGuide OnLine-Help for OS V2.04+ (asynchroneous & localized with 2.1+)
- detailed configuration via Config-File, Cli-Options and Workbench-Tooltypes
- Graphical User Interface (GUI) for Workbench-Users (optional)
- conversion of the supported File-Formats
- information about the displayed graphics via Requester,

SuperView-Library 26 / 174

```
selectable via GUI-Menu
- and more
```

It is Shareware and can be found on AmiNet under gfx/show (for example gfx/show/SView.lha). It's direct successor is called SViewNG and can be downloaded as gfx/show/SViewNG.lha

SuperView/SViewNG WWW pages:

http://home.t-online.de/home/Andreas_Kleinert/
http://www.amigaworld.com/support/sview/

1.15 sqopalnote

SqOpal is an Image Processing, display and manipulation package especially for the OpalVision 24 bit Graphics and FrameBuffer hardware.

It has been written by Steve Quartly and Paul Huxham and optionally uses SuperView-Library.

It is Shareware and can be found on AmiNet under gfx/show (for example gfx/show/SqOpal20.lha).

Steve Quartly: steveq@mafeking.scouts.org.au Paul Huxham: paulh@perth.DIALix.oz.au

1.16 superloadernote

SuperLoader is a Loader Module for OpalPaint (OpalPaint comes with the OpalVision 24 bit Graphics and FrameBuffer hardware).

It has been written by Steve Quartly and Paul Huxham and uses SuperView-Library.

It is Freeware and can be found on AmiNet under gfx/board (for example gfx/board/SuperLoader11.lha).

Steve Quartly: steveq@mafeking.scouts.org.au Paul Huxham: paulh@perth.DIALix.oz.au

1.17 imageengineernote

Image Engineer is a shareware image processing application for any Amiga with 68020 and OS 2.x or greater.

Image Engineer can be used for tasks varying from converting images between different file formats, rendering 24 bit images down to standard Amiga screen modes, enhancing badly scanned images, applying special effects even up to advanced image composition.

SuperView-Library 27 / 174

What you can use it for is basically limited by what you can think of.

Registration fee is only 35 US dollar (45 AUS dollar, 55 DEM). Registration sites are in the Netherlands (Simon Edwards) and Germany (Andreas R. Kleinert).

Registered users will be sent a personal keyfile which will unlock all of Image Engineer removing the limits on the image size, and the 'Register Now...' requesters.

This keyfile will also work for future versions. Keyfiles can be sent out via mail or Email.

IE can be found in (currently) two archives on AmiNet under gfx/edit (for example gfx/edit/ImEngV3.41p1.lha and /ImEngV3.41p2.lha).

Simon Edwards: sbe@worldonline.nl

IE WWW page: http://www.amigaworld.com/support/imageengineer/

1.18 picmanagernote

Picture Manager Professional (PMPro) V5.5 is an excellent commercial image catalogization program with a large number of features for creation and handling of thumbnail tables.

It is a powerful database and allows loading, processing and displaying images via SuperView-Library and includes an automatic conversion function for catalogs of images, which allows to convert between all file formats SuperView-Library does support ... AND MORE ...

It even can directly scan LHA and LZX archives for images.

- For a demo version of the ENGLISH version V5 of Jürgen Schäfer's Picture Manager prof. please see Aminet:biz/demo/pm5_demo.lha
- The GERMAN version V5.5 of Jürgen Schäfer's Picture Manager prof. can be obtained from

IrseeSoft SPCS
Meinrad-Spieß-Platz 2

D-87660 Irsee Voice: +49-(0)8341-74327 Germany Fax: +49-(0)8341-12042

Or from any distributor. The official pricing as with December 1998 is 129 DEM (no quarantee). Ask them for it.

IrseeSoft also are the manufacturers of the TurboPrint V7 high quality printer driver enhancement system.

A CD-ROM containing catalogues of more than 25000 graphics from Amiga CD-ROMs as well as a full version of PM 2.0 and demo versions (german) of PMPro 4 and TurboPrint 5 is available for 29 DEM (no guarantee). It's the first one of a new CD-ROM series - the second

SuperView-Library 28 / 174

already has been released and does contain graphic catalogs for the Aminet 1-16 and Aminet Set 1-4 CD-ROMs.

IrseeSoft WWW page: http://www.irseesoft.com
IrseeSoft: mail@irseesoft.com

1.19 drafunote

DRAFU plus is a function plotter, which optionally supports SuperView-Library for saving the drawings from single windows.

It includes the following features:

- freely defineable function terms $(x^?, \sin, \cos, \tan, ...)$ (function parser by Dipl.Ing. Ulrich Degens)
- unlimited number of sizeable windows on the screen
- unlimited number of functions per window (presented as a list)
- upto 256 colors on the screen (AGA):
 - freely selectable draw color for each function
 - freely selectable background, drawing and axis color for each window
- loading and saving of function lists
- flexible axis' description (decimal, logarithmically, scientific)
- single/double axis description
- saving windows drawings in any of the graphics file formats SuperView-Library does support (optionally, library is not needed)
- hardcopy function

AND MUCH MORE

DRAFU can be found on AmiNet under misc/math (for example misc/math/DRAFU.lha).

Author: me ;-)

1.20 genesisnote

GenesisPro is a 3D Level Editor, that is usable for Dungeonmaster style and Wolfenstein 3D style/DOOM style games (it does not feature not-rectangular walls, but it DOES feature floors of different height).

It has been written by Alex Grasso and Steffen Haeuser.

GPE is Freeware and can be found on AmiNet under game/demo (for example game/demo/GenesisPro.lha).

Steffen Haeuser: Fido 2:2487/3009.0, MagicSN@Birdland.es.bawue.de

SuperView-Library 29 / 174

1.21 And thanks for all the fish:

```
I perhaps have to thank many persons for supporting me with ideas,
Bug-reports and so on :
Thanks go to (in alphabetical order) :
 * Jan van den Baard
   ... for his great tool GadToolsBox, which I formerly used to
   design the GUI of
                SVPrefs
 * Ian O'Connor
   ... for the Designer, which I used before Wizard for GUI creation.
 * Simon "ImageEngineer" Edwards
   ... for a lot of things concerning SuperView-Library :-)
 * Gerd Frank
   ... for Beta-Testing, Bug-Reports and for his many ideas and suggestions,
   concerning SuperView-Library and SuperView (also see notes there) !
   And last not least for the first draft of the Guide Documentation...;-)
 * Roman Patzner
   \dots for the nice icons he designed for use with Martin Huttenloher's
   MagicWB (8 Colors minimum) and sent to me for inclusion with SuperView.
   With SuperView-Library only the InstallerScript-Icon is used yet
   (several times ;-)
 * Steve Quartly and Paul Huxham
   ... for the various versions of OPAL.svdriver included with the
   library (Steve and Paul) and for Steve's SQ-Operators, included
   with his friendly permission.
   Steve also did "SuperLoader" and "SqOpal" together with Paul Huxham.
   THANKS !
 * Georg Rottlaender <Georg.Rottlaender@home.ivm.de> for redesigning
   the Wizard GUI of the prefs program
 * Jürgen Schäfer
   ... for speficic Beta-Testing and related Bug-Reports, as well as
   several useful hints and suggestions on implementing new features
   to the library.
 * Martin Schulze
   ... for uploading SuperView onto the AmiNet and including it into
   the SaarAG series, so that it reached more people out there.
```

SuperView-Library 30 / 174

Also for sending and receiving all those mails, which did not find their way through the labyrinth of Fido-Gateways;-)

* Detlef Winkler

 \dots for the new Icons for Doc- and AmigaGuide-files, included with the Library. He also designed some graphics and icons for use with SuperView and new drawer icons.

Additionally, he had a lot of ideas, suggestions and graphics for 24 bit IFF-ILBM, IFF-YUVN, IFF-DEEP and SGI support.

* to the translators

| Francais: | Julien Wilk | (wilkj@esiee.fr) |
|-------------------|---------------------|---|
| | Pascal Rullier | (rullier@triade.fr) |
| Italiano: | Alessandro Basso | (cralex@amiga.dei.unipd.it) |
| | Luca Giolo | (grifon@vega.unive.it) |
| Svenska: | Patrik M Nydensten | (ie96_pny@isk.kth.se) |
| | Torbjörn Aronsson | <pre>(torbjorn.aronsson@mailbox.swipnet.se)</pre> |
| Norsk: | Roger Hagensen | (msi@sn.no) |
| Srpski: | Ljubomir Jankovic | (lurch@afrodita.rcub.bg.ac.yu) |
| | Andrija Antonijevic | (TheAntony@bigfoot.com) |
| Russian: | Oleg Sergeev | (bigblack@neworder.com) |
| Nederlands: | Frits Letteboer | (dagraver@dds.nl) |
| Suomi: | Mika Lundell | (c71829@uwasa.fi) |
| | Linus Silvander | (linus@icenet.fi) |
| Português: | Joel Alvim | <pre>(mindwalker@mail.telepac.pt)</pre> |
| | Alexandre Gabriel | (chryse@mail.telepac.pt) |
| Polski: | Boguslaw Dziewierz | (db7@earthdome.com) |
| Lithuania: | Levas | (savel@kaunas.omnitel.net) |
| Español: | Dámaso D. Estévez | <pre>(amidde@arrakis.es)</pre> |
| Català: | Llorenç Grau | (llg@cryogen.com) |
| Português-Brasil: | Otto Carvalho | (ottocarvalho@alternex.com.br) |
| | Gustavo Sarmento | (sarmento@nutecnet.com.br) |
| Türkçe | Sinan Gurkan | (sgurkan@artemis.efes.net) |

* and last NOT LEAST

```
- all _registered_ users of SuperView for supporting Shareware !!

*** COMMERCIAL BREAK - BEGIN ***

ORDER YOUR KEYFILE NOW !

*** COMMERCIAL BREAK - END  ***
```

- the people mentioned below (still in alphabetical order ;-) :

```
for managing/coordinating the ATO work
Joel
         Alvim
Torbjörn Aronsson
                      for suggestions and bug reports
Ralph
                      for writing the useful "Amiga Guru Book"
         Babel
                      and for competent statements in
                      DE.COMP.SYS.AMIGA.TECH
Alex
                      TuC / Co-Sysop Century
         Carbin
Rüdiger
         Dombrowski ADX-Datentechnik
Thomas
         Dorn
                      Author of XiPaint (thx for 3.2 and 4.0)
                      "Indy" - Creator of "Power-Brei" DiskMag
Sven
         Drieling
```

SuperView-Library 31 / 174

| | | and the Oberon2-Language interfaces and modules |
|-----------|-------------|--|
| Oliver | Eichhorn | for technical discussions about EGS support |
| Thomas | Eigentler | Programmer of MERLIN.svdriver (included) |
| Wolf | Faust | Studio programmer |
| Thomas | Fischbach | did various online support for a long time |
| Fred | Fish | AmigaLibDisks and Fish CD-ROMs |
| Klaus | Gillarek | Beta testing Picasso96.svdriver :-) |
| Stefan | Grad | GPD-Disks |
| Klaus | Holtorf | for detailed information on graphic file formats |
| Ingbüro | Helfrich | for supplying the PiccoloSD64 Graphics Card |
| Colin J. | Knight | for debugging |
| Stefan | Kremer | TuC / Sysop Century |
| Alex | Lange | Time PD-Disks (former aps-electronic) |
| н.Р. | Lattka | Franz PD-Disks |
| Andreas | Manewaldt | Taifun PD-Disks |
| Axel | Melzener | Game Object Design |
| Andreas | Neumann | Creator of the PCQPascal-Language includes |
| | | and modules |
| Patrik M | Nydensten | for lots of suggestions and bug reports |
| Dr. Greg | Perry | for help on IFF-FAXX implementation |
| Michael | Petrikowski | Amiga Szene PD-Disks, SEP - Software-Entwicklung |
| Albi | Rebmann | supplier of my ftn.neckar-alb.de domain |
| Frank | Taha | thanks for the DP II (PC) PBM graphics |
| Michael | Trautes | Sysop of Micky's box - my current Fido Boss |
| Michael | Trautmann | PC-Programmer, for information on Win icons |
| Christian | Wincziers | Sent me some PICT-2 graphics. Thanks! |
| Florian | Zeiler | Sending me the RetinaZ3 and PicassoII graphic |
| | | cards enabled me to write own Drivers for these. |

- some users, which e.g. reported bugs via mail, e-mail or telephone or did something else related to my programming work on the library (only the ones, which have not already been listed above):

| Thomas
Joachim
Rudi
Aaron | Alexnat
Baumeister
Brand
Digulla | |
|------------------------------------|---|------------------------------------|
| C. Davis | Sprague | (dsprague@mhv.net; MCP bug report) |
| Michael | Flad | |
| Grant | Fribbens | |
| Thomas | Gundlach | |
| Michael | Gruber | |
| Richard | Hartmann | |
| Mats | Jansson | (for reporting 060 problems) |
| Michael | Kilimann | (for reporting 060 problems) |
| Mika | Lundell | MERLIN testing and so on. Thanks. |
| Mats | Jansson | |
| Jim & Becky | Maciorowski | (thanks for the nice card :-) |
| William | Maddock | |
| Michel | De Meerleer | |
| Neil | Mohr | |
| Patrik | Nydensten | lots (tons $;$ -) of suggestions |
| Patrick | Ohly | |
| Andy | Philpotts | |
| Dr. Heiko | Pollmann | |
| Fabio | Rotondo | |
| Jürgen | Schneider | |

SuperView-Library 32 / 174

```
Tommy
               Simonsen
   Klaus
              Stengel
   Reinhard Theling
Henrik Tikanvaara
    Marco
               Vernaglione
    Marc-Tell Volkmann
    Fabien Wernly
    Tilo
               Winkler
                             (thanks for the strange TIFFs ;-)
    and more.
Maybe I forgot somebody to list here, but nobody's perfect...;-)
Please note: If you wrote to me and didn't get an answer,
             this need not necessarily mean, that I didn't
             answer - mails can get lost sometimes.
             Please tell me and ask again!
```

1.22 How to contact the author

```
** General PerSuaSiVe SoftWorX WWW Support Site is http://wdo.de/ark/
** - actually redirected to http://home.t-online.de/home/Andreas_Kleinert/
```

```
You may reach me the following way.
   Send bug-reports, money or whatever to:
     -----
      * SuperView Development & Registration *
        * DRAFU Development & Registration *
     * Image Engineer Registration Site Europe *
                PerSuaSiVe SoftWorX
                Andreas R. Kleinert
                Sandstrasse 1
                D-57072 Siegen
                Germany, Europe
Any snail mail to the old address will still be routed. |
                Phone: +49-271-22869 also FAX + AM
                Weekdays after 18.00h.
       When calling via phone you may leave a message, |
       if I'm not available - but don't expect me
       calling back to USA, Australia, ... since
       german phone rates are HIGHLY expensive.
```

EMail:

SuperView-Library 33 / 174

Please send binaries via ARK@News.wwbnet.de, and keep them smaller than 16 KB - otherwise ask before. Please think twice before sending them - my postbox is not unlimited in size.

* Do not send binaries via Fido or Fido-Gates! *

```
- Fido Andreas Kleinert 2:2457/350.18
```

- Usenet

>>> Andreas_Kleinert@t-online.de (T-Online)
ARK@News.wwbnet.de (Z-Netz)
ARK@superview.ftn.neckar-alb.de (Fido-Gate)
Andreas_Kleinert@gmx.de (GMX)

(note, that mail sent to @gmx.de currently will be forwarded to @t-online.de - so, as long as it works, try to address the latter directly)

- If nothing else works, try one of these public Fido-Usenet gateways:

```
In Germany:
   Andreas_Kleinert@p18.f350.n2457.z2.fido.sub.org
```

From USA or elsewhere:
Andreas_Kleinert@p18.f350.n2457.z2.fidonet.org

When reporting any bugs, please don't forget to include a detailed description of the bug and tell me, if it is reproduceable or not. Also mention the version number of SuperView-Library (and e.g. SuperView) which caused the bug and describe your system configuration (Amiga model CDTV/CD-32/600(HD)/500(+)/1000/1500/1200(+/HD)/2000/2200/2500(UX/AT)/3000(+/T)/4000(/030/040/060/PPC)(T)/DraCo(/040/060)/4060L/5050T, Kickstart/OS Version, RAM, HardDisk, GfxCard, any special Hardware/Software)

Since there recently have been some problems: please don't forget to mention, whether your machine is accelerated in any way, or not (68020/.../060 plus 68881/882, PMMU or PowerUp/PPC).

Would be nice to know, whether it is going to run under UAE or any other Amiga or AmigaOS emulation, etc.

1.23 The future of SuperView-Library...

SuperView-Library 34 / 174

I'll try to do this, but I hope that there's enough support from the Amiga programmers all over the world (via Inter/AmiNet, Fido, etc.) to help me to continue doing so.

This does not only mean fincancial support, but also additional programming efforts like third-party improvements on the library.

You may contact me for developer support - like already mentioned before.

- Andy

1.24 Known bugs and suggestions for workarounds

Harddisk MaxTransfer problem

(workaround)

Problems with specific applications (workaround) Crashes on 060 systems should no longer appear - if the library \hookleftarrow crashes

on specific modules at startup-time, please trace it back with SnoopDOS, delete that specific modules, and contact me for a bug-report.

Minor problems:

o C. Davis Sprague told me, that the combination superview.library and MCP with active NEWTOOLTYPES patch did cause crashing the library at startup time. So don't use that patch...

There seem to be more options in MCP, which may become 'critical'...

Whenever you encounter any problems: first try it again without any patches running !

o Do not mix libraries from Picasso96 and CyberGraphX - when again switching from P96 to CGfx with Picasso96API.library still being in LIBS: then your system will immediately crash with the next opening of that library. (This may have been fixed with newer versions of Picasso96, but don't be suprised if not.)

1.25 Harddisk MaxTransfer Problem

IDE-MaxTransfer Problem (in rare cases, SCSI concerned, too)

Since SuperView-Library usually holds very large buffers within memory, it also likes to read and write these completely from and to disk. This means, that the specific device drivers are confronted with quite large values of bytes to be read or written, which perhaps usually does not happen very often.

SuperView-Library 35 / 174

Sometimes the firmware of IDE harddrives, like shipped with the A4000/030-040 or A1200HD, does not support transfers of blocks larger than 64K (65535 Bytes) during one single write operation. Ususally the DOS splits larger writing calls to take care of this restriction. But since this is just a lack of performance and actually does not comply to the IDE/AT standard, the default value for this "MaxTransfer" is not 0xFFFFF (64K) but 0xFFFFFF or 0xFFFFFFFF instead.

If any written graphics files are mysteriously damaged or will be read incorrectly (writing usually is more critical than reading), you should start your "HDToolBox" and select "Partition Drive" for the concerned HardDrive. After that activate "Advanced Options" and chose "Change". Modify the "MaxTransfer" field, so that it does reflect "0x00008000" (which is the safest value - "0x0001Fe00" or "0x0000FFFF" may work as well, but this would have to be explicitely tested).

After that leave all the windows by confirming "OK" and select "Save Changes to Drive" (no longer disabled) on the first window.

Do not change any other settings within "Partition Drive", if you don't know, what you're doing, since actually partitioning your HardDisk would cause your complete data to be lost. If you did change something you didn't want to change, just "Cancel" the whole thing and start from the beginning.

Please note that, if you don't have correct MaxTransfer value settings, this may cause damage to data on your harddisk. Either when reading/writing via SuperView-Library or with other programs.

1.26 Problems with specific applications

Here's a list of several programs, which either cause SuperView- \leftarrow Library

to crash, or which may crash or fail unexpected (so that it might seem, as if SuperView-Library did crash or were the reason of the fault):

o p5 Mk3 problems

==========

Problem

Drivers are not correctly loaded, preferences can't be changed.

Solution

It has been reported, that a firmware upgrade from V44.38 to V44.57 did fix the problem. So, please only use versions equal or greater than this one.

o Crashes PicassoIV and Picasso96 $\,$

Problem/Solution

If the library crashes at startup-time silenty always, or the machine produces strange visual effects, make sure that you're using the newest version of

SuperView-Library 36 / 174

Picasso96 AND that you've an uptodate flash ROM on your PicassoIV. There seem to have been problems with older versions, so you may wish to upgrade your card's software.

o Mixed Picasso96 and CyberGfx environment

Problem #1

Picasso96 users, which have the Picasso96.svdriver installed (that's default, unless you "exclude" it via SVPrefs

or

delete it), and do switch between P96 and CyberGfx, should note the following: without removing Picasso96API.library from Libs: when CyberGfx is running, any program that tries to open Picasso96API.library will make it crashing (since that library tries to create another, emulated instance of cybergraphics.library, which must fail).

Solution #1

Either

- delete/exclude Picasso96.svdriver
- move all libraries, not only the monitor drivers, when switching between P96 and CyberGfx
- wait for a bugfix (Tobias Abt and Frank Mariak both have been informed)

Problem #2

There's a Picasso96API.library replacement for CyberGraphX, written by Steffen Haeuser. V20.0 does produce a couple of Enforcer hits when being opened.

Solution #2

Either

- remove it
- remove Picasso96.svdriver
- upgrade to a bug-fixed version

o EGS libraries V6 and V7 © VIONA Development

Problem

When flushing the EGS libraries, it seems that the libraries will cause recoverable alerts with OS 3.x.

Maybe on some systems real crashes will occur.

Don't know, whether the libraries are really the source, but it's likely.

Solution

Don't flush ;-)

SuperView-Library 37 / 174

o ${\tt DOpus5}$ (supposed to be fixed with Magellan release)

Problem

Not a serious problem. DOpus5 does not seem to figure the correct version numbers from sv library files, when requested to do so.

Solution

C: Version libraryname

o LX/020 1.03 © 1993 Xenomiga Technologie (Jonathan Forbes)

Problem

Obviously can't correctly extract large LZH/LHA archives.

o MCP (various versions)

Problem

Seems to cause: ramlib-crashes, odd address gurus, check instruction gurus or bad screen colors, ...

Solution

Disable the following MCP patches:

- new tooltypes
- regtols patch
- onereq
- library search
- SetRGB32
- o NewMode V3.3 (and below) © 1992-95 by Andreas Linnemann

Problem

Has been reported to cause serious problems when running together with e.g. SuperView (when attaching a fixed ViewMode to the program).

Solution

Already fixed for newer versions.

I, personally, would strongly recommend not to promote any SuperView Screens via NewMode, since now for almost any configuration there should be suitable SVDrivers - alternatively also a RTG-configuration for AGA.svdriver.

o SnoopDOS

======

Problem

Some external libraries (being opened by SV modules) seem not to be snoop'able without causing crashes, then.

SuperView-Library 38 / 174

Solution

Turn off SnoopDOS OR try disabling its library/loadseg snooping function and/or specify its "NOPATCHRAMLIB" option (via CLI/Tooltypes).

o VMM (supposed to be fixed) $\,$

Former versions of SuperView-Library did allocate all buffers with the MEMF_PUBLIC flag set, which prevented e.g. VMM from storing these as virtual memory on disk.

As with current versions, the large image buffers - where it makes sense - are no longer prevented from being accessing by VMM. MEMF_PUBLIC no longer is set for these.

Before - and with old modules - this could have been by-passed by setting the 10240 flag value within VMM's advanced options - but this should not be done any longer, since it may become dangerous under certain circumstances.

o Shutdown

=======

Problem

LIODICI

The program "Shutdown" (Aminet:util/misc/shutdown2_3.lha) may cause SViewNG to crash at startup time under CyberGraphX, while under Picasso96 there did not occur any problems.

However, the bug does not seem to be in CGfx originally, since a recompilation (the source comes with Shutdown) with SAS/C 6.58 did fix it.

Solution

Avoid using Shutdown (Olaf Barthel dropped development/support for this program several years ago, anyway) or make sure that you don't use it under CyberGraphX unless you've got your hands on a version that has been recompiled with a newer SAS/C version.

1.27 History

Please note the version-dependencies – with older versions you may encounter error messages like "version conflict":

superview.library SVObjects SVDrivers SVOperators

Version 15-22 Version 4 Version 2-3 Version 3

(superviewsupport.library V13)

V22.2 (20.02.1999) :

SuperView-Library 39 / 174

```
- SVObjects: - RGFX: - (see there)
              - TIFF: - basic multi-image support
              - PNG: - (see there)
 - NEW SVDrivers: - CgxOverlay
                    !! BE WARNED !! This still is a beta version...
 - Docs: - updated press feedback section
 - Misc: - additional $VER string to make everyone happy
         - etc. ;)
V22.1 (22.11.1998) :
 - SVOperators: - (see Blur, Sharpen)
 - added StackSwap code to library startup code;
  this should fix the very last stack-related crash problems
 - added "known bugs" entry concerning the p5's Mk3 boards
 - bumped main library version to V22
 - bumped support library version to V13 (V13+ required now)
 - Support-Library: - (see there)
 - installer script now will no longer fail, if the libs/68030
  directory isn't present
 - Note: V21.10 was not on Aminet
V21.10 (31.10.1998) :
 - SVObjects: - EPS: - (see there)
 - updated docs
V21.9 (5.10.1998) :
 - SVObjects: - PNM: - fixed small bug
              - IMG: - (see there)
              - RGB8: - added RGBN support
 - SVDrivers: - Window: - (see there)
 - SVPrefs: - doubleclicks now possible... (no more "Modify")
 - Installer: - localized some more texts (MCP, PPC)
                (-> Dámaso D. Estévez)
 - Misc: - added several new and updated translations by ATO
```

SuperView-Library 40 / 174

```
V21.8 (8.9.1998) :
______
- SVObjects: - Unpack: - now supports .hqx extraction
              - PNG, JPEG, TIFF: - (see there)
- Support-Lib: - (see there)
V21.7 (9.8.1998) :
- SVObjects: - BMP: - (see there)
V21.6 (30.7.1998) :
_____
- NEW SVObjects: - Spectrum: - (ZX Spectrum files, see there)
- SVObjects: - PNM, C64: - (see there)
             - BMP: - (see there)
             - PNG:
                        - fixed alpha+interlaced bug
                        - fixed grayscale+alpha bug
- SVDrivers: - Window: - (see there)
- Misc: - added español translation by Dámaso D. Estévez <amidde@arrakis.es>
- Docs: - rewrote the docs section about 040/060 and math patch
          recommendations; don't patch your system worse !
V21.5 (5.7.1998) :
- Prefs: - SVPrefs tended to crash from WB because of lacking
           a sufficient stack size in the icon
V21.4 (28.6.1998) :
______
- Support-Lib: - added another, alternative viewmode generation
                 routine (to be selected via preferences)
- Note: V21.3 was not on Aminet
V21.3 (27.6.1998) :
______
- NEW SVObjects:
                     - CVP:

    for video/passphoto format

- NEW SVDrivers:
                      - Window:
                                     - Window.svdriver for AGA/RTG
- SVObjects:
                      - MetaView:
                                    - added support for IFF-DSDR
                                       and (some) Win CLP files
                      - PNG:
                                     - (see there)
                      - fixed the "STACKSIZE" entry in various
- Misc:
                        .cpinfo files of SVObjects
```

SuperView-Library 41 / 174

- ECS/AGA/Window (now) have Dither24Bit as default for colorspace adjustment - JPEG.cpinfo specified "PROGRESSION" option instead of "PROGRESSIVE", so saving progressive JPEGs might not have worked (-> Olivier Jeannet) - SVPrefs: - fixed slider/integer bug - fixed enforcer hits (see there) - Docs: - updated information on powerUP (TM) modules - fixed several bugs and mistakes, updated - see updated notes on SnoopDOS usage V21.2 (5.4.1998) : _____ - SVObjects: - added support for 32 bit files - BMP: - fixed RLE 4/8 and OS/2 support - TIFF: - fixed and upgraded - 68k loader was screwed up to 90 $\,\leftarrow$ percent - GhostScript: - added controlpad to allow changing stacksize (in case of \leftarrow crashes) - added controlpad to allow - GPlot (CGM): changing stacksize (in case of $\ensuremath{\hookleftarrow}$ crashes) - changed way of calling the program - AmiFIG (FIG): - added controlpad to allow changing stacksize (in case of \leftarrow crashes) - changed way of calling the program - Limbo (LMB): - added controlpad to allow changing stacksize (in case of \leftarrow crashes) - changed way of calling the program - MetaView: - added controlpad to allow changing stacksize (in case of \leftarrow crashes) - changed way of calling the program - reading of CGM and FIG now can be redirected to MetaView, as well - PNG, JPEG: - upgraded - added note about problems with - FAXX: MultiFax files - Targa: - fixed several bugs - YUVN: - fixed several bugs - SVOperators: - RotateFree: - see there - SVDrivers: - Picasso96: - fixed problem with 8/24 bit \leftrightarrow viewmodes - CyberGraphics: - see there - SVPrefs: - now can be used for changing controlpad settings

SuperView-Library 42 / 174

fromout the Shell or (ARexx) scripts, too

- Support-Lib: - see there

Locale: - added lithuanian catalogs

(-> Levas <savel@kaunas.omnitel.net>)

- Installer: - it's now assumed that "SVPrefs" is

in the search path, so the entry

in s:user-startup no longer does include

an absolute path
(-> Tilo Hanich)

- Known bugs: - added note about the "Shutdown" crash

problem under CyberGraphX

(-> Tilo Hanich)

V21.1 (6.3.1998) :

- various Modules:

- updated to new .svm style PPC modules (completely redesigned with SAS/C)

NOTE, THAT THE OLD MODULES WILL NO LONGER WORK, WHILE THE NEW MODULES WILL ONLY WORK WITH THIS VERSION AND UP! NEW MODULES ARE AVAILABLE UNDER Aminet:gfx/show/svppc211.lha

- SVObjects: - Limbo: - the Limbo package now is

available in a PPC version, on Aminet

- SVOperators: - PaletteDither, OptimizePalette,

AnyTo24Bit, HilbertDither256:

- now with optional PPC support, too

- AnyTo24Bit, HilbertDither256:

- fixed small bugs (see there)

V20.1 (11.2.1998) :

- SVObjects: - JPEG, PNG: - now with support for PPC native ELF loader/saver; incredible speedup

- TIFF, PICT: - dito, plus fixed some bugs

- V19.11 (1.1.98) accidentally still was labeled V19.10 (27.12.97) internally
- updated Steve Quartly's 14 SQOperators to version 3.5.
 They're now adjusted to the latest library specs, have
 been improved and bug-fixed and all seem to have
 decreased their file size a little bit
 (-> supplied by Steve Quartly)

SuperView-Library 43 / 174

```
- Prefs: - (see there)
 - Docs: - updated press feedback section
         - updated "known bugs" on PicassoIV with Picasso96
         - updated information on powerUP (TM) plugins
           for PPC in ELF format (ppc.library).
V19.11 (1.1.1998) :
 - Note: V19.10 obviously was not on Aminet - not my fault
 - SVObjects: - JPEG: - (see there)
 - installer script did show the PPC warning message
  unconditionally, even without a PPC being present
   (this was left there from the testing phase). Fixed.
 - Support-Lib: with a PPC, take care that C2P=SV is
                set (see there). Otherwise the PPC
                can't be utilized for c2p/p2c conversion.
V19.10 (27.12.1997) :
 - Support-Lib: - MODEGEN was missing in .cpinfo file
                    (thus also not accessible from SVPrefs)
                  - updated info on ImageEngineer: Simon
 - Docs:
                   now has a new email and homepage
                  - updated PMPro info
                  - same for ScanQuix
                  - updated the rest, too...
V19.9 (24.12.1997) :
 - Note: V19.8 was not on Aminet
 - NEW SVObjects: - TIM (PSX): - console graphics, as e.g. written
                                 by Personal Paint (!! BETA !!)
 - SVObjects:
                  - JPEG, PNG: - smarter, faster
                  - BMP:
                              - fixed bug in writing (4 bit, only)
 - SVDrivers:
                  - CyberGraphics: - (see there)
 - Support-Lib: - new preferences option for viewmode generation
                   (-> Ramiro Garcia)
V19.8 (8.12.1997) :
- SVObjects: - Amilcon: - fixed bug, that could make the system
                           crash when sv-lib was loaded/flushed
```

SuperView-Library 44 / 174

```
V19.7 (6.12.1997) :
______
 - Note: V19.6 was not on Aminet
              - AGA, ECS: - fixed SetPatch-Bug (see there)
 - SVDrivers:
 - SVObjects: - RGFX: - fixed small bug
 - Support-Lib: - fixed SetPatch-Bug (see there)
V19.6 (27.11.1997) :
 - SVObjects: - RGFX: - (see there)
 - Support-Lib: - (see there)
 - Docs:
                - updated Pressfeedback section: CU Amiga
                  granted "SuperView" 5 out out 5 stars
                  in a very positive review article :-)
V19.5 (16.11.1997) :
 - NEW SVObjects: - Amilcon: - reading/writing Amiga icon (.info)
                               files with either WB (4/8 \text{ color}) or
                               MagicWB (16 color) palette, supports
                               NewIcons for > 16 colors
                   Note: Reading explicitely needs to be enabled
                          by a Controlpad setting switch!
                  - IFF-RGFX: - new graphics file format standard
                                proposal for AGA/RTG Amigas now
                                supported, too
                                (see Aminet:dev/misc/IFF-RGFX.lha)
 - SVObjects:
                 - C-Source: - now can write assembler source code
                               as well
                  - ILBM:
                            - (see there)
                  - SVG:
                            - (see there)
 - SVOperators:
                 - XOR: - (see there)
 - Prefs:
                 - (see there)
 - Docs:
                  - updated
                  - updated infos on Scanner and Printer SVObject
V19.4 (19.10.1997) :
 - SVDrivers: - ECS, AGA: (see there)
 - MISC: - added note about possible ppc.library and powerpc.library
           conflicts (when using the PPC-Modules) to the installer
           script: always use powerpc.library V7, when using one.
```

SuperView-Library 45 / 174

```
- BTW: the MCP and PPC notes in the installer script are not
          yet localized. Would be nice, if someone could do that.
         - updated polish catalog by Boguslaw Dziewierz <cut@localbar.com>
           Now placed in correct directory, with correct spelling (polski)
         - updated "Press feedback" section
         - updated information on english PMPro in 3rd party section
 - Prefs: - fixed small bug
          - new Wizard-GUI with lots of improvements done by
            Georg Rottlaender <Georg.Rottlaender@home.ivm.de>
V19.3 (28.9.1997) :
 - Note: V19.2 was not on Aminet
 - SVObjects: - Printer: - now also supports TurboPrint for
                          8 Bit modes as well as EHB/HAM
                         - added support for Wolf Faust's Studio
                          printer system
 - SVDrivers: - ECS, AGA: - more fixes
 - LIBRARY: - svsupport (see there)
 - MISC: - added polish catalog by Boguslaw Dziewierz <cut@localbar.com>
         - added explicite note about ppc.library V44+
V19.2 (21.9.1997) :
           SVPrefs
           : - now finally with a wizard GUI, too
              (-> Patrik Nydensten, and more)
 - Crashes: - some people still reported, that SV-Library could crash
              on startup; most often deleting all unused SVDrivers did
   #1
              help. Since I could not find any related bugs, and the
              only SVDriver I don't maintain myself is OPAL.svdriver,
              it will now be moved to a new directory called
              "LIBS:svstorage" if it is not needed
            - the (unsupported) SVO.svobject and CyberDataType.svobject
              will be moved there, too
            - did the same for EGS7, PicassoII, MERLIN and Retina drivers,
              as well as Picasso96. All these drivers now are mutually
              exclusive - the only possible parallel use now is together
              with the CyberGraphX driver (since they fixed this nasty
             bug as with V1.27 or 1.28 AFAIK)
            - if you want to try parallel use nevertheless, just copy
              the files back from LIBS:svstorage/ to LIBS:svdrivers/
            - there's also the possibility to install these to
              LIBS:svdrivers/ and add their names to the file
              ENV:superview-library/svdrivers.exclude (respectively ENVARC:) ←
              so that you can try to add them on demand (use "+" fromout
              SVPrefs)
```

SuperView-Library 46 / 174

```
- Crashes: - there's a Picasso96API.library replacement for CyberGraphX,
             written by Steffen Haeuser. V20.0 does produce a couple
             of Enforcer hits when being opened.
              Solution: - remove it
                        - or remove Picasso96.svdriver
                        - upgrade to a bug-fixed version
 - Crashes: - SVPrefs: ensuring, that ppc.library already is in memory,
   #3
                      before superviewsupport.library does try to open it
                       (-> Frank Mariak)
V19.1 (18.9.1997) :
______
 - SVDrivers: - ECS, AGA: - (see there)
 - MISC:
              - added francais catalog and installer script
               by Julien Wilk (wilkj@esiee.fr)
                and Pascal Rullier <rullier@triade.fr>
 - Libs:
             - svsupport-lib: - (see there)
 - Docs:
             - updated ATO credits
 - PPC:
             - PPC modules 19.1 now are incompatible with ppc.library
               versions 44.8 and below. Since 18.x is incompatible
               with 44.9 and up, all previous buyers already did receive
               a free update, which again will work (44.20 recommended).
              - "DEEP_Decode24" PPC module had a bug, maybe this could
               have caused occasional crashes. Fixed.
              - due to PPC changes, bumped main library versions to
               19 resp. 11
V18.2 (5.9.1997) :
 - SVObjects: - PNG: - fixed some heavy bugs
V18.1 (20.8.1997) :
 - general 'clean-up' release
 - thus bumped version
 - ALL SVObjects: - recompiled with SAS/C V6.58
 - ALL SVDrivers: - recompiled with SAS/C V6.58
 - ALL SVOperators: - recompiled with SAS/C V6.58
 - SVDrivers:
                   - Picasso96, CyberGraphics,
                     PicassoII, Retina
                    - Picasso96 now 'out of beta stadium'
```

- SVObjects:

- SunRaster, SGI

SuperView-Library 47 / 174

- LIBRARIES: - superview.library,

superviewsupport.library:
recompiled with SAS/C V6.58

- LIBRARY: - if a SVObjects/Driver/Operator

can't be loaded (initialized),
the library now will give a
second try immediately, which
will help when memory is low
(when "avail flush" effect taking
place during library initialization)

- DOCS: - flushed, cleaned, fixed all revision histories

- updated 'press feeedback' section

- MISC: - fixed PCD.cpinfo description

- I am sick/tired/bored of getting bug reports, which simply are caused by *MCP* patching the system. It may be a nice tool, but all patches should work as reliable as the original... So the installer script now does ask you to disable the following MCP patches (as long as still being buggy) when using SuperView-Library:

new tooltypesreqtols patch

- onereq

- library search

- SetRGB32

Otherwise you may get: ramlib-crashes, odd address gurus, check instruction gurus or bad screen colors, ...

Thanks to the (big) number of people who told be about problems with MCP.

1.28 Printer.svobject

 \odot 1996-98 by Andreas R. Kleinert. FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Version : 4.8

Release Date : 27.09.1997

Description

~~~~~~~~

Printer.svobject is an external library module for superview.library.

It supports printing from any Screen (upto 256 Colors)

SuperView-Library 48 / 174

or graphics buffer (upto 256 Colors or 24 Bit).

The standard printer.device of AmigaOS does not support printing of 24 Bit graphics (rastports) upto version 3.0. There are two ways to pass this by:

- either dithering to 256 colors before printing the 24 Bit graphics (still looks ugly with standard printer drivers)
- OR installing TurboPrint V3 through V7 by IrseeSoft, which replaces printer.device greatly and besides improved 256 color printing also offers 24 Bit support
- OR installing the Studio Printer Software (Studio Professional II or any other Studio version like e.g. CanonStudio) by Wolf Faust, which consists of an external server program. Printer.svobject will write the graphics as either IFF-ILBM (upto 8 Bit) or PNG (24 Bit), and the Studio Server then will read the file, open its GUI and allow you to print it, while also being able to do some settings.

#### Printing without installed TurboPrint/Studio

Currently, all 24 Bit images will be dithered to 256 colors before printing (using the "Dither24Bit" operator).

Usually you get best results, when first applying "AnyTo24Bit" to a 256 color graphics and then call Printer.svobject from your application's DEVICE SVObject list.

#### Printing with TurboPrint/Studio being installed -----

When printing 24 Bit graphics, TurboPrint/Studio will automatically be used when available. You can do all the necessary settings fromout their GUIs.

### Credits

o TurboPrint V7 does support most of the available printers and makes these useable with the Amiga. It improves AmigaOS' native printer drivers as well as adding 24 Bit capability to its printer.device.

In Germany, TurboPrint can be obtained directly from IrseeSoft, but they'll as well be able to tell you a distributor near you:

IrseeSoft SPCS Meinrad-Spieß-Platz 2

D-87660 Irsee Voice: +49-(0)8341-74327 Germany Fax: +49-(0)8341-12042

IrseeSoft WWW page: http://www.irseesoft.com

IrseeSoft: mail@irseesoft.com

Or from any distributor. The official pricing as of December 1998

SuperView-Library 49 / 174

```
is been 149 DEM (no quarantee). Ask them for it.
  IrseeSoft also are the manufacturers of the Picture Manager
  professional image catalogization system.
  A CD-ROM containing catalogues of more than 25000 graphics from
  Amiga CD-ROMs as well as a full version of PM 2.0 and demo versions
  (german) of PMPro 4 and TurboPrint 5 is available for 29 DEM
  (no quarantee). It's the first one of a new CD-ROM series - the second
  one just has been released and does contain graphic catalogues for
  Aminet 1-16 and Aminet Set 1-4 CD-ROMs.
  Thanks to Florian Zeiler for providing TurboPrint.
o Studio Professional II does support many printers, too.
  In Germany, Studio 2.x can be obtained directly from arXon,
  but they'll as well be able to tell you a distributor near you:
       arXon GmbH
      Assenheimer Str. 17
      D-60489 Frankfurt
                              Voice: +49-(0)69-978410-26
                              Fax: +49-(0)69-978410-30
       Germany
  Or from any distributor. The pricing as of September 1997
  has been about 109 DEM (no guarantee). Ask them for it.
  Thanks to Wolf Faust for providing Studio and CanonStudio.
ControlPad-Switches
: "ENV:SuperView-Library/Printer.controlpad"
ControlPad-Name
ControlPad-Commands : - DENSITY = < density value for printing quality>
                        ; Amiga's printer device does allow seven
                        ; modes of printing density (1-7)
                        ; (not with TurboPrint)
                        ; default is: 3
History
~~~~~~
V4.8 (27.09.1997) :
 - now also supports TurboPrint for
 8 Bit modes as well as EHB/HAM
 - added support for Wolf Faust's Studio printer system
V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

# 1.29 Scanner.svobject

SuperView-Library 50 / 174

© 1996-98 by Andreas R. Kleinert.

FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Version : 4.8

Release Date : 14.08.1997

Description

~~~~~~~~~

Scanner.svobject is an external library module for superview.library.

It supports scanning images by using Andreas Günther's scanner.device, as supplied with the ScanQuix software package.

Currently, all scanned images are imported as 24 Bit.

#### Credits

~~~~~

ScanQuix currently supports more than 20 different scanner models:

| Vendor | Model                                                                  | Connection               |
|--------|------------------------------------------------------------------------|--------------------------|
| Epson  | GT-4000, GT-5000, GT-6000, GT-6500, GT-8500, GT-9000                   | SCSI, serial or parallel |
| HP     | ScanJet 2c, 2cx, 3c, 4c, 4p, 5p                                        | SCSI                     |
| Mustek | Paragon 600, 600 SP,<br>600 II SP, 800 SP,<br>800 II SP, 1200, 1200 SP | SCSI                     |
| Artec  | ViewStation A6000C,<br>A6000C Plus, AT-3, AT-6                         | SCSI                     |

#### It is available from:

RBM Computertechnik

Bernd Rudolf http://www.rbm.de/ScanQuix/

Kleinenberger Weg 2a info@rbm.de

D-33100 Paderborn Phone: +49-5251-16191-9 Germany Fax: +49-5251-640655

As of December 1997, ScanQuix 4 was publicly offered for 179 DM. For more information, please contact this company. For a special "Artec&ScanQuix3" package you may contact AB Union under: http://ourworld.compuserve.com/homepages/AB\_Union/

#### ControlPad-Switches

ControlPad-Name : "ENV:SuperView-Library/Scanner.controlpad"

ControlPad-Commands : - PUBSCREEN\_NAME = < PubScreenName >

; where the scanner drivers should open

; their windows (if not set or not available,

; the default Public Screen will be used).

SuperView-Library 51 / 174

```
History
~~~~~~
V4.8 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

# 1.30 AmiFIG.svobject

```
© 1996-98 by Andreas R. Kleinert.
(Also see notes under "Credits".)
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
            : 4.8
Release Date : 02.04.1998
Description
AmiFIG.svobject is an external library module for superview.library,
which needs any SVDriver with Bit-/Oneplane-Support, a working
GhostScript.svobject and an installed fig2dev executeable.
It supports importing AmiFIG/Xfig vector drawings as bitmapped graphics.
This is done by using fig2dev for conversion to Postscript (TM) files,
which then will be parsed using a working Ghostscript installation
with
              GhostScript.svobject
Alternatively, you now can redirect FIG handling to
              MetaView.svobject
AmiFIG.svobject will create a temporary file, which then will be
parsed through superview.library again.
Reading :
 (Any FIG drawings as long as the resulting Postscript (TM) commands
  are readable for Ghostscript).
Configuration
~~~~~~~~~~~
This FIG support module has been tested with:
 - the AmiFIG 1.1 port from Aminet: AmiFIG is (C) 1996 Andreas Schmidt
AND NOT YET, because of missing fig2dev:
 – the Xfig 1.9d amiga port from AmiNet, which has been done
 by Terje Pedersen (terjepe@login.eunet.no)
At first, you have to correctly install and configure Ghostscript
and
 GhostScript.svobject
```

After that you have to install AmiFIG/Xfig and either supply an AmigaDOS

SuperView-Library 52 / 174

search path to a directory, where the executable "fig2dev" is stored

```
(default), or explicitely specify path plus name of the program by
 the controlpad entry AMIFIG_PATH (see below).
 Where to DOWNLOAD from
 Aminet:gfx/edit/Amifig#?.lha (#?=version and CPU)
 ControlPad-Switches
  ~~~~~~~~~~~~~~~~
                     : "ENV:SuperView-Library/AmiFIG.controlpad"
 ControlPad-Name
 ControlPad-Commands : - STACKSIZE=<value>
                         ; stacksize to be used for calling GPlot,
                         ; increasing may help on crashes
                         ; default is: 32768
                        - AMIFIG_PATH=<fig2dev command path plus name>
                         ; how fig2dev is to be called
                         ; e.g. AMIFIG_PATH=Work:AmiFIG/fig2dev
                          ; default is: fig2dev
                        - STATUS=<ENABLED|DISABLED>
                         ; allows to disable this module - for example
                         ; to be able to use an other, program-specific
                         ; import-module for the same file format
 History
  ~~~~~
 V4.8 (02.04.1998) :
 - changed way of calling the program (SystemTagList), which may
 fix crashes on certain FIG graphics
 - added possibility to increase stacksize, when necessary (crashes ?)
 - now has a lower priority than MetaView.svobject which allows
 to redirect FIG file recognition (and processing). [see there]
 V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
1.31
 Degas.svobject
 © 1996-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Version
 : 4.7
 Release Date : 14.08.1997
```

It supports reading of Atari Degas files.

which needs any SVDriver with Oneplane-Support.

Degas.svobject is an external library module for superview.library,

Description

SuperView-Library 53 / 174

```
In detail these are :
 Reading:
 - uncompressed Degas PI1 320x200, 16 colors
 - uncompressed Degas PI2 640x200, 4 colors
 - uncompressed Degas PI3 640x400, 2 colors
 History
 V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
1.32 ILBM.svobject
 © 1994-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
 Version
 : 4.16
 Release Date : 16.02.1998
 Description
 ILBM.svobject is an external library module for superview.library,
 which needs any SVDriver with Bitplane-Support.
 It supports reading and writing of IFF-ILBM files.
 In detail these are :
 Reading:
 - IFF-ILBM uncompressed
 1..8/24 bit
 - IFF-ILBM CmpByteRun1 compressed 1..8/24 bit
 Writing:
 - IFF-ILBM uncompressed
 1..8/24 bit
 - IFF-ILBM CmpByteRun1 compressed 1..8/24 bit
 Reading/writing from/to ClipBoard is supported.
 ControlPad-Switches
  ~~~~~~~~~~~~~~~~~
                      : "ENV:SuperView-Library/ILBM.controlpad"
 ControlPad-Name
 ControlPad-Commands : - ANIM_BODIES
                          ; if set, ANIM files' ILBM-BODY chunk
                          ; (first frame) will be extracted when
                          ; such a file is encountered. Otherwise
                          ; anim.datatype may do that task later.
                          ; (not actually IFF-ILBM support: it's
                          ; IFF-ANIM support)
                        - DRACO
                          ; tries to avoid possible problems on
```

SuperView-Library 54 / 174

```
; the Draco computer (modeid generation)
  History
  ~~~~~
 V4.16 (16.02.1998) :
 - changed for new .svm style PPC modules
 V4.15 (16.11.1997) :
 - transparency information might not have been exported
 correctly after reading (V2 gfxbuffer instead of V3)
 V4.14 (14.08.1997) :
 - recompiled with SAS/C 6.58
1.33 PBM.svobject
 © 1996-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
 Version
 : 4.9
 Release Date : 16.02.1998
 Description
  ~~~~~~~~~~
  PBM.svobject is an external library module for superview.library,
  which needs any SVDriver with Oneplane-Support.
  It supports reading and writing of IFF-PBM files, which originally
  only were written by Deluxe Paint II for the PC, when saving
  chunky 256 Color graphics.
  In detail these are :
  Reading:
   - IFF-PBM uncompressed
   - IFF-PBM CmpByteRun1 compressed 8 Bit
  Writing:
   - IFF-PBM uncompressed
                                     8 Bit
                                           (less than 256 colors will be
   - IFF-PBM CmpByteRun1 compressed 8 Bit
                                            increased to 256 colors)
  Reading/writing from/to ClipBoard is supported.
  History
  ~~~~~~
 V4.9 (16.02.1998) :
 - changed for new .svm style PPC modules
```

SuperView-Library 55 / 174

```
V4.8 (14.08.1997) :
- recompiled with SAS/C 6.58
```

### 1.34 ACBM.svobject

```
© 1994-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 : 4.9
Version
Release Date : 14.08.1997
Description
~~~~~~~~~
ACBM.svobject is an external library module for superview.library,
which needs any SVDriver with Bitplane-Support.
It supports reading and writing of IFF-ACBM files.
In detail these are :
Reading :
- IFF-ACBM uncompressed 1..8 Bit
Writing:
 - IFF-ACBM uncompressed 1..8 Bit
Reading/writing from/to ClipBoard is supported.
History
~~~~~
V4.9 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

# 1.35 Datatypes support

Loading Graphics via DataTypes under OS3

```
In General
```

The library generally also accesses OS3-Datatypes, if none of the installed SVObjects was able to identify a specific graphics file format.

Usually by default only Datatypes of class "picture" will be accepted.

This means, no Samples, Texts, AmigaGuide File or whatever else will be loaded and displayed via superview.library - by default.

But it is possible to enable these also - see configuration section

SuperView-Library 56 / 174

for more information on how to change settings - so that for example introduction pictures of ANIMs may as well be loaded.

### Specific Problems

\_\_\_\_\_

As you may have expected, it is as well possible to replace single SVObjects by the corresponding Datatypes in case you think that the Datatype does work better or more reliable.

For temporarily enabling this, you would just have to "Remove" the SVObject and load the Datatype.

For permanently enabling this, you would have to delete the SVObject from "LIBS:svobjects".

But remember, that DTs in general cannot export 24 bit Data and are not able to save any graphics (other than as IFF-ILBM).

Ralph Schmidt's picture.datatype V43 does allow loading of 24 bit pictures by enhancing the datatype system with additional functionality. To be able using these features with SuperView, you need a working installation of picture.datatype V43 (with ECS/AGA you'll also need a version of cyberncg.library, which had been removed from newer pic-dt 43 distributions).

The picture.datatype V43 which is coming with the Picasso96 Workbench Emulation RTG Software should work as well - any problems with this one should be reported to its author in the first place, though.

This also applies to any other, future picture.datatype V43 clones.

# 1.36 PCX.svobject

© 1994-98 by Andreas R. Kleinert.

FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Supports powerUP (TM).

Version : 4.9

Release Date : 16.02.1998

Description

~~~~~~~~~

PCX.svobject is an external library module for superview.library, which needs any SVDriver with Bit-/Oneplane-Support.

It supports reading and writing of PCX files. In detail these are :

Reading:

2-256 Colors, 24 bit. In detail:

- PCX V2.5 upto 16 Colors (supports 4/8 color EGA/VGA palette)
- PCX V2.8a upto 16 Colors (supports 4/8 color EGA/VGA palette)
- PCX V2.8b upto 16 GrayScales

SuperView-Library 57 / 174

```
- PCX V3.00 upto 256 Colors
 - PCX V2.5 - V3.00 with 24 bit Data (see Remarks !)
 Writing:
 Depending on the Colordepth of the source the following is written:
 Source Colors
 Version
 Type
 Destination Colors
 2 .. 16
 PCX V2.8a
 planar bitmap
 16
 32 .. 256
 PCX V3.00
 256
 chunky pixel
 (24 bit)
 PCX V3.00
 RGB planar
 (24 bit)
 For 2-256 Colors It is always tried, to write the files RLE-encoded,
 but if encoding is ineffective (output data nearly as large or even
 larger than input data), the files will be written unencoded.
 24 bit files will currently only be written unencoded.
 History
  ~~~~~
  V4.9 (16.02.1998) :
   - changed for new .svm style PPC modules
  V4.8 (14.08.1997) :
   - recompiled with SAS/C 6.58
1.37 Spectrum.svobject
  © 1998 by Andreas R. Kleinert.
  FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
  Version
            : 4.1
  Release Date : 30.07.1998
  Description
  Spectrum.svobject is an external library module for superview.library,
  which needs any SVDriver with Oneplane-Support.
  It supports reading of ZX Spectrum Graphics files.
  In detail these are :
  Reading:
```

# Note

Format

normal

Dimensions

256x192

Only files with a length of 6912 bytes plus the filename extension ".scr" will be recognized.

Colors

16

SuperView-Library 58 / 174

```
History
~~~~~
V4.1 (30.07.1998) :
- first release
```

# 1.38 SVG.svobject

```
© 1994-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 : 4.8
Version
Release Date : 16.11.1997
Description
SVG.svobject is an external library module for superview.library,
which needs any SVDriver with Bit-/Oneplane-Support.
It supports reading and writing of SVG Graphics files, which is
SuperView-Library's own graphics file format with XPK support.
In detail these are :
Reading:
- SVG ONEPLANE 8/24 bit
 BITPLANE 1..8 Bit
Writing:
- SVG ONEPLANE 8/24 bit
 BITPLANE 1..8 Bit
ControlPad-Switches
~~~~~~~~~~~~~~~~~~~
                : "ENV:SuperView-Library/SVG.controlpad"
ControlPad-Name
ControlPad-Commands : - PACKMETHOD=<xxxx>
                       ; if this one is specified, it is tried to
                       ; pack the resulting file with the specified
                       ; XPK-Packer. If this fails, the file keeps
                       ; unpacked.
File Format Information
As "Aminet:util/dtype/akSVG43x.lha" there's a separate package available,
which consists of a "SVG.datatype" for applications not using
SuperView-Library,
             the description of the file format
a conversion tool "AnyToSVG" (using Datatypes upto 24 Bit).
```

SuperView-Library 59 / 174

```
History
~~~~~
V4.8 (16.11.1997) :
 - fixed possible enforcer hit (writing XPK)
V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

# 1.39 The SVG Graphics File Format Specification

```
= The SVG Graphics File Format = - Version 1, draft version: 03.01.1997
```

File Format Information

Pictures in the "SVG Graphics File Format" consist of two parts: a header and an attached xpk-packed or unpacked data file. Both parts are put into one single file.

Construction (all fields in Motorola BYTE order):

ID	UBYTE[18]	"SVG Graphics File" + 0-Byte
Version	UWORD	always 1 yet
GfxDataOffset	ULONG	header length (depends on version)
LeftEdge	ULONG	as with e.g. ILBM
TopEdge	ULONG	•••
Width	ULONG	•••
Height	ULONG	•••
ColorDepth	ULONG	used colors as x of 2^x
ViewMode32	ULONG	32 Bit Amiga ViewMode
PixelBits	UBYTE	1, 8, 24 (future: 16, 32)
PixelPlanes	UBYTE	# of planes with PixelBits
BytesPerLine	ULONG	bpl of a PixelPlane
ColorMap	UBYTE [256][3]	unused, if > 256 Colors (zero-ed)
	Version GfxDataOffset LeftEdge TopEdge Width Height ColorDepth ViewMode32 PixelBits PixelPlanes BytesPerLine	Version UWORD  GfxDataOffset ULONG  LeftEdge ULONG  TopEdge ULONG  Width ULONG  Height ULONG  ColorDepth ULONG  ViewMode32 ULONG  PixelBits UBYTE  PixelPlanes UBYTE  BytesPerLine ULONG

After that either follows XPK compressed data or uncompressed data, which can be detected by the leading chars "XPK" or "PP20" for packed data at GfxDataOffset (relative to beginning of the file).

Please note, that with upto 256 colors (Colordepth <= 8) it has to be checked, whether the graphics actually is EHB or HAM. Use the Viewmode32 field for these assumptions when reading, and maybe OR with HAM\_KEY or EHB\_KEY when saving.

#### Note:

\_\_\_\_

Actually used and supported by current software are only the following:

<sup>&</sup>quot;Pixelbits" and Planes do allow a lot of combinations.

SuperView-Library 60 / 174

Bits	Planes	Depth	Content
1	18		(unaligned Bitmaps with 2256 colors)
8	1	18	(chunky Bitmaps with 2256 colors)
24	1	24	(24 Bit RGB Bitmaps with 8:8:8 RGB)

So 24 Bit Data should not be saved planewise, but as 24 Bit RGB instead.

If you ever should save any other data, please avoid any planar configurations and respect the following rules for RGB data chunks:

Bits	Planes	Depth	Content
16	1	15/16	(15/16 Bit Bitmap with 5:5:5:1 RGB0/A)
32	1	24/32	(24/32 Bit RGB Bitmaps with 8:8:8:8 RGB0/A)
48	1	48	(48 Bit RGB Bitmaps with 16:16:16 RGB)
64	1	48/64	(48/64 Bit RGB Bitmaps with 16:16:16:16 RGB0/A)
et	С		

Note, that an alpha channel can only be correctly identified, when "ColorDepth" is handled as an indicator, whether there actually is one, or not. Programs not supporting alpha channels should simply ignore the color depth and interpret "Bits=16 and Planes=1" as 5:5:5:0 RGB and "Bits=32 and Planes=1" as 8:8:8:0 RGB and so on...

Planar configuration actually only was thought for support of 2..256 color Bitmap contents. We all new, that actually 24 or more bitplanes are nearly unuseable and actually ugly to handle.

So please respect the "Planes" variable only being valid for values between 1..8 and only, if "Bits=1" has been set, also note, that with "Planes=1..8" you must set "ColorDepth=Planes", since other than with 8 Bit chunky there is no support of unused planes.

### 1.40 GPlot.svobject

© 1996-98 by Andreas R. Kleinert.

FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Version : 4.8

Release Date : 02.04.1998

Description

~~~~~~~~

GPlot.svobject is an external library module for superview.library, which needs any SVDriver with Bit-/Oneplane-Support, a working GhostScript.svobject and an installed GPlot executeable.

It supports importing CGM metafile vector drawings as bitmapped graphics. This is done by using gplot for conversion to Postscript (TM) files, which then will be parsed using a working Ghostscript installation with

GhostScript.svobject

Alternatively, you now can redirect CGM handling to

SuperView-Library 61 / 174

MetaView.svobject

GPlot.svobject will create a temporary file, which then will be parsed through superview.library again.

#### Reading:

(Any CGM drawings as long as the resulting Postscript (TM) commands are readable for Ghostscript - especially the Times-Roman font has to be available for Ghostscript).

### Configuration

~~~~~~~~~~~~

This CGM/GPlot support module has been tested with the GPlot 4.3b2al port from Aminet:gfx/conv. GPlot is (C) 1987 by the Pittsburgh Su Center, the original version had been done by Phil Andres, Amiga port by Michael Cheng in 1996.

At first, you have to correctly install and configure Ghostscript and

GhostScript.svobject

After that you have to install GPlot and either supply an AmigaDOS search path to a directory, where the executable "GPlot" is stored (default), or explicitely specify path plus name of the program by

the controlpad entry GPLOT\_PATH (see below).

Please note, that the resulting Postscript (TM) files, which then will be passed through Ghostscript, definitely do contain a reference to the font "Times-Roman" (in Ghostscript's FONTMAP this is redirected to the font file ptmr.gsf, which has to be present in the font directory(ies) specified in the environment variable GS\_LIB). With the Ghostscript version I had for testing, the font support did not work, due to a bug (or configuration fault ;-) of Ghostscript.

So, please make sure, that this font is present - otherwise an error message like "file not found" may appear.

#### ControlPad-Switches

ControlPad-Name : "ENV:SuperView-Library/GPlot.controlpad"

ControlPad-Commands : - STACKSIZE=<value>

- \_ CTACKCI7E-/110>
  - ; stacksize to be used for calling GPlot,
  - ; increasing may help on crashes
  - ; default is: 32768
- GPLOT\_PATH=<gplot command path plus name>
  - ; how gplot is to be called
  - ; e.g. GPLOT\_PATH=Work:GPlot/GPlot

SuperView-Library 62 / 174

```
; default is: GPlot
 - STATUS=<ENABLED|DISABLED>
 ; allows to disable this module - for example
 ; to be able to use an other, program-specific
 ; import-module for the same file format
 History
  ~~~~~~
 V4.8 (02.04.1998) :
  - changed way of calling the program (SystemTagList), which should
    fix some crashes on certain CGM graphics
     (-> Steven Taylor)
   - added possibility to increase stacksize, when necessary (crashes ?)
   - now has a lower priority than MetaView.svobject which allows
    to redirect CGM file recognition (and processing). [ see there ]
 V4.7 (14.08.1997) :
   - recompiled with SAS/C 6.58
1.41 BMP.svobject
 © 1994-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
 Version
              : 4.15
 Release Date : 01.08.1998
 Description
 BMP.svobject is an external library module for superview.library,
 which needs any SVDriver with Bit-/Oneplane-Support.
 It supports reading and writing of Windows (TM) and OS/2 (TM)
 BitMap files (BMP). Not all derivates might be supported, though.
 Extraction of Bitmaps from RIFF-BMP files (DIB) also is possible.
  In detail these are :
 Reading:
  Windows BMP: - unencoded in 1, 4, 8, 24, 32 bit colordepth
                                   4, 8
                 - RLE-encoded in
                                                bit colordepth
  OS/2 1.x BMP: - unencoded in 1, 4, 8, 24
                                                bit colordepth
 Writing:
  Depending on the Colordepth of the source the following is written:
  Source Colors
                   Version
                                 Type
                                                   Destination Colors
```

SuperView-Library 63 / 174

```
BMP (misc) packed chk. pix.
                                                      2
  4 .. 16
                 BMP (misc)
                              packed chk. pix.
                                                      16
 32 .. 256
                  BMP (misc)
                              chunky pixel
                                                     256
 (24 bit)
                 BMP (misc)
                              RGB pixel
                                                  (24 bit)
History
V4.15 (01.08.1998) :
 - there are BMPs around, which don't just have a zero bitmap size
   given, but even a completely wrong one. Did a workaround
   by adding a plausibility check (24 bit only, yet - too
   difficult for the others, since compression doesn't allow
   to do guesses, here)
   (-> Don Paul)
V4.14 (28.07.1998) :
 - fixed bug in memory handling (avoid freeing some data twice);
   did not occur yet
V4.13 (03.04.1998) :
 - added support for 32 bit files (some strange Windows backdrops)
   (-> Andreas Friedrich)
 - fixed reading of 4 and 8 bit RLE compressed graphics;
   IMHO all the available BMP file format docs are contradictory
  in parts, some even really buggy
   (-> Waldemar Scheu sent some graphics that did not work before)
 - reading of OS/2 1.x BMPs did not work due to another error
   in the BMP specs and a few errors in my code
   (-> Waldemar Scheu sent a graphics that did not work before)
 - etc.
V4.12 (16.02.1998) :
 - changed for new .svm style PPC modules
V4.11 (23.12.1997) :
 - long-standing bug: a 4 bit graphics (16 colors) with an odd width would
   have been distorted when writing. Fixed for 68k (temporarily fixed for
   PPC by falling back to 68k code for this rare case).
V4.10 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

### 1.42 Amilcon.svobject

```
© 1997 by Andreas R. Kleinert. FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
```

SuperView-Library 64 / 174

Version : 4.2 Release Date : 08.12.1997 Description Amilcon.svobject is an external library module for superview.library, which needs any SVDriver with Bitplane-Support. It supports reading and writing of Amiga Icon (.info) files. In detail these are : Reading: - plain 4/8 color icons - 16 color icons with MagicWB palette When newicon.library is present, it will be used for reading icons instead of icon.library. This means, the following types of icons are supported, too: - NewIcons with a max. size of 93x93 and max. 256 colors Writing: - plain 4/8 color icons, using BEST PEN color adjustment - 16 color icons with MagicWB palette, using BEST PEN color adjustment When newicon.library is present, it will be used for writing icons instead of icon.library - as long as the icon size is smaller or equal than 93x93. With newicon.library 40.1 also a minimum of 32 colors is required to actually activate the "newicon" mode. This means, the following types of icons are written, too: - NewIcons with a max. size of 93x93 and 32..256 colors, additionally containg the corresponding plain or MagicWB icon data Note Reading explicitely needs to be enabled by a Controlpad setting switch! ControlPad-Switches : "ENV:SuperView-Library/Amilcon.controlpad" ControlPad-Name ControlPad-Commands : - ICON\_DEPTH=<colordepth> ; Depth of icon to be saved. ; Also: WB (depth=2-3, 4-8 colors) or ; MagicWB (depth=4, 16 colors) ? ; default is: 2 - ICON\_TYPE=<DISK|DRAWER|TOOL|PROJECT|GARBAGE> ; Type of icon to be saved. ; default is: PROJECT - ICON\_TOOL=rogram name> ; The default tool of the icon to be saved. ; default is: "InsertHere" ;)

- WRITE\_NEWICON=<ON|OFF>

SuperView-Library 65 / 174

```
; Write NewIcons, when there is newicon.library
; available ?
; Default is: ON
- READ_SUPPORT=<ON|OFF>
; Allow reading of icons at all ?
; Default is: OFF

History
-----
V4.2 (8.12.1997) :
- fixed bug, which could make the system crash (broken semaphore ?)
- also, now opening newicon.library when needed, no longer in startup-code (would have caused a crash when e.g. running SnoopDos3 in parallel)

V4.1 (13.11.1997) :
- first version
```

# 1.43 Winlcon.svobject

```
© 1994-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
            : 4.7
Release Date : 14.08.1997
Description
~~~~~~~~~~
WinIcon.svobject is an external library module for superview.library,
which needs any SVDriver with Oneplane-Support.
It supports reading of W*nd*ws V3.x (TM) Icon files.
In detail these are :
Reading:
 - WinIcon files with _exactly_ 16 Colors
 (more than one Icon per file should work, but hasn't been tested yet.)
History
V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

# 1.44 FBM.svobject

```
© 1994-98 by Andreas R. Kleinert. (Also see notes under "Credits".) FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
```

SuperView-Library 66 / 174

```
Version
 : 4.7
 Release Date : 14.08.1997
 Description
 FBM.svobject is an external library module for superview.library,
 which needs any SVDriver with Oneplane-Support.
 It supports reading and writing of FBM (*nix) files.
 In detail these are :
 Reading:
 - FBM 8 Bit x 1 Plane: 2..256 Colors/256 Grayscales
 - FBM 8 Bit x 3 Planes: 24 bit
 Writing:
 - FBM 8 Bit x 1 Plane: 2..256 Colors/256 Grayscales
 - FBM 8 Bit x 3 Planes: 24 bit
 Following to the specifications, a 2..128 color file takes as much
 space as a 256 color file: always 8 Bits are written.
 Only the colormap is sized differently for different colordepths.
 History
  ~~~~~
  V4.7 (14.08.1997) :
   - recompiled with SAS/C 6.58
1.45 Limbo.svobject
  © 1996-98 by Andreas R. Kleinert.
  (Also see notes under "Credits".)
  FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
  Supports powerUP (TM).
  Version
  Release Date : 02.04.1998
  *** THIS ONE IS REALLY EXPERIMENTAL - IT WORKS, BUT REQUIRES
      A LOT OF MEMORY AND A FAST PROCESSOR.
      DO NOT SAVE IMPORTANT DATA AS LIMBO/LMB. IT'S HIGHLY LOSSY! ***
  Description
  Limbo.svobject is an external library module for superview.library,
  which needs any SVDriver with Oneplane-Support and an installed
  Limbo 4.0 executeable.
  It supports importing Limbo 4.0 fractal-compressed bitmapped graphics.
```

SuperView-Library 67 / 174

This is done by using Limbo for conversion of LMB files to temporary PNM files, which then will be parsed through superview.library again. Exporting is supported by creating temporary PNM files, which then will be converted to LMB files via Limbo.

A VMEM: assignment is needed to be present to allow doing the temporary file and directory management.

So it supports reading and writing of Limbo 4.0 files. In detail these are:

#### Reading:

(Limbo 4.0 fractal-compressed files, as far as supported by the used Limbo program.)

### Writing:

(Any input will be converted to 24 Bit, which then will be converted to Limbo 4.0 fractal-compressed files, by the Limbo program.)

### Configuration

~~~~~~~~~~~

This Limbo support module has been tested with the Limbo 4.0 port from Aminet:gfx/conv, which was based on a version developed by Carsten Frigaard, Jess Gade, Thomas Therp Hemmingsen and Torben Sand in 1993/94 on Aalborg University, Denmark.

At first you have to install Limbo by simply copying it into a directory where you like it to reside.

You also have to either supply an AmigaDOS search path to a directory, where the executable "Limbo.68000" is stored (default), or explicitely specify path plus name of the program by the controlpad entry LIMBO_PATH (see below).

There's now also a PPC version available, which can be utilized when the LoadSegPatch of ppc.library has been installed (so that the ELF modules can be loaded and started as regular programs).

```
Where to DOWNLOAD from
```

Aminet:gfx/conv/Limbo.lha (68k version)

Aminet:gfx/conv/PPCLimbo.lha (PPC version; with LoadSegPatch, only)

ControlPad-Switches

~~~~~~~~~~~~~~~~~~

ControlPad-Name : "ENV:SuperView-Library/Limbo.controlpad"

ControlPad-Commands : - STACKSIZE=<value>

- ; stacksize to be used for calling GPlot,
- ; increasing may help on crashes
- ; default is: 32768
- LIMBO\_PATH=<Limbo command path plus name>
  - ; how Limbo is to be called
  - ; e.g. LIMBO\_PATH=Work:Limbo/Limbo.68030.881
  - ; default is: Limbo.68000

SuperView-Library 68 / 174

```
- STATUS=<ENABLED|DISABLED>
 ; allows to disable this module - for example
 ; to be able to use an other, program-specific
 ; import-module for the same file format
 ; DECODING settings
  ; **********
- DECODE_ITERATIONS=<number>
 ; option -i of Limbo 4.0
 ; default is: 6
- EXPANSION_LEVEL=<number>
  ; option -1 of Limbo 4.0
 ; default is: 0
- DECODE_VERBOSE=<ON|OFF>
 ; Should decoding output be sent to stdio ?
 ; default is: OFF
 ; ENCODING settings
  ; **********
- EXPANSION LEVEL=<number>
 ; option -1 of Limbo 4.0
  ; default is: 0
- MIN_RANGE_BLOCKSIZE = < number >
 ; option -b of Limbo 4.0
 ; default is: 4
- DOMAIN_SLIDE_BLOCKSIZE=<number>
  ; option -d of Limbo 4.0
  ; default is: 8
- MIN_COMPARE_DOMAIN_BLOCKS=<number>
 ; option -m of Limbo 4.0
  ; default is: 4
- MAX_COMPARE_DOMAIN_BLOCKS=<number>
 ; option -s of Limbo 4.0
  ; default is: 10
- FEATURE_SPACE_DIMS=<number>
 ; option -f of Limbo 4.0
  ; default is: 3
- GRID_DIV_RES=<number>
 ; option -r of Limbo 4.0
  ; default is: 1000
- QUADTREE_LEVEL=<number>
  ; option -n of Limbo 4.0
  ; default is: 0
- TRESHOLD_SPLIT=<number>
 ; option -Tm of Limbo 4.0
  ; default is: 100
- TRESHOLD_CLASS=<number>
 ; option -Te of Limbo 4.0
  ; default is: 50
- TRESHOLD_POST=<number>
 ; option -\text{Tp} of Limbo 4.0
  ; default is: -1
- ENCODE_VERBOSE=<ON|OFF>
 ; Should encoding output be sent to stdio ?
  ; (recommended, since endocing is
 ; _extremely slow_)
  ; default is: ON
```

SuperView-Library 69 / 174

```
History
  ~~~~~
 V4.9 (02.04.1998) :
 - changed way of calling the program (SystemTagList), which may
 help to avoid crashes under certain circumstances (reading and writing)
 - added possibility to increase stacksize, when necessary (crashes ?)
 (reading and writing)
 V4.8 (14.08.1997) :
 - recompiled with SAS/C 6.58
1.46 PNM.svobject
 © 1994-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Version
 : 4.9
 Release Date : 03.10.1998
 Description
 PNM.svobject is an external library module for superview.library,
 which needs any SVDriver with Oneplane-Support.
 It supports reading and writing of PNM (*nix) files.
 In detail these are :
 Reading:
 All binary (non-ASCII) derivates of the PNM format will be read
 (P4/P5/P6), non-binary (ASCII) derivates are not supported (P1/P2/P3).
 - PBM (P4) Black & White
 - PGM (P5)
 256 Grayscales
 - PPM (P6)
 24 bit TrueColor
 Writing:
 - PGM (P5) 256 Grayscales
 - PPM (P6) 24 bit Truecolor
 Writing graphics as binary 24 bit PPM data (P6) is the
 only way to prevent color information from getting lost.
 ControlPad-Switches
 ControlPad-Name : "ENV:SuperView-Library/PNM.controlpad"
 ControlPad-Commands : - SUPPRESS_HEADER
 ; setting this keyword will suppress
 ; writing the PNM header for P5/P6
 ; files, which actually will generate
```

SuperView-Library 70 / 174

```
; a RAW data file, which cannot be loaded
 ; with superview.library again, but may be
 ; used for different purposes
 ; Default: (not set)
 History
 V4.9 (03.10.1998) :
 - fixed problem concerning graphics with multiple comment lines
 (-> Waldemar Scheu)
 V4.8 (06.07.1998) :
 - fixed small, bug source in writer code (obviously not a problem
 with SAS/C, but...)
 - fixed history: was V4.7, now is 4.8
 V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
1.47 PNG.svobject
 © 1996-99 by Andreas R. Kleinert.
 (Also see notes under "Credits".)
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
 : 4.23
 Version
 Release Date : 20.02.1999
 Description
  ~~~~~~~~~~
 PNG.svobject is an external library module for superview.library,
 which needs any SVDriver with Oneplane-Support.
 It supports reading of Portable Network Graphics (PNG - pronounce
 it "PiNG", if you like ;-) files.
  In detail these are :
 Reading:
  - 8 Bit color mapped files
   - any grayscaled images, 16 Bit derivates scaled down to 8 Bit
  - True color files (24/48 Bit, alpha channel ignored) as 24 bit
     (so 48 Bit 16:16:16 will be cut down to 24 Bit 8:8:8)
    So the following types of PNG images (all valid ones) should be
    imported in the described way:
      Bit depths
                   Interpretation
       1,2,4,8,16
                    pixels are grayscaled samples
```

SuperView-Library 71 / 174

```
8,16
                  pixels are R,G,B triple samples
     1,2,4,8
                  pixels are palette indices
       (plus variations with - here ignored - alpha channel)
Writing:
 - 8 Bit color mapped files
 - True color files (24 Bit)
ControlPad-Switches
: "ENV:SuperView-Library/PNG.controlpad"
ControlPad-Name
ControlPad-Commands : - PNG8_TRANSPARENCY=<ON|OFF>
                        ; whether 8 Bit PNGs should contain
                        ; transparency information
                        ; Default: OFF
                      - PNG8 TRANSPARENT COLOR=<0..255>
                        ; Default color to be enabled and set
                        ; (graphics control extension block)
                        ; Default: 0
                      - Z COMPRESSION=<0..9>
                        ; allows changes in compression/speed.
                        ; 0 results in uncompressed data, 9 compresses
                        ; best, but increases decompression time.
                        ; Default: 6
                      - SAVE_INTERLACED=<ON|OFF>
                        ; Save image as interlaced (progressive) ?
                        ; Default: OFF
History:
~~~~~~~
V4.23 (20.02.1999) :
 - upgraded to libpng 1.0.3
V4.22 (06.09.1998) :
 - smaller, faster
V4.21 (30.07.1998) :
 - all changes: fixed for 68k with this version, fixed for PPC in PPC-V21.6
 - upgraded to zlib 1.1.3
 - loading _interlaced_ alpha channel images (e.g. 32 bit = 24 bit
 plus 8 bit alpha channel) would not have worked correctly
 - long-standing bug: gray scaled images (in 8 or 16 bit) _with_
 8 or 16 bit alpha channel would not have been read correctly;
 some strange kind of colored true color image would have been
 exported. On the PPC side, even crashes (through damaged memory list)
 were possible. Perhaps the same problems could have happened with
 8 bit colormapped files plus alpha channel, not sure
V4.20 (27.06.1998) :
```

SuperView-Library 72 / 174

```
- upgraded to libpng 1.0.2
 - there was a small bug in writing PNGs:
 files with 1..256 colors always would have been
 written as 8 bit (256 color) files, resulting in
 slightly bigger file sizes with 1..128 graphics.
 Now you may save some more bytes...
 (-> Christian Beck, originally concerning PNG-Box)
 - fixed bug introduced with PPC support;
 in 68k mode (loader) an already opened file
 handle would have been overwritten another time,
 thus the first one never would have been
 released - thus the opened PNG file could
 no longer be deleted
 (-> Torsten Jung)
V4.19 (30.03.1998) :
 - upgraded to libpng 1.0.1 and zlib 1.1.2
 - using libmoto.a for PPC part now (faster)
V4.18 (16.02.1998) :
 - changed for new .svm style PPC modules
V4.17 (11.02.1998) :
 - added support for PPC native ELF plugin module, allowing
 to speed up loading and saving incredibly with powerUP (TM)
 - PNG core now single-threaded due to problems with reentrancy
 - upgraded to libpng 0.99 and zlib 1.0.8
V4.16 (23.12.1997) :
 - faster, smarter
V4.15 (05.09.1997) :
 - 'interlaced' switch was ignored, when there was no
 'z_compression' switch
 - saving progressive PNG did not work at all
 - writing transparent PNG was heavily buggy (wrong/no chunk content)
 - reading transparent PNG was heavily buggy (wrong/no chunk content)
V4.14 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

## 1.48 C64.svobject

```
© 1994-98 by Andreas R. Kleinert.

(Also see notes under "Credits".)

FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Version : 4.8

Release Date : 09.07.1998
```

SuperView-Library 73 / 174

```
Description
 C64.svobject is an external library module for superview.library,
 which needs any SVDriver with Oneplane-Support.
 It supports reading of C64 Graphics files (Koala, Doodle).
 In detail these are :
 Reading :
 Format
 Dimensions
 Colors
 320x200
 Doodle
 2/16
 Koala
 160x200 -> 320x200
 4/16
 History
  ~~~~~
 V4.8 (09.07.1998) :
  - "Doodle" was reported to be "Koala"
 V4.7 (14.08.1997) :
  - recompiled with SAS/C 6.58
1.49 CDR.svobject
 © 1996 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Version
 Release Date : 14.08.1997
 Description
 ~~~~~~~~~
 CDR.svobject is an external library module for superview.library,
 which needs any SVDriver with Bit-/Oneplane-Support and BMP.svobject
 to be present.
 It supports reading of the previews which may be part of CorelDraw
 .CDR files (e.g. with version 4) - these are related with plain
 Windows BMP files, so that CDR.svobject will extract the graphics data,
 create a temporary file, write it as a BMP file and then parse it
 through superview.library again.
 (See documentation of BMP.svobject for which
 BMP derivates currently are supported).
 Reading:
 (Any contained preview, as long as the specific contained BMP derivate
 is supported by superview.library).
 History
```

SuperView-Library 74 / 174

```
V4.7 (14.08.1997) :
- recompiled with SAS/C 6.58
```

# 1.50 CVP.svobject

```
© 1998 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
Release Date : 07.06.1998
Description
~~~~~~~~~~
CVP.svobject is an external library module for superview.library,
which needs any SVDriver with Oneplane-Support.
It supports reading of CVP (passphoto) files.
In detail these are :
Reading:
 24 bit CVP files (taken with a video camera, output done with
 a video printer, put onto a disk)
Notes
CVP files must have the extension ".CVP" and a size of exactly
786432 bytes - otherwise they won't be recognized.
Credits
~~~~~~
Thanks to Manfred Hoffmann for a sample CVP graphics and
an arexx script that built the base for my own decoder.
History
~~~~~~
V4.1 (07.06.1998) :
 - first release
```

# 1.51 IMG.svobject

```
© 1994-98 by Andreas R. Kleinert.

FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Version : 4.8

Release Date : 04.10.1998

Description
```

SuperView-Library 75 / 174

```
IMG.svobject is an external library module for superview.library,
  which needs any SVDriver with Bitplane-Support.
  It supports reading of IMG (GEM/Metafile) files.
  In detail these are :
  Reading :
   - IMG (16 byte header) grayscaled (1..8 bits = 2..256 scales)
   - IMG (18 byte header) grayscaled (1..8 bits = 2..256 scales)
  History
  ~~~~~
 V4.8 (04.10.1998) :
 - removed some unused code
 - fixed memory handling
 V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
1.52 TIFF.svobject
 © 1994-99 by Andreas R. Kleinert.
 (Also see notes under "Credits".)
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
 Version : 4.14
 Release Date : 03.01.1999
 Description
 TIFF.svobject is an external library module for superview.library,
 which needs any SVDriver with Bit-/Oneplane-Support.
 It supports reading and writing of TIFF-files (V5.0).
 In detail these are :
 Reading :
 Compression types (as far as known):
 - uncompressed
 - CCITT Group 3 Fax
 - NeXT (2-bit RLE) - CCITT/3 1D (Huffman RLE)
 - CCITTRLEW (word-aligned uncompressed)
 - Mac PackBits
 - JPEG (decompression not possible)
 - Thunderscan RLE
 ...and maybe more. LZW is not supported, though.
 Bit depths:
 Planes => resulting Bit Depth
 Pixelbits
```

SuperView-Library 76 / 174

```
1
 1
 (Mac Packbits only)
 Х
 Х
 12 (imported as 24 Bit)
 4
 3
 8
 1
 8
 (256 colors or gray)
 8
 3
 24
 8
 4
 24
 (24 Bit + alpha Channel)
Writing:
 Depth
 written as
 <= 256 colors
 Motorola (MM), None, 8, 1
 (24 bit)
 Motorola (MM), None, 8, 3
ControlPad-Switches
~~~~~~~~~~~~~~~~~~~~
                  : "ENV:SuperView-Library/TIFF.controlpad"
ControlPad-Name
ControlPad-Commands : - PAGENUMBER=<0..n>
                        ; number of image to be displayed
                        ; (e.g. for TIFFs with image directories
                        ; or multi-page FAX documents)
History
~~~~~
V4.14 (03.01.1999) :
 - added multi-image support, intentionally for multi-page
 FAX documents
 (-> Martin Ruston)
V4.13 (06.09.1998) :
 - smaller, faster
V4.12 (30.03.1998) :
 - upgraded to libtiff 3.4beta037
 - no more debugging output; should fix some strange crashes
 (-> thanks to Steve Taylor for pointing me to this)
 - 68k TIFF loader was almost completely screwed up;
 with most images it would have been caught in an endless
 loop and crashed very quickly
V4.11 (16.02.1998) :
 - changed for new .svm style PPC modules
V4.10 (11.02.1998) :
 - added powerUP support (optional)
 - single-threaded
V4.9 (14.08.1997) :
```

SuperView-Library 77 / 174

- recompiled with SAS/C 6.58

## 1.53 EPS.svobject

© 1994-98 by Andreas R. Kleinert. (Also see notes under "Credits".) FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Version : 4.8

Release Date : 16.11.1998

### Description

~~~~~~~~~

EPS.svobject is an external library module for superview.library, which needs any SVDriver with Bit-/Oneplane-Support and TIFF.svobject (respectively GhostScript.svobject) to be present.

It allows two operations, depending on controlpad preferences settings:

- extraction of the trailers/previews which may be part of EPS(F) files. This usually will be TIFF graphics, but it makes no matter, which file format actually is included, because EPS.svobject will create a temporary file, which then will be parsed through superview.library again.

(See documentation of TIFF.svobject for which TIFF derivates currently are supported).

- extraction of the Postscript (TM) part of EPS(F) files, which then, in form of a temporary file, will be parsed through superview.library (and perhaps also GhostScript.svobject) again.

### Reading :

- Any contained trailers/previews/thumbnails, as long as the specific contained file format - if any - is supported by superview.library
- Postscript (TM) as far as supported by the installed Ghostscript implementation

### Writing:

- EPS files with Postscript (TM) image content, without TIFF header (only from 24 bit sources -> use the AnyTo24Bit operator).

The graphics will NOT be vectorized – instead a bitmap-like representation of it will be translated into Postscript (TM) format.

### Remarks

~~~~

Please note, that the Encoding Routines of the Library are not (yet) fully re-entrant, so that only one Task may Encode a picture at a time. The Library itself manages it, that the other Task has to Delay() until the Encoding Routines are "free" again.

ControlPad-Switches

SuperView-Library 78 / 174

```
: "ENV:SuperView-Library/EPS.controlpad"
ControlPad-Name
ControlPad-Commands : - EXTRACTMODE=<HEADER|PS>
 ; Determines, whether the preview image or
 ; the Postscript (TM) part should be extracted,
 ; while parsing the Postscript (TM) part requires
 ; a working Ghostscript installation with
 ; GhostScript.svobject being correctly configured
 ; default is: HEADER
 - NO_EPS_HEADER
 ; if this option is set, the EPS file will be
 ; written without EPS header, thus turn into a
 ; plain P*stscript file; useful for sending
 ; it directly to the printer or for use with % \left(1\right) =\left(1\right) \left(1\right)
 ; FinalWriter, WordWorth, TurboPrint
 - SAVE_ROTATE=<ON|OFF>
 ; by default, the picture seems to be rotated
 ; with Postscript (TM) output of this module.
 ; Enabling SAVE_ROTATE will again re-rotate it to
 ; the original position.
 ; default is: OFF
 - SAVE_CENTER=<ON|OFF>
 ; centers the images on the page with the
 ; desired size of SAVE WIDTH x SAVE HEIGHT (or not)
 ; default is: ON
 - SAVE_RLE=<ON|OFF>
 ; allows to apply RLE compression to the
 ; PS output
 ; default is: OFF
 - SAVE_DPI=<value>
 ; DPI value to use for the output
 ; default is: 300
 - SAVE_WIDTH=<value>
 ; Width of the PS page
 ; default is: 612
 - SAVE HEIGHT=<value>
 ; Width of the PS page
 ; default is: 762
History
~~~~~~
V4.8 (16.11.1998) :
 - saving of EPS header now can be switched off (resulting in pure P*stscript)
   (-> Florian Zeiler)
V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

# 1.54 Winlcon.svobject

```
© 1994-98 by Andreas R. Kleinert. FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
```

SuperView-Library 79 / 174

```
Version
              : 4.7
 Release Date : 14.08.1997
 Description
 WinIcon.svobject is an external library module for superview.library,
 which needs any SVDriver with Oneplane-Support.
 It supports reading of W*nd*ws V3.x (TM) Icon files.
 In detail these are :
 Reading:
  - WinIcon files with _exactly_ 16 Colors
     (more than one Icon per file should work, but hasn't been tested yet.)
 History
  ~~~~~
 V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
1.55 TIM.svobject
 © 1997 by Andreas R. Kleinert.
```

```
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
 : 4.1
Release Date : 23.12.1997
Description
~~~~~~~~
TIM.svobject is an external library module for superview.library,
which needs any SVDriver with Oneplane-Support.
It supports reading of TIM (PSX) files.
In detail these are :
Reading :
 - 16 color TIM
 - 256 color TIM
 - 15 bit TIM (imported as 24 bit)
 - 24 bit
           TIM
Disclaimer
Note: Only files with the extension ".TIM" will be recognized.
Disclaimer
~~~~~~~~~~
Since there - aren't any developer docs for TIM and PSX freely available,
 reverse engineering of the file format was the only possible way \,\,\hookleftarrow\,
 support this graphics standard.
```

SuperView-Library 80 / 174

- was no PSX available (and reading from original PSX CD-ROMs would have caused other legal problems), we did the complete programming and testing with an other third party program: PPaint 7.1 is able to read and write PSX graphic files.

This made it possible to read and write TIM files without ever getting in touch with any PSX native, copyrighted stuff.

```
History
~~~~~
V4.1 (23.12.1997) :
   - initial release (!! BETA !!)
```

# 1.56 GhostScript.svobject

```
© 1996-98 by Andreas R. Kleinert.
(Also see notes under "Credits".)
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
```

Version : 4.10 Release Date : 01.04.1998

# Description ~~~~~

GhostScript.svobject is an external library module for superview.library, which needs any SVDriver with Bit-/Oneplane-Support and PNG.svobject to be present.

It supports importing Postscript (TM) language and PDF files as bitmapped graphics. This is done by using Ghostscript for conversion, giving a DPI resolution and a description code for one of the supported output file format, like e.g. PNG.

GhostScript.svobject will create a temporary file, which then will be parsed through superview.library again.

(See documentation of PNG.svobject for which PNG derivates currently are supported).

### Reading:

(Any Postscript (TM) and PDF files as long as readable for Ghostscript).

## Configuration

~~~~~~~~~~

This Ghostscript support module has been tested with the Ghostscript 3.53 and 4.03 ports from Aminet, with amiga driver & no ixemul.library: Aladdin Ghostscript is Copyright (C) 1989, 1995 Aladdin Enterprises. All rights reserved.

Recommended is V5.01 or greater, Ghostscript 2.6.1 may work, if you don't use PNG as output file format.

SuperView-Library 81 / 174

At first, Ghostscript must have been successfully installed, and working (test it via command line access).

For enabling Ghostscript support, you either have to supply an AmigaDOS search path to a directory, where the executable "gs000" is stored (default), or explicitely specify path and/or name of the program by the controlpad entry GS_PATH (see below).

But as mentioned before, Ghostscript has to be installed and set-up first.

Setting-up Ghostscript

Since the documentation of some Ghostscript versions is anything-but-not-very-verbose I decided, to shortly explain here, what steps to perform to successfully install Ghostscript on your system:

- unpack Ghostscript to where you wish it to be located at (e.g. "Work:Ghostscript/")
- make an assign "Ghostscript:" to that Ghostscript directory
 (e.g. put the line "Assign Ghostscript: Work:Ghostscript"
 into your "S:User-Startup")
- assign PSFonts: to your postscript font directory (anywhere)
 (e.g. put the line "Assign PSFonts: Work:Ghostscript/Fonts"
 into your "S:User-Startup", if that font directory already
 does exist there)
- create some environment variables in ENV: _and_ ENVARC: which have to look as follows (respecting upper and lowercase):

```
Variable Content Remark

GS_FONTPATH *NOT* to be created (do delete)

GS_LIB PSFonts:

GS_OPTIONS create, but leave *EMPTY* (blank)

GS_DEVICE amiga
```

- create a file "PSFonts:FONTMAP" with at least the following lines:

The single ps fonts are assigned via the FONTMAP. For fonts used by ps files there must be an entry to allow interpretation of these files, but basically each font can easily substituted by an other.

It does not matter, which font files are assigned for which fontname; in general entries within the FONTMAP file at "PSFonts:" just have to go conformeous with the following scheme:

/Fontname (Filename) ;

SuperView-Library 82 / 174

```
for example
        /Helvetica
                             (Helvet.pfb)
 This means that the corresponding files must actually exist.
 But one also may substitute fonts symbolically by other fonts
  (to be understood like an alias or replacement font as known
  from Windows (TM) for "Arial" and "Helvetica") like for example:
        /Helvetica_Bold
                             /Helvetica
Remarks
~~~~~~
 - if special versions for specific CPUs do crash, then try versions
  for "smaller" CPUs (e.g. 68000 version instead of 040+FPU version).
- please note, that setting DPI to higher values does not necessarily
  increase image quality, but memory usage (default is DPI=72).
  Same is to mention for the output colordepth:
  256 colors give better results, when you've to perform dithering.
- files to be recognized must either have the standard Postscript (TM)
  header (containing '%!PS-Adobe' in it) or have the file extension
  ".ps" and begin with '%' (containing instructions for GhostScript).
 - PDF files are also supported (extension ".pdf" and beginning with '\%'),
  but having the correct and needed fonts installed is more critical
  for these. Had not enough fonts to successfully test loading of any
  of these.
 - error output of Ghostscript still is directed to stdio/Output(),
  so problems may be visible transparently
Where to DOWNLOAD from
Aminet:gfx/show/gs#?.lha (#?=version, CPU and archive content)
ControlPad-Switches
: "ENV:SuperView-Library/GhostScript.controlpad"
ControlPad-Name
ControlPad-Commands : - STACKSIZE=<value>
                        ; stacksize to be used for calling Ghostscript,
                       ; increasing may help on crashes
                        ; default is: 32768
                      - GS_PATH=<gs command path plus name>
                       ; how Ghostscript is to be called
                        ; e.g. GS_PATH=Ghostscript:gs000
                       ; default is: gs000
                      - OUTPUTMODE=<PNG256|PNG24BIT|OTHER>
                       ; Output file format to be used
                       ; (-sDEVICE parameter of Ghostscript's gs).
                       ; Only PNG supported yet.
                        ; default is: PNG256
                     - OTHER_OUTPUTMODE=cxmono|pcxgray|pcx16|pcx256|
                                         pcx24b|tiffcrle|tiff24nc|
                                         pngmono|pnggray|png16|png256|
```

png16m|bmpmono|bmp16|bmp256|

SuperView-Library 83 / 174

```
bmp16m>
                          ; If OUTPUTMODE=OTHER has been set, the string
                          ; specified here will directly be passed as
                          ; Ghostscript's "-sDEVICE" parameter
                          ; default is: png256
                        - DPI=<value>
                          ; DPI value to use for the converted output
                          ; (-r parameter of Ghostscript's qs)
                          ; default is: 72
                        - STATUS=<ENABLED|DISABLED>
                          ; allows to disable this module - for example
                          ; to be able to use an other, program-specific
                          ; import-module for the same file format
 History
  ~~~~~~
 V4.10 (01.04.1998) :
  - added possibility to increase stacksize, when necessary (crashes ?)
   - improved interfacing/error handling with Ghostscript
 V4.9 (14.08.1997) :
  - recompiled with SAS/C 6.58
1.57 Targa.svobject
 © 1994-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
 Version
             : 4.12
 Release Date : 02.04.1998
 Description
  ~~~~~~~~~
 Targa.svobject is an external library module for superview.library,
 which needs any SVDriver with Bit-/Oneplane-Support.
  It supports reading and writing of TGA (Truevision Targa) files.
  In detail these are :
 Reading:
  Colors Depth Organisation
                                                 RLE-Compression
             1
                 planar monochrome
                                                 supported
                                                supported
    256
             8
                 chunky pixel (colors/gray)
    32768 16
                 "HighColor 15/16 Bit" Pixel
                                                supported
                BGR-Pixel
      (24 bit)
                                                 supported
 Writing:
  Depending on the Colordepth of the source the following is written:
```

SuperView-Library 84 / 174

Source Colors	Туре	Destination Colors
2 256	Uncompressed chunky pixel	256
(24 bit)	Uncompressed BGR	(24 bit)

Remarks

~~~~~

- PaintShop (3.0) and PaintShopPro (2.01) seem to write Targa files with a bad colormap (the same does apply to PixView 1.8, which perhaps was programmed using PaintShop files for testing).

Corel PhotoPaint 4.0 crashed when opening one of these, PPaint 7.0 and Targa.svobject did import a strange gray palette instead of the real one. PaintShop(Pro) however seems to be able to read SuperView-Library written Targa files correctly.

Anyway, PaintShop(Pro) here does not seem to conform to the specs - I've tried everything to extract the real colormap from the written one, but it's simply too strange. It claims to be a 3x8 BGR colormap, but it must be something else that fits into 24 bit (I've tried nearly everything and it did not work, though). So, be careful - use some other file format when exchanging data with PC people that may like to use PaintShop(Pro).

- 32 Bit graphics files are not supported yet
- The flags for "mirroring" Images vertically and/or horizontally are not fully interpreted yet, nevertheless these will be reported by SVL\_FileInfoRequest()

If the VERTINV flag is not set, the picture will be assumed to be written as "from bottom to top", otherwise as "from top to bottom". Some programs do not set these flags right, when writing, so that you might get just the opposite result as expected. The HORIZINV flag is currently ignored: when reading such a picture as usual, you'd get a mirrored image. But this flag is also set wrong sometimes ...

## History

~~~~~

V4.12 (02.04.1998) :

- due to a bad check in the file recognition routine (introduced with a bug fix some time) colormapped Targa files written by this SVObject were not recognized and loaded by it any longer; this did affect other Targa files of the same kind, too (-> Waldemar Scheu)
- fixed another (logical) bug in file recognition routine
- colormapped Targa files had a RGB instead of BGR colormap when being written (didn't I fix this already a zillion times ?!)
- when reading colormapped Targa files, their BGR colormap would have been interpreted as RGB colormap (same as above, consequently)
- added support for 16/32 bit (2/4 byte) colormaps
 - (just followed the specs; not tested, though report any bugs)
- added note about garbage PaintShop/PixView targa files
- fixed bug in little/big endian conversion, which (yet) did not have had any effects (luckily)
- fixed a bunch of other things

SuperView-Library 85 / 174

```
V4.11 (16.02.1998) :
   - changed for new .svm style PPC modules
V4.10 (14.08.1997) :
   - recompiled with SAS/C 6.58
```

1.58 MetaView.svobject

```
© 1996-98 by Andreas R. Kleinert.
(Also see notes under "Credits".)
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
            : 4.10
Version
Release Date : 07.04.1998
Description
~~~~~~~~~~
MetaView.svobject is an external library module for superview.library,
which needs any SVDriver with Bit-/Oneplane-Support, a working
ILBM.svobject and an installed MetaView executeable with CLI interface.
It supports importing WMF (also embedded in Win CLP), AMF, IFF-DR2D, IFF-DRSF, \leftrightarrow
may be handled through MetaView instead of using the default methods for CGM (
             GPlot.svobject
and FIG (
             AmiFIG.svobject
             ) .
This is done by using MetaView for conversion of WMF (Windows Meta File)
or Windows CLP, AMF (Amiga Meta File), IFF-DR2D, IFF-DRSD (DrawStudio), DXF (CAD ↔
   ) or WPG
vector files (optionally also FIG and CGM files) to IFF-ILBM files, which then \leftrightarrow
   will be
parsed through superview.library again using
             ILBM.svobject
Reading:
 (Any WMF, Win CLP, AMF, IFF-DR2D, IFF-DRSD, DXF and WPG vector drawings ( \hookleftarrow
 also FIG and CGM) as long as understood and correctly converted to IFF-ILBM by \hookleftarrow
      MetaView)
Configuration
This WMF/AMF/IFF-DR2D/DXF/WPG (plus FIG nad CGM) vector support module has been
tested with: MetaView 2.0 (C) by Henk Jonas, which is Shareware (30 DEM/20 USD)
```

SuperView-Library 86 / 174

and can be obtained from Aminet (see below). For some features, a newer version may be required, though (follow the homepage URL for a download link). Henk Jonas - eMail: subvcbhd@dattel.zrz.tu-berlin.de WWW: http://www.cs.tu-berlin.de/~jonash At first, you have to correctly install and configure MetaView and the libraries it is using for vector graphics parsing. Also, you have to supply an AmigaDOS search path to a directory, where the executable "MetaView" is stored (default), or explicitely specify path plus name of the program by the controlpad entry METAVIEW_PATH (see below). Notes ~~~~ DXF and CLP files will only be recognized, if the file extensions have not been changed (.DXF and .CLP). Where to DOWNLOAD from Aminet:gfx/conv/MetaView.lha ControlPad-Switches ~~~~~~~~~~~~~~~~ : "ENV:SuperView-Library/MetaView.controlpad" ControlPad-Name ControlPad-Commands : - STACKSIZE=<value> ; stacksize to be used for calling MetaView, ; increasing may help on crashes ; default is: 32768 - METAVIEW_PATH=<MetaView command path plus name> ; how MetaView is to be called ; e.g. METAVIEW_PATH=Work:AMF/MetaView ; default is: MetaView - FIG_SUPPORT ; if this keyword is set, AmiFIG.svobject will ; be overriden and instead MetaView will be ; utilized for imporint FIG drawings - CGM SUPPORT ; if this keyword is set, GPlot.svobject will ; be overriden and instead MetaView will be ; utilized for imporint CGM graphics - STATUS=<ENABLED|DISABLED> ; allows to disable this module - for example ; to be able to use an other, program-specific ; import-module for the same file format History V4.10 (07.04.1998) :

- added file recognition code for IFF-DRSD and CLP

(-> thanks to Henk Jonas)

SuperView-Library 87 / 174

```
V4.9 (01.04.1998) :
   - changed way of calling the program (SystemTagList), which should
     fix some crashes on certain graphics
   - added possibility to increase stacksize, when necessary (crashes ?)
  V4.8 (14.08.1997) :
   - recompiled with SAS/C 6.58
1.59 WPG.svobject
  © 1994-98 by Andreas R. Kleinert.
  FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
  Supports powerUP (TM).
  Version
             : 4.10
  Release Date : 16.02.1998
  Description
  WPG.svobject is an external library module for superview.library,
  which needs any SVDriver with Bit-/Oneplane-Support.
  It supports reading of WPG (WordPerfect) BitMap files.
  In detail these are :
  Reading:
   - WPG Bitmap (grayscaled) with 1, 2, 4 or 8 bits colordepth
   - WPG Bitmap (colorMap)
                           with 1, 2, 4 or 8 bits colordepth
  Remarks
  WordPerfect WPG files do not necessarily have to contain bitmap graphics,
  they also may contain various other data, e.g. vector graphics.
  If a WPG file contains a bitMap graphic in any of its chunks, it will
  be loaded, otherwise the file will be rejected - these rejected files
  may be loaded by a correctly configured and installed MetaView.svobject,
  though.
  If a file does not contain any color information, WPG.svobject will
  generate grayscales by default.
  This will be mentioned in the file-info requester.
  This version actually has been tested with graphics with 1, 4 and 8 Bit
  colordepth (2, 16 and 256 Colors).
  Due to the fact, that the 2 bit-routine is identically to the 1 bit-
  routine you should not get any problems with those pictures.
```

History

V4.10 (16.02.1998) :

SuperView-Library 88 / 174

```
changed for new .svm style PPC modulesV4.9 (14.08.1997) :recompiled with SAS/C 6.58
```

1.60 SunRaster.svobject

```
© 1994-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
            : 4.7
Release Date : 14.08.1997
Description
SunRaster.svobject is an external library module for superview.library,
which needs any SVDriver with Bit-/Oneplane-Support.
It supports reading and writing of SunRaster (RAS) files.
In detail these are :
Reading:
 - SunRaster with 2 Colors (1 Bit, planar)
 - SunRaster with 256 Colors ( 8 Bit, chunky pixel)
 - SunRaster with 24 bit (24 bit, R-G-B)
Writing:
 Depending on the Colordepth of the source the following is written:
 Source Colors
                                                 Destination Colors
                  Type
                 Uncompressed Chunky Pixel
  2..256
                                                   256
  (24 bit)
                 Uncompressed 24 bit RGB
                                                  (24 bit)
Remarks
 - files with Colorbits other than 1, 8 or 24 are not supported yet
 - only RGB-planar colormaps supported (or monochrome, without map)
 - max. 1 plane of bitmap data allowed
History
~~~~~~
V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
 - obviously had been broken since V4.4 (V4.4 included instead ?)
```

1.61 SGI.svobject

SuperView-Library 89 / 174

```
© 1994-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
            : 4.7
Release Date : 14.08.1997
Description
~~~~~~~~~
SGI.svobject is an external library module for superview.library,
which needs any SVDriver with 24 bit Oneplane-Support.
It supports reading and writing of SGI files.
In detail these are :
Colors Depth Organisation
                                              RLE-Compression
   256 8
              8 Bit Chunky Pixel (gray)
                                              supported
  (24 Bit)
             8:8:8 24 bit RGB
                                              supported
Writing:
Source Colors
                                              Destination Colors
                  Type
 (24 bit)
                 Uncompressed RGB
                                              (24 bit)
Remarks
 - Currently files with BPC-Values of 2 are not supported, which
  means that pixel data has to be stored in bytes, not words
   (either gray 8 Bit or 24 bit RGB as 8:8:8, not 16 or 16:16:16)
History
~~~~~~
V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
 - SVDriver flag was not set
```

1.62 PICT.svobject

SuperView-Library 90 / 174

```
In detail these are :
 Reading:
  - Mac PICT-2 with 1, 2, 4, 8 or 24 bit colordepth
    always as 24 bit RGB Data (JPEG optionally as dithered 8 Bit)
 Remarks
  - the file extension has to be ".pct" (as on PCs), ".pic"
    or ".pict", otherwise it will be rejected
     (there do more checks take place, but those are less relieable)
   - pictures always will be exported as 24 bit RGB data
   - font handling always will operate with the internal
    standard font instead of the appropriate ones
     (derived from PBM package, see Credits)
 Limitations
  ~~~~~~~~~~
 Please note, that the Decoding Routines of the Library are not (yet)
 fully re-entrant, so that only one Task may Decode a picture at a time.
 The Library itself manages it, that the other Task has to Delay() until
 the Decoding Routines are "free" again.
 Since Decoding usually is managed very fast, this should not
 actually matter.
 History
  ~~~~~
 V4.9 (16.02.1998) :
  - changed for new .svm style PPC modules
 V4.8 (11.02.1998) :
   - added powerUP support (optional)
   - fixed some small bugs
 V4.7 (14.08.1997) :
  - recompiled with SAS/C 6.58
1.63 Pictor.svobject
 © 1994-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Version
              : 4.7
 Release Date : 14.08.1997
 Description
 Pictor.svobject is an external library module for superview.library,
```

which needs any SVDriver with Bit-/Oneplane-Support.

It supports reading of Pictor/PC Paint (PIC) files.

SuperView-Library 91 / 174

```
In detail these are :
  Reading:
   - Files with 1, 4, or 8 Bit colordepth
     (monochrome or with EGA or VGA palette).
  History
  V4.7 (14.08.1997) :
   - recompiled with SAS/C 6.58
     MAC.svobject
1.64
  © 1994-98 by Andreas R. Kleinert.
  FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
  Version
  Release Date : 14.08.1997
  Description
  MAC.svobject is an external library module for superview.library,
  which needs any SVDriver with Bitplane-Support.
  It supports reading of MAC (MacIntosh MacPaint) files.
  In detail these are :
  Reading:
  - MAC Black & White 576x720
  Remarks
  ~~~~~
  MacPaint files, which are to be loaded into "MAC.svobject" should contain
  the specific MacBinary Header (first the 128 Byte-Header, then the
  MacPaint specific data appended to it).
  In the PC area, there may sometimes files be found, which just contain
  the MacPaint 576x720 black and white Data.
  These files - without the header - can only be identified via the three
  leading zero bytes at the beginning of the 512 Byte MacPaint header.
  But there's never a 100% guarantee that a File with three leading zeroes
  really is a MacPaint File, so we also request a filename ending with
  ".mac" or ".MAC" in this special case.
  History
```

~~~~~~

V4.7 (14.08.1997) :

- recompiled with SAS/C 6.58

SuperView-Library 92 / 174

# 1.65 JPEG.svobject

```
© 1994-98 by Andreas R. Kleinert.
(Also see notes under "Credits".)
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Supports powerUP (TM).
This software is based in part on the work of the Independent JPEG Group.
Version
            : 4.18
Release Date : 06.09.1998
Description
~~~~~~~~~~
JPEG.svobject is an external library module for superview.library,
which needs any SVDriver with Oneplane-Support.
It supports reading and writing of JPEG files as written by
"The Independent JPEG Group's JPEG Software" (release 6).
In detail these are :
Reading:
 - JPEG (IJG-JFIF), with output in 256 Colors or 24 bit
Writing:
 - JPEG (IJG-JFIF), from upto 8 or 24 bit Input
Remarks
~~~~~~
* Temporary data might be written to a directory assigned to "VMEM:",
  if neccessary, but please note, that this might affect your HardDisk,
  if this program crashes (e.g. on a corrupt JPEG-picture) !
  So don't blame me, if this happens, but select a _safe_ place for this
  temporary-file directory !
* Writing JPEG-files :
* Note, that JPEG-compression is lossy, which means that the original
  picture cannot be reconstructed totally.
  Only JPEG-compress files, of which you have backups, or files which
  you never want to edit and enhance again.
  You should always control the results from saving an JPEG-File : in
  some special cases (e.g. many thin lines on the screen) there may
  occur strong differences to the original picture.
ControlPad-Switches
~~~~~~~~~~~~~~~~
 : "ENV:SuperView-Library/JPEG.controlpad"
ControlPad-Name
ControlPad-Commands :
 ;
 ; STANDARD settings
 ; **********
 - COLORDEPTH=<8 | 24>
 ; For READING colored 24 bit images:
```

SuperView-Library 93 / 174

```
; should the output be done as 8 or 24 bit Data ?
 ; default is 8 Bit data. Grayscaled graphics
 ; will _always_ be exported as 8 Bit
- QUANTIZATION=<0..100>
 ; For WRITING 8/24 bit images as 24 bit JPEG:
 ; 0 - poor quality, big compression
 ; 100 - best quality, no compression
 ; never use such extreme values, but try
 ; something like 20, 50, 75
 ; default is: 75)
 ; ADVANCED settings
 ; *********
FORCE_GRAY_DECODE
 ; For READING images:
 ; this switch overrides the selected depth
 ; for colored images and always exports them
 ; as 8 Bit grayscaled pictures
 ; default is: not set
- DECODE METHOD=<FAST INTEGER|SLOW INTEGER|
 FLOATING POINT>
 ; For READING images:
 ; how to DECODE the 24 bit or gray data
 ; default is: FAST INTEGER
- DITHERMODE=<DITHER_FLOYD-STEINBERG|
 NO_DITHERING|DITHER_ORDERED>
 ; For READING and dithering 24 bit images
 ; to 8 Bit images:
 ; how and whether to DITHER the 24 bit data
 ; default is: DITHER_FLOYD-STEINBERG
- COLOR_QUANTIZING=<FAST|SLOW>
 ; For READING and dithering 24 bit images
 ; to 8 Bit images:
 ; whether to QUANTIZE the 24 bit data within
 ; two passes (not with DITHER_ORDERED)
 ; default is: SLOW
- UPSAMPLING=<ON|OFF>
 ; For READING and dithering 24 bit images
 ; to 8 Bit images:
 ; whether to do fancy upsampling on the 24 bit
 ; default is: ON
- FORCE GRAY ENCODE
 ; For WRITING images:
 ; this switch causes grayscales to be written
 ; no matter, whether the input was colored
 ; default is: not set
- ENCODE_METHOD=<FAST_INTEGER|SLOW_INTEGER|
 FLOATING_POINT|FASTEST_INTEGER>
 ; For WRITING images:
 ; how to ENCODE the 24 bit or gray data
 ; default is: FAST_INTEGER
- OPTIMIZE=<ON|OFF>
 ; For WRITING 24 bit images:
 ; whether to optimize the generated huffman
 ; code (good compression, but slow)
 ; default is: OFF
- PROGRESSIVE=<ON|OFF>
```

SuperView-Library 94 / 174

```
; For WRITING 24 bit images:
 ; whether to write progressive JPEG files
 ; default is: OFF
History
~~~~~
V4.18 (06.09.1998) :
 - smaller, faster
V4.17 (30.03.1998) :
 - upgraded to libjpeg V6b
V4.16 (16.02.1998) :
 - changed for new .svm style PPC modules
V4.15 (11.02.1998) :
 - added support for PPC native ELF plugin module, allowing
  to speed up loading and saving incredibly with powerUP (TM)
 - JPEG core now single-threaded due to problems with reentrancy
 - in 4.13 accidentally linked the 68000 and 030 version with
   060 code. No problem for 020+ users, but for 68000 users.
V4.14 (31.12.1997) :
 - fixed error handling (according to hint by Tom Lane)
V4.13 (23.12.1997) :
 - faster, smarter
 - JPEGMEM env variable no longer checked
V4.12 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

# 1.66 PCD.svobject

```
as BASE/16 (192x128), BASE/4 (384x256) and BASE (768x512) directly, and additionally BASE*4 (1536x1024) and BASE*16 (3072x2048) via the external NetPBM-tool "hpcdtoppm". It does not read the BASE*4 (1536x1024) and BASE*16 (3072x2048)
```

It does not read the BASE\*4 ( $1536 \times 1024$ ) and BASE\*16 ( $3072 \times 2048$ ) resolutions directly, since these are encrypted in a way, which is not only undocumented, but also copyrighted by Kodak, who are taking a license fee for their decoding algorithms.

# Legal Issues

This program module is FREEWARE.

The author does not claim any copyrights on the code, which is used to decode the YUV-data fromout the PCD-file (see credits) or on the other PCD-related information.

Copyright is only claimed for the program as a whole, which means that some parts of the library module, which are also used within other SVObjects, are copyrighted by the author.

If the writing or the publication of this program should ever be considered to be partly any kind of a violation of third party copyrights, it is hereby expressed that the usage of this program is only allowed, if any user of it agrees to the following: If the case as described above takes place, any user has to delete any copies of this program immediately when he gets informed about it.

```
Configuration
```

```
"hpcdtoppm" does not need to be configured. Just copy it somewhere.
Where to DOWNLOAD from
Aminet:gfx/pbm/#?.lha (#? something with "pbm" in it)
ControlPad-Switches
ControlPad-Name : "ENV:SuperView-Library/PCD.controlpad"
ControlPad-Commands: - OUTPUTFORMAT=<BASE/16 | BASE/4 | BASE
                                  | BASE * 4 | BASE * 16 >
                      ; specifies the output resolution to be used
                     - HPCDTOPPM_PATH=<hpcdtoppm command path plus name>
                      ; how NetPBM's hpcdtoppm is to be called
                      ; e.g. HPCDTOPPM_PATH=Work:NetPBM/ppm/hpcdtoppm
                      ; If this one is not set, "BASE" will be
                      ; used as default resolution, even if OUTPUFORMAT
                      ; has been set to BASE*4 or BASE*16
```

```
History
```

```
V4.12 (16.02.1998) :
```

- changed for new .svm style PPC modules

V4.11 (14.08.1997) :

SuperView-Library 96 / 174

- recompiled with SAS/C 6.58

© 1994-98 by Andreas R. Kleinert.

# 1.67 FastILBM24.svobject

```
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
             : 4.7
Release Date : 14.08.1997
Description
FastILBM24.svobject is an external library module for superview.library,
which needs any SVDriver with Oneplane-Support.
It has especially been written to allow fast and "low-memory"
loading and dithering of ILBM 24 bit graphics.
This means, that no compressed or uncompressed 24 bit data will
be completely loaded into memory, but directly be dithered
to HAM6/8, so that even people with less memory and no graphics
card will be able to view those nice 24 bit graphics.
May be deactivated, even if installed; may be switched between
HAM6 and HAM8; allows increasing/decreasing of internal cache buffer.
ControlPad-Switches
                  : "ENV:SuperView-Library/FastILBM24.controlpad"
ControlPad-Name
ControlPad-Commands : - BUFFERSIZE = < Size in Bytes>
                        ; how many bytes should be buffered
                          (more = faster)
                        ; Default is 8192, minimum is 256
                      - PASSTHROUGH
                        ; do not recognize ANY pictures, so that
                        ; they e.g. might be passed through to
                        ; ILBM.svobject instead
                      - DITHERMODE=<HAM6_QUICK|HAM8_QUICK>
                        ; Default is HAM6_QUICK
History
V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

# 1.68 YUVN.svobject

```
© 1994-98 by Andreas R. Kleinert.
(Also see notes under "Credits".)
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
```

SuperView-Library 97 / 174

```
Version
              : 4.8
 Release Date : 02.04.1998
 Description
 YUVN.svobject is an external library module for superview.library,
 which needs any SVDriver with 24 bit Oneplane-Support.
 It supports reading and writing of IFF-YUVN (YUVN) files.
 In detail these are :
 Reading:
  - IFF-YUVN 24 bit (gray, 411, 422, 444, 211, 222)
    Gray will be imported as 24 bit with R=G=B.
    Use "ExtractGrayScales" operator to reduce
    memory usage - and redundancy
 Writing:
  - IFF-YUVN 24 bit (411)
 Reading/writing from/to ClipBoard is supported.
 Remarks
   - only 24 bit sources will be written as IFF-YUVN.
    256 color graphics are NOT automatically transformed to 24 bit,
    so that you may have to use the "AnyTo24Bit" operator before saving.
 History
  ~~~~~~
 V4.8 (02.04.1998) :
 - when wrinting, due to bad chunk size alignment, images sometimes later
 might not have been parsed correctly (by iffparse.library), resulting
 in a "data not found" or similar message with YUVN.svobject
 (-> reported by Waldemar Scheu)
 V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
1.69 DEEP.svobject
 © 1995-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
 Version
 : 4.9
```

Release Date : 16.02.1998

Description

SuperView-Library 98 / 174

```
DEEP.svobject is an external library module for superview.library,
 which needs any SVDriver with 24 bit Oneplane-Support.
 It supports reading and writing of specific IFF-DEEP (DEEP) files.
 In detail these are :
 Reading:
 - IFF-DEEP 24 bit RGB 8:8:8,
 uncompressed
 32 bit RGBA 8:8:8, uncompressed
 (Alpha channel ignored)
 - IFF-DEEP 24 bit RGB 8:8:8, RLE-compressed
 32 bit RGBA 8:8:8, RLE-compressed (Alpha channel ignored)
 Writing:
 - IFF-DEEP 24 bit RGB 8:8:8, uncompressed
 Reading/writing from/to ClipBoard is supported.
 Remarks
 - only 24 bit sources will be written as IFF-DEEP.
 There's no conversion done from e.g. 256 Colors to 24 bit
 to perform the requirements of this file format.
 - other compression methods (e.g. Huffman) aren't yet supported
 due to a lack of information on implementation
 History
  ~~~~~~
 V4.9 (16.02.1998) :
  - changed for new .svm style PPC modules
 V4.8 (14.08.1997) :
   - recompiled with SAS/C 6.58
1.70 FAXX.svobject
 © 1997 by Andreas R. Kleinert.
  (Also see notes under "Credits".)
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Version
              : 4.5
 Release Date : 05.03.1998
 Description
```

FAXX.svobject is an external library module for superview.library,

which needs any SVDriver with Bitplane-Support.

It supports reading of IFF-FAXX (GPFax) files.

In detail these are :

Reading:

SuperView-Library 99 / 174

```
- IFF-FAXX 1 bit black & white, compressed
```

Reading from ClipBoard is supported.

#### Not.es

~~~~

Note, that only IFF-FAXX files compliant to the official FAXX (Facsimile image FORM) as registered at CATS 11/13/91 by Christopher E. Darsch (Atlantis Design Group, Inc.) are supported. These files do consist of the three chunks FXHD, PAGE and FLOG and may be extended by the GPHD chunk as defined by GPSoftware.

NOT supported are the completely incompatible (and obviously non-standard) files as written by MultiFax, which seem to mainly consist of text and also may include an attached IFF-FTXT file. MultiFax, as a second option, also seems to output partly standard-compliant files, which in theory should be read correctly - in practice there did occur some problems with garbaged output though (yet it's not clear, whether it's the fault of the MultiFax encoder or our decoder).

A typical file written by GPFax may look like this:

```
FORM FAXX
FXHD
GPHD
PAGE
```

A supported MultiFax file may look like this:

```
FORM FAXX (19102 data bytes)
FXHD
PCON
PAGE
```

A non-supported MultiFax file may look like this:

```
FORM FAXX

TELE

CNFG

PFLG

FDSC

FORM FTXT

MCMD

MCMD

MCMD

MCMD

MCMD

CHRS
```

Credits

~~~~~

Thanks to Dr. Greg Perry (GPSoft) for help on implementation.

SuperView-Library 100 / 174

```
History
  ~~~~~
 V4.5 (05.03.1998) :
 - small changes
 V4.4 (14.08.1997) :
 - recompiled with SAS/C 6.58
 RGB8.svobject
1.71
 © 1997-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
 Version
 : 4.7
 Release Date : 03.10.1998
 Description
 RGB8.svobject is an external library module for superview.library,
 which needs any SVDriver with 24 bit Oneplane-Support.
 It supports reading and writing of IFF-RGB8 and IFF-RGBN
 (Turbo Silver, Imagine, ArtEffect) files.
 In detail these are :
 Reading:
 - IFF-RGBN 12 bit RGB 4:4:4, RunLength4 compressed (Genlock bit ignored)
 - IFF-RGB8 24 bit RGB 8:8:8, RunLength4 compressed (Alpha channel ignored)
 Writing:
 - IFF-RGB8 24 bit RGB 8:8:8, RunLength4 compressed (no Alpha channel)
 Reading/writing from/to ClipBoard is supported.
 Remarks
 - only 24 bit sources will be written as IFF-RGB8.
 There's no conversion done from e.g. 256 Colors to 24 bit
 to perform the requirements of this file format.
 - other compression methods are not available, thus not supported...
 History
 V4.7 (03.10.1998) :
 - was checking for 5 instead of 2 (4) IFF-IDs. Possible crash reason...
 (-> Waldemar Scheu)
 - added support for IFF-RGBN
 (-> sample gfx supplied by Waldemar Scheu)
```

SuperView-Library 101 / 174

```
V4.6 (16.02.1998) :
 - changed for new .svm style PPC modules
 V4.5 (14.08.1997) :
 - recompiled with SAS/C 6.58
1.72 RGFX.svobject
 © 1997-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Version
 : 4.4
 Release Date : 05.12.1998
 Description
  ~~~~~~~~~~
  RGFX.svobject is an external library module for superview.library,
  which needs any SVDriver with 8/24 bit Oneplane- and Bitplane-Support.
  It supports reading and writing of the new IFF-RGFX graphics file
  standard for AGA and RTG Amigas (see Aminet:dev/misc/IFF-RGFX.lha)
  In detail these are :
  Reading:
   - IFF-RGFX 1..24 bit uncompressed
   - IFF-RGFX 1..24 bit XPK-compressed
  Writing:
   - IFF-RGFX 1..24 bit uncompressed
   - IFF-RGFX 1..24 bit XPK-compressed
  Reading/writing from/to ClipBoard is supported.
  ControlPad-Switches
  ~~~~~~~~~~~~~~~~~
 : "ENV:SuperView-Library/RGFX.controlpad"
 ControlPad-Name
 ControlPad-Commands : - PACKMETHOD=<xxxx>
 ; XPK packer to be used for writing
 ; "RGFX xpk-compressed"
 ; Default: NUKE
 - SAVE_CHUNKY
 ; forces chunky data to be saved,
 ; even if source graphics was planar
 ; (e.g. when converting from \mbox{IFF-ILBM}).
 ; May also result in smaller files.
 History
 V4.4 (05.12.1998) :
```

- rscm->rscm\_AGA still may have contained non-AGA modes when

SuperView-Library 102 / 174

```
writing files under CGFx/P96. Fixed again. More redundant checks.
 (-> Achim Stegemann)
 - saving chunky files now can be forced (via SAVE_CHUNKY option)
 (-> Achim Stegemann)
 V4.3 (03.12.1997) :
 - rscm->rscm_AGA may have contained non-AGA modes when writing
 files under CGFx/P96. Fixed.
 (-> Achim Stegemann)
 - HAM would not necessarily have been written with correct mode
 id: P96/CGfx must be INVALID_ID and AGA must be OR'ed with HAM_KEY
 V4.2 (27.11.1997) :
 - write: bytesperline entry always was set to zero in chunky
 mode (accidentally mixed ">> 3" and "/ 8" to ">> 8" :-(
 (-> Achim Stegemann)
 V4.1 (16.11.1997) :
 - first release, implementing IFF-RGFX V1.0
1.73 QRT.svobject
 © 1995-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Version
 : 4.8
 Release Date : 02.08.1998
 Description
 QRT.svobject is an external library module for superview.library,
 which needs any SVDriver with 24 bit Oneplane-Support.
 It supports reading and writing of QRT (POV RayTracer) files.
 In detail these are :
 Reading:
 - QRT Dump 24 bit
 Writing:
 - QRT Dump 24 bit
 Remarks
 - only 24 bit sources will be written as QRT.
 There's no conversion done from e.g. 256 Colors to 24 bit
 to perform the requirements of this file format.
 History
```

~~~~~~

SuperView-Library 103 / 174

```
V4.8 (02.08.1998) :
 - progressbar started at 100% then went down to 0%...
V4.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

## 1.74 C-Source.svobject

```
© 1996 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
 : 4.8
Release Date : 09.11.1997
Description
C-Source.svobject is an external library module for superview.library.
It creates C or Assembler source code in chunky/RGB notation from any input \leftrightarrow
 graphics
(<= 8 Bit and HAM as chunky, 24 bit as RGB).
In detail these are :
Writing:
 C-Source:
 - 8 Bit as C-Source with UBYTE [] pixel array and UBYTE [][3] \leftrightarrow
 colormap
 (HAM6/8 indicated by flag #define)
 - 24 bit as C-Source with UBYTE [][3] pixel array (RGB data)
 Asm-Source: - 8 Bit as asm source dc.b pixel array and dc.b (3-byte wise)
 colormap
 (HAM6/8 indicated by EQU defined flag)
 - 24 bit as asm source dc.b pixel array (3-byte RGB data)
For simple extraction of a colormap from a graphics file, you should
apply the Crop operator with parameters
 CROP_LEFTEDGE=0
 CROP_TOPEDGE=0
 CROP_WIDTH=1
 CROP HEIGHT=1
and then save the result as C-Source.
Remarks
```

- this module uses buffered I/O, but nevertheless is quite slow for larger graphics (I/O buffer is set to 64K for OS version >= 39)
- usage of RAM-Disk for output buffers is strongly suggested
- the module does raw output, which should be compileable with any Amiga C compiler - and any other compiler, when simply replacing

SuperView-Library 104 / 174

## 1.75 UXFormats

 ${\tt XWD}$  and  ${\tt UtahRLE}$  are not included with this distribution, but can be found on  ${\tt AmiNet}$  or any related BBS.

Look out for an archive called "Aminet:gfx/show/svoUXFormats.lha" or similar.

## 1.76 ECS.svdriver

```
© 1994-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
 : 2.17
Release Date : 02.12.1997
Requirements
- OS V2.04+ (V37+) and its libraries
- AMIGA with Old or Enhanced Chip Set (OCS/ECS)
Description
~~~~~~~~~~
ECS.svdriver is an external SV_GfxBuffer display module for
superview.library, which allows object-oriented displaying on
ECS displays.
This Driver supports the following :
Dimensions
                  Depth
                                Type
[ECS]
                  [ECS]
                                BITPLANE
[ECS]
                  8/(24)
                                           (Chunky Pixel)
                                ONEPLANE
```

SuperView-Library 105 / 174

```
The 8-Bit mode will perhaps only work on ECS systems which have any
Graphic Card installed, which allows 256 or more colors in a way
of an Intuition emulation.
24 bit Graphics will be displayed as "best guess of 256 colors"
if no SVOperator is specified.
Autoscrolling of Screens larger than the actual display is supported :
Just move the mouse to the boundings !
ControlPad-Switches
: "ENV:SuperView-Library/ECS.controlpad"
ControlPad-Name
ControlPad-Commands : - 24BITOPERATOR=<OperatorName>
                        ; (case-sensitive, ".svoperator" may be added)
                        ; e.g. "24BITOPERATOR=24BitToHAM.svoperator"
                               "24BITOPERATOR=ExtractGrayScales"
                        ; specifies, which operation should be performed
                        ; on 24 bit graphics _before_ displaying them
                        ; (if not specified displaying will fail)
                      - 8BITOPERATOR=<OperatorName>
                        ; (case-sensitive, ".svoperator" may be added)
                        ; e.g. "8BITOPERATOR=ExtractGrayScales"
                        ; specifies, which operation should be performed
                        ; on non-ECS graphics (more than 16 Colors in
                        ; HighRes, more than 32 Colors in LowRes, HAM8)
                        ; (if not specified, will be tried to display)
                      - BITMAPCOPY=<DIRECT|RTG>
                        ; "BITMAPCOPY=RTG" prevents ECS.svdriver from
                        ; directly copying into Bitmaps, which will
                        ; result in a usage of more memory, but keeps it
                        ; working.
                        ; Default is "BITMAPCOPY=DIRECT".
                      - SCREENINFRONT
                        ; Put Screen to front _before_ the graphics
                        ; has been displayed (useful with GfxCards)
History
~~~~~~
V2.17 (29.11.1997) :
 - improved resource management and temporary buffer delocation
 (may fix some hidden bugs as well)
 - tried to reconstruct 5.81/16.2 behaviour for OS 3.0/3.1
 systems *without* SetPatch V43 (and only for these), since another
 strange effect seems to have caused distortion of the original
 bitmap *although* we made copies (compiler bug ?)
 (-> Sven Drieling, Colin J. Knight)
 - SetPatch check was missing __saveds
 - in RTG mode, we used the wrong pointer to reference our
 buffer, once (here: could have been a problem when a 8BITOPERATOR
 had been selected and used on a ONEPLANE graphics, which then
 did become a BITPLANE graphics - highly unlikely case, though)
 - AI's original CheckSetPatch routine was buggy, it actually did
 the opposite as expected: with any version lower or equal
 it did return TRUE, for any greater version it returned FALSE.
 Since we check for V43.4, it would only have worked with this
 one - otherwise we applied our bugfix, although it was no
```

SuperView-Library 106 / 174

```
longer necessary, and with e.g. V40.16 there would not have
 been a bug-fix at all!
 This could have resulted in a destroyed source bitmap
 graphics, i.e. a black screen after certain times of viewing
 or usage of certain image processing operators.
 (-> 'black screen' effect noticed, and debugging done by
 Colin J. Knight and Sven Drieling)
 V2.16 (03.10.1997) :
 - more changes
 V2.15 (26.09.1997) :
 - c2p conversion did allocate a temporary line buffer even if not
 needed/used (when SetPatch 43.x being installed)
 - added another patch for systems not having SetPatch 43.x
 V2.14 (15.09.1997) :
 - if HAM (HAM6) is unavailable for a selected (RTG ?) screen mode,
 an automatic fallback to LowRes will take place
 - dito for EHB
 - if a screen mode is not available we now will compute (OS 37) or
 look for (OS 39+) a better one - just like AGA.svdriver
 V2.13 (14.08.1997) :
 - recompiled with SAS/C 6.58
1.77 AGA.svdriver
 © 1994-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Version
 : 2.20
 Release Date : 02.12.1997
 Requirements
 - OS V3+ (V39+) and its libraries (takes advantage of V40+)
 - AMIGA with AGA ChipSet (OCS/ECS still supported, but with restrictions)
 or an appropriate Graphics Card with Workbench Emulation
 Description
 AGA.svdriver is an external SV_GfxBuffer display module for
 superview.library, which allows object-oriented displaying on
 AGA displays.
 This Driver supports the following:
 Dimensions
 Depth
 Type
```

SuperView-Library 107 / 174

```
[AGA]
 BITPLANE
 [AGA]
[AGA]
 8/(24)
 ONEPLANE
 (Chunky Pixel)
24 bit Graphics will be displayed as "best guess of 256 colors"
if no SVOperator is specified.
Autoscrolling of Screens larger than the actual display is supported :
Just move the mouse to the boundings !
ControlPad-Switches
: "ENV:SuperView-Library/AGA.controlpad"
ControlPad-Name
ControlPad-Commands : - 24BITOPERATOR=<OperatorName>
 ; (case-sensitive, ".svoperator" may be added)
 ; e.g. "24BITOPERATOR=24BitToHAM.svoperator"
 "24BITOPERATOR=ExtractGrayScales"
 ; specifies, which operation should be performed
 ; on 24 bit graphics _before_ displaying them
 ; (if not specified, "best guess" colors will
 be used, which is really slow)
 - BITMAPCOPY=<DIRECT|RTG>
 ; "BITMAPCOPY=RTG" prevents AGA.svdriver from
 ; directly copying into Bitmaps, which will
 ; result in a usage of more memory, but keeps it
 ; working.
 ; Default is "BITMAPCOPY=DIRECT".
 - SCREENINFRONT
 ; Put Screen to front _before_ the graphics
 ; has been displayed (useful with GfxCards)
History
V2.20 (02.12.1997) :
 - improved resource management and temporary buffer delocation
 (may fix some hidden bugs as well)
 - fixed bug in internal 24 bit "best pen" routine (under V40, only)
 - WriteChunkPixel() now only will be used, when SetPatch V43 is
 installed (maybe it inherits some problems from WritePixelLine8()
 - tried to reconstruct 5.81/16.2 behaviour for OS 3.0/3.1
 systems *without* SetPatch V43 (and only for these), since another
 strange effect seems to have caused distortion of the original
 bitmap *although* we made copies (compiler bug ?)
 (-> Sven Drieling, Colin J. Knight)
 - removed two unused pointer variables
 - SetPatch check was missing __saveds
 - in RTG mode, we used the wrong pointer to reference our
 buffer, once (here: harmless)
 - AI's original CheckSetPatch routine was buggy, it actually did
 the opposite as expected: with any version lower or equal
 it did return TRUE, for any greater version it returned FALSE.
 Since we check for V43.4, it would only have worked with this
 one - otherwise we applied our bugfix, although it was no
 longer necessary, and with e.g. V40.16 there would not have
 been a bug-fix at all!
 This could have resulted in a destroyed source bitmap
 graphics, i.e. a black screen after certain times of viewing
```

SuperView-Library 108 / 174

```
or usage of certain image processing operators.
 (-> 'black screen' effect noticed, and debugging done by
 Colin J. Knight and Sven Drieling)
V2.19 (03.10.1997) :
 - more changes
V2.18 (26.09.1997) :
 - c2p conversion did allocate a temporary line buffer even if not
 needed/used (when SetPatch 43.x being installed)
 - added another patch for systems not having SetPatch 43.x
V2.17 (15.09.1997) :
 - if HAM (HAM6/8) is unavailable for a selected (RTG ?) screen mode,
 an automatic fallback to LowRes/HighRes will take place
 - dito for EHB
 - fixed a possible bug source, which would have caused problems
 when 24BITOPERATOR resulted in a BITPLANE buffer (usually ONEPLANE)
V2.16 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

## 1.78 Window.svdriver

Version : 2.4

Release Date : 31.10.1998

Requirements

AGA and/or CyberGraphX RTG system.

# Description

Window.svdriver is an external SV\_GfxBuffer display module for superview.library, which allows object-oriented displaying on AGA/RTG displays in a window on a selectable Intuition public screen.

The driver adjusts itself to the given display - which means, that colors either are remapped to the given screen colors using a "best pen" algorithm (OS compliant) or - in case of a RTG 24 bit screen - will be rendered in true color.

Scrolling within the window boundaries is possible, if the displayed graphics is larger than the original window size - if

SuperView-Library 109 / 174

that is the case, the SVDriver runs in a special scroll mode, which does not give the control back to the calling program until that mode ended.

If the graphics completely fits into the window or the window - which is resizeable - afterwards became smaller than the graphics, the scroll mode will not be entered.

When in scroll mode, the user may scroll the graphics into four directions using the cursor keys. Pressing the left mouse button or any other (vanilla) key ends the scroll mode and again gives control back to the calling application (usually another mouse click or special keyboard shortcut then will close the graphics window).

The title bar of the display window states in which mode the SVDriver currently is.

### Notes

When scroll mode isn't turned on, there's no interaction between the SVDriver and the calling program possible; so the possibility of resizing the window is disabled. Unfortunately, the normal window refresh (caused by window overlays) is disabled as well. You may wish to take a look at the "WinSlide" tool coming with SuperView, which does not suffer from these problems.

## Credits

Thanks to (in alphabetical order) Frank Dietrich, Sven Drieling, Tom Lively and several others for intensive beta testing.

### ControlPad-Switches

: "ENV:SuperView-Library/Window.controlpad" ControlPad-Name ControlPad-Commands: - 24BITOPERATOR=<OperatorName> ; (case-sensitive, ".svoperator" may be added) ; e.g. "24BITOPERATOR=Dither24Bit.svoperator" ; or "24BITOPERATOR=ExtractGrayScales" ; specifies, which operation should be performed ; on 24 bit graphics \_before\_ displaying them ; on a screen with a colordepth <= 8 ; (if not specified, "best guess" colors will be used, which is really slow). Note, that ; HAM is not allowed (thus don't specify the ; 24BitToHAM operator). - SCROLLSPEED=<Pixels> ; determines, how many pixel should ; be scrolled in any direction when ; being in scroll mode and a cursor key ; is pressed ; Default: 10 (medium slow)

- PUBSCREEN\_NAME=<PubScreenName>

SuperView-Library 110 / 174

```
; where the window driver should open
 ; its windows (if not set or not available,
 ; the default Public Screen will be used).
 - SCROLLMODE=<AUTO|NEVER|ALWAYS>
 ; - 'ALWAYS' activates scroll mode even for
 ; non-oversized graphics; this will block
 ; the input of the calling program as
 ; long as no key or mouse button has been
 ; pressed inside the display window - but
 ; will avoid window-refresh problems.
 ; - 'NEVER' is to avoid the blocking of
 ; input handling that is caused by the
 ; scrolling handler (-> PMPro Diashow, ...)
 ; Default: AUTO
 - TRUECOLOR8
 ; if the Pubscreen is a 24 bit screen but
 ; the graphics to be displayed is 'only'
 ; 8 bit or HAM6/8, usually remapping is
 ; done nevertheless. This option instead
 ; allows to call "AnyTo24Bit" first,
 ; thus giving better display quality
 ; on 24 bit screens. This is memory
 ; intensive, because for scrolling we
 ; need another complete 24 bit buffer.
 ; (requires AnyTo24Bit.svoperator)
 - PEN_PRECISION=<IMAGE|EXACT>
 ; you should not change this
 ; default: IMAGE
History
~~~~~~
V2.4 (31.10.1998) :
 - added special fix for PMPro + DitherFix24.svoperator
 - added new option "PEN_PRECISION"
 - removed SCROLLALWAYS again and replaced by (more flexible)
   SCROLLMODE option
V2.3 (05.10.1998) :
 - added "SCROLLALWAYS" option to allow to avoid the known
   window-refresh problems when in non-scroll mode
 - added "TRUECOLOR8" option to allow 8 bit and HAM display
   without remapping on 24 bit screens
 - added special (undocumented ;) option for PMPro's public screens
V2.2 (19.07.1998) :
 - tried to speed up remapping a little
V2.1 (21.06.1998) :
 - first release
```

SuperView-Library 111 / 174

## 1.79 CgxOverlay.svdriver

```
© 1998 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
            : 2.1
Release Date : 20.12.1998
Requirements
~~~~~~~~~~
 CyberGraphX
 RTG system, plus a graphics
card that does support CyberGraphX' video/overlay feature (e.g. CyberVision64/3D \leftarrow
) .
!! BE WARNED !! This still is a beta version...
Description
~~~~~~~~
CgxOverlay.svdriver is an external SV_GfxBuffer display module for
superview.library, which allows object-oriented displaying on
RTG displays in an overlay window on a selectable Intuition public
screen.
When in overlay mode, a true color window (16 Bit) can be created on
a given screen - the difference to a normal window just is, that a) the
underlying screen does not need to have the same colordepth and b) nothing
can be moved over this window (if do it, it won't be visible).
The driver does not need to adjust itself to the given display - which
means, that no dithering is needed, because always 16 bit true color
data can be written to the output overlay window.
Currently, no scrolling is possible - but the overlay window can
be resized to fit (handled in hardware).
ControlPad-Switches
ControlPad-Name
                  : "ENV:SuperView-Library/CgxOverlay.controlpad"
ControlPad-Commands : - PUBSCREEN_NAME = < PubScreenName >
                        ; where the window driver should open
                        ; its windows (if not set or not available,
                        ; the default Public Screen will be used).
History
~~~~~
V2.1 (20.12.1998) :
 - first release (after some beta testing)
```

SuperView-Library 112 / 174

## 1.80 CyberGraphics.svdriver

© 1995-98 by Andreas R. Kleinert. FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Version : 2.20

Release Date : 03.04.1998

### Requirements

~~~~~~~~~

- OS V3+ (V39)+ and its libraries
- AMIGA with CyberGraphX V2/V3 System and appropriate Graphics Card
- cybergraphics.library V40+

### Description

CyberGraphics.svdriver is an external SV\_GfxBuffer display module for superview.library, which allows object-oriented displaying on Amigas with the 16/24 bit CyberGraphX RTG System.

This Driver displays any 1..8 or 24 bit graphics via the CyberGraphX System. Graphics upto 256 Colors will be displayed via usual graphics routines, 24 bit graphics will be displayed via CyberGraphX in either 16 or 24 bit (16 Bit is default, because the unregistered version of CyberGraphX does not support more and I guess, that not yet all the users out there registered it already).

HAM6/8 will be converted to 24 bit, which then will either be displayed as 16 or 24 bit.

The driver will not open any Screens in standard ECS/AGA modes, since it makes more sense to use AGA.svdriver in such a case. If no CyberGraphX screenmode is specified, it will be generated, which is just the same effect like with an intelligent screen promoter. No ECS/AGA screenmodes will be passed through, since this is neither useful nor practicable on two Monitor systems or with single 31khZ-limited Monitors.

### Credits

Thanks to Ingenieurbüro Helfrich, for supplying the PiccoloSD64 card (in the meantime using a CyberVision64/3D and CyberGraphX V3, BTW).

The CyberGraphX Software of course is copyrighted by its authors, which is hereby expressesively respected in all points.

#### ControlPad-Switches

ControlPad-Name : "ENV:SuperView-Library/Cybergraphics.controlpad"

ControlPad-Commands : - EMUSCREENDEPTH=<16|24>

; beginning depth for opening CyberGraphX Screens

; Default is 16 Bit (which will also be tried

SuperView-Library 113 / 174

```
; when opening of a 24 bit Screen fails)
 ; This does not concern colordepths < 16 Bit,
 ; except HAM6/8.
 - SMALLSCREENS
 ; unless this keyword is specified, it is not
 ; tried to open screens smaller than 320x240
 History
 V2.20 (3.4.1998) :
 - small changes
 V2.19 (23.12.1997) :
 - now labeled "CyberGraphX Screendriver" instead of "Cybergraphics Screendriver
 (-> Frank Mariak)
 - recompiled with SAS/C 6.58
 V2.18 (14.08.1997) :
 - removed some unused, dead code
 - recompiled with SAS/C 6.58
1.81 EGS7.svdriver
 © 1994-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Version
 : 2.11
 Release Date : 14.08.1997
 Requirements
 ~~~~~~~~~~~
 - OS V2.04+ (V37)+ and its libraries
 - AMIGA with EGS Graphic Card (or EGS distribution with Amiga Emulation)
 - egs.library
                 V1+ (should be V7+)
 - egsintui.library V1+ (should be V7+)
                   V1+ (should be V7+)

    egsgfx.library

 Description
 EGS7.svdriver is an external SV_GfxBuffer display module for
 superview.library, which allows object-oriented displaying on
 EGS V7 (Enhanced Graphic System).
 This Driver displays any 1..8 or 24 bit graphics via the EGS7
 System. Any source Graphics with less than 24 bit, like 256 Color
 or HAM6/8 graphics, are converted to 24 bit before displaying them.
 This EGS7.svdriver is based on my former "EGS.svdriver", which is
 to be replaced by the new one. But of course you may still continue
 using the older one.
 The difference is, that the EGS7.svdriver really does display any
```

of the available source graphics formats (even HAM) and is x-times

SuperView-Library 114 / 174

faster than the old one. Also, it is now possible to directly close the EGS-Displaywindow via its Close-Gadget, since some kind of self-written Intuition-Emulation enables us to do so.

#### Note:

You may consider not to use this EGS7.svdriver, but instead EGSPlus from Aminet (Aminet:gfx/board/EGSPlus.lha), which offers its own cybergraphics.library clone, and thus should work with CyberGraphics.svdriver.

#### Credits

~~~~~

Thanks to Ingenieurbüro Helfrich, for supplying the PiccoloSD64 card.

The EGS7 Software is of course copyrighted by its authors, which is hereby expressesively respected in all points.

Notes

~~~~

This EGS-SVDriver should still work with the AMIGA driver for EGS.

When using the ECS/AGA emulation, you should set the max. possible colordepth in the ScreenMode preferences program.

#### AGA:

With AGA any Graphics with less than 256 Colors should be displayed 100% correctly. Only 256 Color-graphics will usually have some Colors wrong, because those are obtained by the EGS-System for the Display itself (Window-Borders, etc.), so that they usually can't be used for the graphics. 24 bit graphics will be dithered to 256 Colors under AGA (usually grayscaled).

#### ECS:

Using the ECS emulation will perhaps nearly always result in very ugly Colors, if you're displaying more than, let's say, 8 Colors. This results out of the maximum colordepth of 16 Colors in Hires, of which some - see AGA notes - are already reserved. Of course 24 bit graphics may also be dithered to 16 Colors/Grayscales, but better don't try it out ...

```
History ~~~~~ V2.11 (14.08.1997) :
```

- recompiled with SAS/C 6.58

## 1.82 Picasso96.svdriver

```
\odot 1997 by Andreas R. Kleinert. FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
```

Version : 2.5

SuperView-Library 115 / 174

Release Date : 03.04.1998

### Requirements

~~~~~~~~~

- OS V3+ (V39)+ and its libraries
- AMIGA with Picasso96 System and appropriate Graphics Card
- Picasso96API.library V2+

Description

~~~~~~~~~

Picasso96.svdriver is an external SV\_GfxBuffer display module for superview.library, which allows object-oriented displaying on Amigas with the Picasso96 RTG System.

The related Picasso96 libraries are needed.

This Driver supports the following :

| Source   | Depth | Special Modes | Dimensions           | Dest. Depth |
|----------|-------|---------------|----------------------|-------------|
| ONEPLANE | 8/24  | нам6, нам8    | [ Picasso-Dependent] | 8 / 24      |
| BITPLANE | 18    | HAM6, HAM8    | [ Picasso-Dependent] | 8 / 24      |

HAM6/8 will be converted to 24 bit, which then will either be displayed as 16 or 24 bit.

24 bit will either be displayed in 16 or 24 bit.

#### Credits

~~~~~~

Thanks to Tobias Abt and Alexander Kneer (Picasso 96 team) for developer support and beta-testing/debugging.

The Picasso96 Emulation Software of course is copyrighted by it authors, c/o Tobias Abt and Alexander Kneer, which is hereby expressesively respected in all points.

ControlPad-Switches

ControlPad-Name : "ENV:SuperView-Library/Picasso96.controlpad"

ControlPad-Commands : - SMALLSCREENS

- ; unless this keyword is specified, it is not ; tried to open screens smaller than 320x240
- EMUSCREENDEPTH=<16|24>
 - ; beginning depth for opening Picasso96 Screens ; Default is 24 bit (if opening fails, it is

 - ; also tried to open a 16 Bit Screen, then)

History

V2.5 (03.04.1998) :

- no longer tries to open 16/24 bit screens on 8 bit mode IDs; should fix known problems with PMPro and SViewNG
 - (-> thanks to IrseeSoft for pointing out and to Alexander Kneer for reporting and help on debugging)

SuperView-Library 116 / 174

```
- cleaned up source a little bit, smaller now V2.4 (20.08.1997):
```

- explicitely clears screen (SetRast) before displaying
- WritePixelArray8() seems to have produced crap sometimes, now doing it the same way as in CyberGraphics.svdriver
- recompiled with SAS/C 6.58
- fixed a bunch of bugs; should work as expected, now.
 Did some testing with P96/PicassoIV, P96/PicassoII and P96-CGfx emulation
 - (-> Paul Lesurf, Jürgen Schäfer, me)

1.83 Picassoll.svdriver

© 1995-98 by Andreas R. Kleinert. FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Version : 2.11
Release Date : 14.08.1997

Requirements

~~~~~~~~~~~

- OS V2.04+ (V37)+ and its libraries
- AMIGA with Picasso II/II+/IV Graphics Card and Software,
   Picasso96 emulation should work as well (not tested yet)
- vilintuisup.library V1+

## Description

~~~~~~~~

PicassoII.svdriver is an external SV_GfxBuffer display module for superview.library, which allows object-oriented displaying on Amigas with the Picasso Workbench Emulation System.

The related Picasso-libraries are needed.

This Driver supports the following:

Source Depth Special Modes Dimensions Dest. Depth
ONEPLANE 8/24 HAM6, HAM8 [Picasso-Dependent] 8 / 24
BITPLANE 1..8 HAM6, HAM8 [Picasso-Dependent] 8 / 24

HAM6/8 will be converted to 24 bit, which then will either be displayed as 16 or 24 bit.

24 bit will either be displayed in 16 or 24 bit.

Credits

~~~~~~

Thanks to Florian Zeiler (IrseeSoft) for supplying the Gfx Card.

The Picasso Emulation Software is of course copyrighted by Village Tronic Marketing GmbH, which is hereby expressesively respected in all points.

SuperView-Library 117 / 174

### Known Bugs

~~~~~~~

Problem:

As with V1.8 (6. Apr 1994) of the Picasso II Software Set, the vilintuisup.library sometimes supplies Screens, which differ between internal dimensions and actual dimensions.

A 24 bit graphics with 1165x712 would be displayed on a Screen with correct dimensions in best ViewMode. But for some reason, the Intuition Part of the Screen will be opened in 1168x712 with a related ViewMode. Whenever this ViewMode is the best fitting one, this seems to make problems to the Picasso Emulation. If the ViewMode is one with a larger or smaller display (so that either Autoscroll has to be used, or the graphics does not fill the whole screen) this does not occur. This is not a bug of the PicassoII.svdriver, since width adjustments will occur independently from the viewmode selection.

Solution:

Whenever the Picture is weirdly distorted, at first try an other viewmode. This bug does not seem to cause crashes, only destroyed displays.

Maybe a newer version of the Picasso Software already did fix this (seems to be an alignment problem when copying from RAM into the Picasso onboard-memory).

Problem:

When using AUTOSCROLLADJUST the Picasso Software may destroy about two lines within the displayed picture (get black).

Solution:

Don't use it.

ControlPad-Switches

ControlPad-Name

- : "ENV:SuperView-Library/PicassoII.controlpad"
- ControlPad-Commands : SMALLSCREENS
 - ; unless this keyword is specified, it is not
 - ; tried to open screens smaller than 320x240
 - BLITTER
 - ; uses the Picasso blitter to copy graphics
 - ; into screens. Otherwise CPU is used.
 - ; On 68000 systems you may wish to use the blitter
 - EMUSCREENDEPTH=<16|24>
 - ; beginning depth for opening Picasso Screens
 - ; Default is 24 bit (if opening fails, it is
 - ; also tried to open a 16 Bit Screen, then)
 - SCREENMODEREQUEST
 - ; if this one is specified, the $\ensuremath{\mathsf{SVDriver}}$ ITSELF
 - ; will open a ScreenMode-Requester and ask
 - ; for an appropriate Screenmode to use.
 - ; Useful, if you always like to change modes.
 - AUTOSCROLLADJUST
 - ; this keyword will force Autoscroll whenever
 - ; it would make sense, but the Picasso Software
 - ; would not manage it by itself (when either
 - ; only width or height need to be autoscrolled)

SuperView-Library 118 / 174

```
History

~~~~~

V2.11 (14.08.1997) :

- removed some unnecessary parts 2.7 compatibility code

- explicitely clears screen (SetRast) before displaying

- recompiled with SAS/C 6.58
```

1.84 OPAL.sydriver

Just a short note before using and installing OPAL.svdriver and (of course ;-) reading the following documentation:

There's a little problem causing some OPAL programs not to be displayed correctly on certain systems with specific chipsets.

That was the reason why it did not work on the machines of some people - mine was one of these - but nevertheless it is easy to workaround and even already has been described within the official OpalVision Reference Manual [page 326].

To speak clearly, the color palette has to be adjusted concerning Color O (the magic color), but only the BLUE component, within the Palette Preferences.

Any other colors and components are freely selectable.

```
OCS and ECS Chipset Machines with Zorro Bus (2000-3000)
```

```
BLUE of COLOR 0 must be either 1, 3, 5, 7, 9, 11, 13, or 15.
```

AGA Chipset Machines with Zorro Bus (4000)

BLUE of COLOR 0 must have Bit 4 set, which restricts it to one of the following ranges:

```
16-31 or 48-63 or 80-95 or 112-127 or 144-159 or 176-191 or 208-223 or 240-255
```

Otherwise you may get a black or weirdly distorted screen (I tested it ;-) or must use some tricks and Amiga+M fiddling to get a picture.

```
[ Please also note, that Steve's eMail did change as follows Steve Quartly: steveq@mafeking.scouts.org.au ]
```

OPAL.svdriver/Documentation

OPAL.svdriver/Documentation

PROGRAM

OPAL.svdriver Version 2.3 Relase date: 29.6.95 SuperView-Library 119 / 174

COPYRIGHT

© 1995 Paul Huxham and Steve Quartly. Bonusware, all rights reserved.

DISTRIBUTION

Freely distributable with any non-commerical application that uses superview, however all copyright remains with the authors. This distribution archive may not be split for further distribution.

PURPOSE

OPAL.svdriver is an external display driver module for superview.library. It can display superview buffers on an OpalVision display card.

CONTENTS

OPAL.svdriver - This is the driver to copy to LIBS:svdrivers. OPAL.svdriver.doc - Documenation you are reading now.

USAGE

Select OPAL.svdriver as the display driver from SuperViewPrefs and/or from the superview compatible software you are using.

While conversion for OpalVision is taking place, the following information will be displayed:

OPAL.svdriver version number,
and the image size (which can be larger than the screen size).

REQUIREMENTS

- 1) An OpalVision card :-)
- 2) opal.library must be in LIBS: otherwise the driver will fail with an internal error.
- 3) A minimum of Kickstart 2.0.

CONTROL PAD

ControlPad-Name:

"ENV: SuperView-Library/OPAL.controlpad"

ControlPad-Commands:

OVERSCAN=ON | OFF

Force Opal to display in either overscan or non-overscan. Not specifiying an overscan setting informs OPAL.svdriver to intelligently select an overscan screen mode for you.

CENTER_IMAGE

Force the displayed image to be taken from the centre section of the image buffer, i.e. If the image is 640×512 and the display mode is LoRes, Non-interlace and CENTER_IMAGE is specified then the top left of the visible display will be 160, 156 offset into the original image.

If not present, the image will be displayed from the top left of the image buffer.

NOTES

Opal images cannot be scrolled yet (until superview supports scrolling images larger than the drivers screen size), so if the picture is larger than the display area, the displayed image will be cropped.

SuperView-Library 120 / 174

HISTORY

V0.0 First the earth cooled.

V1.0 Initial release.

V2.2 Supports new features of superview.library version 11.6

- Selectable screen modes.
- Control pads for configuration.
- V2.3 Fixed byte aligning of 24 bit images.
 - Drastically reduced memory requirements and increased speed by removing the conversion from RGB triplets through RGB planes.

COMPLIER

OPAL.svdriver was written using CED V3.5 and compiled with SAS/C 6.55 on an Amiga 2000/030 and Amiga 4000/040. Enforcer was used to detect and correct programming errors.

BUGS

Should you find any bugs, please report them so that they can be fixed. Likewise any suggestions for improvment of the driver should be forwarded so that they can be addressed.

THANKYOU

Very many thanks to Andreas, the author of Superview.library for implementing some of our suggestions and also for explaining some of the internals of superview.library. Without superview this driver would be a boat anchor. (It would probably float :-)

AUTHORS

You can contact the authors via:
Email:
 Paul Huxham
 paulh@Perth.DIALix.oz.au

Steve Quartly
steveq@sndcrft.DIALix.oz.au

or
 P.O. Box 875
 Morley,
 Perth,
 Western Australia 6943

1.85 Retina.svdriver

```
© 1995-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Version : 2.14
Release Date : 14.08.1997
```

Requirements

~~~~~~~~~

- OS V2.04+ (V37)+ and its libraries
- AMIGA with Retina  ${\tt Z2/Z3}$  Graphics Card and Software

SuperView-Library 121 / 174

```
- retina.library V7+
- retinaemu.library V1+
```

### Description

~~~~~~~~

Retina.svdriver is an external SV_GfxBuffer display module for superview.library, which allows object-oriented displaying on Amigas with the 16/24 bit Retina Workbench Emulation System.

The related Retina-libraries are needed.

This Driver supports the following:

```
Source Depth Special Modes Dimensions Dest. Depth

ONEPLANE 8/24 HAM6, HAM8 [Retina-Dependent] 16 / 24

BITPLANE 1..8 HAM6, HAM8 [Retina-Dependent] 16 / 24
```

 ${\rm HAM6/8}$ will be converted to 24 bit, which then will either be displayed as 16 or 24 bit.

USAGE

~~~~

#### RetinaEmu:

\_\_\_\_\_

For SuperView's "svdRetina-Screen" screen entry, select an AutoScroll-Area of "800x600" and "No Refresh" with "Retina Standard" (Z2) or "Retina Blitter" (Z3) output.

#### RetinaScreenMode:

\_\_\_\_\_

The Monitor specifications need to be 100% correct.

### What using instead?

\_\_\_\_\_

Retina.svdriver always displays graphics in 16/24 bit - so when running on AGA systems, AGA.svdriver would be the better solution for upto 256 Colors. On ECS systems this may only apply to 16/32 Color graphics as long as you don't have OS 3.1 and a RetinaEmu which supports 256 Color Screens for this configuration (should be available). Otherwise with ECS.svdriver you would still have to specify "8BITOPERATOR" for more than 16/32 Colors, which then would be as slow or even slower.

## Credits

~~~~~

Thanks to Florian Zeiler (IrseeSoft) for supplying the Gfx Card.

The Retina Emulation Software is of course copyrighted by MS MacroSystem Computer GmbH Germany, which is hereby expressesively respected in all points.

ControlPad-Switches

ControlPad-Name : "ENV:SuperView-Library/Retina.controlpad"

ControlPad-Commands : - EMUSCREENDEPTH=<16|24>

; beginning depth for opening Retina Screens

SuperView-Library 122 / 174

```
; Default is 24 bit (if opening fails, it is ; also tried to open a 16 Bit Screen, then)

History

V2.14 (14.08.1997):

- there was a BSS allocation for "chip" left

- recompiled with SAS/C 6.58
```

1.86 MERLIN.svdriver

```
© 1994-96 by Thomas Eigentler,
© 1996-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
```

Version : 2.9

Release Date : 14.08.1997

Requirements

~~~~~~~~~~~

- OS V2.04+ (V37)+ and its libraries
- AMIGA with MERLIN Graphics Card and Software
- hrgsystem.library V38+
- hrgrender.library V38+

#### Description

~~~~~~~~

MERLIN.svdriver is an external SV_GfxBuffer display module for superview.library, which allows object-oriented displaying on Amigas with the 16/24 bit Merlin Workbench Emulation System.

Original Author

~~~~~~~~~~~~~~

MERLIN.svdriver has been included into the SuperView-Library distribution with friendly permission by the original author, who also supplied the source code to continue development.

Thomas' does no longer continue development of MERLIN.svdriver, which I took over from him, but for any other issues you may Thomas Eigentler reach him via one of his email adresses:

FidoNet: Thomas Eigentler 2:246/1511.0

## Credits

~~~~~

The Merlin Emulation Software is of course copyrighted by its authors (ProDev), which is hereby expressesively respected in all points.

Thanks go to Mika Lundell and Thomas Eigentler for reporting bugs and doing beta testing.

SuperView-Library 123 / 174

```
Notes
  It has been reported, that MERLIN.svdriver crashes, when it is tried
  to open the 040 version of hrgblitter.library on a 060.
  Not a bug of superview.library (-> Thomas Eigentler).
  History
  ~~~~~~
  V2.9 (14.08.1997) :
   - recompiled with SAS/C 6.58
1.87 XOR.svoperator
  © 1994-98 by Andreas R. Kleinert.
  FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
            : 3.9
  Version
  Release Date : 02.11.1997
  Description
  ~~~~~~~~~
  XOR.svoperator is an external SV_GfxBuffer modification module
  for superview.library.
  XOR.svoperator modifies a graphics in a way, that the color register
  numbers of the supplied picture's pixels are XOR'ed with a given value,
  which may be specified via ControlPads (see below).
  Note, that the supplied XOR value must be be smaller or equal the
  number of colors, thus smaller or equal 2^(depth) - 1.
  ControlPad-Switches
  ~~~~~~~~~~~~~~~~~
                   : "ENV:SuperView-Library/XOR.controlpad"
  ControlPad-Name
  ControlPad-Commands : - XORVALUE=<0..255>
                          ; 0 and 255 will not be the best decision ;-)
                          ; Use 15 or something like this.
                          ; Values greater (depth^2)-1 (is: colors-1) won't
                          ; be accepted.
  History
  V3.9 (02.11.1997) :
  - fixed old bug with graphics < 256 colors
  V3.8 (14.08.1997) :
```

- recompiled with SAS/C 6.58

SuperView-Library 124 / 174

1.88 24BitToHAM.svoperator

```
© 1994-98 by Andreas R. Kleinert.
(Also see notes under "Credits".)
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Supports powerUP (TM).
Version
            : 3.11
Release Date : 16.02.1998
Description
24BitToHAM.svoperator is an external SV_GfxBuffer modification module
for superview.library.
24BitToHAM.svoperator dithers 24 bit RGB graphics to HAM6/HAM8,
either quick or well.
ControlPad-Name
                    : "ENV:SuperView-Library/24BitToHAM.controlpad"
ControlPad-Commands : - DITHERMODE=< HAM6_QUICK|HAM6_WELL</pre>
                                     |HAM8_QUICK|HAM8_WELL>
                        ; specifies the HAM-Mode to be used and
                        ; the resulting speed/quality
History
~~~~~
V3.11 (16.02.1998) :
 - changed for new .svm style PPC modules
V3.10 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

1.89 Blur.svoperator

SuperView-Library 125 / 174

- included with public library release (PPC support and 030 version !)

1.90 Crop.svoperator

```
© 1995-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
            : 3.8
Release Date : 14.08.1997
Description
Crop.svoperator is an external SV_GfxBuffer modification module
for superview.library.
Crop.svoperator may extract shapes of any size from any 2..256 Color
or 24 bit graphics.
Values for "LeftEdge", "TopEdge", "Width" and "Height", describing
the crop box have to be supplied via ControlPad settings.
ControlPad-Switches
~~~~~~~~~~~~~~~~~
ControlPad-Name
                    : "ENV:SuperView-Library/Crop.controlpad"
ControlPad-Commands : - CROP_LEFTEDGE=<Value>
                        ; crop from x position
                        ; (will be adjusted, if >= source width)
                      - CROP_TOPEDGE=<Value>
                        ; crop from y position
                        ; (will be adjusted, if >= source height)
                      - CROP_WIDTH=<Value>
                        ; crop how many x pixels from leftedge
                        ; (will be adjusted, if too large)
                      - CROP HEIGHT=<Value>
                        ; crop how many y pixels from topedge
                        ; (will be adjusted, if too large)
History
~~~~~~
V3.8 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

1.91 Dither24Bit.svoperator

```
© 1994-98 by Andreas R. Kleinert.

(Also see notes under "Credits".)

FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Supports powerUP (TM).

Version : 3.14

Release Date : 16.02.1998
```

SuperView-Library 126 / 174

```
Description
~~~~~~~~~
Dither24Bit.svoperator is an external SV_GfxBuffer modification module
for superview.library.
Dither24Bit.svoperator dithers 24 bit RGB graphics to 256 Colors
by default. Possible is also dithering to less colors (2..128),
if specified via ControlPad-Settings.
This module applies Heckbert's median cut and dithers
using Floyd-Steinberg.
ControlPad-Switches
: "ENV:SuperView-Library/Dither24Bit.controlpad"
ControlPad-Name
ControlPad-Commands : - COLORDEPTH=<1..8>
                        ; specifies the colordepth of the dithering
                        ; output (1->2 Colors .. 8->256 Colors)
                      - DITHERMODE=<BESTPEN|DITHER FLOYD-STEINBERG
                                    |ORDERED|BURKES>
                        ; whether to just select the best pen or
                        ; do Floyd-Steinberg pixel error adjustment
History
V3.14 (16.02.1998) :
 - changed for new .svm style PPC modules
V3.13 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

1.92 HilbertDither256.svoperator

```
© 1994-98 by Andreas R. Kleinert.
(Also see notes under "Credits".)
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Supports powerUP (TM).
Version
          : 3.9
Release Date : 21.02.1998
Description
~~~~~~~~~
HilbertDither256.svoperator is an external SV_GfxBuffer modification module
for superview.library.
HilbertDither256.svoperator modifies any supplied source SV_GfxBuffer in a
way, that all supplied graphics with upto 256 Colors are dithered to
Black & White graphics (2 Colors), as e.g. needed for desktop publishing
or output on matrix printers.
It uses the fractal Hilbert curve for getting best results in
eliminating the resulting errors.
```

SuperView-Library 127 / 174

```
As a side effect, the resulting picture will always have a width and
 height, which is divideable by 16 (graphics will be adjusted this way).
 ControlPad-Switches
  ~~~~~~~~~~~~~~~~~~~
                    : "ENV:SuperView-Library/HilbertDither256.controlpad"
 ControlPad-Name
 ControlPad-Commands : - BACKGROUND=<BLACK|WHITE>
                          ; defines, which of the two colors will act
                          ; as background color. Useful e.g. for printing.
 History
 V3.9 (21.02.1998) :
  - added PPC support (via optional plugin)
   - improved memory handling
  - now correctly rejects HAM, as it already should have from the
    very beginning (bug!)
 V3.8 (14.08.1997) :
  - recompiled with SAS/C 6.58
1.93
     AnyTo24Bit.svoperator
 © 1995-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
 Version
           : 3.9
 Release Date : 21.02.1998
 Description
  ~~~~~~~~
 AnyTo24Bit.svoperator is an external SV_GfxBuffer modification module
 for superview.library.
 AnyTo24Bit.svoperator converts any input graphics into TrueColor
 RGB graphics with 24 bit.
 Input may be any (upto) 256 Color graphics or HAM6/HAM8 data.
 History
 V3.9 (21.02.1998) :
  - added PPC support (via optional plugin)
  - fixed possible bug in HAM viewmode handling
  - fixed bug in EHB viewmode/info handling
 V3.8 (14.08.1997) :
  - recompiled with SAS/C 6.58
```

SuperView-Library 128 / 174

1.94 ExtractGrayScales

```
© 1994-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
            : 3.8
Release Date : 14.08.1997
Description
~~~~~~~~~
ExtractGrayScales.svoperator is an external SV_GfxBuffer modification module
for superview.library.
ExtractGrayScales.svoperator modifies any supplied source SV_GfxBuffer
in a way, that its colormap will be changed to reflect gray-scales
(works with (upto) 256 Colors and 24 bit files).
Output is done in input colordepth or 256 Colors by default (fastest).
This is a sample SVOperator for simple demonstration how to write one.
It's simple, but effective.
ControlPad-Switches
~~~~~~~~~~~~~~~~~
                    : "ENV:SuperView-Library/ExtractGrayScales.controlpad"
ControlPad-Name
ControlPad-Commands : - COLORDEPTH=<1..8>
                        ; specifies the colordepth of the grayscaled
                        ; output (1->2 Colors .. 8->256 Colors)
                      - OUICK
                        ; uses >>2, >>1, >>3 (*0.25, *0.5, *0.125)
                        ; instead of *0.3, *0.59, *0.11
History
~~~~~~
V3.8 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

1.95 ExtractRed

```
© 1994-98 by Andreas R. Kleinert.

FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Version: 3.8

Release Date: 14.08.1997

Description

-------------

ExtractRed.svoperator is an external SV_GfxBuffer modification module for superview.library.

ExtractRed.svoperator modifies any supplied source SV_GfxBuffer in a way, that only the RED values of a picture will be extracted for creation of a new (upto) 256 Color graphics (works with (upto) 256 Colors and 24 bit files).
```

SuperView-Library 129 / 174

```
History ~~~~~ V3.8 (14.08.1997) : - recompiled with SAS/C 6.58
```

1.96 ExtractGreen

```
© 1994-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
Version
          : 3.8
Release Date : 14.08.1997
Description
ExtractGreen.svoperator is an external SV_GfxBuffer modification module
for superview.library.
ExtractGreen.svoperator modifies any supplied source SV_GfxBuffer
in a way, that only the GREEN values of a picture will be extracted
for creation of a new (upto) 256 Color graphics
(works with (upto) 256 Colors and 24 bit files).
History
~~~~~
V3.8 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

1.97 ExtractBlue

```
© 1994-98 by Andreas R. Kleinert.

FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

Version : 3.8

Release Date : 14.08.1997

Description

-------

ExtractBlue.svoperator is an external SV_GfxBuffer modification module for superview.library.

ExtractBlue.svoperator modifies any supplied source SV_GfxBuffer in a way, that only the BLUE values of a picture will be extracted for creation of a new (upto) 256 Color graphics (works with (upto) 256 Colors and 24 bit files).

History

------

V3.8 (14.08.1997) :
```

SuperView-Library 130 / 174

- recompiled with SAS/C 6.58

1.98 TopToBottom

```
© 1994-98 by Andreas R. Kleinert.
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
          : 3.8
Version
Release Date : 14.08.1997
Description
~~~~~~~~~~
TopToBottom.svoperator is an external SV_GfxBuffer modification module
for superview.library.
TopToBottom.svoperator modifies any supplied source SV_GfxBuffer
in a way, that it will be swapped from bottom to top
(works with (upto) 256 Colors and 24 bit files).
History
~~~~~
V3.8 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

1.99 LeftToRight

1.100 Rotate

SuperView-Library 131 / 174

© 1995-98 by Andreas R. Kleinert.

```
FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Version
              : 3.8
 Release Date : 14.08.1997
 Description
  ~~~~~~~~~
 Rotate.svoperator is an external SV_GfxBuffer modification module
 for superview.library.
 Rotate.svoperator rotates any (upto) 256 Color or 24 bit graphics
 by (default) 90 degrees (reverse clockwise).
 The default behaviour may be overwritten via controlpad settings,
 which also allow 180 and 270 degrees (no extra memory needed: uses
 different algorithm).
 ControlPad-Switches
  ~~~~~~~~~~~~~~~~~~
                     : "ENV:SuperView-Library/Rotate.controlpad"
 ControlPad-Name
 ControlPad-Commands : - DEGREES=<90|180|270>
                         ; rotate by how many degrees (reverse clockwise) ?
 History
 V3.8 (14.08.1997) :
  - recompiled with SAS/C 6.58
1.101 RotateFree
 © 1995-98 by Andreas R. Kleinert.
  (Also see notes under "Credits".)
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
            : 3.13
 Version
 Release Date : 05.04.1998
 Description
  ~~~~~~~~~~
 RotateFree.svoperator is an external SV_GfxBuffer modification module
 for superview.library.
 Rotate.svoperator rotates any (upto) 256 Color or 24 bit graphics
 by 0..360 (default is 90) degrees (reverse clockwise) about any
 given point (default is the middle, which is width/2, height/2).
 The default behaviour may be overwritten via controlpad settings.
 ControlPad-Switches
                  : "ENV:SuperView-Library/RotateFree.controlpad"
 ControlPad-Name
```

; rotate by how many degrees (reverse clockwise) ?

ControlPad-Commands : - ROTATE_ANGLE=<0..360>

SuperView-Library 132 / 174

```
- METHOD=<MIDDLE|GIVENPOINT>
                          ; default is rotation about the middle
                        - X_COORD=<Value>
                          ; if METHOD=GIVENPOINT we need (X/Y)
                          ; Default is (0/0)
                        - Y_COORD=<Value>
                          ; if METHOD=GIVENPOINT we need (X/Y)
                          ; Default is (0/0)
                        - KEEPSIZE
                          ; if this keyword is set, it is NOT tried to
                          ; readjust the image size and to center the
                          ; image, so that parts, which would be out of
                          ; range won't be cut off (which works best
                          ; with (X/Y) pairs in the left, upper quarter)
 History
  ~~~~~
 V3.13 (05.04.1998) :
  - now using mathffp/mathtrans.library: smaller, faster (68k only)
  - now using libmoto.a: faster (PPC only)
  - better optimization, compiler settings
  - there was a major bug in the algorithm, which could cause patterns
    of black pixels within the image (-> Tilo Hanich, Florian Zeiler).
    This has been fixed; for this, the algorithm completely had to
    be redesigned and rewritten.
  - heavy optimization on the new algorithm
 V3.12 (19.02.1998) :
  - changed for new .svm style PPC modules
   - fixed size calculation for resulting image;
    plus added special cases for 90/270 and 180/360 degrees
 V3.11 (14.08.1997) :
  - recompiled with SAS/C 6.58
1.102 Scale50
 © 1995-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
 Version
             : 3.10
 Release Date : 16.02.1998
 Description
 Scale50.svoperator is an external SV_GfxBuffer modification module
 for superview.library.
```

Scale 50. svoperator scales any (upto) 256 Color or 24 bit graphics

The default behaviour may be overwritten via controlpad settings,

to their half size by default.

SuperView-Library 133 / 174

```
which also allows to double the size instead.
 ControlPad-Switches
  : "ENV:SuperView-Library/Scale50.controlpad"
 ControlPad-Name
 ControlPad-Commands : - METHOD=<HALF|DOUBLE>
                         ; scale to which size ?
 History
 V3.10 (16.02.1998) :
  - changed for new .svm style PPC modules
 V3.9 (14.08.1997) :
  - recompiled with SAS/C 6.58
1.103 Sharpen.svoperator
 © 1994-98 by Andreas R. Kleinert.
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
             : 3.7
 Version
 Release Date : 17.11.1998
```

History

Description

V3.7 (17.11.1998) :

for superview.library.

- included with public library release (PPC support and 030 version !)

Sharpen.svoperator is an external SV_GfxBuffer modification module

It applies a Sharpen style operator to a given graphics.

1.104 CallPNM

SuperView-Library 134 / 174

This is not an operator in the common sense.

Instead it is just an Interface to allow easy access to any external operators from the well known PBM package (distributed as NetPBM).

When using this operator, the given GfxBuffer will be saved as a 24 bit PNM file (8 Bit input as well), after that the specified PBM program module will be externally called and its output will be written into another temporary file.

This file then will be parsed through superview.library (perhaps it will be in PNM format, but one never know) and the buffer will be returned as the result of the "CallPNM" operation.

Please note, that the whole internal construction of the operator is a little bit more complicated than usual, so that any error handling will perhaps not always result in very clear statements (can't parse the output of the PBM programs).

BTW, any temporary files will of course be placed into "VMEM:", from where they will be deleted later.

```
ControlPad-Switches
ControlPad-Name : "ENV:SuperView-Library/CallPNM.controlpad"
ControlPad-Commands : - STACKSIZE=<value>
                       ; stacksize to be used for calling PNM program,
                       ; increasing may help on crashes
                       ; default is: 32768
                     - PNMCOMMAND=<PBM command path and name>
                       ; PNM command to be called
                       ; e.g. PNMCOMMAND=Work:NetPBM/pnm/pnmscale
                     - PNMOPTIONS=<Options>
                       ; Options for PNM command to be called
                        ; e.g. PNMOPTIONS=-xscale 2.0 -yscale 2.0
History
~~~~~~
V3.8 (01.04.1998) :
- changed way of calling the program (SystemTagList), which should
   fix some crashes on certain programs/graphics
 - added possibility to increase stacksize, when necessary (crashes ?)
V3.7 (14.08.1997) :
 - recompiled with SAS/C 6.58
```

1.105 OptimizePalette

```
\odot 1995-98 by Andreas R. Kleinert. FREEWARE. All rights reserved. Only to be distributed with SuperView-Library. Supports powerUP (TM).
```

SuperView-Library 135 / 174

```
Version
              : 3.10
 Release Date : 21.02.1998
 Description
 OptimizePalette.svoperator is an external SV_GfxBuffer modification module
 for superview.library.
 OptimizePalette.svoperator filters all unused colors out of a palette
 of a given graphics with upto 256 Colors
  (EHB, HAM6/8 and 24 bit graphics will be rejected).
 A new palette will be created - which also misses any duplicate color
 table entries - to which then the given graphics is remapped.
 This Operator may have three effects (plus combinations):
   a) none, if the palette already was or has been optimized
   b) only some black colors at the end of the color map, if
       removing of unused colors did not suffice to fall back to
       the next lower depth boundary
       (<= 256 to <= 1, 2, 4, 8, 16, 32, 64 or 128)
   c) a reduced colordepth to one of the next lower depth boundaries
       (as described under b) if there've been a lot of actually
       unused colors
   d) combinations of b) and c)
 History
 V3.10 (21.02.1998) :
  - added missing __saveds
  - added PPC support (via optional plugin)
 V3.9 (14.08.1997) :
  - recompiled with SAS/C 6.58
1.106
      PaletteDither.svoperator
 © 1996 by Andreas R. Kleinert.
  (Also see notes under "Credits".)
 FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.
 Supports powerUP (TM).
              : 3.10
 Version
 Release Date : 19.02.1998
 Description
```

PaletteDither.svoperator dithers 24 bit RGB graphics 2..256 color graphics by using a selectable number of colors from a specified

for superview.library.

PaletteDither.svoperator is an external SV_GfxBuffer modification module

SuperView-Library 136 / 174

fixed palette for that (taken from a given graphics file) and

calculating the (optional) rest by itself.

o The GUI of the

under "biz/haage/WizardLibrary.lha").

This is useful for creation of ANIMations, where the palette for all single frames have to be (mostly) identical or for games and other applications where the palette of used graphics have to harmonize together. ControlPad-Switches ~~~~~~~~~~~~~~~~~~~ : "ENV: SuperView-Library/PaletteDither.controlpad" ControlPad-Name ControlPad-Commands : - COLORDEPTH=<1..8> ; specifies the colordepth of the final, ; dithered graphics (1..8 for 2..256 colors) - DITHERMODE=<BESTPEN|DITHER_FLOYD-STEINBERG> ; whether to just select the best pen or ; do Floyd-Steinberg pixel error adjustment - PALETTEDEPTH=<1..8> ; number of colors (depth) to be taken from the ; fixed palette - the possible rest will be ; generated (if specifying more palette colors ; than available, all available will be taken) - PALETTEFILE=<palette graphics filename> ; any 2...256 color graphics file, of which ; superview.library is able to extract a ; palette from (for example an IFF-ILBM file, ; but including a BMHD and - maybe empty - BODY). ; Allows to take one graphics as sample for ; the others (concerning the palette). History V3.10 (19.02.1998) : - fixed bug in colormap calculation - added PPC support (via optional plugin) V3.9 (14.08.1997) : - recompiled with SAS/C 6.58 Requirements for the SuperView-Library Package Generally, you need at least an 68000 Amiga, running with OS \leftrightarrow 2.04 + .Better performance results require better software/hardware. More requirements (software, hardware, legal):

program has been designed with StormWizard 2.0, so this program needs "wizard.library" V37+ (you can find a copy on Aminet

\textdegree{} For usage of the IFF-based SVObjects, like ILBM, ACBM, PBM, DEEP

SuperView-Library 137 / 174

```
and YUVN, you should take care to have iffparse.library V37+
    on your bootdisk or system partition.
  \textdegree{} For DataType support with OS 3.x+ you need datatypes.library V39 \leftrightarrow
    to be present. If it is not present, datatype-support is disabled,
    but you might not need it, anyway.
  \textdegree{} For being able to use 24 bit Datatypes extension,
    you need Ralph Schmidt's picture.datatype V43 to be installed
    (with ECS/AGA you'll also need a version of cyberncq.library, which
    had been removed from newer pic-dt 43 distributions).
    The picture.datatype V43 which is coming with the Picasso96 RTG
    package will work as well, even with ECS/AGA.
  \textdegree{} Postscript (TM) support via
              GhostScript.svobject
               and EPS.svobject
    requires Ghostscript being correctly installed and configured.
    Without working GhostScript.svobject and a special flag set,
    EPS.svobject will not be able to extract any of the Postscript (TM)
    data from EPS(F) files, but only the possibly included preview
    images from the header (which usually are TIFFs).
  \textdegree{} FIG (-> AmiFIG) support requires both, Ghostscript and
              AmiFIG.svobject
    being correctly installed and configured.
  \textdegree{} CGM (-> GPlot) support requires both, Ghostscript and
              GPlot.svobject
    being correctly installed and configured.
  \textdegree{} WMF/AMF/IFF-DR2D/DXF/WPG-Vector (-> MetaView) support requires
              MetaView.svobject
              , being correctly installed and configured.
  \ensuremath{\mbox{ }} \textdegree{} SVG.svobject, Unpack.svobject and RGFX.svobject may/will require \leftrightarrow
      xpkmaster.library
    to work fully/properly. The Xpk package can be found on Aminet
    as Aminet:util/pack/xpk_User.lha (also present are xpk_Develop.lha
    and xpk_Source.lha).
  \textdegree{} AmiIcon.svobject optionally supports newicon.library for reading ←
     /writing
    NewIcons. The NewIcon package can be found on Aminet as Aminet:util/wb/ \leftarrow
       NewIcon#?.lha
    (replace #? with the corresponding version number).
  \textdegree{} Support for highest PhotoCD resolutions BASE*4 (1536x1024) and \leftarrow
     BASE*16 (3072x2048)
    does require the NetPBM-Tool "hpcdtoppm" to be installed and configured for
    use with PCD.svobject. See
              PCD.svobject
               description for
    more information. The lower resolutions upto BASE (768x512) will work \leftrightarrow
       without.
GIF is obsolete - you neither should use nor support it any longer. If
you are doing WWW design, use PNG and JPEG instead. It's important !
Additionally there are some more requirements, which do not
```

SuperView-Library 138 / 174

necessarily depend on the OS or the hardware:

\textdegree{} Some SVObjects, SVDrivers or SVOperators additionally require
different hardware/software configurations, but usually this is
stated within their own documentation.

Turbo versions will be installed by the installer-script automatically, if it makes sense (CPU auto-detection - should even work with 68060).

1.108 NotesAndHints

Notes and Hints

How much Memory does this program eat ?!

Problems with displaying 24 bit files

Problems with converting 24 bit files

1.109 Memory Usage

How much Memory does this program eat ?!

Simply enough, there are no fixed limits ...

Superview.library and its attached SVObjects, SVDrivers and SVOperators request as much memory as they need - which directly depends on the size of the processed graphics - and there's no automatic virtual memory manager or such (I added some virtual memory support, but up to now there aren't any modules making use of it).

But actually no CHIP memory is needed for most of the actions (only some chunky-to-planar conversion operations and some specific SVDrivers may make use of CHIP memory) - so perhaps nearly anything will be performed in FAST ram, when your configuration offers enough. You should have at least 2 MB Ram at all (1 CHIP, 1 FAST or 2 CHIP), better 4 MB (2 CHIP, 2 FAST) or more.

The large memory usage results out of the buffering-technique, which is used with the SuperView-Library.

This technique increases memory usage by using large (full-sized) buffers, which often do exist twice e.g. for conversion from chunky-pixel to bitplane format or vice versa.

But this increases SPEED !!

SuperView-Library 139 / 174

There are perhaps no "real" multimedia-systems out there, which have less than 6 - 16 MB and why shouldn't we use this memory (you may BTW use VMM or so, if you don't have so much RAM).

Anyway, here's a check-list for what you can do to make more memory available to superview.library:

- o first of all, check if there are some background-programs running, which you do not really need (especially Commodities).

 Remove them !
- o call "avail flush" in the Shell or select "flushlibs" in the WB-debug menu (available when started with "LoadWB -debug"). (SuperView and Image Engineer do also allow flushing Libraries directly fromout the program.)
- o decrease the "AddBuffers" values of drives, which you do not really need (e.g. DF2, DF3, PC0, ...)
- o last not least : leave/close Workbench, stay in the Shell
- o start your favorite viewer or conversion program (e.g. SuperView)
- o again: call "avail flush"
 (this time also all unused SVObjects and SVDrivers will be flushed
 out of the memory, so that we later only will have the needed ones
 in Ram)

If you tried all of the above, and memory still does not suffice, you should buy some more SIMMs at your local Computer Shop...

1.110 Displaying 24 bit graphics

The Problem

"All of my attempts in displaying my really nice 24 bit graphics with AGA.svobject resulted in really ugly colors. What shall I do?"

The Reason

You did not set an available or valid 24 bit SVOperator, which could have been used by the selected SVDriver (e.g. AGA.svdriver, ECS.svdriver) adjusting the number of colors to less than 256 (by dithering, conversion to gray, etc.).

The solution

- -----
- o Within the SVDriver's controlpad settings file (e.g. AGA.controlpad, ECS.controlpad) you may set "24BITOPERATOR=<operatorname>" and specify a specific operator for e.g. dithering 24 bit graphics to 256 colors (Dither24Bit), converting them to grayscales (ExtractGrayScales) or HAM6/8 (24BitToHam), etc.
- o The same trick may take place for ECS.svdriver on systems, which can't display more than 16/32(64EHB) colors, so that specifying the (optional) "8BITOPERATOR=<operatorname>" would allow automatic conversion to less colors.
- o Besides this, a special case perhaps perhaps is the combination of AGA.svdriver and JPEG.svobject, where it may be good for

SuperView-Library 140 / 174

performance and memory usage to simply use the internal on-the-fly dithering of JPEG.svobject, which then simply does not make 24 bit, but 256 color output anymore, when the colordepth controlpad switch has been set as: "COLORDEPTH=8" within JPEG.controlpad.

These default settings intuitively can be changed via ${\sf SVPrefs}$

or possibly via your application's GUI as well.

o An other possibly way is, to always do the dithering only when needed - by simply invoking the needed SVOperator fromout your application's GUI.

1.111 Converting 24 bit graphics

The Problem

You have problems converting from one 24 bit file format into other 24 bit file formats ?

The Reason

Not necessarily all SVObjects, which support reading of 24 bit files do also support writing of 24 bit files.

SVObjects, which support writing 24 bit data yet are for example:

| non-lossy | | | |
|-----------|-----------|----------|------------------------|
| | | | |
| IFF-ILBM | BMP | Targa | SunRaster PNG |
| IFF-DEEP | PCX | PNM | SGI SVG |
| IFF-RGB8 | TIFF | QRT | FBM UtahRLE |
| | | | |
| lossy | not for r | reimport | not importable |
| | | | |
| IFF-YUVN | EPS | | C-Source |
| JPEG | | | PNM (when in Raw-Mode) |
| Limbo | | | |

The solution

A temporary solution might be to use other 24 bit programs for conversion, if you don't want to use one of the file formats, which are already supported.

1.112 SVPrefs

© 1994-98 by Andreas R. Kleinert. FREEWARE. All rights reserved. Only to be distributed with SuperView-Library.

SuperView-Library 141 / 174

Version : 22.1

Release Date : 18.11.1998

Description

SVPrefs is the Preferences Program for superview.library.

Any specific ControlPad settings for superview.library, superviewsupport.library and all the SVObjects, SVDrivers and SVOperators may be modified fromout here in a comfortable GUI-based way - as long as these ControlPad requirements are documented in form of a CPInfo-file placed in ENVARC: SuperView-Library (as usually).

Additionally, adding and removing of single SVObjects, SVDrivers or SVOperators is possible from here, if no other program is accessing superview.library and the related modules at the same time (to keep the internal lists valid).

Inclusion and Exclusion: Explanation

As one of the newest features of superview.library, you may also decide here, which of the installed SVObjects, SVDrivers and/or SVOperators should not be loaded into memory at startup time. This works as follows:

- excluded modules will be written to a specific configuration file at ENVARC:superview-Library and ENV:superview-Library (svobjects.exclude, svdrivers.exclude, svoperators.exclude)
- excluded modules will not be opened when the library starts its initialization phase, which means that these modules will never be loaded. May speed up opening and save memory. On the other side, these modules are not available as long as you don't re-add them to the system, either only temporarily or also by re-including.
 - So you only should apply this to modules you seldomly or never use, but don't want to de-install (everytime) nevertheless.
- any of these modules may temporarily be loaded via the "Add" function of SVPrefs as well as these (or others) may again temporarily be removed
- SVPrefs can apply (re)inclusion and exclusion to modules currently held in memory (to re-include an currently excluded module you at first have to re-load it via "Add")

Inclusion and Exclusion: Overview

INCLUDE temporarily ADD permanently ADD,

ADD, INCLUDE

EXCLUDE temporarily REMOVE

> permanently EXCLUDE, REMOVE

If you don't need that feature: simply don't use it...

SuperView-Library 142 / 174

Commandline Options

1. INIT

Syntax: SVPrefs INIT

Explanation: Initializes ppc.library

2. SET

Syntax: SVPrefs SET file NAME [VALUE]

Explanation: Can be used to change controlpad settings fromout

the Shell or an ARexx script

Example: 1. SVPrefs SET AGA 24BITOPERATOR Dither24Bit

(sets 24BITOPERATOR=Dither24Bit in ENV:SuperView-Library/AGA. \leftarrow

controlpad)

2. SVPrefs SET AGA SCREENINFRONT

(sets keyword SCREENINFRONT in ENV:SuperView-Library/AGA. \hookleftarrow

controlpad)

Requirements

~~~~~~~~~

GUI has been designed with StormWizard 2.0, so this program needs "wizard.library" V37+ (you can find a copy on Aminet under "biz/haage/WizardLibrary.lha").

#### History

~~~~~

SVPrefs' version depends on the version of superview.library it first has been included with.

V22.1 (18.11.1998) :

- adjusted version requirements

V21.10 (07.10.1998) :

- maybe skipped some revisions...

V21.5 (03.07.1998) :

- the stack as given in the program icon was far too small (4096 bytes), which caused crashes when started from WB. Increased to 32768 bytes.

(-> Gertrud Kiefer, Wolfgang Krause, various)

V21.3 (12.06.1998) :

- fixed nasty bug in "?" (preferences) with the slider/integer combination (slider was not precise enough, integer gadget did not allow to modify slider value, changes were not kept)
- fixed certain conditional enforcer hits within the prefs'
 slider and string selection routines
 (-> Sven Drieling)

SuperView-Library 143 / 174

```
V21.2 (05.04.1998) :
- added commandline option "SET" for changing controlpad settings
  fromout the shell or (ARexx) scripts
   (-> Tilo Hanich)
- documented INIT command
- no longer detaches from CLI (not useful in scripts)
V20.1 (07.02.1998) :
------
- the gadgets for "Library" and "Support-Library"
  preferences had been switched
V19.5 (31.10.1997) :
_____
 - small GUI changes
  (-> Georg Rottlaender)
- fixed revision history
V19.4 (19.10.1997) :
- fixed small bug
- new Wizard-GUI with lots of improvements done by
  Georg Rottlaender <Georg.Rottlaender@home.ivm.de>
- the screen had been locked twice, but only
  unlocked once (closing not possible)
   (-> Georg Rottlaender)
V19.3 (27.09.1997) :
______
 - misc
V19.2 (21.09.1997) :
- cleaned version history
- now using StormWizard for GUI creation,
  wizard.library V37 required
- some more gimmicks
- ensuring, that ppc.library already is in memory, before
  superviewsupport.library does try to open it
   (-> Frank Mariak)
 - added "INIT" option, which does ensure this, too.
  To be called as "SYS:Prefs/SVPrefs >NIL: <NIL: INIT"
  from S:User-Startup (see revised installation description)
```

1.113 SuperViewSupport-Library

© 1994-98 by Andreas R. Kleinert. FREEWARE. All rights reserved. Only to be distributed with SuperView-Library. Supports powerUP (TM).

Version : 13.2 Release Date : 20.02.1999 SuperView-Library 144 / 174

Description

```
superviewsupport.library contains functions, which are heavily used
by the superview.library and its SVObjects, SVDrivers and SVOperators.
superviewsupport.library helps saving diskspace by just holding this
functions for usage by the other libraries, also some superview.library
debugging functions are included.
ControlPad-Switches
~~~~~~~~~~~~~~~~~
                    : "ENV:superview-library/superviewsupport.controlpad"
ControlPad-Name
ControlPad-Commands : - C2P=<OS|SV>
                        ; determines, whether chunky to planar conversion
                        ; is managed via the appropriate OS functions
                        ; or via internal ones.
                        ; Due to various problems with the OS functions
                        ; "SV" is now default.
                        ; Be careful when using "OS" with GfxCards,
                        ; which carelessly patched graphics.library.
                        ; NOTE: PPC code will automatically be utilited,
                                when a PPC is available, but only with
                                C2P=SV
                        ; Default: SV
                      - MODEGEN=<OS|SV|SVEXT>
                        ; determines, whether viewmode generation should
                        ; rely on internal/OS functions only, or make
                        ; use of P96/CGfx(/PII) functions when available.
                        ; Similar to ModeP. "SV" may cause problems on
                        ; some systems, may work fine on others.
                        ; "SVEXT" is known from the ak-datatypes series.
                        ; Note: applicable for OS 3.0 and beyond, only.
                        ; Default: OS
History
~~~~~~
V13.2 (20.02.1999) :
 - additional $VER string to make everyone happy
V13.1 (18.11.1998) :
 - bumped to V13 (new requirement for superview.library V22+)
 - fixed error handling for cgfx-based screen grabbing (RTG 24 bit mode)
V12.4 (06.09.1998) :
 - smaller, faster
V12.3 (28.06.1998) :
 - added another optional alternative viewmode generation routine
   (already known from the ak-datatypes series)
```

```
V12.2 (03.04.1998) :
 - forgot to mention 12.1 (upgraded ppc modules to new .svm format)
 - recompiled (especially PPC modules)
V11.5 (24.12.1997) :
 - new preferences option for viewmode generation
 - fixed another possible problem in the viewmode generation
V11.4 (2.12.1997) :
 - AI's original CheckSetPatch routine was buggy, it actually did
   the opposite as expected: with any version lower or equal
   it did return TRUE, for any greater version it returned FALSE.
   Since we check for V43.4, it would only have worked with this
   one - otherwise we applied our bugfix, although it was no
   longer necessary, and with e.g. V40.16 there would not have
   been a bug-fix at all!
   This could have resulted in a destroyed source bitmap
   graphics, i.e. a black screen after certain times of viewing
   or usage of certain image processing operators.
   (-> 'black screen' effect noticed, and debugging done by
       Colin J. Knight and Sven Drieling)
V11.3 (19.11.1997) :
 - fixed some small oddities in the gfxbuffer allocation routine,
   smarter now
 - SetPatch check routine was missing a __saveds (oops)
V11.2 (27.09.1997) :
 - in internal V39 c2p and p2c functions (mode C2P=OS) there was a
   BMF_STANDARD missing
 - V37 c2p version did allocate a temporary buffer even if not
  needed/used (when SetPatch 43.x being installed)
 - if there's a PPC present, all buffers allocated via
   SVSUP_AllocGfxBuffer() will be 32-aligned at the end now
   (not mentioned in svgfx_BufferSize, though)
V11.1 (18.09.1997) :
 - due to PPC changes, bumped main library version to V11
 - c2p conversion should finally have become 'trash-save'
  under all OS versions, with and without SetPatch V43
 - there was a similar (possible) bug for OS V37/38 within
  CopyScreenToBuffer8()
 - fixed small error handling bug in screen-save routine
   (can't handle 24 Bit under non-CGfx RTG systems)
V10.4 (14.08.1997) :
 - recompiled with SAS/C 6.58
V10.3 (29.06.1997) :
```

SuperView-Library 146 / 174

```
- fixed 'memory loss on LibInit failure bugfix' ;-)
V10.2 (24.06.1997) :
 - fixed "memory loss on LibInit failure" bug
V10.1 (11.04.1997) :
 - now support PPC via powerUP's ppc.library for the following tasks:
    - chunky to planar conversion (c2p)
    - planar to chunky conversion (p2c)
V9.1 (02.04.1997) :
 - new, universal screen grabbing function with 24 Bit Cybergraphics
   support added
*****************
* Older revision descriptions have been deleted to save diskspace!
*****************
```

1.114 SuperView in the Press

```
F E E D B A C K (26.1.1999)
PRESS
```

which directly or indirectly reported about SuperView(/Library) in the

```
Following some excerpts from articles - mainly from the computer press -
past (if german, these have not been translated).
  - CU Amiga Magazine (UK)
  - Amiga Format (Future Publishing Ltd, UK)
  - Amiga Informer (Eldritch Enterprises, US)
  - Amiga Computing (IDG Media, UK)
  - Amiga Magazin, Amiga Public Domain Sonderheft (Magna Media, Germany)
  - Amiga Plus (ICP, Germany)
  - Amiga special (media, Germany)
(If you found an article in a magazine I did not list here - please
tell me. I'm usually not reading the english magazines, and probably
won't be aware of many other reviews, too)
********************
CU Amiga Magazine (UK)
  ______
  "Now this is a serious piece of work. [...]
   When you look into the features list and the PowerPC support,
   you see why the author thinks that being too tight to pay the
```

30 DM (£10) registration fee is a bit out of order. [...] this is a serious power application. [...] The whole idea behind this package is that it's quick and powerful. [...]

```
There just isn't enough space avaiable to go on over all the
    features of SuperView NG here, so listen to my advice and get the
    demo to try it for yourself. [...]
    Most definitely a must for serious graphics users."
    "Rating: ****" [ 5 stars out of 5 ]
   [ October issue 1997. Refered to SViewNG 7.xx ]
    "SuperView is a new PD picture viewer that relies on 'datatypes'.
    It also has support for 'operators' which can perform a variety of
    functions on pitures before they are viewed/saved (eg: sharpening,
    oil-painting effects and dithering of 24-bit pictures).
    "It will load and save virtually all formats [...]"
    Rating: 89 percent.
   [ March issue 1996. Referred to SuperView 5.32. Information taken from
     database under http://www.cu-amiga.co.uk/database/p11-19.html ]
Amiga Format (Future Publishing Ltd, UK)
 _____
    "[...] Picture Manager Pro makes use [...] of Superview libraries [...]"
    "[...] Picture Manager Pro is well thought out and silky smooth in
    operation. [...] It is exceptionally stable [...]"
    Rating: 92 percent (Gold Award)
   [ January 1998, issue 106. Referred to Picture Manager 4, which
     heavily makes use of SuperView-Library - so in means of speed
     and stability the rating perhaps does concern the library, too ]
Amiga Informer (Eldritch Enterprises, US) - www.amigainformer.com
_____
   "Picture Manager Pro uses the SuperView libraries to integrate the
    use of scanners, printers, and display boards. This allows versatility as
    well as modular upgrading. [...] First, using the SuperView
    processing libraries, it can color correct and enhance the thumbnail
    images that make up the catalog. There are no other packages I^{\prime}m
    aware of with this option. [\ldots] I think that Blittersoft's distribution
    teamed with Andreas Kleinert's SuperView libraries is a real winner."
   [ Issue 10. Referred to Picture Manager 4.1 + Library V19.x ]
   "SuperView itself is a neat small viewer program with a window to allow
    loading and processing images with the included libraries. The program
    allows optional use of any of the included library functions. It supports
    over forty graphic formats, along with being able to use datatypes, supports
    scanners and printers, drives nine different display formats including OCS/ \leftrightarrow
       ECS,
    AGA, EGS, OpalVision, Retina, CyberGraphX, Merlin and both Picasso II and
    Picasso96, and saves in most of the same forty plus formats. [\ldots]
    The SuperView libraries are the integral powerhouse of this package.
    These shared libraries do all the actual work, allowing the viewing program
    to be small and versatile. This modular approach also allows for frequent
    expansion and updating, which the author appears to be dedicated to.
    The author Andreas Kleinert deserves a very honorable mention. He
    is very active and available for debugging and development, as well as
    attentive, patient and courteous. [\dots] I think if you take the time to \leftrightarrow
       install
    SuperView, you'll agree that it is well worth the space and effort required \leftrightarrow
   [ Issue 10. Refered to SuperView 7.x + Library V19.x ]
```

SuperView-Library 148 / 174

```
Amiga Computing (IDG Media, UK)
-----
   "The SuperViewLibraries [...] allow other programs, that support
   SuperView to easily load, save, convert and process images
   with the minimum of ease. This allows programmers to concentrate
   on perfecting their program without having to worry about
   supporting every different type of picture format out there."
   [ Issue 12/1995, page 21. Referred to SuperView V5.10 + Library V12.3.
    The CoverDisk contained ImageEngineer V2.1a and licensed V12.3 ]
   "SuperView is a set of libraries, that allows Image Engineer to
   load and save a large number of different file types, [...]
   "Installation of SuperView is very straightforward using the
   standard Amiga installer program, [...]"
   [ Issue 7/1996, page 18/20. Referred to SuperView V5.41 + Library V12.9.
    The CoverDisk contained ImageEngineer V3.0 Demo and licensed V12.9 ]
Amiga Magazin (Magna Media, Germany)
 ______
   "Zum Betrachten von Bildern ist dieses PD-Programm wohl
   die beste Lösung. [...]"
   [ Issue 12/1994, p. 120. Referred to SuperView V2.1 ]
   "[...] SuperView besticht durch seinen modularen Aufbau. [...]
   SuperView kennt sehr viele Bildformate. Jedes Format wird durch
   ein SVObject verwaltet. Das erlaubt eine flexible Erweiterbarkeit des
   Programms. [...] Daß das Programm [...] alle Features des Amiga-OS
   bis hin zur Version 3.1 unterstützt [...] ist angesichts des großen
   Funktionsumfanges klar. [...]
   Fazit: SuperView ist ein sehr leistungsfähiger Bildanzeiger und
   eine echte Konkurrenz [...]"
   [ Issue 7/1995, p. 134. Refered to SuperView V4.52 on Time #386 ]
   "[...] Das Programm ist komplett modular aufgebaut und somit
   erweiterbar. Sogar die Benutzerschnittstelle ist austauschbar. [...]"
   [ Issue 2/1996, p. 50. Refered to SuperView V5.10 on German #561 ]
   "'SuperView' als Bildanzeiger zu beschreiben, wäre nur die halbe
   Wahrheit. Diese Aufgabe erfüllt das Programm zwar mit Bravour,
   hält aber noch anderes auf Lager. [...]"
   [ Issue 4/1996, p. 92. Refered to SuperView V5.32 on Time #486 ]
   "[...] Es dürfte kaum ein Bitmap-Format geben, mit dem der PM nichts
   anfangen kann. [...]"
   [ Issue 3/1997, p. 87. Article about Picture Manager professional
     (PMPro) V4.0, which uses superview.library 15.x for images ]
   "[...] Andreas Kleinerts Programm trennt die Spreu vom Weizen. [...]
   Es repräsentiert auch bedeutend mehr als andere Bild-Anzeigeprogramme.
   Zahlreiche Effekte bringen einen Hauch von Bildbearbeitung. [...]
   Durch sein modulares Aufbaukonzept kann man 'SuperViewNG' jederzeit
   um weitere Funktionen erweitern [...]
```

SuperView-Library 149 / 174

```
Fazit: Bilder werden schnell angezeigt; die unkomplizierte Benutzer-
    oberfläche erlaubt problemlose Anzeige. [...]"
   [ Issue 9/1997, p. 35. Article about SViewNG 6.21 ]
   "Meister der Bildformate"
    [...] Umwandeln von Bildern erledigt SuperView tatsächlich mit links. [...]
    SuperView II hat einen leistungsfähigen ARexx-Port und läßt sich auch
    als AmigaDOS-Befehl ansprechen. [...] Als Bildumwandlungsprogramm
   weiß SuperView zu überzeugen. Kaum ein anderes Programm unterstützt
    so viele Formate wie SuperView. [...]"
   [ Issue 2/1999, p. 13/14. Article about SViewII 8.20 ]
   "Viele neue Features ergeben sich aus der Verwendung einer neuen
   SuperView-Library. [...]"
   "[...] besserer PowerPC-Support (u.a. bei TIF, JPEG und PNG [...]"
   [ Issue 2/1999, p. 10-12. Article about Picture Manager professional
     (PMPro) V5.5., which uses superview.library 21.x for images ]
Amiga Plus (ICP, Germany)
   "SuperView benutzt zwar auch ab OS3.0 Datatypes, zeigt aber
   ab OS2.0 auch bereits IFF-, [...] -Grafiken an.
   Erreicht wird dies durch eine eigene 'superview.library',
   die [...] es ermöglicht, Grafiken in diesen Formaten zu speichern"
   [ Issue 7/1994, p. 42. Referred to SuperView V2.1 ]
   "Wir haben für Sie eine Auswahl der besten und wichtigsten
   Tools und Utilities aus allen Sparten des Computeralltags
   zusammengetragen" [...]
   "SuperView [...] Bildanzeiger, der ab OS3 Datatypes zum Erkennen der
   Grafikformate verwendet. Mit Hilfe der SuperView-Library sind die
   wichtigsten Formate auch ab OS2 lesbar."
   [ Issue 4/1995, p. 46. Refered to SuperView V2.1 ]
   [ Formatvielfalt, Konvertierung ]
   "[...] Dieses Kunststück verdankt unser Testkandidat unter anderem
   der exzellenten SuperView.library von Andreas Kleinert [...]
   [ Issue 2/1996, p. 73. Article about Picture Manager professional
     (PMPro) V3.0, with superview.library 12.x ]
   ***
   "SuperView [...] ist ein Anzeiger, der durch unzählige externe Module
    erweiterbar ist und alle erdenklichen Bildformate auf ECS- und
   AGA-Amigas, sowie auf EGS-, OpalVision, Picasso-, Merlin-, Retina-
   und CyberGraphX-Grafikkarten darstellt. [...]"
   [ Issue 3/1996, p. 61. Refered to SuperView V4.63, V4.70, V5.10 ]
   "'SuperView' zeichnet sich durch seine Vielseitigkeit aus. [...]
   Mehr als nur ein kleiner Bonus sind die 31 Operatoren [...].
    Selbstverständlich lassen sich die Bilder auch wieder
    speichern. [...]"
   [ Issue 6/1996, p. 43. Referred to SuperView V5.32 ]
```

SuperView-Library 150 / 174

```
"[...] Dieses Programm unterstützt eine deutlich höhere Anzahl
von Bildformaten (wie PCX, BMP und TIFF) und kann auch Effekte
hinzufügen und Bilder zwischen verschiedenen Formaten
konvertieren [...]"
[ Issue 9/1996, p. 58. Referred to SuperView V5.30 ]
"[...] In der Ausgabe 6/96 haben wir Ihnen das hervorragende
Anzeige- und Konvertierungsprogramm 'SuperView' vorgestellt.
"[...] SuperView beherrscht eine Vielzahl von Grafikformaten"
"[...] Neben IFF-ILBM, GIF, JPEG und TIFF beherrscht SuperView
unter anderem auch die Formate BMP, Targa, PNM, FBM, PCX,
IFF-ACBM, IFF-YUVN, IFF-DEEP, Sun Raster, SGI, RT, UtahRLE
und SVO. Puh. [...]"
[ Issue 10/1996, p. 39. Refered to SuperView V5.50 ]
"[...] Image Engineer verwendet die Superview-Library und
versteht daher beim Laden und Schreiben eine Vielzahl von
Formaten, unter anderem IFF, GIF, [...]"
[ Issue 10/1996, p. 46. Article about Image Engineer 3.1,
 which uses SuperView-Library ]
***
"[...] Die besten Tools für Ihren Amiga [...]
Bildanzeiger [...]"
"Wer schnell Grafiken in Top-Qualität sehen will,
braucht Bildanzeige-Tools. Ein weitverbreiteter
Vertreter dieser Programmgattung ist SuperView. [...]
SuperView kennt alle wichtigen [...] Grafikformate. [...]"
[ Issue 11/1996, p. 53. Article about "Best Tools For Your Amiga" ]
"[...] Eine Stärke des Programms ist das automatische Erkennen
der vorhandenen Grafikformate [...]
Picture Manager unterstützt jetzt auch die Scanner-Software
'ScanQuix3', respektive deren Pseudo-Twain-Standard. [...]
Gut gemacht."
[ Issue 1/1997, p. 26. Article about Picture Manager prof. V4.0,
 which uses SuperView-Library ]
"[...] Alle weiteren Dateiformate ließen sich bislang nur über
das Installieren entsprechender Datatypes nutzen.
[...] Damit haben Sie jetzt Zugriff auf nahezu jede Art von
Bildmaterial. [...] Über die Qualität und Arbeitsgeschwindigkeit
dieser Library braucht man wohl kaum noch ein Wort zu verlieren,
sie hat sich mittlerweile zu einer Art Standard bei der automatischen
Erkennung von Bild- und Grafiktypen entwickelt. [...]"
[ Issue 2/1997, p. 32. Article about "AE SuperView" plugin for ArtEffect
 which uses SuperView-Library ]
"'SuperView' ist eine Art Schweizer Taschenmesser für Computer-
Grafiker: [...] Das Programm unterstützt eine stolze Liste von
```

SuperView-Library 151 / 174

```
Formaten: [...]"
   [ Issue 5/1997, p. 45. Overview article about "The best freely
     distributable graphics and animation programs" ]
   "[...] Der Daseinszweck von Andreas Kleinerts Shareware-Programm
    'SViewNG' besteht darin, Grafikdateien anzuzeigen, in andere
    Formate zu konvertieren und sogar zu bearbeiten. Das Programm ist
   dabei sehr schnell, versteht eine Unmenge an Grafikformaten und
    unterstützt erfreulicherweise auch Grafikkarten. [...]
   [ Issue 8/1997, p. 40. Referred to SuperView V6.21 ]
Amiga special (media, Germany)
   "SuperView - Bildbetrachter" [...]
   "Bildanzeiger gibt es viele [...]
   Doch ein Programm, das all dies beherrscht und dabei noch
    anwenderfreundlich und kompakt ist, das fehlte bisher.
    Die Situation hat sich nun geändert [...]"
   "Superview.library [...] Programmierer können mit diesen frei
    vetreibbaren Routinen interessante und komplexe Anwendungen
   realisieren. [...] Sämtliche Module sind [...] gut dokumentiert,
   so daß sich jeder Interessierte schnell zurechtfindet [...]"
   "Die grafische Benutzeroberfläche [...]"
   "Diese [...] ist einleuchtend aufgebaut, so daß man nach kürzester
   Einarbeitung damit klarkommt." [...]
   "Fazit [...] SuperView ist ein tolles Paket zum Anzeigen und
    Bearbeiten von Grafiken [...]. Anwender haben mit SuperView endlich
    einen kleinen und leistungsfähigen Bildanzeiger gefunden, der [...]
   sogar kleine Funktionen zur Bildbearbeitung enthält."
   [ Issue 1/1995, p. 62-63. Article about SuperView V4.0 ]
   "Gerade auch die Unterstützung von Grafikkarten geschieht
   "mit SuperView einfach und effizient." [...]
   [ Issue 6/1995, p. 77. Article about SuperView V4.0 ]
   * * *
   "Im Zusammenspiel mit der 'SuperView.library' von Andreas Kleinert
   konnte diese Weiterentwicklung [...] seine Leistungsfähigkeit
   eindrucksvoll unter Beweis stellen"
   [ Issue 12/1995, p. 116. Article about Picture Manager Professional
     Beta 0.97 ]
   * * *
   "SuperView gehört mit zu dem Besten, was im Amiga-Sektor an
    Grafikbetrachtungs-Programmen verfügbar ist. Es ist kompatibel
   mit fast allen gängigen Formaten [\ldots], besitzt [\ldots] eine
    durchdachte und komfortable Oberfläche. Erfreulicherweise trägt
    die mehrsprachige umfangreiche Anleitung [...] und das durchdachte
    Installationsprogramm ebenfalls zum hervorragenden Gesamteindruck
    von 'SuperView' bei."
   [ Issue 5/1996, p. 66. Article about SuperView V5.30 on Time #472 ]
   "[...] Zum Laden und Speichern werden die Libraries von SuperView
    genutzt. [...] Durch diese Libraries werden fast alle Grafikformate
```

SuperView-Library 152 / 174

1.115 Books and other written stuff used during development

- [1] "Bitmapped Graphics", 2nd Edition, Steve Rimmer, Windcrest/McGraw-Hill, © 1993 by Windcrest Books (registered Trademark of TAB Books). ISBN 0-8306-4209-9
- [2] "Supercharged Bitmapped Graphics", Steve Rimmer, Windcrest/McGraw-Hill, © 1992 by Windcrest Books (registered Trademark of TAB Books). ISBN 0-8306-3788-5
- [4] "Amiga Magazin", Issue 2/1992, Markt & Technik Verlag AG
- [5] "DOS Extra", Issue 4/1993, DMV-Verlag
- [7] "Formats.doc" of the ShowVIC distribution on SaarAG-Disk #616. ShowVIC is (C)opyright 1993 by Matt Francis.

- [10] The Independent JPEG Group's software package(s) with Source-Code(s) and Documentation. Release 4 through 6b.
- [11] "The Programmer's PC Sourcebook", Thom Hogan,
 published by Microsoft Press, © 1991 by Thom Hogan.
 ISBN 1-55615-321-X
- [12] "Struktur und Interpretation von Computerprogrammen", H. Abelson, G.J. Sussman, J. Sussman, Springer-Verlag, © 1985 by the M.I.T, ISBN 3-540-56934-0

SuperView-Library 153 / 174

```
[15] ... and perhaps books/magazines/articles, which I don't remember yet !
[16] ... as well as texts found on AmiNet, BBS or CD-ROM.
[17] Newsgroups in Fido (mostly *.GER) and UseNet (mostly DE.* and Z-Netz)
...plus a bunch of Amiga-related books, like RKMs and the Guru Book, etc.
```

1.116 Overview: Other Program Projects

```
For this, please take a look at:

http://home.t-online.de/home/Andreas_Kleinert/index_ami.html
  and http://home.t-online.de/home/Andreas Kleinert/support.htm
```

1.117 Credits

```
24BitToHAM.svoperator
This SVOperator bases on code, which has been included with
FBM Release 1.0 25-Feb-90 by Michael Mauldin.
The original code had been written by Harald C. Koch to convert
24 bit RGB data (FBM format) to HAM6-ILBM files.
I modified it to create format-independent 8 Bit chunky pixel buffers,
which can be handled by SuperView-Library.
The code used for the "quick" option of the SVOperator (without palette)
is not related in any way to code of the FBM package.
The ham8-well code originally was drived from fbham.c, but now
no longer does show any similarities to it.
Here's the copyright notice as found in "fbham.c"
(revision headers cut off / left out) :
 * fbham.c: FBM Release 1.0 25-Feb-90 Michael Mauldin
 * Copyright (C) 1989,1990 by C. Harald Koch & Michael Mauldin.
 * Permission is granted to use this file in whole or in part for
 * any purpose, educational, recreational or commercial, provided
 * that this copyright notice is retained unchanged. This software
 \star is available to all free of charge by anonymous FTP and in the
 * UUNET archives.
 [\ldots]
 * based on ray2.c from DBW_Render, Copyright 1987 David B. Wecker
 [...]
AmiFIG.svobject
This FIG support module accesses the external program "fig2dev",
which for example is available as port of the fig port AmiFIG 1.1
from AmiNet, which is (C) 1996 Andreas Schmidt.
```

SuperView-Library 154 / 174

C64.svobject

For getting information about the C64 Koala and Doodle formats I took a look into the source code of ComView 1.0 by Paul Grebenc, which can be found as "C64View" on the SaarAG-Disk #523.

I did not include and use the Source Code as such, but I really learnt a much out of it. The algorithms are perhaps nearly the same, but because I do not use file-to-screen decoding my code is perhaps some 100% faster (different structure, many optimizations).

EPS.svobject

EPS.svobject uses strongly modified code from

/* pnmtops.c - read a portable anymap and produce a PostScript file
**
** Copyright (C) 1989 by Jef Poskanzer.
**

[...]

which is allowed by its copyright statements.

FBM.svobject

For getting information on the FBM-Format I took a look into the file "fbm.h" and other source-files, which describe this file format and are part of FBM Release 1.0 25-Feb-90 by Michael Mauldin. No source-code from this package - only the "pure information" - has been used for FBM.svobject.

GhostScript.svobject

GhostScript.svobject accesses an external Ghostscript port, like for example Ghostscript 3.53 from AmiNet, which is based on Aladdin Ghostscript.

Aladdin Ghostscript is Copyright (C) 1989, 1995 Aladdin Enterprises. All rights reserved.

Limbo.svobject

Limbo.svobject does support the Limbo 4.0 port from Aminet:gfx/conv, which was based on a version developed by Carsten Frigaard, Jess Gade, Thomas Therp Hemmingsen and Torben Sand in 1993/94 on Aalborg University, Denmark.

JPEG.svobject

This software is based in part on the work of the Independent JPEG Group. Various releases, starting with V4, have been used. Current release: V6b.

SuperView-Library 155 / 174

```
PICT.svobject
  ______
 The PICT loader module is based on code derived from the PBM package,
 namely the standalone-module "picttoppm.c".
 It is said it can be used freely, so I decided to do this instead
 of trying to implement this weird PICT-2 stuff of QuickDraw
  (is it a vector format or a bitmap format ;-)
 The original source has been stronlgy modified to fulfil the needs
 of being integrated as a library module for superview.library.
 To be more independent from the pbm.package (great improvments on
 code size) I also extracted the standard bdf font from the pbm
 part (also free).
 Here are the Copyright notice of these modules as found in the files
 "picttoppm.c" and "libpbm5.c" (revision headers cut off / left out) :
 * picttoppm.c -- convert a MacIntosh PICT file to PPM format.
 [...]
 * Copyright 1989, 1992, 1993 George Phillips
 * Permission to use, copy, modify, and distribute this software and its
 \star documentation for any purpose and without fee is hereby granted, provided
 \star that the above copyright notice appear in all copies and that both that
 * copyright notice and this permission notice appear in supporting
 * documentation. This software is provided "as is" without express or
 * implied warranty.
 * George Phillips <phillips@cs.ubc.ca>
 * Department of Computer Science
 * University of British Columbia
 * $Id: picttoppm.c,v 1.7 1993/10/26 22:40:31 phillips Exp phillips $
 */
Only the default font definition has been taken from this one:
/* libpbm5.c - pbm utility library part 5
** Font routines.
** Support for BDF fonts Copyright 1993 by George Phillips.
** Copyright (C) 1991 by Jef Poskanzer.
** Permission to use, copy, modify, and distribute this software and its
** documentation for any purpose and without fee is hereby granted, provided
** that the above copyright notice appear in all copies and that both that
** copyright notice and this permission notice appear in supporting
** documentation. This software is provided "as is" without express or
** implied warranty.
*/
```

SuperView-Library 156 / 174

PNG.svobject

Is based on the png reference library (including libpng and zlib), which allows being used e.g. for freely distributable and commercial programs

libpng:

libpng 1.0.1

Copyright (c) 1995, 1996 Guy Eric Schalnat, Group 42, Inc.

Copyright (c) 1996, 1997 Andreas Dilger

Copyright (c) 1998 Glenn Randers-Pehrson

zlib:

zlib 1.1.2

(C) 1995-1998 Jean-loup Gailly and Mark Adler

RotateFree.svoperator

The basic algorithm for rotation about any given point with any possible angle had been described in "C/C++ Users Journal", issue August 1995. It was strongly dependend on TIFF input, did only work with 8 Bit input and was not able to adjust the image buffer size to prevent image parts to be cut off. Used only the basic algorithm as a hint how to do hit.

TIFF.svobject

Since V3.7 this module makes use of the freely distributable TIFF Library (libtiff). For this version V3.4 beta 037 has been used.

Please note the following copyrights:

Copyright (c) 1988-1997 Sam Leffler

Copyright (c) 1991-1997 Silicon Graphics, Inc.

Permission to use, copy, modify, distribute, and sell this software and its documentation for any purpose is hereby granted without fee, provided that (i) the above copyright notices and this permission notice appear in all copies of the software and related documentation, and (ii) the names of Sam Leffler and Silicon Graphics may not be used in any advertising or publicity relating to the software without the specific, prior written permission of Sam Leffler and Silicon Graphics.

THE SOFTWARE IS PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND EXPRESS, IMPLIED OR OTHERWISE, INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

IN NO EVENT SHALL SAM LEFFLER OR SILICON GRAPHICS BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES OF ANY KIND, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER OR NOT ADVISED OF THE POSSIBILITY OF DAMAGE, AND ON ANY THEORY OF

SuperView-Library 157 / 174

LIABILITY, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

YUVN.svobject and PCD.svobject For the 24 bit YUV <-> RGB Conversion Routines I used some code of the NetPBM Package. The code of the original routines has been _strongly_ modified and enhanced/improved (there are almost no similarities to the original code left now, except the main algorithm). For PCD also the factors to scale YCbCr to RGB had to be adjusted, since the ones of PCD are slightly different to those of JPEG. Here are the Copyright notices as found in the specific source files : /* ppmtoyuvsplit.c - convert a portable pixmap into 3 raw files: ** - basename.Y : The Luminance chunk at the size of the Image $\star\star$ - basename.U : The Chrominance chunk U at 1/4 ** - basename.V : The Chrominance chunk V at 1/4** The subsampled U and V values are made by arithmetic mean. ** If CCIR601 is defined, the produced YUV triples are scaled again $\star\star$ to fit into the smaller range of values for this standard. ** by A.Beck ** Internet: Andre_Beck@IRS.Inf.TU-Dresden.de * * ** Based on ppmtoyuv.c ** Permission to use, copy, modify, and distribute this software and its ** documentation for any purpose and without fee is hereby granted, provided ** that the above copyright notice appear in all copies and that both that ** copyright notice and this permission notice appear in supporting ** documentation. This software is provided "as is" without express or ** implied warranty. */ /* yuvsplittoppm.c - construct a portable pixmap from 3 raw files: ** - basename.Y : The Luminance chunk at the size of the Image ** - basename.U : The Chrominance chunk U at 1/4 $\star\star$ - basename.V : The Chrominance chunk V at 1/4 $\star\star$ The subsampled U and V values are made by arithmetic mean. ** If ccir601 is defined, the produced YUV triples have been scaled again $\star\star$ to fit into the smaller range of values for this standard. ** by Marcel Wijkstra <wijkstra@fwi.uva.nl> ** Based on ppmtoyuvsplit.c

** Permission to use, copy, modify, and distribute this software and its

** documentation for any purpose and without fee is hereby granted, provided

** that the above copyright notice appear in all copies and that both that

** copyright notice and this permission notice appear in supporting

SuperView-Library 158 / 174

```
** documentation. This software is provided "as is" without express or ** implied warranty.  
\star/
```

MetaView.svobject

This WMF/AMF/IFF-DR2D/DXF/WPG-Vector support module accesses the external program "MetaView", which is (C) Henk Jonas.

HilbertDither256.svoperator

The description of the "fractal Hilbert dithering" method has been found in the "mc magazine, issue 6/94, Franzis-Verlag GmbH". The basic techniques (L-System, 16x16 block error approximation) are perhaps the same, but the source code as such has been rewritten completely in almost any of its parts, so that it has not just been "taken out of there" (any limits have been removed; e.g. the original source was a standalone-program, which only worked with TARGA graphics, which had a width and height divideable by 16, but max. 1280x960 or 2560x1920).

1.118 ControlPad Fileformat

Many SVObjects, SVDrivers and SVOperators have to handle globally set preferences, which may also have to be handled and/or modified by custom programs or SuperViewPrefs.

To prevent multiple different ways of storing these preferences data, I introduced a common standard fileformat for such configuration files: The ControlPad fileformat (please read the notes under "Style Guide" below).

- To allow easy reading and understanding of these files, these are stored in plain ASCII
- To prevent people from learning just another technique of configuring files, these are constructed just like a kind of "tooltype lists"
- a single ControlPad takes a full line of the file
 and looks like that : <Name>=<Content> or <keyword>
 Content and Name may contain any ASCII characters except "=", because
 the first "=", which is found, is used to separate the Name from the
 Content in the line. A keyword is anything, which does not contain
 a "=" somewhere, but is not a comment.
- So all other special characters are possible (although you should not make too much use of them for ergonomical reasons).
- it is supported to write as much comments to the files, as wished. A comment line has to begin with "/" or ";" in its first column. A totally blank line fits to the same category as "/" or ";" lines.
- any single line should not exceed 255 characters

Additional Notes

~~~~~~~~~~~~~~~

 $\star$  Note, that comments are safely read and written by the current library version.

SuperView-Library 159 / 174

\* The SVSUP\_FindControlPad() function is case-sensitive, so if nothing else is specified, the ControlPad entries are always also case-sensitive. Case-insensitive functions already have been added (SVSUP\_FindControlPadNoCase()) but are not used widely yet.

By using GUI-based functions for ControlPad modifications which prevent the user from changing them directly, you may be able to avoid such conflicts.

# Style Guide

Common "style guide" rules (PLEASE NOTE) :

- ControlPads should be located in "ENV:superview-library/" and have the plain name of the SVDriver/SVObject/... plus ".controlpad" as extension.
  - For example a ControlPad for JPEG.svobject should be named "ENV:superview-library/JPEG.controlpad".
- for boolean entries use <YES|NO> choices, not <TRUE/FALSE>
   or just set single keywords like "USE\_..."
- for switches, <ON|OFF> choices are most often preferable
  against setting single keywords for either "on" or "off"
- use short names and statements, not long and complicated ones :
   "ColorDepth=24" instead of "Number\_of\_Colors=16.7\_million"

### Examples

~~~~~~

In "Programmers/C-Language/Example_Tools/ControlPad" you find some example sources, which deal with ControlPads and should explain anything you need to know about these.

1.119 CPInfo Fileformat

Some applications might wish to enable the user to interactively specify controlpad settings just when reading, writing or processing an image and not before or after by setting preferences.

Until this will be managed by superview.library, superviewsupport.library or the single modules by introducing new functions for handling this, applications may take this information from ".cpinfo" files, where the specific ControlPad entries are dynamically described.

Content

- Structure in general
- Structure in detail
- Structure Entry Description in detail
- Examples
- Last Words and Exceptions
- Future

SuperView-Library 160 / 174

- Special configuration Standards

Structure in general

Every CPInfo-File is constructed like an usual ControlPad file, but in this case, the _order_ of the entries becomes meaningful. These files are separated into SECTIONs, where any necessary information about specific ControlPad entries are stored.

To allow easy enhancements and improvements on this format, there's an important note:

- the number of sections is not limited
- each SECTION _must_ contain at least the entries described below
- each SECTION _may_ contain more entries, so that it might be necessary to skip all the following entries until another "SECTION" entry will be reached
- the order of the entries is _fixed_
- if any of the following _needed_ entries makes no sense, it will still be present as a "dummy", thus just a keyword is placed there and no value is given via "="
- any single line should not exceed 255 characters
- as with usual ControlPad files, comments and blank lines are allowed

Structure in detail

CPINFO ; identification SECTION=<Name of ControlPad entry> ; the name of the entry TYPE=<INTEGER | FLOAT | ASCII | NONE> ; type of data ; (signed or unsigned for INTEGER or FLOAT may ; be detected via MIN and MAX). ; NONE is used for keywords. MIN=<Value> ; - minimum value for numbers ; - minimum length for strings ; - or empty ("MIN") ; Empty with keywords. MAX=<Value> ; - maximum value for numbers ; - maximum length for strings ; - or empty ("MAX") ; Empty with keywords. ; what will be used if nothing DEFAULT=<Default value for entry> ; is specified ?! ; Empty e.g. with keywords. DESCRIPTION=<descriptive text> ; what does it do ? ; this one allows to separate MASK=<input mask> ; choices and "free" enterings ; Empty with keywords. WHEN=<READ|WRITE|ALWAYS|PREFS|NEVER>; ask for it, when the user ; does reading or writing ; (SVObjects) ? Or always ; (SVDrivers/SVOperators) ? ; Or never ? (Undocumented) ; Or Just handle it as a real ; preferences thing ?

SuperView-Library 161 / 174

Structure Entry Description in detail

o A few words to the MASK entry:

Any entries which don't have a specific meaning (just comments) or mutual exclude entries do have to begin with "<" and end with ">". Anything else are control sequences, qhich either are to be supported or have to be ignored.

a) "<...>" or "<...|...|...>"

Usually you should print out this text as a little help for the user, how to enter the data, e.g. into a string/integer gadget. But if the string included by "<" and ">" does contain one or more "|" these are meant as exclusice choices, which e.g. might be represented as mx-, cycle- or listview-gadgets. So you may a) present this mask to the user while editing a string/integer gadget or b) parse it and just "filter" the input via supplying appropriate input gadgets. Please note, that the "MIN" and "MAX" values (if specified) still have to be valid for this input (if the file definition has been done correctly;-) So for a "MASK=<8|24>" these would equal "MIN=8" and "MAX=24". But note, that this "mask" is not really meant to define ranges with gaps, like "anything between 5 and 37, but except the numbers between 33.3 und 36.5" 8-)

b) Control Sequences

MASK=_SVOBJECT means, that a file from "LIBS:svobjects"

has to be requested, which matches

"#?.svobject".

MASK=_SVDRIVER means, that a file from "LIBS:svdrivers"

has to be requested, which matches

"#?.svdriver".

MASK=_SVOPERATOR means, that a file from "LIBS:svoperators"

has to be requested, which matches

"#?.svoperator".

MASK=_FILE a file to be selected e.g. fromout a

requester (it is supposed, that the user

does the right choice).

Examples

Anentry for a keyword might look like this:

SECTION=ANYDATATYPES

TYPE=NONE

 ${\tt MIN}$

MAX

DEFAULT

DESCRIPTION=Switches Datatypes support to ANY

MASK

WHEN=PREFS

An entry for a float value: SECTION=SCALE_FACTOR TYPE=FLOAT MIN=0.1MAX=2.0DEFAULT=1.0 DESCRIPTION=Factor for scaling graphics MASK=<Value> WHEN=ALWAYS An entry for an ASCII text: SECTION=PACKMETHOD TYPE=ASCII MIN=4MAX=4DEFAULT=NUKE DESCRIPTION=How to pack the written data MASK=<XPK-Packer> WHEN=WRITE An example for an ignoreable keyword: SECTION=DEBUGMODE TYPE=NONE MIN MAX DESCRIPTION=Enables debugging mode with Confirm-Requesters MASK WHEN=NEVER Last Words and Exceptions ______ So you see, that it's easy to describe any of the existing ControlPad variations this way. The "WHEN" statement is a help for applications to decide, whether and when to allow changing of specific ControlPad entries. Applications should either ignore entries of type "WHEN=NEVER" or prepared to handle slightly differing entries, like e.g. TYPE=INTEGER entries with a non-set default value. (An example had been the "AVAILMEM" switch of interim versions of JPEG.svobject - which was both: a keyword and a common setting,

but should never be changed during runtime.)

"WHEN=NEVER" is just for options with experimental state or

Future

debugging purposes.

SuperView-Library 163 / 174

In the future, there may be a function in superview.library, which allows passing a controlpad list to it, which then may be passed to the attached SVObject/SVDriver/SVOperator as a "local" setting, which will override the "global" ControlPad files.

So the CPInfo Files will be helpful for applications on how to find out, which ControlPads might be possibly set.

Special configuration Standards

For special cases it seems to be suitable to define a common behaviour, so that GUI-based and interactive selections for those special cases may become independent from specific modules.

Operators and other modules, which allow to apply their specific operations to either the whole given image or only a defined part of it, should use the following controlpads as a standard for allowing the application to better visualize the process of selecting the concerned parts of the graphics.

REGION=<ENTIREIMAGE | RECTANGULAR>

- ; if this one exists, you have the choice.
- ; Then, if REGION=ENTIREIMAGE, the following are supposed to be
- ; 0, 0, width, height, otherwise they have to be specified.

LEFTEDGE=<Value smaller or equal width>

TOPEDGE=<Value smaller or equal height>

WIDTH=<width of shape>

HEIGHT=<height of shape>

; just like opening a window

1.120 ControlPad Overview

______ MAIN LIBRARIES ControlPad-Name : "ENV:SuperView-Library/LIBRARY.controlpad" ControlPad-Commands : - DEFAULTSVDRIVER=<#?.svdriver> ; Which SVDriver should be set, when ; SuperView-Library is being initialized ? ; For example: "DEFAULTSVDRIVER=AGA.svdriver" - ANYDATATYPES ; if this keyword is set, ANY DataTypes will ; be loaded and tried to be displayed in some ; way (e.g. not only pictures, but also 8SVX; sounds or ANIM-Files ...) ; This changes are recognized each time, when ; a new handle for loading a file is being ; initialized - but may be superseded by specific ; program's settings internally.

SuperView-Library 164 / 174

```
: "ENV:superview-library/superviewsupport.controlpad"
ControlPad-Name
ControlPad-Commands : - C2P=<OS|SV>
                       ; determines, whether chunky to planar conversion
                       ; is managed via the appropriate OS functions
                       ; or via internal ones.
                       ; Due to various problems with the OS functions
                       ; "SV" is now default.
                       ; Be careful when using "OS" with GfxCards,
                       ; which carelessly patched graphics.library.
                       ; NOTE: PPC code will automatically be utilited,
                               when a PPC is available, but only with
                              C2P=SV
                       ; Default: SV
                     - MODEGEN=<OS|SV|SVEXT>
                       ; determines, whether viewmode generation should
                       ; rely on internal/OS functions only, or make
                       ; use of P96/CGfx(/PII) functions when available.
                       ; Similar to ModeP. "SV" may cause problems on
                       ; some systems, may work fine on others.
                       ; "SVEXT" is known from the ak-datatypes series.
                       ; Note: applicable for OS 3.0 and beyond, only.
                       ; Default: OS
______
SVOBJECTS
ControlPad-Name : "ENV:SuperView-Library/AmiFIG.controlpad"
ControlPad-Commands : - STACKSIZE=<value>
                       ; stacksize to be used for calling GPlot,
                       ; increasing may help on crashes
                       ; default is: 32768
                     - AMIFIG_PATH=<fig2dev command path plus name>
                       ; how fig2dev is to be called
                       ; e.g. AMIFIG_PATH=Work: AmiFIG/fig2dev
                       ; default is: fig2dev
                     - STATUS=<ENABLED|DISABLED>
                       ; allows to disable this module - for example
                       ; to be able to use an other, program-specific
                       ; import-module for the same file format
ControlPad-Name : "ENV:SuperView-Library/Amilcon.controlpad"
ControlPad-Commands : - ICON_DEPTH=<colordepth>
                       ; Depth of icon to be saved.
                       ; Also: WB (depth=2-3, 4-8 colors) or
                       ; MagicWB (depth=4, 16 colors) ?
                       ; default is: 2
                     - ICON_TYPE=<DISK|DRAWER|TOOL|PROJECT|GARBAGE>
                       ; Type of icon to be saved.
                       ; default is: PROJECT
                     - ICON_TOOL=cprogram name>
                       ; The default tool of the icon to be saved.
                       ; default is: "InsertHere" ;)
                     - WRITE NEWICON=<ON|OFF>
                       ; Write NewIcons, when there is newicon.library
                       ; available ?
                       ; Default is: ON
```

SuperView-Library 165 / 174

```
- READ SUPPORT=<ON|OFF>
                       ; Allow reading of icons at all ?
                       ; Default is: OFF
ControlPad-Name
                   : "ENV:SuperView-Library/EPS.controlpad"
ControlPad-Commands : - EXTRACTMODE=<HEADER|PS>
                        ; Determines, whether the preview image or
                        ; the Postscript (TM) part should be extracted,
                        ; while parsing the Postscript (TM) part requires
                        ; a working Ghostscript installation with
                        ; GhostScript.svobject being correctly configured
                        ; default is: HEADER
                      - NO_EPS_HEADER
                        ; if this option is set, the EPS file will be
                        ; written without EPS header, thus turn into a
                        ; plain P*stscript file; useful for sending
                        ; it directly to the printer or for use with
                        ; FinalWriter, WordWorth, TurboPrint
                      - SAVE ROTATE=<ON|OFF>
                       ; by default, the picture seems to be rotated
                        ; with Postscript (TM) output of this module.
                        ; Enabling SAVE_ROTATE will again re-rotate it to
                        ; the original position.
                        ; default is: OFF
                      - SAVE_CENTER=<ON|OFF>
                        ; centers the images on the page with the
                        ; desired size of SAVE_WIDTH x SAVE_HEIGHT (or not)
                        ; default is: ON
                      - SAVE_RLE=<ON|OFF>
                       ; allows to apply RLE compression to the
                        ; PS output
                        ; default is: OFF
                      - SAVE_DPI=<value>
                        ; DPI value to use for the output
                        ; default is: 300
                      - SAVE WIDTH=<value>
                       ; Width of the PS page
                        ; default is: 612
                      - SAVE_HEIGHT=<value>
                        ; Width of the PS page
                        ; default is: 762
                    : "ENV:SuperView-Library/FastILBM24.controlpad"
ControlPad-Name
ControlPad-Commands : - BUFFERSIZE=<Size in Bytes>
                        ; how many bytes should be buffered
                          (more = faster)
                        ; Default is 8192, minimum is 256
                      - PASSTHROUGH
                        ; do not recognize ANY pictures, so that
                        ; they e.g. might be passed through to
                        ; ILBM.svobject instead
                      - DITHERMODE=<HAM6_QUICK|HAM8_QUICK>
                       ; Default is HAM6_QUICK
                      ______
ControlPad-Name : "ENV:SuperView-Library/GhostScript.controlpad"
ControlPad-Commands : - STACKSIZE=<value>
                        ; stacksize to be used for calling GhostScript,
```

SuperView-Library 166 / 174

```
; increasing may help on crashes
                        ; default is: 32768
                      - GS_PATH=<gs command path plus name>
                        ; how GhostScript is to be called
                        ; e.g. GS_PATH=Ghostscript:gs000
                        ; default is: gs000
                      - OUTPUTMODE=<PNG256|PNG24BIT|OTHER>
                        ; Output file format to be used
                        ; (-sDEVICE parameter of Ghostscript's qs).
                        ; Only PNG supported yet.
                        ; default is: PNG256
                      - OTHER_OUTPUTMODE=<pcxmono|pcxgray|pcx16|pcx256|
                                         pcx24b|tiffcrle|tiff24nc|
                                         pngmono|pnggray|png16|png256|
                                         png16m|bmpmono|bmp16|bmp256|
                                         bmp16m>
                       ; If OUTPUTMODE=OTHER has been set, the string
                        ; specified here will directly be passed as
                        ; Ghostscript's "-sDEVICE" parameter
                        ; default is: png256
                      - DPI=<value>
                        ; DPI value to use for the converted output
                        ; (-r parameter of GhostScript's gs)
                        ; default is: 72
                      - STATUS=<ENABLED|DISABLED>
                        ; allows to disable this module - for example
                        ; to be able to use an other, program-specific
                        ; import-module for the same file format
                    : "ENV:SuperView-Library/GPlot.controlpad"
ControlPad-Name
ControlPad-Commands : - STACKSIZE=<value>
                        ; stacksize to be used for calling GPlot,
                        ; increasing may help on crashes
                        ; default is: 32768
                      - GPLOT_PATH=<gplot command path plus name>
                        ; how gplot is to be called
                        ; e.g. GPLOT_PATH=Work:GPlot/GPlot
                        ; default is: GPlot
                      - STATUS=<ENABLED|DISABLED>
                        ; allows to disable this module - for example
                        ; to be able to use an other, program-specific
                        ; import-module for the same file format
                       _____
ControlPad-Name
                   : "ENV:SuperView-Library/ILBM.controlpad"
ControlPad-Commands : - ANIM_BODIES
                        ; if set, ANIM files' ILBM-BODY chunk
                        ; (first frame) will be extracted when
                        ; such a file is encountered. Otherwise
                        ; anim.datatype may do that task later.
                        ; (not actually IFF-ILBM support: it's
                        ; IFF-ANIM support)
                      - DRACO
                        ; tries to avoid possible problems on
                        ; the Draco computer (modeid generation)
                : "ENV:SuperView-Library/JPEG.controlpad"
ControlPad-Name
ControlPad-Commands: ;
```

SuperView-Library 167 / 174

```
; STANDARD settings
  ; **********
- COLORDEPTH=<8 | 24>
 ; For READING colored 24 bit images:
  ; should the output be done as 8 or 24 bit Data ?
  ; default is 8 Bit data. Grayscaled graphics
  ; will _always_ be exported as 8 Bit
- QUANTIZATION=<0..100>
 ; For WRITING 8/24 bit images as 24 bit JPEG:
       - poor quality, big compression
  ; 100 - best quality, no compression
 ; never use such extreme values, but try
 ; something like 20, 50, 75
 ; default is: 75)
 ; ADVANCED settings
 ; *********
- FORCE_GRAY_DECODE
 ; For READING images:
 ; this switch overrides the selected depth
 ; for colored images and always exports them
 ; as 8 Bit grayscaled pictures
 ; default is: not set
- DECODE METHOD=<FAST INTEGER|SLOW INTEGER|
                FLOATING_POINT>
  ; For READING images:
  ; how to DECODE the 24 bit or gray data
  ; default is: FAST_INTEGER
- DITHERMODE=<DITHER_FLOYD-STEINBERG|
              NO_DITHERING|DITHER_ORDERED>
  ; For READING and dithering 24 bit images
 ; to 8 Bit images:
 ; how and whether to DITHER the 24 bit data
  ; default is: DITHER_FLOYD-STEINBERG
- COLOR_QUANTIZING=<FAST|SLOW>
 ; For READING and dithering 24 bit images
 ; to 8 Bit images:
 ; whether to QUANTIZE the 24 bit data within
 ; two passes (not with DITHER_ORDERED)
 ; default is: SLOW
- UPSAMPLING=<ON|OFF>
 ; For READING and dithering 24 bit images
 ; to 8 Bit images:
 ; whether to do fancy upsampling on the 24 bit
 ; default is: ON
- FORCE_GRAY_ENCODE
 ; For WRITING images:
 ; this switch causes grayscales to be written
 ; no matter, whether the input was colored
  ; default is: not set
- ENCODE_METHOD=<FAST_INTEGER|SLOW_INTEGER|
                FLOATING_POINT|FASTEST_INTEGER>
 ; For WRITING images:
  ; how to ENCODE the 24 bit or gray data
  ; default is: FAST INTEGER
- OPTIMIZE=<ON|OFF>
  ; For WRITING 24 bit images:
```

SuperView-Library 168 / 174

```
; whether to optimize the generated huffman
                       ; code (good compression, but slow)
                       ; default is: OFF
                     - PROGRESSIVE=<ON|OFF>
                       ; For WRITING 24 bit images:
                       ; whether to write progressive JPEG files
                       ; default is: OFF
                                       _____
ControlPad-Name
                  : "ENV: SuperView-Library/Limbo.controlpad"
ControlPad-Commands : - STACKSIZE=<value>
                       ; stacksize to be used for calling GPlot,
                       ; increasing may help on crashes
                       ; default is: 32768
                     - LIMBO_PATH=<Limbo command path plus name>
                       ; how Limbo is to be called
                       ; e.g. LIMBO_PATH=Work:Limbo/Limbo.68030.881
                       ; default is: Limbo.68000
                     - STATUS=<ENABLED|DISABLED>
                       ; allows to disable this module - for example
                       ; to be able to use an other, program-specific
                       ; import-module for the same file format
                      -----
ControlPad-Name : "ENV:SuperView-Library/MetaView.controlpad"
ControlPad-Commands : - STACKSIZE=<value>
                       ; stacksize to be used for calling MetaView,
                       ; increasing may help on crashes
                       ; default is: 32768
                     - METAVIEW_PATH=<MetaView command path plus name>
                       ; how MetaView is to be called
                       ; e.g. METAVIEW_PATH=Work:AMF/MetaView
                       ; default is: MetaView
                     - FIG SUPPORT
                       ; if this keyword is set, AmiFIG.svobject will
                       ; be overriden and instead MetaView will be
                       ; utilized for imporint FIG drawings
                     - CGM SUPPORT
                       ; if this keyword is set, GPlot.svobject will
                       ; be overriden and instead MetaView will be
                       ; utilized for imporint CGM graphics
                     - STATUS=<ENABLED|DISABLED>
                       ; allows to disable this module - for example
                       ; to be able to use an other, program-specific
                       ; import-module for the same file format
                         -----
                   : "ENV:SuperView-Library/PCD.controlpad"
ControlPad-Name
ControlPad-Commands: - OUTPUTFORMAT=<BASE/16 | BASE/4 | BASE
                                   | BASE * 4 | BASE * 16 >
                       ; specifies the output resolution to be used
                     - HPCDTOPPM_PATH=<hpcdtoppm command path plus name>
                       ; how NetPBM's hpcdtoppm is to be called
                       ; e.g. HPCDTOPPM_PATH=Work:NetPBM/ppm/hpcdtoppm
                       ; If this one is not set, "BASE" will be
                       ; used as default resolution, even if OUTPUFORMAT
                       ; has been set to BASE*4 or BASE*16
ControlPad-Name : "ENV:SuperView-Library/PNG.controlpad"
ControlPad-Commands : - PNG8_TRANSPARENCY=<ON|OFF>
```

SuperView-Library 169 / 174

```
; whether 8 Bit PNGs should contain
                       ; transparency information
                       ; Default: OFF
                     - PNG8_TRANSPARENT_COLOR=<0..255>
                       ; Default color to be enabled and set
                       ; (graphics control extension block)
                       ; Default: 0
                     - Z_COMPRESSION=<0..9>
                       ; allows changes in compression/speed.
                       ; 0 results in uncompressed data, 9 compresses
                       ; best, but increases decompression time.
                       ; Default: 6
                     - SAVE_INTERLACED=<ON|OFF>
                       ; Save image as interlaced (progressive) ?
                       ; Default: OFF
                  ______
ControlPad-Name : "ENV:SuperView-Library/PNM.controlpad"
ControlPad-Commands : - SUPPRESS_HEADER
                      ; setting this keyword will suppres
                       ; writing the PNM header for P5/P6
                       ; files, which actually will generate
                       ; a RAW data file, which cannot be loaded
                       ; with superview.library again, but may be
                       ; used for different purposes
                       ; Default: (not set)
ControlPad-Name : "ENV:SuperView-Library/Printer.controlpad"
ControlPad-Commands : - DENSITY=<density value for printing quality>
                       ; Amiga's printer device does allow seven
                       ; modes of printing density (1-7)
                       ; (not with TurboPrint)
                       ; default is: 3
ControlPad-Name
                   : "ENV:SuperView-Library/RGFX.controlpad"
ControlPad-Commands : - PACKMETHOD=<xxxx>
                       ; XPK packer to be used for writing
                       ; "RGFX xpk-compressed"
                       ; Default: NUKE
                     - SAVE_CHUNKY
                       ; forces chunky data to be saved,
                       ; even if source graphics was planar
                      ; (e.g. when converting from IFF-ILBM)
                       ; May also result in smaller files.
                   : "ENV:SuperView-Library/Scanner.controlpad"
ControlPad-Name
ControlPad-Commands : - PUBSCREEN_NAME=<PubScreenName>
                       ; where the scanner drivers should open
                       ; their windows (if not set or not available,
                       ; the default Public Screen will be used).
            ______
ControlPad-Name : "ENV:SuperView-Library/SVG.controlpad"
ControlPad-Commands : - PACKMETHOD=<xxxx>
                       ; if this one is specified, it is tried to
                       ; pack the resulting file with the specified
                       ; XPK-Packer. If this fails, the file keeps
                       ; unpacked.
```

SuperView-Library 170 / 174

```
: "ENV:SuperView-Library/TIFF.controlpad"
ControlPad-Name
ControlPad-Commands : - PAGENUMBER=<0..n>
                       ; number of image to be displayed
                       ; (e.g. for TIFFs with image directories
                       ; or multi-page FAX documents)
______
SVDRIVERS
ControlPad-Name : "ENV:SuperView-Library/AGA.controlpad"
ControlPad-Commands : - 24BITOPERATOR=<OperatorName>
                       ; (case-sensitive, ".svoperator" may be added)
                       ; e.g. "24BITOPERATOR=24BitToHAM.svoperator"
                       ; or
                              "24BITOPERATOR=ExtractGrayScales"
                       ; specifies, which operation should be performed
                       ; on 24 bit graphics _before_ displaying them
                       ; (if not specified, "best guess" colors will
                       ; be used, which is really slow)
                     - BITMAPCOPY=<DIRECT|RTG>
                       ; "BITMAPCOPY=RTG" prevents AGA.svdriver from
                       ; directly copying into Bitmaps, which will
                       ; result in a usage of more memory, but keeps it
                       ; working.
                       ; Default is "BITMAPCOPY=DIRECT".
                     - SCREENINFRONT
                       ; Put Screen to front _before_ the graphics
                       ; has been displayed (useful with GfxCards)
ControlPad-Name
                   : "ENV:SuperView-Library/ECS.controlpad"
ControlPad-Commands : - 24BITOPERATOR=<OperatorName>
                       ; (case-sensitive, ".svoperator" may be added)
                       ; e.g. "24BITOPERATOR=24BitToHAM.svoperator"
                       ; or "24BITOPERATOR=ExtractGrayScales"
                       ; specifies, which operation should be performed
                       ; on 24 bit graphics _before_ displaying them
                       ; (if not specified displaying will fail)
                     - 8BITOPERATOR=<OperatorName>
                       ; (case-sensitive, ".svoperator" may be added)
                       ; e.g. "8BITOPERATOR=ExtractGrayScales"
                       ; specifies, which operation should be performed
                       ; on non-ECS graphics (more than 16 Colors in
                       ; HighRes, more than 32 Colors in LowRes, HAM8)
                       ; (if not specified, will be tried to display)
                     - BITMAPCOPY=<DIRECT|RTG>
                       ; "BITMAPCOPY=RTG" prevents ECS.svdriver from
                       ; directly copying into Bitmaps, which will
                       ; result in a usage of more memory, but keeps it
                       ; working.
                       ; Default is "BITMAPCOPY=DIRECT".
                     - SCREENINFRONT
                       ; Put Screen to front _before_ the graphics
                       ; has been displayed (useful with GfxCards)
ControlPad-Name : "ENV:SuperView-Library/CgxOverlay.controlpad"
ControlPad-Commands : - PUBSCREEN_NAME = < PubScreenName >
                       ; where the window driver should open
                       ; its windows (if not set or not available,
                       ; the default Public Screen will be used).
```

SuperView-Library 171 / 174

```
ControlPad-Name : "ENV:SuperView-Library/CyberGraphics.controlpad"
ControlPad-Commands : - EMUSCREENDEPTH=<16|24>
                       ; beginning depth for opening CyberGraphics Screens
                       ; Default is 16 Bit (which will also be tried
                       ; when opening of a 24 bit Screen fails)
                       ; This does not concern colordepths < 16 Bit,
                       ; except HAM6/8.
                     - SMALLSCREENS
                       ; unless this keyword is specified, it is not
                       ; tried to open screens smaller than 320x240
                   : "ENV:SuperView-Library/Picasso96.controlpad"
ControlPad-Name
ControlPad-Commands : - SMALLSCREENS
                       ; unless this keyword is specified, it is not
                       ; tried to open screens smaller than 320x240
                     - EMUSCREENDEPTH=<16|24>
                       ; beginning depth for opening Picasso96 Screens
                       ; Default is 24 bit (if opening fails, it is
                       ; also tried to open a 16 Bit Screen, then)
                  : "ENV:SuperView-Library/PicassoII.controlpad"
ControlPad-Name
ControlPad-Commands : - SMALLSCREENS
                       ; unless this keyword is specified, it is not
                       ; tried to open screens smaller than 320x240
                     - BLITTER
                       ; uses the Picasso blitter to copy graphics
                       ; into screens. Otherwise CPU is used.
                       ; On 68000 systems you may wish to use the blitter
                     - EMUSCREENDEPTH=<16|24>
                       ; beginning depth for opening Picasso Screens
                       ; Default is 24 bit (if opening fails, it is
                       ; also tried to open a 16 Bit Screen, then)
                     - SCREENMODEREQUEST
                       ; if this one is specified, the SVDriver ITSELF
                       ; will open a ScreenMode-Requester and ask
                       ; for an appropriate Screenmode to use
                       ; Useful, if you always like to change modes.
                     - AUTOSCROLLADJUST
                       ; this keyword will force Autoscroll whenever
                       ; it would make sense, but the Picasso Software
                       ; would not manage it by itself (when either
                       ; only width or height need to be autoscrolled)
                       -----
                   : "ENV:SuperView-Library/Retina.controlpad"
ControlPad-Name
ControlPad-Commands: - EMUSCREENDEPTH=<16|24>
                       ; beginning depth for opening Retina Screens
                       ; Default is 24 bit (if opening fails, it is
                       ; also tried to open a 16 Bit Screen, then)
                     ______
ControlPad-Name
                   : "ENV:SuperView-Library/Window.controlpad"
ControlPad-Commands : - 24BITOPERATOR=<OperatorName>
                       ; (case-sensitive, ".svoperator" may be added)
                       ; e.g. "24BITOPERATOR=Dither24Bit.svoperator"
                             "24BITOPERATOR=ExtractGrayScales"
                       ; specifies, which operation should be performed
                       ; on 24 bit graphics _before_ displaying them
```

SuperView-Library 172 / 174

```
; on a screen with a colordepth <= 8
                       ; (if not specified, "best guess" colors will
                         be used, which is really slow). Note, that
                       ; HAM is not allowed (thus don't specify the
                       ; 24BitToHAM operator).
                     - SCROLLSPEED=<Pixels>
                      ; determines, how many pixel should
                       ; be scrolled in any direction when
                       ; being in scroll mode and a cursor key
                       ; is pressed
                       ; Default: 10 (medium slow)
                     - PUBSCREEN_NAME=<PubScreenName>
                       ; where the window driver should open
                       ; its windows (if not set or not available,
                       ; the default Public Screen will be used).
                     - SCROLLMODE=<AUTO|NEVER|ALWAYS>
                      ; - 'ALWAYS' activates scroll mode even for
                       ; non-oversized graphics; this will block
                      ; the input of the calling program as
                       ; long as no key or mouse button has been
                      ; pressed inside the display window - but
                      ; will avoid window-refresh problems.
                      ; - 'NEVER' is to avoid the blocking of
                       ; input handling that is caused by the
                       ; scrolling handler (-> PMPro Diashow, ...)
                       ; Default: AUTO
                     - TRUECOLOR8
                       ; if the Pubscreen is a 24 bit screen but
                       ; the graphics to be displayed is 'only'
                       ; 8 bit or HAM6/8, usually remapping is
                       ; done nevertheless. This option instead
                      ; allows to call "AnyTo24Bit" first,
                      ; thus giving better display quality
                      ; on 24 bit screens. This is memory
                       ; intensive, because for scrolling we
                       ; need another complete 24 bit buffer.
                       ; (requires AnyTo24Bit.svoperator)
                     - PEN_PRECISION=<IMAGE|EXACT>
                       ; you should not change this
                       ; default: IMAGE
______
SVOPERATORS
ControlPad-Name : "ENV:SuperView-Library/24BitToHAM.controlpad"
ControlPad-Commands : - DITHERMODE=< HAM6_QUICK|HAM6_WELL</pre>
                                  | HAM8_QUICK | HAM8_WELL>
                       ; specifies the HAM-Mode to be used and
                       ; the resulting speed/quality
         ______
ControlPad-Name
                   : "ENV:SuperView-Library/CallPNM.controlpad"
ControlPad-Commands : - STACKSIZE=<value>
                       ; stacksize to be used for calling PNM program,
                       ; increasing may help on crashes
                       ; default is: 32768
                     - PNMCOMMAND=<PBM command path and name>
                       ; PNM command to be called
                       ; e.g. PNMCOMMAND=Work:NetPBM/pnm/pnmscale
```

SuperView-Library 173 / 174

```
- PNMOPTIONS=<Options>
                      ; Options for PNM command to be called
                      ; e.g. PNMOPTIONS=-xscale 2.0 -yscale 2.0
ControlPad-Name
                  : "ENV:SuperView-Library/Crop.controlpad"
ControlPad-Commands : - CROP_LEFTEDGE=<Value>
                      ; crop from x position
                      ; (will be adjusted, if >= source width)
                     - CROP TOPEDGE=<Value>
                      ; crop from y position
                      ; (will be adjusted, if >= source height)
                     - CROP_WIDTH=<Value>
                      ; crop how many x pixels from leftedge
                       ; (will be adjusted, if too large)
                     - CROP_HEIGHT=<Value>
                      ; crop how many y pixels from topedge
                      ; (will be adjusted, if too large)
      _____
ControlPad-Name
                  : "ENV:SuperView-Library/Dither24Bit.controlpad"
ControlPad-Commands : - COLORDEPTH=<1..8>
                      ; specifies the colordepth of the dithering
                      ; output (1->2 Colors .. 8->256 Colors)
                    - DITHERMODE=<BESTPEN|DITHER_FLOYD-STEINBERG
                                  |ORDERED|BURKES>
                      ; whether to just select the best pen or
                      ; do Floyd-Steinberg pixel error adjustment
                        _____
                  : "ENV:SuperView-Library/ExtractGrayScales.controlpad"
ControlPad-Name
ControlPad-Commands : - COLORDEPTH=<1..8>
                      ; specifies the colordepth of the grayscaled
                      ; output (1->2 Colors .. 8->256 Colors)
                     - OUICK
                      ; uses >>2, >>1, >>3 (*0.25, *0.5, *0.125)
                      ; instead of *0.3, *0.59, *0.11
ControlPad-Name : "ENV:SuperView-Library/HilbertDither256.controlpad"
ControlPad-Commands : - BACKGROUND=<BLACK|WHITE>
                      ; defines, which of the two colors will act
                      ; as background color. Useful e.g. for printing.
                     _____
ControlPad-Name
                 : "ENV:SuperView-Library/PaletteDither.controlpad"
ControlPad-Commands : - COLORDEPTH=<1..8>
                      ; specifies the colordepth of the final,
                      ; dithered graphics (1..8 for 2..256 colors)
                     - DITHERMODE=<BESTPEN|DITHER_FLOYD-STEINBERG>
                      ; whether to just select the best pen or
                      ; do Floyd-Steinberg pixel error adjustment
                     - PALETTEDEPTH=<1..8>
                      ; number of colors (depth) to be taken from the
                      ; fixed palette - the possible rest will be
                      ; generated (if specifying more palette colors
                       ; than available, all available will be taken)
                     - PALETTEFILE = < palette graphics filename >
                      ; any 2...256 color graphics file, of which
                      ; superview.library is able to extract a
                      ; palette from (for example an IFF-ILBM file,
                      ; but including a BMHD and - maybe empty - BODY).
```

SuperView-Library 174 / 174

```
; Allows to take one graphics as sample for
                       ; the others (concerning the palette).
             _____
ControlPad-Name : "ENV:SuperView-Library/Rotate.controlpad"
ControlPad-Commands : - DEGREES=<90|180|270>
                     ; rotate by how many degrees (reverse clockwise) ?
ControlPad-Name : "ENV:SuperView-Library/RotateFree.controlpad"
ControlPad-Commands : - ROTATE ANGLE=<0..360>
                       ; rotate by how many degrees (reverse clockwise) ?
                     - METHOD=<MIDDLE|GIVENPOINT>
                       ; default is rotation about the middle
                     - X_COORD=<Value>
                      ; if METHOD=GIVENPOINT we need (X/Y)
                       ; Default is (0/0)
                     - Y_COORD=<Value>
                      ; if METHOD=GIVENPOINT we need (X/Y)
                       ; Default is (0/0)
                     - KEEPSIZE
                      ; if this keyword is set, it is NOT tried to
                       ; readjust the image size and to center the
                       ; image, so that parts, which would be out of
                      ; range won't be cut off (which works best
                       ; with (X/Y) pairs in the left, upper quarter)
                : "ENV:SuperView-Library/Scale50.controlpad"
ControlPad-Name
ControlPad-Commands : - METHOD=<HALF|DOUBLE>
                     ; scale to which size ?
                   : "ENV:SuperView-Library/XOR.controlpad"
ControlPad-Name
ControlPad-Commands : - XORVALUE = <0..255>
                      ; 0 and 255 will not be the best decision ;-)
                       ; Use 15 or something like this.
                      ; Values greater (depth^2)-1 (is: colors-1) won't
                      ; be accepted.
```