

CFG_NODELIST

COLLABORATORS

	<i>TITLE :</i> CFG_NODELIST		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		December 31, 2022	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	CFG_NODELIST	1
1.1	HBBS:Nodes/NodeList	1
1.2	NodeLocation_XX	1
1.3	AutoStart_XX	2

Chapter 1

CFG_NODELIST

1.1 HBBS:Nodes/NodeList

Description:

The HBBS:Nodes/NodeList file defines the paths for each node

Options:

```
NodeLocation_XX=<path>
    More...
    AutoStart_XX=<boolean>
    More...
```

1.2 NodeLocation_XX

```
NodeLocation_XX=<path>
```

E.G.

```
NodeLocation_1=HBBS:Nodes/Node1
NodeLocation_2=HBBS:Nodes/Node2
```

No Default, MUST be set!

Specifies Location of the Node directory (in which logs are created, file uploaded etc, etc..)

We recomend you use the settings in the example as it makes your life a bit easier and your BBS more structured, This option was put in so that you can run a multinode BBS using two networked computers (parnet/sernet) as some sysops like to do (Hi Cruise! :-)

Note: The UploadLog.txt and DownloadLog.TXT are created in this directory if enabled.

1.3 AutoStart_XX

AutoStart_XX=<boolean>

E.G.

```
AutoStart_1=NO
AutoStart_2=YES
```

No Default, Must be set for each node that you have.

This tells control whether or not to start each node when control itself is started.

Same as /X's IDLENODE option.
