PCHG

COLLABORATORS							
	<i>TITLE</i> : PCHG						
ACTION	NAME	DATE	SIGNATURE				
WRITTEN BY		May 17, 2022					

REVISION HISTORY						
NUMBER	DATE	DESCRIPTION	NAME			

Contents

1 PCHG

1.1	PCHG.guide	1
1.2	PCHG.guide/Why PCHG?	2
1.3	PCHG.guide/Design goals	2
1.4	PCHG.guide/Informal description	3
1.5	PCHG.guide/Compression	5
1.6	PCHG.guide/Writing changes	7
1.7	PCHG.guide/The transition phase	8
1.8	PCHG.guide/Formal specification	8
1.9	PCHG.guide/Author Info	9

1

Chapter 1

PCHG

1.1 PCHG.guide

This file contains the PCHG (Palette CHanGe) IFF chunk specs. ↔ The new IFF chunk PCHG allow to specify line-by-line palette changes in a simple way which is independent of the video mode; while it allows up to 65536 registers, it's usually shorter of an equivalent CTBL or SHAM chunk. Library code with full source and documentation is provided for a straightforward implementation in your programs. PCHG has been developed in BIX through an open discussion of many Amiga programmers, and it is our hope that it will become the Amiga standard for palette change technology.

```
Why PCHG?
                An introduction to the reasons for a new format
Design goals
             What we hope to do with PCHG
Informal description
     What's inside a PCHG chunk
Compression
              The compression technique used in PCHG
Writing changes
          The current hardware limitations of Copper lists
The transition phase
     What happens now
Formal specification
     An (almost) precise regular grammar for PCHG
Author Info
              Where to find the author of this document
```

1.2 PCHG.guide/Why PCHG?

Why PCHG? *****

After struggling a lot with CTBL, SHAM, and whatever else was invented for specifying palette changes at every scan line in order to implement them in 'Mostra' (my ILBM viewer), I decided there was no way to make them really work. Each program uses them in a different way, with different non-documented specifications. SHAM is hardwired to 200 lines, and the color of the last pixels of a screen depends on the horizontal position of the screen itself because of a wrong computation of the free Copper DMA slots. CTBL is theoretically undisplayable without freezing everything and yet all images I ever saw changed much less than 15 colors per scan line, which you can perfectly do with the Copper (thanks to ASDG's 'DDHR' utility for this info). There is moveover a great confusion about the role of the CMAP chunk with respect to all those guys.

Yet the technology is very simple. Just change some color register each scan line. Very Amiga specific, but it works, and it works really well.

This document describes the PCHG (Palette Changes) chunk, an ILBM property chunk for controlling efficiently and reasonably the palette changes at each scan line. Also, I included technical info and code about the current allowable per line palette changes. A picture with a PCHG chunk is called a "multi-palette" picture, just like a picture with a CTBL chunk is called a "dynamic" or "enhanced" picture. Multi-palette pictures are not restricted to a particular video mode. You can have EHB, hires, HAM, etc. multi-palette pictures.

This proposal is a team work. It was lively discussed with many other people, including Joanne Dow, Andy Finkel, J. Edward Hanway, Charles Heath, David Joiner, Jim Kent, Ilya Shubentsov, Mike Sinz, Loren Wilton. There is certainly some other people I'm forgetting to mention though.

What's good in what follows was suggested by them. I'm responsable for any error, omission, bad English and bad design.

1.3 PCHG.guide/Design goals

Design goals *****

- * Being able to specify *only* the changes which are really required.
- * Being able to specify 24-bit precision color changes, and an alpha

channel.

- * Specifying correctly the relation PCHG/CMAP.
- * Getting a chunk which is usually smaller than SHAM or CTBL.
- * Having a policy about Copper-only displayability.
- * Being able to change 65536 registers.
- * Specifying two storage formats: a very dense 4-bit 32 register format for current technology, and an open-ended, 24-bit+alpha channel, 65536 register format with compression for all future uses.
- * Distributing public domain code for PCHG compression/decompression and Copperlist building.

1.4 PCHG.guide/Informal description

Informal description

PCHG starts with the following header:

struct PCHGHeader {
 UWORD Compression;
 UWORD Flags;
 WORD StartLine;
 UWORD LineCount;
 UWORD ChangedLines;
 UWORD MinReg;
 UWORD MaxReg;
 UWORD MaxChanges;
 ULONG TotalChanges;
};

The only 'Compression' values currently defined are 'PCHG_COMP_NONE' and 'PCHG_COMP_HUFFMANN'. The 'Flags' field has three bits currently defined, 'PCHGF_12BIT', 'PCHGF_32BIT', 'PCHGF_USE_ALPHA'. The 'StartLine' and 'LineCount' fields specify the range controlled by the line mask, as we will see later. The 'ChangedLines' field specify the number of lines on which at least a change happens (i.e., the number of 1's in the line mask). The 'MinReg' and 'MaxReg' fields specify the minimum and the maximum register changed in the chunk: their purpose is to allow optimization (such as grouping of the modified registers in some special bank). The 'MaxChanges' field specify the maximum number of changes on a single line. The 'TotalChanges' field specify the total number of color changes in the whole PCHG chunk.

If Compression is 'PCHG_COMP_HUFFMANN', the rest of the chunk is a compressed format. It is formed by a

struct PCHGCompHeader {

```
ULONG CompInfoSize;
ULONG OriginalDataSize;
};
```

followed by 'CompInfoSize' bytes which contain the decompression tree, after which there is the compressed chunk (originally 'OriginalDataSize' bytes long). For information about the coding used by PCHG, see

Compression

The unpacked data (or the data following the 'PCHGHeader' in the non-compressed case) are divided as follows.

First of all, there is a array of '(LineCount+31)/32' longwords (that is, a bit mask of LineCount bits rounded up to the nearest longword). Each bit in the mask tells you if there are palette changes in the corresponding line. Bit 0 of the mask (i.e., bit 31 of the first longword) corresponds to line 'StartLine', bit 1 (i.e., bit 30 of the first longword) to line 'StartLine+1' and so on. The number of 1's will be equal to 'ChangedLines'. Note that 'StartLine' is a (possibly negative) offset from the top of the screen.

The information about the palette changes is stored immediately after the bit mask. For each bit set to 1 in the mask there is a variable length structure. These structures are recorded contiguously, and they are different depending on the 'PCHGF_12BIT' or the 'PCHGF_32BIT' flags being set. In the first case, we use

```
struct SmallLineChanges {
    UBYTE ChangeCount16;
    UBYTE ChangeCount32;
    UWORD PaletteChange[];
};
```

The 'PaletteChange' array contains 'ChangeCount16+ChangeCount32' elements. For each element, the lower 12 bits specify a color in 4-bit RGB form, while the upper 4 bits specify the register number. More precisely, for the first 'ChangeCount16' elements you take as register number the upper 4 bits, and for the following 'ChangeCount32' elements you take as register number the upper 4 bits+16. Thus, you can address a 32 register palette.

```
In the second case, we use
   struct BigLineChanges {
     UWORD ChangeCount;
     struct BigPaletteChange PaletteChange[];
   };
where
   struct BigPaletteChange {
```

```
UWORD Register;
UBYTE Alpha, Red, Blue, Green;
};
```

The array 'PaletteChange' contains 'ChangeCount' elements. For each elements, Register specifies the register number, while the 'Alpha', 'Red', 'Blue', 'Green' values specify the 8-bit content of the respective channels. 'Alpha' should be parsed only if the 'PCHGF_USE_ALPHA' flag is set in the header. The meaning of the 'Alpha' bits is currently undefined; it will be specified later. For they time being, they *must* be set to 0.

CMAP and PCHG don't interfere. It's up to the intelligence of the IFF ILBM writer using CMAP for the first line color register values, and then specifying the changes from line 1 (2 for laced pictures) onwards using PCHG. CMAP has to be loaded, as specified by the IFF ILBM specs.

Note that PCHG is mainly a time saver chunk. The "right thing" for a program should be generating at run-time the palette changes when a picture with more colors than available on the hardware has to be shown. However, the current computational power make this goal unrealistic. PCHG allows to display in a very short time images with lot of colors on the current Amiga hardware. It can be also used to write down a custom Copper list (maybe changing only the background color register) together with an image.

Some politeness is required from the PCHG writer. PCHG allows you to specify as many as 65535 per line color changes, which are a little bit unrealistic on the current hardware. Programs should never save with a picture more changes than available by using Copper lists only. This issue is thoroughly explained in

Writing changes

. Moreover, under

Release 2 you may want to set the 'USER_COPPER_CLIP' of your 'ColorMap' (via the 'VideoControl()' function); this will stop your Copper list from debording on another screen.

This kind of politeness is enforced by the specification. I have yet to see people which is interested in freezing their machine just in order to view a picture. DMA contention is a thing, lockup is another one. PCHG chunks which do not conform to the rules explained below are to be considered syntactically incorrect. If you want specify more changes than available through the system Copper macro calls 'CWAIT/CMOVE', please have good reasons (such as a new Commodore chip set or OS upgrade); otherwise, please use another chunk and don't mess up the PCHG interpretation.

1.5 PCHG.guide/Compression

(Caveat: you don't need to read this if you're not really interested because there are ready-to-use C functions for compression and decompression; moreover, 4-bit PCHG chunks are usually so entropic that the size gain is less than the size of the tree, so you shouldn't

compress them.)

PCHG uses a classical static Huffmann encoding for the line mask and the 'LineChanges' array. The coding tree is recorded just before the compressed data in a form which takes 1022 bytes or less (usually ~700). Its (byte) length is stored in the 'CompInfoSize' field of the 'PCHGCompHeader' structure. Moreover, this form is ready for a fast and short decompression algorithm--no preprocessing is needed. For references about the Huffmann encoding, see Sedgewick's 'Algorithms in C'. Note that the number of compressed data bits stored is rounded up to a multiple of 32 (the decompression routine knows the original length of the data, so the exceeding bits won't be parsed). Note also that left branches are labelled by 0, right branches are labelled by 1.


The format of the tree is recursive. We start to code from the end of a 511 'WORD' array, and we work backwards. To code an internal node at the position 'WORD *Pos', the left subtree is recorded at 'Pos-1' with a code of length 't', and the left subtree is coded at 'Pos-1-t'. Then an offset '(-t-1)*2' is stored in 'Pos', and the length of the resulting coding is '1+t+'length of the left subtree code. An external node is coded as the character associated with the ninth bit set. As a final optimization, if the left subtree to code is an external node, we just store the character associated in the place of the negative offset

For instance, the tree

/\ / \ > b

is coded as the word array [a | 0x100] [b]'. Note that without the ninth bit trick, it would be impossible to store this tree, since it would be confused with the tree formed by the external node b only.

Another simple example:



is coded as

[d | 0x100] [e] [c | 0x100] [-4] [a | 0x100] [b] [-6].

Decompression is very easy. We start from the end of the tree code.

If we pick a 0 bit in the packed data, we move a word to the left and fetch the current word. If it's positive and with the ninth bit set the tree is finished and we store to the destination the lower byte of the word we fetched, otherwise we pick another bit.

If we pick a 1 bit, we fetch the current word. If it's positive, we

store it. Otherwise we add it to the current position and we pick another bit. (Here you can see the reason why the offset is not stored as a word offset, but rather as a byte offset. We avoid a conversion word->byte offset for each bit set to 1 of the source).

1.6 PCHG.guide/Writing changes

```
Writing changes ****
```

PCHG is a machine-independent format. Nonetheless, it's been developed mainly for supporting the Amiga Copperlist palette changes. Thus, it's not a surprise to find included with the format definition a policy about the amount of color changes which you should write.

Under the current Amiga hardware and system software, you should never generate more than 7 (seven) changes per line. Moreover, in laced pictures the changes can only happen on even lines. Thus, for a 400 lines laced picture you have 200*7=1400 color changes at lines 0, 2, 4, etc., while for a 256 lines non laced picture you have 256*7= 1792 color changes at lines 0, 1, 2, etc. Of course you can save less changes, or no changes at all on some lines. (When displaying a scrolling playfield the DMA prefetch needed by the video hardware limits the changes to 5. High resolution screens with more than 5 changes can exhibit glitches in some positions if scrolled, for instance, with a viewer which supports the new 'AUTOSCROLL' screens. This constraint, however, is not relevant enough to force the general bound to 5 changes.)

The point here is that you shouldn't save more changes than that. If you want to write a picture with more changes, or changes on odd laced lines, please make aware the user of the fact that probably most viewer supporting PCHG won't be able to display it. The Amiga community has been already bitten by the problems of SHAM and CTBL, and we have neither need nor willing of repeating the experience.

Of course, when faster, better Amiga chips will be around, this magic number will change. But for the time being, this is the system limitation.

If you have a technical background about the Copper, that's why:

The Copper y register has 8-bits resolution. When it arrives at the 255th video line, it wraps up to 0. Thus, the system places a 'WAIT(226,255)' Copper instruction in order to stop correctly the video display on PAL screens.

If you want more than 7 changes, you have to start poking the color registers with the Copper just after a video line is finished. But on the 255th video line, 'MrgCop()' will merge your user Copperlist with the system one in such a way that the 'WAIT(226,255)' will happen *after* the counter wrapped, so the Copper will be locked until the next vertical blank. As a result, the following color changes won't be executed, and some trash will be displayed at the bottom of the screen

(this indeed happens with SHAM).

In order to avoid this, it is necessary to use only 'WAIT(0,<line>)' instructions. The time available before the display data fetch start allows only 7 color changes, and wide range experiments confirmed this.

Finally, due to a limitation of 'MrgCop()', it's not possible specifying 'WAIT' instructions on odd interlaced lines (it is because interlaced screens are displayed in two passes).

1.7 PCHG.guide/The transition phase

```
The transition phase *********
```

This specification is distributed with a complete set of C functions which take care of compression, decompression and Copperlist building. Adding support for PCHG in your programs should be pretty straightforward: you simply have to link with 'pchg.lib'. Documentation is provided in the standard Amiga autodoc format (thus, you can turn it in an AmigaGuide hypertext document via the suitable utility).

1.8 PCHG.guide/Formal specification

```
Formal specification
struct PCHGHeader {
       UWORD Compression;
       UWORD Flags;
       WORD StartLine;
       UWORD LineCount;
       UWORD ChangedLines;
       UWORD MinReg;
       UWORD MaxReg;
       UWORD MaxChanges;
       ULONG TotalChanges;
     };
    struct PCHGCompHeader {
       ULONG CompInfoSize;
       ULONG OriginalDataSize;
     };
    struct SmallLineChanges {
       UBYTE ChangeCount16;
       UBYTE ChangeCount32;
       UWORD PaletteChange[];
     };
```

```
struct BigLineChanges {
  UWORD ChangeCount;
   struct BigPaletteChange PaletteChange[];
};
struct BigPaletteChange {
  UWORD Register;
  UBYTE Alpha, Red, Blue, Green;
};
PCHG ::= "PCHG" #{ (struct PCHGHeader) (LINEDATA | HUFFCOMPLINEDATA) }
HUFFCOMPLINEDATA ::= { (struct PCHGCompHeader) TREE HUFFCOMPDATA }
TREE ::= { UWORD* }
HUFFCOMPDATA ::= { ULONG* }
HUFFCOMPDATA, when unpacked, gives a LINEDATA.
LINEDATA ::= { LINEMASK ((struct SmallLineChanges) * |
                         (struct BigLineChanges) *) }
LINEMASK ::= { ULONG* }
The following relations hold:
#LINEDATA == PCHGCompHeader.OriginalDataSize
#TREE == PCHGCompHeader.CompInfoSize
#LINEMASK == ((PCHGHeader.LineCount+31)/32) *4
```

PCHG is a property chunk. For the meaning of the above grammar, see the IFF documentation (the grammar does not give account for all the aspects of PCHG though). Note that my use of the '[]' notation for variable length arrays is not a C feature, but a shorthand.

1.9 PCHG.guide/Author Info

```
Author Info
********
Sebastiano Vigna
Via California 22
I-20144 Milano MI
BIX: svigna
INTERNET: vigna@imiucca.csi.unimi.it
vigna@ghost.sm.dsi.unimi.it
UUCP:cbmehq!cbmita!sebamiga!seba@cbmvax.cbm.commodore.com
...{uunet|pyramid|rutgers}!cbmvax!cbmehq!cbmita!sebamiga!seba
FIDO: 2:332/607.28
```