

Stable Implementation Agreements for Open Systems Interconnection Protocols: Part 5 - Upper Layers

Output from the March 1994 Open Systems Environment
Implementors' Workshop (OIW)

SIG Chair: **James Quigley, Hewlett-Packard**
SIG Editors: **Debra Britt, NCTS** **Laura Emmons, Telenex**

Foreword

This part of the Stable Implementation Agreements was prepared by the Upper Layers Special Interest Group (ULSIG) of the Open Systems Environment Implementors' Workshop (OIW). The charter for the OIW is located in Part 1 - Workshop Policies and Procedures of the "Draft Working Implementation Agreements Document."

The text in this part has been approved by the Plenary of the OIW. This part replaces the previously existing part on the Upper Layers.

Annex B is for information purposes only. Annex A forms an integral part of these Implementor Agreements.

Future changes and additions to these Implementor Agreements will be published as change pages. Deleted and replaced text will be shown as struck. New and replacement text will be shown as shaded.

Table of Contents

Part 5 - Upper Layers		1
0	Introduction	1
1	Scope	1
2	Normative References	1
	2.1 Session Layer	1
	2.2 Presentation Layer	2
	2.3 Application Layer	2
	2.4 Application Layer – ASE/ACSE	2
3	Status	3
4	Errata	3
	4.1 Technical Corrigenda and Defect Reports	3
	4.2 Defect Registers	4
	4.3 Exception Handling	6
5	Association Control Service Element	6
	5.1 Introduction	6
	5.2 Services	6
	5.3 Protocol Agreements	6
	5.3.1 Application Context	6
	5.3.2 AE Title	6
	5.3.3 Peer Entity Authentication	7
	5.4 ASN.1 Encoding Rules	7
	5.5 Connectionless	7
6	ROSE	7
7	RTSE	8
8	Presentation	8
	8.1 Introduction	8
	8.2 Service	8
	8.3 Protocol Agreements	8
	8.3.1 Transfer Syntaxes	8
	8.3.2 Presentation Context Identifier	9
	8.3.3 Default Context	9
	8.3.4 P-Selectors	9
	8.3.5 Provider Abort Parameters	10
	8.3.6 Provider Aborts and Session Version	10
	8.3.7 CPC-Type	10
	8.3.8 Presentation-context-definition-result-list	10

8.3.9	RS-PPDU	11
8.4	Presentation ASN.1 Encoding Rules	11
8.5	Presentation Data Value (PDV)	11
8.6	Connection Oriented	11
8.7	Connectionless	12
9	Session	12
9.1	Introduction	12
9.2	Services	12
9.3	Protocol Agreements	13
9.3.1	Concatenation	13
9.3.2	Segmenting	13
9.3.3	Reuse of Transport Connection	13
9.3.4	Use of Transport Expedited Data	13
9.3.5	Use of Session Version Number	13
9.3.5.1	Selection of session version	13
9.3.5.2	User data in session version 2	14
9.3.6	Receipt of Invalid SPDUs	14
9.3.7	Invalid SPM Intersections	15
9.3.8	S-Selectors	15
9.4	Connectionless	16
10	UNIVERSAL ASN.1 ENCODING RULES	17
10.1	TAGS	17
10.2	Definite Length	17
10.3	External	17
10.4	Integer	17
10.5	String Types	18
10.6	Extensibility	18
11	Additions to ISP on Common Upper Layer Requirements	18
11.1	Service	18
11.2	Provider Abort Parameters	18
11.3	Concatenation	19
11.4	Segmenting	19
11.5	Reuse of Transport Connection	19
11.6	Use of Transport Expedited Data	19
12	Character Sets	19
13	Conformance	19
14	Specific ASE Requirements	20
14.1	FTAM Phase 2	20
14.1.1	ACSE Requirements	20
14.1.2	Presentation Requirements	20
14.1.3	Session Requirements	21
14.1.4	Session Options	21
14.1.5	ASN.1 Encoding Requirements	22

14.2	MHS	22
14.2.1	Phase 1 (1984 X.400) Session Requirements	22
14.2.2	Phase 2, Protocol P1 (1988 X.400)	23
14.2.2.1	ROSE Requirements	23
14.2.2.2	RTSE Requirements	23
14.2.2.3	ACSE Requirements	23
14.2.2.4	Presentation Requirements	24
14.2.2.5	Session Requirements	24
14.2.3	Phase 2, Protocol P7 (1988 X.400)	24
14.2.3.1	ROSE Requirements	24
14.2.3.2	RTSE Requirements	24
14.2.3.3	ACSE Requirements	25
14.2.3.4	Presentation Requirements	25
14.2.3.5	Session Requirements	26
14.2.4	Phase 2, Protocol P3 (1988 X.400)	27
14.2.4.1	ROSE Requirements	27
14.2.4.2	RTSE Requirements	27
14.2.4.3	ACSE Requirements	27
14.2.4.4	Presentation Requirements	27
14.2.4.5	Session Requirements	27
14.3	DS Phase 1	27
14.3.1	ACSE Requirements	27
14.3.2	Presentation Requirements	28
14.3.3	Session Requirements	28
14.4	Virtual Terminal	28
14.4.1	Phase 1a	28
14.4.1.1	ACSE Requirements	28
14.4.1.2	Presentation Requirements	29
14.4.1.3	Session Requirements	29
14.4.2	Phase 1b	29
14.4.2.1	ACSE Requirements	29
14.4.2.2	Presentation Requirements	30
14.4.2.3	Session Requirements	30
14.5	MMS	31
14.5.1	ACSE Requirements	31
14.5.2	Constructed Encodings	31
14.5.3	Presentation Requirements	31
14.5.4	Session Requirements	31
14.6	Transaction Processing	32
14.6.1	ACSE Requirements	32
14.6.2	Presentation Requirements	32
14.6.3	Session Requirements	32
14.7	Network Management	33
14.7.1	ROSE Requirements	33
14.7.2	ACSE Requirements	33
14.7.3	Presentation Requirements	33
14.7.4	Session Requirements	33
14.8	Remote Database Access	34
14.8.1	ACSE Requirements	34

Part 5 - Upper Layers

March 1994 (Stable)

14.8.2	Presentation Requirements	34
14.8.2.1	Presentation Contexts for the RDA Basic Application Context	34
14.8.2.2	Presentation Contexts for the RDA TP Application Context	34
14.8.3	Session Requirements	35

Annex A (normative)

Object Identifier Register	36
A.1 Register Index	36
A.2 Object Identifier Descriptions	36

Annex B (informative)

Recommended Practices	37
------------------------------------	----

List of Tables

Table ISO Defect Reports	5
Table 1 - Called and Responding P-Selectors	9
Table 2 - Called and Responding S-Selectors	16
Table 3 - Calling S-Selectors	16
Table A.1 - Session States	38
Table A.2 - Incoming Events	39

Part 5 - Upper Layers

0 Introduction

In this portion of the Implementors' Agreements, the Upper Layers SIG is primarily concerned with providing implementation agreements for ACSE, ROSE, RTSE, and the Presentation and Session layers, so that systems implemented according to these agreements can successfully interoperate.

1 Scope

The agreements in this part apply to all ASE agreements in this document.

A referencing specification may use the requirements in this part in one of the following ways:

- a) The referencing specification does not duplicate any of the requirements of this part of the document within its own specifications and instead requires an implementation to conform to the requirements of this part. This is the preferred method.
- b) The referencing specification duplicates all of the requirements of this part of the document as part of its requirements and related conformance statements.

Each ASE SIG supplements the common requirements in this part of the document by a statement in the "Specific ASE Requirements" clause of this part which outlines the ASE's specific requirements for the use of the ACSE, presentation and session protocol standards.

2 Normative References

2.1 Session Layer

- [1] ISO 8326: 1987 (E), *Information Processing Systems - Open Systems Interconnection - Basic Connection Oriented Session Service Definition*.
- [2] ISO 8327: 1987 (E), *Information Processing Systems - Open Systems Interconnection - Basic Connection Oriented Session Protocol Specification*.
- [3] ISO/IEC JTC1/SC21 N2494, *Information Processing Systems - Open Systems Interconnection - Basic Connection Oriented Session Service Definition-AD 2 to ISO 8326 to Incorporate Unlimited User Data*.
- [4] ISO/IEC JTC1/SC21 N2495, *Information Processing Systems - Open Systems Interconnection - Basic Connection Oriented Session Protocol Specification - AD 2 to ISO 8327 to Incorporate Unlimited User Data*.
- [5] ISO/AD3 8326, *Information Processing Systems - Open Systems Interconnection-Session Service Definition: Addendum 3 Covering Connectionless-Mode Session Service*.
- [6] ISO/IS 9548, *Information Processing Systems - Open Systems Interconnection-Connectionless*

Session Protocol to Provide the Connectionless-Mode Session Service.

2.2 Presentation Layer

- [7] ISO 8822: 1988 (ISO/IEC JTC1/SC21 N2335), *Information Processing Systems - Open Systems Interconnection - Connection-Oriented Presentation Service Definition.*
- [8] ISO 8823: 1988 (ISO/IEC JTC1/SC21 N2336), *Information Processing Systems - Open Systems Interconnection - Connection Oriented Presentation Protocol Specification.*
- [9] ISO 8824: 1990 (E), *Information Processing Systems - Open Systems Interconnection - Specification of Abstract Syntax Notation One (ASN.1).*
- [10] ISO 8825: 1990 (E), *Information Processing Systems - Open Systems Interconnection - Specification of Basic Encoding Rules for Abstract Syntax Notation One (ASN.1).*
- [11] ISO/DAD1 8822: 1989-02-15(e) (ISO/IEC JTC1/SC21 N 3171), *Information Processing Systems - Open Systems Interconnection - Presentation Service Definition: Draft Addendum 1 Covering Connectionless-Mode Presentation Service.*
- [12] ISO/IS 9576: 1989-02-25 5(E) (ISO/IEC JTC1/SC21 N 3172), *Information Processing Systems - Open Systems Interconnection - Connectionless Presentation Protocol to Provide the Connectionless-Mode Presentation Service.*

2.3 Application Layer

- [13] ISO/DP 9545, ISO/TC97/SC21/N1743, July 24, 1987, revised November 1987, *Information Processing Systems - Open Systems Interconnection - Application Layer Structure.*

2.4 Application Layer - ASE/ACSE

- [14] ISO 8649: 1987 (E) (ISO/IEC JTC1/SC21 N2326), *Information Processing Systems - Open Systems Interconnection - Service Definition for the Association Control Service Element.*
- [15] ISO 8650: 1987 (E) (ISO/IEC JTC1/SC21 N2327), *Information Processing Systems - Open Systems Interconnection - Protocol Specification for the Association Control Service Element.*
- [16] ISO 8649/DAD2, *Information Processing System - Open Systems Interconnection - ACSE Service Definition: Draft Addendum 2 Covering Connectionless-Mode ACSE Service.*
- [17] *ISO 8649/DAD1 (ISO/IEC JTC1/SC21 N3771), Information Processing Systems - Open Systems Interconnection - Service Definition for the Association Control Service Element - Addendum 1: Peer-Entity Authentication During Association Establishment*

- [18] *ISO 8650/DAD1 (ISO/IEC JTC1/SC21 N3772), Information Processing Systems - Open Systems Interconnection - Protocol Specification for the Association Control Service Element - Addendum 1: Peer-Entity Authentication During Association Establishment*
- [19] *ISO 8649/Cor.1: 1991 (E) (ISO/IEC JTC1/SC21 N5630), Information Processing Systems - Open Systems Interconnection - Technical Corrigendum 1 to ACSE Service (ISO 8649: 1988) Covering Defects 8649/001, 8649/002 and 8649/003.*
- [20] *ISO 8650/Cor.1: 1991 (E) (ISO/IEC JTC1/SC21 N5631), Information Processing Systems - Open Systems Interconnection - Technical Corrigendum 1 to ACSE Protocol (ISO 8650: 1988) Covering Defects 8650/001, 8649/004.*
- [21] *ISO IS 10035: 1989-02-25 (ISO/IEC JTC1/SC21 N 3456), Information Processing Systems - Open Systems Interconnection - Connectionless ACSE Protocol to Provide the Connectionless-Mode ACSE Service.*

3 Status

This text is stable.

NOTE - Changes due to errata are summarized in clause 4

4 Errata

In accordance with FIPS 146-1, with specific exceptions as noted below, this edition of the Part 5 - Stable Implementation Agreements remains backwardly compatible with Part 5 - Stable Implementation Agreements, Version 3, Edition 1. The method for assuring continued interoperability when these specific exceptions occur is detailed below and has been approved by the plenary of the OIW. Therefore, this edition of Part 5 - Stable Implementation Agreements supersedes all previous versions and editions of the Part 5 - Stable Implementation Agreements.

4.1 Technical Corrigenda and Defect Reports

An existing ISO base standard (e.g., ISO 8649 -- ACSE service) may be modified by an approved/registered Technical Corrigenda (TC) that fixes problems as reported in one or more Defect Reports (DR).

An error or request for clarification concerning a base standard is brought to the attention of ISO by a Defect Report. Defect Reports may be submitted to ISO by the OIW or by national bodies such as ANSI X3T5 task group in the USA.

A Defect Report is processed by the Defect Editing Group of the base standard as part of the ISO "Rapid Amendment Process." If the Defect Editing Group agrees that the Defect Report concerns an

error in the base standard, the Defect Editing Group prepares a fix to the error in the form of a Draft Technical Corrigenda (DTC). A DTC is not used to add new or revised facility to the base standard. The purpose of the DTC is to rectify inconsistencies and or mechanisms that do not provide the defined facility.

NOTE - The amendment procedure is not used to add facility to a base standard.

A DTC undergoes a 3-month draft ballot by national bodies. An editing meeting may be necessary to resolve national body comments.

An accepted/registered DTC becomes a TC. A TC immediately becomes a part of the base standard that it references. For a referencing standard or profile, the modification by a TC or an errata immediately takes effect unless it applies to an option that is "out-of-scope" or prohibited by the referencing standard or profile.

A TC may impact the interoperability of a base standard. In some cases, recertification may be necessary.

4.2 Defect Registers

Table ISO Defect Reports

Defect	Source	Circ. by Sec.	Distr. as WG doc.	Resp to Sec. by	Returned to Editor for -				Ballot ends	Voting Sum'ry	Final text	Remarks
					info	actn	DTC/49	DTC/50				
8649/001	Editor	88-12	--	89-11	--	--	N4447	--	90-05-15	N4687	N5630	Closed: Part of 8649/TC1
8649/002	Editor	89-11	--	89-11	--	--	N4448	--	90-05-15	N4688	N5630	Closed: Part of 8649/TC1
8649/003	Editor	89-11	--	89-11	--	--	N4449	--	90-05-15	N4689	N5630	Closed: Part of 8649/TC1
8649/004	Editor	90-02	N765	90-05-30	--	yes	tbd	tbd	tbd	tbd	tbd	Open: ULA advice - wait for XALS developments
8649/005	--											Number not used
8649/006	Japan	90-03	N782	90-06	--	--	N5320	--	91-01	N5690	--	Referred back to WG6 ULA group; response Nxxxx AFNOR: no vote Revised DTC due from Editor
8649/007	CCITT	90-12	N962	91-03-25	--	--				N6628	Ed 2	Closed: DTC text unchanged; add to Edition 2
8650/001	Editor	88-08	N533	89-11	--	--	--	N3473	89-08	N3862	N4286	Closed: Part of 8650/TC1
8650/002	Editor	88-08	N534	89-11	N653	--	--	--	--	--	--	Closed: Not recommended for progression
8650/003	Japan	88-10	N573	89-01	N654	--	--	--	--	--	--	Closed: Editorial change already in IS text
8650/004	Editor	88-12	--	88-12	--	--	--	N3475	89-08	N4286	N4286	Closed: Part of 8650/TC1
8650/005	--											Number not used
8650/006	CCITT	90-10	N915	91-01-11	tbd	--	--	--	--	--	--	Closed: Not recommended for progression
8650/007	CCITT	90-10	N916	91-01-11	--	--	--	N6338	91-12-10	N6629	Ed 2	Closed: Add to Edition 2 of 8650
8650/008	Editor	90-06	--	90-06	N911	--	--	--	--	--	--	Closed: Response only - did not change text
8650/009	Editor	93-??	N???	93-03	--	--	--	Nxxxx	93-12	tbd	tbd	Open: under discussion preparing for DTC text

4.3 Exception Handling

For those cases where backwards compatibility cannot be assured due to a Technical Corrigenda (see clause 4.6), interoperability will be maintained by requiring existing implementations to incorporate the change within 12 months after it has been registered as a Technical Corrigenda. The registration authority for conformance testing will determine in each case whether or not recertification is necessary.

5 Association Control Service Element

5.1 Introduction

This clause details the implementation requirements for the Association Control Service Element (ACSE) of the Application layer as defined in ISO 8649 and ISO 8650.

5.2 Services

All ACSE services are within the possible scope of a workshop-conformant system.

5.3 Protocol Agreements

5.3.1 Application Context

Values for and uses of Application Context names are determined by specific ASEs. Values used by ASE SIGS are listed in the clause entitled "Specific ASE Requirements."

5.3.2 AE Title

Support of AE-Title-form1, the Name form, or AE-Title-form2, the Object Identifier form for sending, is dependent on the referencing specification.

NOTE - AE-Title-form1 is a directory name that has to be allocated by an authorized naming authority. It is part of the responsibilities of the naming authority to determine how this name is built from its two constituents, AP-Title-form1 and AE-Qualifier-form1.

NOTE - AE-Title-form2 is an Object Identifier registered by an authorized Registration Authority. It is part of that registration to determine how this Object Identifier is built from its two constituents, AP-Title-form2 and AE-Qualifier-form2.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 6.1.

5.3.3 Peer Entity Authentication

If supported, peer-entity authentication during association establishment shall be implemented as specified in Addendum 1 to ISO 8650 (ISO 8650/DAD1).

5.4 ASN.1 Encoding Rules

When the Abort APDU is used during the association establishment phase, the Presentation layer negotiation is considered complete. Therefore, a PDV-list presentation-context-identifier has been assigned to the association and it should be used in the indirect-reference component of the Association Information parameter. The direct-reference component shall not be present.

NOTE - The presentation context negotiation is completed by the presentation context identifier list of the ARU PPDU.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 6.2.

5.5 Connectionless

The connectionless ACSE protocol shall be implemented as specified in ISO IS 10035.

No further agreements beyond those specified elsewhere in this part have been made regarding this standard.

6 ROSE

ROSE shall be implemented as specified in ISO DIS 9072-1.2 and ISO DIS 9072-2.2.

No further agreements beyond those specified elsewhere in this part have been made regarding this standard.

7 RTSE

RTSE shall be implemented as specified in ISO 9066-1 and ISO 9066-2.

No further agreements beyond those specified elsewhere in this part have been made regarding this standard.

NOTE - "If checkpointing is not used, the VALUE of window size is not meaningful and shall be ignored."

8 Presentation

8.1 Introduction

This clause details the implementation requirements for the Presentation layer as defined in the Presentation Service Definition, ISO 8822, and the Presentation Protocol Definition, ISO 8823.

The task of the Presentation layer is to carry out the negotiation of transfer syntaxes and to provide for the transformation to and from transfer syntaxes. The transformation to and from a particular transfer syntax is a local implementation issue and is not discussed within this clause. This clause is concerned with the protocol agreements, and thus is entirely devoted to the issues involved with the negotiation of transfer syntaxes and the responsibilities of the Presentation protocol.

NOTE - The complete size of encoding of the CP PDU, CPA PDU, and CPR PDU is derived from the SS user-data size restricted to 10 K such as specified in 9.3.5. This limitation applies also to the ARP and ARU PDUs.

8.2 Service

(Refer to clause 11.1)

8.3 Protocol Agreements

8.3.1 Transfer Syntaxes

The following transfer syntax must be supported for all mandatory abstract syntaxes; the basic encoding rules for ASN.1. This syntax is derived by applying the basic encoding rules for ASN.1 to the abstract syntax (see the Basic Encoding Rules for ASN.1, ISO 8825).

The number of transfer syntaxes proposed is dependent upon the recognized transfer syntaxes which are available to support the particular abstract syntaxes used by an Application Entity.

8.3.2 Presentation Context Identifier

A conformant implementation shall not encode Presentation context identifiers outside the range of 0 to 32,767.

Implementations must be able to handle a minimum of two Presentation contexts per connection.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 7.1.

8.3.3 Default Context

If the Presentation expedited data service is required, the default context must be explicitly present in the P-CONNECT PPDU at Presentation connect time.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 7.6.

8.3.4 P-Selectors

Local P-selectors shall be a maximum of four octets. This applies only to P-selectors in PPDUs whose receipt by a workshop-conformant system normally results in either a P-CONNECT indication or a P-CONNECT confirmation being issued.

If the Responding P-Selector of the CPA-PPDU is not present, it is assumed to have a value equivalent to that of the Called P-Selector of the CP-PPDU. Table 1 summarizes the handling of the Responding-presentation selector parameters of the CP-PPDU and CPA-PPDUs.

Table 1 - Called and Responding P-Selectors

		Responding P-Sel of CPA-PPDU		
		Not present	Length=0	Length>0
Called P-Sel of CP-PPDU	Not present	Note 1	Note 1	Note 2
	Length=0	Note 1	Note 1	Note 2
	Length>0	Note 3	Note 3	Note 2
<p>Note 1 - The resulting value is assumed to be a null value.</p> <p>Note 2 - The resulting value is assumed to be the Responding P-Sel value.</p> <p>Note 3 - The resulting value is assumed to be the Called P-Sel value of the CP-PPDU.</p>				

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 7.2.

8.3.5 Provider Abort Parameters

(Refer to clause 11.2)

8.3.6 Provider Aborts and Session Version

The Presentation Provider Abort PDU (ARP-PPDU) shall be present regardless of the Session version in effect for a given association. This precludes the use of indefinite length encoding of an ARP-PPDU when Session Version 1 is in effect.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 7.7.

8.3.7 CPC-Type

Implementations shall not use any CPC-type values in the SS-user data parameter of the S-CONNECT unless more than one transfer syntax is proposed for a single Presentation context of the Presentation data values. Each CPC-type represents a unique transfer syntax, so if more than one transfer syntax is proposed, CPC-type values may appear in that SS-user data parameter.

For a Presentation context for which the Basic encoding Rules are a proposed transfer syntax, all PDVs in the user data parameter of the CP PDU must be encoded first using the Basic Encoding Rules and must be examined by the receiving Presentation protocol machine. Following CPC-type values may be examined or ignored at the receiver's option see ISO 8823, clause 6.2.5.3).

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 7.3.

8.3.8 Presentation-context-definition-result-list

No semantics are implied by the absence of the optional Presentation-context-definition-result-list component of the CPR-PPDU. This component is required if the Provider-reason is absent in the CPR-PPDU. If the Provider-reason is present, then the Presentation-context-definition-result-list is optional.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 7.5.

8.3.9 RS-PPDU

The Presentation-context-identifier-list shall not be present when only the kernel functional unit is in effect.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 7.8.

8.4 Presentation ASN.1 Encoding Rules

If a received PPDU contains any improperly encoded data values (including data values embedded within the User data field of a PPDU) and an abort is issued, then either an ARU or an ARP PPDU shall be issued.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 7.9.

8.5 Presentation Data Value (PDV)

A Presentation data value (PDV) is a value of a type in an abstract syntax, e.g., a value of an ASN.1 type.

A PDV may contain embedded PDVs in different contexts. A change of context within a PDV is indicated by an EXTERNAL. EXTERNAL implies an embedded PDV.

A PDV cannot be split across PDV-lists in fully-encoded user data.

Fully-encoded-data that is a series of PDVs in the same Presentation context (e.g., grouped FTAM PDUs) shall be encoded either as a single PDV-list (using the octet-aligned choice) or as a series of PDV-lists, each encoding either a single PDV (using the single-ASN1-type choice) or multiple PDVs (using the octet-aligned choice). Note that receivers must accept any of the above encodings.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 7.10.

8.6 Connection Oriented

The Transfer-syntax-name component of a PDV-list value shall be present in a CP PPDU if and only if more than one transfer syntax name was proposed for the Presentation context of the Presentation data values. The Transfer-syntax-name component of a PDV-list value shall always be present in a CPC-type. If only the Kernel functional unit is negotiated, then the Transfer-syntax-name component of a PDV-list value shall only appear in the CP PPDU and CPC-type.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 7.3.

8.7 Connectionless

The connectionless Presentation protocol shall be implemented as specified in ISO 9576.

The Transfer-syntax-name component of a PDV-list value shall be present in a UD PPDU if and only if more than one transfer syntax name was proposed for the Presentation context of the Presentation data values. The Transfer-syntax-name component of a PDV-list value shall always be present in a UDC-type. The Transfer-syntax-name component of a PDV-list value shall only appear in the UD PPDU and UDC-type.

No further agreements beyond those specified elsewhere in this part have been made regarding this standard.

9 Session

9.1 Introduction

This clause details the implementation requirements for the Session layer as defined in the Session Service Definition, ISO 8326 and the Session Protocol Definition, ISO 8327.

9.2 Services

The following functional units are within the scope of a workshop-conformant system:

- a) Kernel;
- b) Duplex;
- c) Expedited Data;
- d) Resynchronize;
- e) Exceptions;
- f) Activity Management;
- g) Half-duplex;
- h) Minor Synchronize;
- i) Major Synchronize;
- j) Typed Data;
- k) Data Separation.

9.3 Protocol Agreements

9.3.1 Concatenation

(Refer to clause 11.3)

9.3.2 Segmenting

(Refer to clause 11.4)

9.3.3 Reuse of Transport Connection

(Refer to clause 11.5)

9.3.4 Use of Transport Expedited Data

(Refer to clause 11.6)

9.3.5 Use of Session Version Number

9.3.5.1 Selection of session version

Session versions 1 and 2 are recognized. The referencing specification shall specify in its specific upper layer requirements section which version of session is required.

NOTE - Session version 2 specifies the use of unlimited user data as dictated by Addendum 2 to ISO 8327. All session version 1 implementations must be able to negotiate version 1 operation when responding to a CN SPDU proposing both version 1 and version 2.

At least session version 2 shall be proposed with ACSE normal mode. With ACSE normal mode, a receiver shall support session version 2, but may reject a proposal requesting only session version 1.

NOTE - Between two conformant implementations supporting ACSE normal mode, session version 2 will be used.

All session version 1 implementations, upon receipt of a CN SPDU proposing only version 2, should respond with an RF SPDU containing a reason code indicating that the proposed version is not supported.

If session version 1 and 2 are both proposed in the CN SPDU, then the maximum length of the user data parameter in the CN SPDU shall be 512 octets.

NOTE - In that case a PGI field of 193 will be associated with this parameter. This implies that an implementation supporting both session version 1 and 2 can establish a connection with an implementation supporting only version 1.

9.3.5.2 User data in session version 2

If only session version 2 is proposed in the CN SPDU, then a size larger than 10,240 octets of the session user data parameter value of the S-CONNECT request primitive is out of scope. This implies that sending the OA and CDO SPDUs is out of scope. Receiving the OA and CDO SPDUs is mandatory but storing and using them is out of scope. If a CDO SPDU is received but not stored or used, an RF SPDU should be issued by the responder. If an OA SPDU is received but not stored or used, a P-Abort SPDU should be issued by the initiator.

NOTE - If the length of the user data parameter value is not greater than 512 octets, then an associated PGI field of 193 is used. Otherwise, a PGI field of 194 is used.

When session version 2 is negotiated, then in all subsequent SPDUs a data length exceeding 10,240 octets of the user data parameter value with an associated PGI field of 193, reason code parameter value (PI = 50) for RF SPDU and user data parameter value (PI = 46) for MIA SPDU is out of scope.

Session version 2 implementations need only support the maximum data lengths specified in the specific upper layer requirements section of the referencing specification, which may be less than 10,240 octets.

NOTE - For session expedited data the limit for user data is 14 octets.

NOTE - These agreements impose no limitation on the size of the user information parameter of DT, TD, and CD SPDUs. Therefore, the user data of P-DATA, P-TYPED-DATA, and P-CAPABILITY-DATA is unconstrained.

9.3.6 Receipt of Invalid SPDUs

Upon receipt of an invalid SPDU, the SPM shall take any action in A.4.3 of the Session Protocol Definition ISO/IS 8327 except Action d.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 9.1.

9.3.7 Invalid SPM Intersections

If the conditions described in A.4.1.2 of the Session Protocol Definition ISO/IS 8327 are satisfied, the SPM shall always take the actions described by A.4.1.2 a.

This implies that no S-P-EXCEPTION-REPORT indications will be generated nor EXCEPTION REPORT SPDUs sent due to invalid intersections of the Session state table resulting from received SPDUs.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 9.4.

9.3.8 S-Selectors

The absence of the Called or Calling S-Sel parameter of the CN SPDU shall be treated equivalent to a zero length Called or Calling S-Sel parameter value.

The absence of the Responding S-Sel parameter of the AC SPDU shall be treated as though its value were equivalent to that of the Called S-Sel parameter of the CN SPDU, i.e., the Responding S-Sel is zero length if the Called S-Sel is either absent or zero length. The Responding S-Sel parameter's value is equal to that of the Called S-Sel parameter's value if it is absent and the Called S-Sel parameter's value is greater than zero.

The Responder may change the value of the Called S-Sel parameter value of the CN SPDU by responding with the Responding S-Sel value of the AC SPDU.

The absence of the Calling S-Sel parameter of the AC SPDU indicates that its value is assumed to be equivalent to the value of the Calling S-Sel parameter of the CN SPDU.

Tables 2 and 3 summarize the handling of the Session Selector parameters of the CN and AC SPDUs (see also ISO 8327 8.3.1.12, 8.3.1.14, 8.3.2.14, 8.3.2.15).

Table 2 - Called and Responding S-Selectors

		Responding S-Sel of AC SPDU		
		Not present	Length=0	Length>0
Called S-Sel of CN SPDU	Not present	Note 1	Note 1	Note 2
	Length=0	Note 1	Note 1	Note 2
	Length>0	Note 3	Note 3	Note 2
<p>Note 1 - The resulting value is assumed to be a null value.</p> <p>Note 2 - The resulting value is assumed to be the Responding S-Sel value.</p> <p>Note 3 - The resulting value is assumed to be the Called S-Sel value of the CN SPDU.</p>				

Table 3 - Calling S-Selectors

		Calling S-Sel of AC SPDU		
		Not present	Length=0	Length>0
Calling S-Sel of CN SPDU	Not present	Note 4	Note 4	Invalid
	Length=0	Note 4	Note 4	Invalid
	Length>0	Note 5	Invalid	Note 6
<p>Note 4 - The calling S-Sel has a null value.</p> <p>Note 5 - The calling S-Sel has the value as indicated in the CN SPDU.</p> <p>Note 6 - Valid if and only if both values are identical.</p>				

9.4 Connectionless

The connectionless Session protocol shall be implemented as specified in ISO 9548.

No further agreements beyond those specified elsewhere in this part have been made regarding this standard.

10 UNIVERSAL ASN.1 ENCODING RULES

10.1 TAGS

The maximum value of an ASN.1 basic encoding tag that need be handled by a workshop-conformant implementation shall be 16,383. This is the maximum unsigned number that can be represented in 14 bits, therefore, the maximum encoding of a tag occupies 3 octets.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 8.1.1.

10.2 Definite Length

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 8.1.2.

10.3 External

It is assumed that "Presentation layer negotiation of encoding rules" is always in effect, and therefore clause 32.5 of the Specification of ASN.1, ISO 8824 never applies.

If a data value to be encapsulated in an EXTERNAL type is an instance of a single ASN.1 type encoded according to the Basic Encoding Rules for ASN.1, then the option "single-ASN.1-type" shall be chosen as its encoding.

If a data value to be encapsulated in an EXTERNAL type is encoded as an integral number of octets, and the above does not apply, then the option "octet-aligned" shall be chosen as its encoding.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 8.1.5.

10.4 Integer

Any incidence of an ASN.1 INTEGER type defined in an abstract syntax describing protocol control information must be encoded so that the length of its contents octets is no more than four octets, unless an explicit Workshop agreement to the contrary is made for a specific INTEGER type.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 8.1.3.

10.5 String Types

The contents octets for a constructed encoding of a BIT STRING, OCTET STRING, or character string value consists of the complete encoding of zero, one, or more data values, and the encoding of these data values must be primitive.

Editor's Note - This clause is technically equivalent to the Common Upper Layers Requirements Profile (ISO DISP 11188-1) and will be replaced by a reference to ISO DISP 11188-1 8.1.6.

10.6 Extensibility

For data values that are ultimately carried on the user data of the CONNECT SPDU (i.e., Presentation CP, ACSE AARQ and any APDU in the user information field of AARQ) a receiver shall

- a) ignore any undefined element,
- b) ignore all unknown bit name assignments within a bit string.

NOTE - Referencing specifications may apply similar requirements to other protocol elements.

11 Additions to ISP on Common Upper Layer Requirements

11.1 Service

Only the Kernel functional unit need be supported. The Context Management and Context Restoration functional units are outside the scope of these agreements.

The requirement that the Presentation kernel functional unit be implemented does not imply that any of the Session functional units for expedited data, typed data, and capability data and the corresponding Presentation service primitives are required to be implemented.

11.2 Provider Abort Parameters

No conformance requirements are implied by the use of either the Abort-reason or the Event-identifier component of the ARP-PPDU. The decision to include these parameters is left up to the implementation issuing the abort.

11.3 Concatenation

When a category 0 SPDU is concatenated with a category 2 SPDU, the category 0 SPDU shall not contain User Data. Extended concatenation is not required and can be refused using the normal negotiation mechanisms of the Session protocol.

11.4 Segmenting

Session segmenting is not required and can be refused using the normal negotiation mechanisms of the Session protocol. All conformant implementations shall be able to interwork without Session segmenting.

11.5 Reuse of Transport Connection

Reuse of a Transport connection is not required and can be refused.

11.6 Use of Transport Expedited Data

The Session use of Transport expedited service is optional.

12 Character Sets

(Refer to Part 21 -- a new chapter expressly for character sets.)

13 Conformance

In order for an implementation to be in conformance with the Implementors' agreements, the rules below shall be followed:

- a) A conformant implementation must meet all of the requirements of this specification. All documents referenced in the Upper Layers part shall be used as the supporting documents for all implementations of ACSE, ROSE, RTSE, Presentation, or Session. The full references for these documents are in clause 2.
- b) Workshop-conformant implementations shall be ISO conformant. PICS may contain limitations on length or value aspects of a protocol. PICS of workshop-conformant systems shall not contain restrictions more severe than those in these implementation agreements.

NOTE - An implementation may abort a connection if the constraints specified in these agreements are violated.

14 Specific ASE Requirements

The following list for each ASE the corresponding SIG's requirements of and restrictions on ACSE, ROSE, RTSE, Presentation, and Session.

All listed requirements and restrictions shall be included in an NIST-conformant system and shall be implemented in accordance with these Implementor's agreements.

14.1 FTAM Phase 2

14.1.1 ACSE Requirements

ACSE Functional Requirements: Kernel

Application Contexts: "ISO FTAM" { iso(1) standard(0) 8571 application-context iso-ftam(1) } - implies the use of the ACSE and the FTAM ASE.

A **value** is defined for the AE Title only to satisfy the FTAM requirement for exchanging fields of this type. This value does not identify an Application Entity and carries no semantics.

If the AE title is used, AE-title-form2 shall be supported. Support of AE-title-form2 includes support of AP-title-form2 and AE-qualifier-form2.

The value for the AP title is { 1 3 9999 1 ftam-nil-ap-title (7) } at this time. Values for the AE qualifier are outside the scope of these agreements.

The use of AP invocation identifiers and AE invocation identifiers by FTAM is outside the scope of these agreements.

14.1.2 Presentation Requirements

Presentation Functional Units: kernel

Presentation Contexts: At least 3 Presentation Contexts must be supported.

Abstract Syntaxes:

a) Abstract Syntaxes for conformant Implementations

1) "ISO 8650-ACSE1" { joint-iso-ccitt(2) association-control(2) abstract-syntax(1) apdus(0) version1(1) }

2) "FTAM-PCI" { iso(1) standard(0) 8571 abstract-syntax(2) ftam-pci(1) }

3) "FTAM unstructured binary abstract syntax" { iso(1) standard(0) 8571

abstract-syntax(2) unstructured-binary(4) }

Editor's Note - In Definitions below, "NBS" designation will be preserved.

b) Abstract Syntaxes Depending on Implementation Profile

1) "FTAM-FADU" { iso(1) standard(0) abstract-syntax(2) ftam-fadu(2) }

2) "FTAM unstructured text abstract syntax" { iso(1) standard(0) 8571
abstract-syntax(2) unstructured-text(3) }

3) "NBS abstract syntax AS1" { iso identified-organization oiw(14) ftamsig(5)
abstract-syntax(2) nbs-as1(1) }

4) "NBS file directory entry abstract syntax" { iso identified-organization oiw(14)
ftamsig(5) abstract-syntax(2) nbs-as2(2) }

c) Associated Transfer Syntax:

1) "Basic Encoding of a single ASN.1 type" { joint-iso-ccitt(2) asn1(1)
basic-encoding(1)}

Editor's Note - The changes above involving "OIW(14)" were not explicitly mentioned at the March 1990 Plenary, but were implied from a correspondingly approved FTAM motion.

14.1.3 Session Requirements

Session Functional Units:

- a) kernel
- b) duplex

Version Number: 2

Maximum size of User Data parameter field: 10,240

14.1.4 Session Options

Session Functional Units:

- a) resynchronize - only a Resynchronize Type value of "abandon"
- b) minor synchronize

NOTES

- 1 The minor synchronize functional unit is required whenever the resynchronize functional unit is available.
- 2 The default value for Minor Sync Point Sync type item PV-field shall be absent if explicit confirmation is required (per ISO 8327, 8.3.20.3) (SIA->value of \$).

14.1.5 ASN.1 Encoding Requirements

Some INTEGER types of the FTAM PCI may exceed the maximum size specified in the UNIVERSAL ASN.1 ENCODING Rules. See the Range of values for INTEGER type Parameters of the FTAM part.

14.2 MHS

14.2.1 Phase 1 (1984 X.400) Session Requirements

Session Functional Units:

- a) kernel
- b) half-duplex
- c) exceptions
- d) activity management
- e) minor synchronize

Version Number: 1

Maximum size of User Data parameter field: 512

NOTES

- 1 Restricted use is made by the RTS of the Session services implied by the functional units selected. Specifically, 1) No use is made of S-TOKEN-GIVE, and 2) S-PLEASE-TOKENS only asks for the data token.
- 2 In the S-CONNECT SPDU, the Initial Serial Number should not be present.
- 3 The format of the Connection Identifier in the S-CONNECT SPDU is described in Version 5 of the X.400-Series Implementors' Guide.

14.2.2 Phase 2, Protocol P1 (1988 X.400)

14.2.2.1 ROSE Requirements

ROSE is not used.

14.2.2.2 RTSE Requirements

The RTSE requirements are:

- a) Monologue
- b) TWA - optional
- c) checkpointing:
 - 1) minimum checkpointsize = 1
 - 2) minimum windowsize = 1
- d) no checkpointing

For the Monologue Association:

- a) initiator keeps initial turn
- b) APDUs are transferred from initiator to responder only
- c) no turn passing
- d) only the initiator effects the orderly release of an association

For the two way alternate Association

- a) the initiator may keep or pass the initial turn, at binding
- b) APDUs are transferred by the holder of the turn
- c) only the initiator effects the orderly release of an association, when it possesses the turn

14.2.2.3 ACSE Requirements

As per Phase 2, Protocol P7.

Application Contexts:

- a) "MTS-transfer-protocol-1984" - mandatory
- b) "MTS-transfer-protocol" - mandatory
- c) "MTS-transfer" - mandatory

14.2.2.4 Presentation Requirements

Presentation Functional Units: kernel

Presentation Contexts: at least 3 must be supported

Abstract Syntaxes:

- a) "ISO 8650-ACSE1" {joint-iso-ccitt(2) association-control(2) abstract-syntax(1) apdus(0) version1(1) }
- b) "MTS-RTSE"
- c) "MTSE"
- d) Associated Transfer Syntax: "Basic Encoding of a single ASN.1 type" { joint-iso-ccitt(2) asn1(1) basic-encoding(1) }

14.2.2.5 Session Requirements

As per Phase 2, Protocol P7.

14.2.3 Phase 2, Protocol P7 (1988 X.400)

14.2.3.1 ROSE Requirements

Operation and association classes are used as per the standard.

14.2.3.2 RTSE Requirements

The RTSE requirements are:

- a) TWA
- b) normal-mode
- c) checkpointing

- d) minimum checkpointsize = 1
- e) minimum windowsize = 1
- f) no checkpointing

For the Monologue Association:

- a) initiator keeps initial turn
- b) APDUs are transferred from initiator to responder only
- c) no turn passing
- d) only the initiator effects the orderly release of an association

For two way alternate Association:

- a) the initiator may keep or pass the initial turn, at binding
- b) APDUs are transferred by the holder of the turn
- c) only the initiator effects the orderly release of an association, when it possesses the turn

14.2.3.3 ACSE Requirements

ACSE Functional Requirements: Kernel

The use of AP-TITLE, AE-QUALIFIER, AP-INVOCATION-ID, and AE-INVOCATION-ID is not recommended; however, a receiving entity must be capable of ignoring them (if present) without refusing the connection.

Application Contexts:

- a) "MS-access" - mandatory; normal mode
- b) "MS-reliable-access" - optional; normal mode

14.2.3.4 Presentation Requirements

Presentation Functional Units: kernel

Presentation Contexts: at least 5

Abstract Syntaxes:

- a) "ISO 8650-ACSE1" { joint-iso-ccitt(2) association-control(2) abstract-syntax(1) apdus(0)

version1(1) }

- b) MSBind/MSUnbind (with or without RTSE)
- c) MSSE (Message Submission)
- d) MASE (Message Administration)
- e) MRSE (Message Retrieval)

Associated Transfer Syntax: "Basic Encoding of a single ASN.1 type" { joint-iso-ccitt(2) asn1(1) basic-encoding(1) }

14.2.3.5 Session Requirements

Session Functional Units:

- a) kernel
- b) half-duplex (if RTSE is supported)
- c) full-duplex (if RTSE is not supported)
- d) exceptions
- e) activity management
- f) minor synchronize

Version Number: 2

Maximum size of User Data parameter field: 10,240

NOTES

- 1 MHS proposes both versions 1 and 2 for pass through mode (X.410 mode), but only version 2 for normal mode.
- 2 Restricted use is made by the RTS of the Session services implied by the functional units selected. Specifically, no use is made of S-TOKEN-GIVE, and S-PLEASE-TOKENS only asks for the data token.
- 3 In the S-CONNECT SPDU, the Initial Serial Number should not be present.
- 4 The format of the Connection Identifier in the S-CONNECT SPDU is described in Version 5 of the X.400-Series Implementors' Guide.

14.2.4 Phase 2, Protocol P3 (1988 X.400)

14.2.4.1 ROSE Requirements

As per Phase 2, P7.

14.2.4.2 RTSE Requirements

As per Phase 2, P7.

14.2.4.3 ACSE Requirements

As per Phase 2, P7.

Application Contexts:

- a) "MTS-access" - mandatory
- b) "MTS-reliable-access" - optional
- c) "MTS-forced-access" - mandatory
- d) "MTS-forced-reliable-access" - optional

14.2.4.4 Presentation Requirements

As per Phase 2, P7.

14.2.4.5 Session Requirements

As per Phase 2, P7.

14.3 DS Phase 1

14.3.1 ACSE Requirements

ACSE Functional Requirements: Kernel

Application Contexts:

- a) "id-ac-directoryAccessAC" { joint-iso-ccitt(2) ds(5) 3 1 }

- b) "id-ac-directorySystemAC" { joint-iso-ccitt(2) ds(5) 3 2 }

14.3.2 Presentation Requirements

Presentation Functional Units: kernel

Presentation Contexts: At least 2 Presentation Contexts must be supported.

Abstract Syntaxes:

- a) "ISO 8650-ACSE1" { joint-iso-ccitt(2) association-control(2) abstract-syntax(1) apdus(0) version1(1) }
- b) "id-as-directoryAccessAS" joint-iso-ccitt(2) ds(5) 9 1 }
- c) "id-as-directorySystemAS" { joint-iso-ccitt(2) ds(5) 9 2 }

Associated Transfer Syntax: "Basic Encoding of a single ASN.1 type" { joint-iso-ccitt(2) asn1(1) basic-encoding(1) }

14.3.3 Session Requirements

Session Functional Units:

- a) kernel
- b) duplex

Version Number: 2

Maximum size of User Data parameter field: 10,240

14.4 Virtual Terminal

14.4.1 Phase 1a

14.4.1.1 ACSE Requirements

ACSE Functional Requirements: Kernel

Application Contexts: "ISO VT" { iso(1) standard(0) 9041 application-context(1) }- implies the use of the ACSE and the VT ASE

14.4.1.2 Presentation Requirements

Presentation Functional Units: kernel

Presentation Contexts: at least 2 must be supported

Abstract Syntaxes:

a) "ISO 8650-ACSE1" { joint-iso-ccitt(2) association-control(2) abstract-syntax(1) apdus(0) version1(1) }

b) "VT Basic" { iso(1) standard(0) 9041 abstract-syntax(2) }

Associated Transfer Syntax: "Basic Encoding of a single ASN.1 type" { joint-iso-ccitt(2) asn1(1) basic-encoding(1) }

14.4.1.3 Session Requirements

Session Functional Units:

a) kernel

b) duplex

c) expedited data

d) major synchronize

e) resynchronize - only a Resynchronize Type value of "restart"

f) typed data

Version Number: 2

Maximum size of User Data parameter field: 10,240

Session Options: expedited data

14.4.2 Phase 1b

14.4.2.1 ACSE Requirements

ACSE Functional Requirements: Kernel

Application Contexts: "ISO VT" { iso(1) standard(0) 9041 application-context(1) } - implies the use of the ACSE and the VT ASE

14.4.2.2 Presentation Requirements

Presentation Functional Units: kernel

Presentation Contexts: at least 2 must be supported

Abstract Syntaxes:

a) "ISO 8650-ACSE1" { joint-iso-ccitt(2) association-control(2) abstract-syntax(1) apdus(0) version1(1) }

b) "VT Basic" { iso(1) standard(0) 9041 abstract-syntax(2) }

Associated Transfer Syntax: "Basic Encoding of a single ASN.1 type" { joint-iso-ccitt(2) asn1(1) basic-encoding(1) }

14.4.2.3 Session Requirements

Session Functional Units:

a) kernel

b) duplex

c) half-duplex

d) expedited data

e) major synchronize

f) resynchronize - only a Resynchronize Type value of "restart"

g) typed data

Version Number: 2

Maximum size of User Data parameter field: 10,240

Session Options: expedited data

14.5 MMS

14.5.1 ACSE Requirements

ACSE Functional Units: Kernel

Application Context: "ISO MMS" { iso(1) standard(0) 9506 part(2) mms-application-context-version1(3)} - implies use of ACSE and MMS ASE

14.5.2 Constructed Encodings

Constructed encodings shall not be used for bit strings shorter than 256 bits, nor for octet strings (or types derived from octet strings by tagging) shorter than 1024 octets. For such strings, only primitive encodings shall be used. Upon receipt of a constructed bit string or octet string that violates this restriction, the receiving implementation may reject the corresponding PDU, but shall not send a P-P-Abort.

14.5.3 Presentation Requirements

Presentation Functional Units: Kernel

At least 2 Presentation Contexts must be supported.

Abstract Syntaxes:

- a) "mms-abstract-syntax-major-version1" { iso(1) standard(0) 9506 part(2) mms-abstract-syntax-major-version1 (1)}
- b) "ISO 8650-ACSE1" {joint-iso-ccitt(2) association-control(2) abstract-syntax(1) apdus(0) version1(1)}

Associated Transfer Syntax: "Basic Encoding of a single ASN.1 type" {joint-iso-ccitt(2) asn1(1) basic-encoding(1)}

14.5.4 Session Requirements

Session Functional Units:

- a) Kernel
- b) Duplex

Version Number: 2

Maximum size of User Data parameter field: 10,240

14.6 Transaction Processing

14.6.1 ACSE Requirements

ACSE Functional Units: Kernel

The application context is user-defined.

14.6.2 Presentation Requirements

Presentation Functional Units: Kernel

Presentation Contexts:

- a) At least 3 must be supported if the commit functional unit of TP is not supported.
- b) At least 4 must be supported if the commit functional unit of TP is supported.

Abstract Syntaxes: "ISO 8650-ACSE1" { joint-iso-ccitt(2) association-control(2) abstract-syntax(1) apdus(0) version1(1) }

Associated Transfer Syntax:

- a) "Basic Encoding of a single ASN.1 type" { joint-iso-ccitt(2) asn1(1) basic-encoding(1) }
- b) "ISO 10026-TP" { joint-iso-ccitt(2) transaction-processing(?) abstract-syntax(2) tp-apdus(1) }
- c) If required, "ISO 9804-CCR" (TBD)
- d) At least one user-defined abstract syntax.

14.6.3 Session Requirements

Session Functional Units:

- a) kernel
- b) duplex
- c) Others as required by CCR (TBD) if the commit functional unit of TP is supported.

Version Number: 2

Maximum size of User Data parameter field: 10,240

14.7 Network Management

14.7.1 ROSE Requirements

The Rose requirements are as specified in ISO 9596 section 5.2: Underlying Services, and section 6.2 Remote Operations.

Operations Classes: 1, 2, and 5

Association Classes: 3

14.7.2 ACSE Requirements

ACSE Functional Units: kernel

Application Contexts: as defined by [SMO]

AE-Title: The association responder shall support both forms of the AE-Title. The association requestor may use either form of the AE-Title.

14.7.3 Presentation Requirements

Presentation Functional Units: kernel

Presentation Contexts: At least 2 must be supported.

Abstract Syntaxes:

a) "ISO 8650-ACSE1" { joint-iso-ccitt(2) association-control(2) abstract-syntax(1) apdus(0) version1(1) }

b) "CMIP-PCI" {joint-iso-ccitt(2) ms(9) cmip(1) cmip-pci(1) abstractSyntax(4)}

Associated Transfer Syntax: "Basic Encoding of a single ASN.1 type" { joint-iso-ccitt(2) asn1(1) basic-encoding(1) }

14.7.4 Session Requirements

Session Functional Units:

a) kernel

b) duplex

Version Number: 2

Maximum size of User Data parameter field: 10,240.

14.8 Remote Database Access

14.8.1 ACSE Requirements

ACSE Functional Units: Kernel

Application Contexts:

a) "RDA-SQL-BASIC-APPL-CONTEXT-V1" {iso(1) standard(0) rda(9579) part-2(2) basic-ac(2) version-1(1)} implies use of the ACSE and RDA SQL ASEs;

b) "RDA-SQL-TP-APPL-CONTEXT-V1" {iso(1) standard(0) rda(9579) part-2(2) tp-ac(3) version-1(1)} implies use of the ACSE, RDA SQL, TP, and optionally CCR ASEs.

14.8.2 Presentation Requirements

Presentation Functional Units: Kernel

14.8.2.1 Presentation Contexts for the RDA Basic Application Context

At least 2 presentation contexts must be supported;

Abstract Syntaxes:

a) "ISO 8650-ACSE1" {joint-iso-ccitt(2) association-control(2) abstract-syntax(1) apdus(0) version1(1)};

b) "RDA-SQL-ABSTRACT-SYNTAX-V1" {iso(1) standard(0) rda(9579) part-2(2) abstract-syntax(1) version-1(1)};

Associated Transfer Syntax: "Basic Encoding of a single ASN.1 type" {joint-iso-ccitt(2) asn1(1) basic-encoding(1)};

14.8.2.2 Presentation Contexts for the RDA TP Application Context

At least 3 presentation contexts must be supported, if the commit functional unit of TP is not supported.
At least four presentation contexts must be supported, if the commit functional unit of TP is supported.

Abstract Syntaxes:

a) "ISO 8650-ACSE1" {joint-iso-ccitt(2) association-control(2) abstract-syntax(1) apdus(0) version1(1)};

b) "RDA-SQL-ABSTRACT-SYNTAX-V1" {iso(1) standard(0) rda(9579) part-2(2) abstract-syntax(1) version-1(1)};

c) "ISO 10026-TP" {joint-iso-ccitt(2) transaction processing(10) modules(1) apdus-abstract-syntax(1) version1 (0)};

d) If required, "ISO 9805-CCR" {joint-iso-ccitt(2) ccr(7) abstract-syntax(2) apdus(1) version1 (1)}.

Associated Transfer Syntax: "Basic Encoding of a single ASN.1 type" {joint-iso-ccitt(2) asn1(1) basic-encoding(1)}.

14.8.3 Session Requirements

Session Functional Units:

a) Kernel;

b) Duplex;

Version: 2:

Maximum size of User Data parameter field: 10,240.

Annex A (normative)

Object Identifier Register

Editor's Note - Annexes A and B have been switched to place the informative annex after the normative annex.

A.1 Register Index

Each entry in the index contains an object identifier value and a reference to the clause describing the object identifier's use:

- a) { iso(1) identified-organization(3) oiw(14) ulsig(8) application-context(1) nil(1) } is defined in 14.2;
- b) { iso(1) identified-organization(3) oiw(14) ulsig(8) abstract-syntax(2) octet-string(1) } is defined in 14.2.

A.2 Object Identifier Descriptions

{ iso(1) identified-organization(3) oiw(14) ulsig(8) application-context(1) nil(1) }

This application context may be used by applications having a prior agreement regarding the application context.

NOTE - This value is intended to be used by private applications that have an a priori agreement concerning the set of ASEs, related options, and any other information necessary for the interworking of AEs on an application association. This value does not identify any specific application context and cannot be used to identify the intended communications environment for the application association. Therefore, it is strongly recommended that private applications define and register an object identifier for their application context.

{ iso(1) identified-organization(3) oiw(14) ulsig(8) abstract-syntax(2) octet-string(1) }

```

NIST-OIW-ULSIG-AS-octet-string
DEFINITIONS ::= BEGIN

Single-octet-string ::= OCTET STRING
END
```

This abstract syntax may be used by applications having a prior agreement regarding the content of the octet string.

Annex B (informative)

Recommended Practices

Editor's Note - Annexes A and B have been switched to place the informative annex after the normative annex.

The optional "Reflect Parameter Values" parameter in the Provider ABORT SPDU shall be encoded so as to represent the Session connection state, the incoming event and the first invalid SPDU field exactly at the moment a protocol error was detected.

The first octet encodes the Session state as a number relative to 0 as detailed in table 1.

The second octet encodes the incoming event as a number relative to 0 as detailed in table 2.

The third octet contains the SI, PGI, or PI Code of any SI field, PGI unit or PI unit in error.

NOTE - The remaining 6 octets are undefined herein.

Table A.1 - Session States

State	Rel	Description
1	0	Idle, no transport connection
1B	1	Wait for T-connect confirm
1C	2	Idle, transport connected
2A	3	Wait for the ACCEPT SPDU
3	4	Wait for the DISCONNECT SPDU
8	5	Wait for the S-CONNECT response
9	6	Wait for the S-RELEASE response
16	7	Wait for the T-DISCONNECT indication
713	8	Data Transfer state
1A	9	Wait for the ABORT ACCEPT SPDU
4A	10	Wait for the MAJOR SYNC ACK SPDU or PREPARE SPDU
4B	11	Wait for the ACTIVITY END ACK SPDU or PREPARE SPDU
5A	12	Wait for the RESYNCHRONIZE ACK SPDU or PREPARE SPDU
5B	13	Wait for the ACTIVITY INTERRUPT SPDU or PREPARE SPDU
5C	14	Wait for the ACTIVITY DISCARD ACK SPDU or PREPARE SPDU
6	15	Wait for the RESYNCHRONIZE SPDU or PREPARE SPDU
10A	16	Wait for the S-SYNC-MAJOR response
10B	17	Wait for the S-ACTIVITY-END response
11A	18	Wait for the S-RESYNCHRONIZE response
11B	19	Wait for the S-ACTIVITY-INTERRUPT response
11C	20	Wait for the S-ACTIVITY-DISCARD response
15A	21	After PREPARE, wait for the MAJOR SYNC ACK SPDU or the ACTIVITY END ACK
15B	22	After PREPARE, wait for the RESYNCHRONIZE SPDU or the ACTIVITY DISCARD SPDU
15C	23	After PREPARE, wait for the RESYNCHRONIZE ACK SPDU, or the ACTIVITY INTERRUPT ACK SPDU or the ACTIVITY DISCARD ACK SPDU
18	24	Wait for GIVE TOKENS ACK SPDU
19	25	Wait for a recovery request or SPDU
20	26	Wait for a recovery SPDU or request
21	27	Wait for the CAPABILITY DATA ACK SPDU
22	28	Wait for the S-CAPABILITY-DATA response
1D	29	Wait for the CONNECT DATA OVERFLOW SPDU
2B	30	Wait for the OVERFLOW ACCEPT SPDU
15D	31	After PREPARE, wait for the ABORT SPDU

Table A.2 - Incoming Events

Event	Rel	Description
SCONreq	0	S-CONNECT request
SCONrsp	1	S-CONNECT accept response
SCONrsp	2	S-CONNECT reject response
SDTreq	3	S-DATA request
SRELreq	4	S-RELEASE request
SRELrsp	5	S-RELEASE accept response
SUABreq	6	S-U-ABORT request
TCONcnf	7	T-CONNECT confirmation
TCONind	8	T-CONNECT indication
TDISind	9	T-DISCONNECT indication
TIM	10	Time out
AA	11	ABORT ACCEPT
AB-nr	12	ABORT - no reuse
AC	13	ACCEPT
CN	14	CONNECT
DN	15	DISCONNECT
DT	16	DATA TRANSFER
FN-nr	17	FINISH - no reuse
RF-nr	18	REFUSE - no reuse
SACTDreq	19	S-ACTIVITY-DISCARD request
SACTDrsp	20	S-ACTIVITY-DISCARD response
SACTEreq	21	S-ACTIVITY-END request
SACTErsp	22	S-ACTIVITY-END response
SACTIreq	23	S-ACTIVITY-INTERRUPT request
SACTIrsp	24	S-ACTIVITY-INTERRUPT response
SACTRreq	25	S-ACTIVITY-RESUME request
SACTSreq	26	S-ACTIVITY-START request
SCDreq	27	S-CAPABILITY-DATA request
SCDrsp	28	S-CAPABILITY-DATA response
SCGreq	29	S-CONTROL-GIVE request
SEXreq	30	S-EXPEDITED-DATA request
SGTreq	31	S-TOKEN-GIVE request
SPTreq	32	S-TOKEN-PLEASE request
SRELrsp	33	S-RELEASE response reject
SRSYNreq(a)	34	S-RESYNCHRONIZE request abandon
SRSYNreq(r)	35	S-RESYNCHRONIZE request restart
SRSYNreq(s)	36	S-RESYNCHRONIZE request set
SRSYNrsp	37	S-RESYNCHRONIZE response
SSYNMreq	38	S-SYNC-MAJOR request
SSYNMrsp	39	S-SYNC-MAJOR response
SSYNmreq	40	S-SYNC-MINOR request
SSYNMrsp	41	S-SYNC-MINOR response
STDreq	42	S-TYPED-DATA request
SUERreq	43	S-U-EXCEPTION-REPORT request

Table A.2 - Incoming Events (continued)

Event	Rel	Description
AB-r	44	ABORT - reuse SPDU
AD	45	ACTIVITY DISCARD SPDU
ADA	46	ACTIVITY DISCARD ACK SPDU
AE	47	ACTIVITY END SPDU
AEA	48	ACTIVITY END ACK SPDU
AI	49	ACTIVITY INTERRUPT SPDU
AIA	50	ACTIVITY INTERRUPT ACK SPDU
AR	51	ACTIVITY RESUME SPDU
AS	52	ACTIVITY START SPDU
CD	53	CAPABILITY DATA SPDU
CDA	54	CAPABILITY DATA ACK SPDU
ED	55	EXCEPTION DATA SPDU
ER	56	EXCEPTION REPORT SPDU
EX	57	EXPEDITED DATA SPDU
FN-r	58	FINISH - reuse SPDU
GT	59	GIVE TOKENS SPDU
GTA	60	GIVE TOKENS ACK SPDU
GTC	61	GIVE TOKENS CONFIRM SPDU
MAA	62	MAJOR SYNC ACK SPDU
MAP	63	MAJOR SYNC POINT SPDU
MIA	64	MAJOR SYNC ACK SPDU
MIP	65	MINOR SYNC POINT SPDU
NF	66	NOT FINISHED SPDU
PR-MAA	67	PREPARE (MAJOR SYNC ACK) SPDU
PR-RA	68	PREPARE (RESYNCHRONIZE ACK) SPDU
PR-RS	69	PREPARE (RESYNCHRONIZE) SPDU
PT	70	PLEASE TOKENS SPDU with Token Item Parameter
RA	71	RESYNCHRONIZE ACK SPDU
RF-r	72	REFUSE - reuse SPDU
RS-a	73	RESYNCHRONIZE - abandon SPDU
RS-r	74	RESYNCHRONIZE - restart SPDU
RS-s	75	RESYNCHRONIZE - set SPDU
TD	76	TYPED DATA SPDU
CDO	77	CONNECT DATA OVERFLOW SPDU
OA7	80	VERFLOW ACCEPT SPDU
PR-AB	79	PREPARE (ABORT) SPDU