

TDSEnglish

COLLABORATORS

	<i>TITLE :</i> TDSEnglish	
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>
WRITTEN BY		January 9, 2023
<i>SIGNATURE</i>		

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	TDSEnglish	1
1.1	TDSEnglish.guide	1
1.2	TDSEnglish.guide/Introduction	2
1.3	TDSEnglish.guide/Requirements	3
1.4	TDSEnglish.guide/Installation	3
1.5	TDSEnglish.guide/Version	3
1.6	TDSEnglish.guide/Ted	4
1.7	TDSEnglish.guide/Ted Workbench	4
1.8	TDSEnglish.guide/Ted Shell	5
1.9	TDSEnglish.guide/Menu File	5
1.10	TDSEnglish.guide/File-New	6
1.11	TDSEnglish.guide/File-Open	6
1.12	TDSEnglish.guide/File-Load	7
1.13	TDSEnglish.guide/File-Insert	7
1.14	TDSEnglish.guide/File-Save	7
1.15	TDSEnglish.guide/File-Save As	7
1.16	TDSEnglish.guide/File-Save Changed	7
1.17	TDSEnglish.guide/File-Delete	7
1.18	TDSEnglish.guide/File-Current Dir	8
1.19	TDSEnglish.guide/File-Hide	8
1.20	TDSEnglish.guide/File-Reveal	8
1.21	TDSEnglish.guide/File-Protect	8
1.22	TDSEnglish.guide/File-About	9
1.23	TDSEnglish.guide/File-Iconify	9
1.24	TDSEnglish.guide/File-Quit	9
1.25	TDSEnglish.guide/Menu Edit	9
1.26	TDSEnglish.guide/Edit-Mark	10
1.27	TDSEnglish.guide/Edit-Mark Vertical	10
1.28	TDSEnglish.guide/Edit-Mark All	11
1.29	TDSEnglish.guide/Edit-Cut	11

1.30	TDSEnglish.guide/Edit-Copy	11
1.31	TDSEnglish.guide/Edit-Paste	11
1.32	TDSEnglish.guide/Edit-Paste Vertical	11
1.33	TDSEnglish.guide/Edit-Erase	12
1.34	TDSEnglish.guide/Edit-Save	12
1.35	TDSEnglish.guide/Edit-Indent	12
1.36	TDSEnglish.guide/Edit-Change To	12
1.37	TDSEnglish.guide/Edit-Format	13
1.38	TDSEnglish.guide/Edit-Undo	13
1.39	TDSEnglish.guide/Edit-Redo	13
1.40	TDSEnglish.guide/Menu Search	13
1.41	TDSEnglish.guide/Search-Find	14
1.42	TDSEnglish.guide/Search-Replace	14
1.43	TDSEnglish.guide/Search-Next	15
1.44	TDSEnglish.guide/Search-Previous	15
1.45	TDSEnglish.guide/Search-Set Bookmark	15
1.46	TDSEnglish.guide/Search-Goto Bookmark	15
1.47	TDSEnglish.guide/Search-Goto Line	16
1.48	TDSEnglish.guide/Search-Match Bracket	16
1.49	TDSEnglish.guide/Search-Find Reference	16
1.50	TDSEnglish.guide/Menu Compile	16
1.51	TDSEnglish.guide/Compile-Compile	17
1.52	TDSEnglish.guide/Compile-Build	18
1.53	TDSEnglish.guide/Compile-Build All	18
1.54	TDSEnglish.guide/Compile-Stop	18
1.55	TDSEnglish.guide/Compile-Run	18
1.56	TDSEnglish.guide/Compile-Debug	19
1.57	TDSEnglish.guide/Compile-Next Error	19
1.58	TDSEnglish.guide/Compile-Previous Error	19
1.59	TDSEnglish.guide/Compile-Load Errors	19
1.60	TDSEnglish.guide/Menu Project	19
1.61	TDSEnglish.guide/Project-New	20
1.62	TDSEnglish.guide/Project-Open	20
1.63	TDSEnglish.guide/Project-Save	21
1.64	TDSEnglish.guide/Project-Save As	21
1.65	TDSEnglish.guide/Project-Close	21
1.66	TDSEnglish.guide/Project-Translators	21
1.67	TDSEnglish.guide/Project-Linker	23
1.68	TDSEnglish.guide/Project-Debugger	24

1.69	TDSEnglish.guide/Project-Command	25
1.70	TDSEnglish.guide/Project-Modules	26
1.71	TDSEnglish.guide/Project-Options	26
1.72	TDSEnglish.guide/Menu Settings	28
1.73	TDSEnglish.guide/Settings-AutoIndent	28
1.74	TDSEnglish.guide/Settings-WordWrap	29
1.75	TDSEnglish.guide/Settings-OverStrike	29
1.76	TDSEnglish.guide/Settings-Create Icons?	29
1.77	TDSEnglish.guide/Settings-Editor	29
1.78	TDSEnglish.guide/Settings-Display	31
1.79	TDSEnglish.guide/Settings-KeyBoard	32
1.80	TDSEnglish.guide/Settings-References	33
1.81	TDSEnglish.guide/Settings-Load Settings	33
1.82	TDSEnglish.guide/Settings-Save Settings	33
1.83	TDSEnglish.guide/Settings-Save Settings As	33
1.84	TDSEnglish.guide/ARexx Commands	33
1.85	TDSEnglish.guide/ABOUT	36
1.86	TDSEnglish.guide/BACKSPACE	36
1.87	TDSEnglish.guide/BUILD	36
1.88	TDSEnglish.guide/CLOSE	36
1.89	TDSEnglish.guide/CMDSHELL	36
1.90	TDSEnglish.guide/COMPILE	37
1.91	TDSEnglish.guide/COPY	37
1.92	TDSEnglish.guide/CURSOR	37
1.93	TDSEnglish.guide/CUT	37
1.94	TDSEnglish.guide/DEBUG	38
1.95	TDSEnglish.guide/DELETE	38
1.96	TDSEnglish.guide/DIR	38
1.97	TDSEnglish.guide/ERASE	39
1.98	TDSEnglish.guide/FIND	39
1.99	TDSEnglish.guide/FIRSTCAPITAL	39
1.100	TDSEnglish.guide/FORMAT	39
1.101	TDSEnglish.guide/GOTOBOOKMARK	40
1.102	TDSEnglish.guide/GOTOCOLUMN	40
1.103	TDSEnglish.guide/GOTOFILE	40
1.104	TDSEnglish.guide/GOTOLINE	40
1.105	TDSEnglish.guide/HIDE	40
1.106	TDSEnglish.guide/ICONIFY	41
1.107	TDSEnglish.guide/INDENT	41

1.108	TDSEnglish.guide/INSERT	41
1.109	TDSEnglish.guide/KEYBOARD	41
1.110	TDSEnglish.guide/LOAD	42
1.111	TDSEnglish.guide/LOWERCASE	42
1.112	TDSEnglish.guide/MARK	42
1.113	TDSEnglish.guide/NEW	43
1.114	TDSEnglish.guide/NEXT	43
1.115	TDSEnglish.guide/OPEN	43
1.116	TDSEnglish.guide/PASTE	43
1.117	TDSEnglish.guide/POSITION	44
1.118	TDSEnglish.guide/PREVIOUS	44
1.119	TDSEnglish.guide/PROJECT	44
1.120	TDSEnglish.guide/PROTECT	45
1.121	TDSEnglish.guide/QUERY	45
1.122	TDSEnglish.guide/QUIT	45
1.123	TDSEnglish.guide/REDO	45
1.124	TDSEnglish.guide/REPLACE	46
1.125	TDSEnglish.guide/REQUESTFILE	46
1.126	TDSEnglish.guide/REQUESTNOTIFY	46
1.127	TDSEnglish.guide/REQUESTNUMBER	46
1.128	TDSEnglish.guide/REQUESTRESPONSE	47
1.129	TDSEnglish.guide/REQUESTSTRING	47
1.130	TDSEnglish.guide/REVEAL	47
1.131	TDSEnglish.guide/RUN	47
1.132	TDSEnglish.guide/RX	48
1.133	TDSEnglish.guide/SAVE	48
1.134	TDSEnglish.guide/SAVEAS	48
1.135	TDSEnglish.guide/SET	49
1.136	TDSEnglish.guide/SETBOOKMARK	49
1.137	TDSEnglish.guide/SETTINGS	49
1.138	TDSEnglish.guide/SPLITLINE	49
1.139	TDSEnglish.guide/STOP	50
1.140	TDSEnglish.guide/TEXT	50
1.141	TDSEnglish.guide/UNDO	50
1.142	TDSEnglish.guide/UPPERCASE	50
1.143	TDSEnglish.guide/TMake	51
1.144	TDSEnglish.guide/TRefs	51
1.145	TDSEnglish.guide/Registration	52
1.146	TDSEnglish.guide/Enhancements	53
1.147	TDSEnglish.guide/Special Thanks	54
1.148	TDSEnglish.guide/Copyright	54

Chapter 1

TDSEnglish

1.1 TDSEnglish.guide

Twilight Development System (TDS) 2.04

This document describes the 'Twilight Development System (TDS)', an integrated programming environment for the Amiga.

Introduction

What is 'TDS' ?

Requirements

What hardware and software do you need ?

Installation

How to install the software ?

Version

Twilight Editor

Twilight Make

Twilight Reference Generator

Registration

How to get the full version ?

Enhancements

Special Thanks

Copyright

1.2 TDSEnglish.guide/Introduction

Introduction

Twilight Development System 'TDS' provides an integrated environment for writing and compiling source files like Turbo Pascal or Borland C/C++. The main program of the package is a powerful text editor called Twilight Editor (

Ted

) which includes an integrated project manager.

This project manager simplifies and speeds up the development of programs composed of different source files (modules). With 'TDS' it's possible to compile and link these modules into an executable file with a single command and if the compiler finds some errors, they will be reported directly by the editor. 'TDS' doesn't provide its own compiler, but can use any compiler or assembler callable from Shell. It can interface directly with many common compilers and assemblers like DICE C, SAS C, Lattice C, Aztec C, DevPac, A68k, PCQ, HCC, GNU-C, Amiga-E, Oberon and even programs like TeX, CatComp and MakeInfo. If the compiler is not supported, it's possible to write a little interface program to convert the error messages in a format readable by the editor. The compile process will be executed concurrently using another program called Twilight Make (

TMake

), so the user can continue

to edit the source files while the compiler is working.

Twilight Editor (

Ted

) has many functions to support the creating and editing of source files. The number of files which can be open at the same time is limited only by the amount of free memory and so is the length of a single text file and line. For every file

Ted

remembers

every change done and allows with the commands

Undo

and

Redo

to go back

through the changes. It also supports many commands to handle horizontal and vertical blocks (like

Cut

,

Copy

,

Paste

,

Indent

) and to

search for strings in the file. It's also possible to change the keyboard bindings, if you don't like the default mapping.

1.3 TDSEnglish.guide/Requirements

Requirements

Twilight Development System 'TDS' runs on any Amiga with Kickstart 2.04 (V37) and greater. If present, it will use the 'locale.library' to support localization. It can also use the 'reqtools.library' V38 by Nico François (Thanks Nico for your wonderful work), but the library is not required to run the software.

1.4 TDSEnglish.guide/Installation

Installation

To install 'TDS' you can use the 'Installer' program from Commodore. To start the installation process simply double-click the icon called 'Install TDS' and follow the instructions. The installation script will modify your 'user-startup' to include an assignment to the directory containing the programs which will be called 'TDS:'. You have also the choice to install some example project files which will help you in building your own project files.

If you don't have the 'Installer' program, then you can manually install the software creating a directory and copying there all files. Finally add an 'assign TDS: <your directory>' to the 'user-startup'.

1.5 TDSEnglish.guide/Version

Version

This version of the software has been greatly enhanced. From version 1.90 on it will run only with Kickstart 2.04 and greater. The format of the project files has been changed.

Ted

can still load projects in the old format, but it saves them only in the new format, so you can't use the new project files with older versions of 'TDS'. The ARexx command set has also been greatly modified and enhanced (to adhere to the standard as described in the 'Amiga User Interface Style Guide'), so any ARexx macro written for

Ted

has to be corrected.

As I use a plain Amiga 1200 to develop the program, I can't use the Enforcer utility (which requires a MMU). So I will greatly appreciate any bug reports and list of Enforcer hits. Criticism and suggestions are always welcome, too.

This software is available now in 3 languages: English (built-in), German and Italian (soon in Spanish, too). If someone wishes to translate the software into another language, he/she can find the necessary catalog description files in the directory 'catalogs/source'.

1.6 TDSEnglish.guide/Ted

Twilight Editor (Ted)

This is the main program of the package. It can be run from either the Workbench or the Shell. When running on the Workbench screen 'Ted' will open its windows as AppWindows which means that if you want to open a file, just drop its icon into one of the windows and the file will be loaded.

Workbench Usage

Shell Usage

Menu File

Menu Edit

Menu Search

Menu Compile

Menu Project

Menu Settings

ARexx Commands

1.7 TDSEnglish.guide/Ted Workbench

Workbench Usage

=====

To start 'Ted' just double-click on its icon. 'Ted' supports multiple icon selection on startup to automatically open the selected files.

'Ted' supports the following tooltypes:

'STARTUP'

ARexx script to execute on startup

'PUBSCREEN'
name of the public screen to use

'FONTNAME'
name of the font to use

'FONTSIZE'
height of the font to use

'CX_POPKEY'
hotkey to access the commodity

'CX_PRIORITY'
priority of the editor

'ICONIFY'
starts the editor in iconified mode

1.8 TDSEnglish.guide/Ted Shell

Shell Usage

=====

Usage: Ted FILE/M,PROJECT/K,STARTUP/K

'FILE/M'
list of text files to load

'PROJECT/K'
project file to load

'STARTUP/K'
ARexx script to execute on startup

There is also a little program called 'Ed' which acts as a frontend to 'Ted'. 'Ed' will try to find a running version of the editor and open the file on it, otherwise it will start a new copy of the editor.

Usage: Ed FILE/M,PROJECT/K

1.9 TDSEnglish.guide/Menu File

Menu File

=====

This menu contains the commands to open, insert, save and close the source files and to hide and reveal the windows. The number of windows which can be open at the same time depends only from the amount of free

memory.

New
Open
Load
Insert
Save
Save As
Save Changed
Delete
Current Dir
Hide
Reveal
Protect
About
Iconify
Quit

1.10 TDSEnglish.guide/File-New

File/New

Opens a new window and creates an empty file.

1.11 TDSEnglish.guide/File-Open

File/Open

Opens a new window and loads a file. Using the SHIFT key the user can select more the one file to open.

1.12 TDSEnglish.guide/File-Load

File/Load

Loads a file in the current window.

1.13 TDSEnglish.guide/File-Insert

File/Insert

Inserts a file in the current window at the cursor position.

1.14 TDSEnglish.guide/File-Save

File/Save

Saves the file with the current name.

1.15 TDSEnglish.guide/File-Save As

File/Save As

Saves the file with a new name.

1.16 TDSEnglish.guide/File-Save Changed

File/Save Changed

Saves all files which have been modified.

1.17 TDSEnglish.guide/File-Delete

File/Delete

Deletes a file (asking for confirmation).

1.18 TDSEnglish.guide/File-Current Dir

File/Current Dir

Changes the current directory.

1.19 TDSEnglish.guide/File-Hide

File/Hide

Hides the current window, but the contents of the file remains in memory. If it was the last window, iconifies the program (See Iconify).

1.20 TDSEnglish.guide/File-Reveal

File/Reveal

Opens a requester listing all the files currently in memory including those hidden. With this requester you can select the file that you want to edit or to reveal a file which has been hidden.

1.21 TDSEnglish.guide/File-Protect

File/Protect

Opens a requester with the comment and protection bits of the current file. Use the gadgets to set the protection bits and the comment.

1.22 TDSEnglish.guide/File-About

File/About

Displays some information about the program and the amount of free memory. If you have the keyfile, it should display your name, otherwise it states that you are using the "Unregistered demo release".

1.23 TDSEnglish.guide/File-Iconify

File/Iconify

Use this command to iconify

Ted

. It closes all windows and the screen, but all files remain still in memory. On the workbench screen appears an application icon. Clicking on this icon will bring back the editor.

Ted

also installs itself as a commodity and can be awaked with the 'Exchange' tool or the hotkey. The hotkey can be set either with the tooltype entry CX_POPKEY or using the

Editor

requester.

1.24 TDSEnglish.guide/File-Quit

File/Quit

Quits the program.

1.25 TDSEnglish.guide/Menu Edit

Menu Edit
=====

This menu contains all the commands necessary to handle selected portions of the file (blocks). The blocks can be of 2 types: horizontal and vertical. To select a horizontal block simply position the mouse pointer at the start of the block and click the left mouse button, then drag the mouse with the left button pressed to the end of the block and finally release the button. Double clicking the left button selects the

word at the mouse pointer, while holding down also the Shift key will select all the line. To select a vertical block hold down the Alt key while selecting it. It's also possible to select a block with the

Mark
or
Mark Vertical
and using the cursor keys.

Mark
Mark Vertical
Mark All
Cut
Copy
Paste
Paste Vertical
Erase
Save
Indent
Change To
Format
Undo
Redo

1.26 TDSEnglish.guide/Edit-Mark

Edit/Mark

Selects a block using the cursor keys.

1.27 TDSEnglish.guide/Edit-Mark Vertical

Edit/Mark Vertical

Selects a vertical block using the cursor keys.

1.28 TDSEnglish.guide/Edit-Mark All

Edit/Mark All

Selects the entire file.

1.29 TDSEnglish.guide/Edit-Cut

Edit/Cut

Cuts the block and copies it into the clipboard.

1.30 TDSEnglish.guide/Edit-Copy

Edit/Copy

Copies the block into the clipboard without modifying the file.

1.31 TDSEnglish.guide/Edit-Paste

Edit/Paste

If there is a block selected then it will be replaced with the contents of the clipboard, otherwise the contents of the clipboard will be inserted at the position of the cursor.

1.32 TDSEnglish.guide/Edit-Paste Vertical

Edit/Paste Vertical

Inserts a block as a column.

1.33 TDSEnglish.guide/Edit-Erase

Edit/Erase

Erases the block without copying it into the clipboard.

1.34 TDSEnglish.guide/Edit-Save

Edit/Save

Saves the block as a file to the disk.

1.35 TDSEnglish.guide/Edit-Indent

Edit/Indent

has a submenu with 2 options:

`Forward'

Moves the block one position to the right.

`Backward'

Moves the block one position to the left.

1.36 TDSEnglish.guide/Edit-Change To

Edit/Change To

has a submenu with 3 options. If there is no block selected, then these commands will change the word at the cursor.

`Upper Case'

Changes the block or the current word to upper case.

`Lower Case'

Changes the block or the current word to lower case.

`First Capital'

Changes every word in the block or the current word to have the first letter in upper case and the rest in lower case.

1.37 TDSEnglish.guide/Edit-Format

Edit/Format

Reformats a portion of text called a paragraph. The paragraph starts at the cursor and ends with the first blank line. The margins of the paragraph can be set with the 'Left Margin' and 'Right Margin' gadgets of the

Editor
requester.

1.38 TDSEnglish.guide/Edit-Undo

Edit/Undo

Use this command to step backward through the changes done to the file.

Ted
remembers for each file a maximum number of changes which can be modified with the
Editor
requester.

1.39 TDSEnglish.guide/Edit-Redo

Edit/Redo

Use this command to step forward through the changes done to the file.

Ted
remembers for each file a maximum number of changes which can be modified with the
Editor
requester.

1.40 TDSEnglish.guide/Menu Search

Menu Search

=====

This menu contains the commands for finding and replacing strings in the file, for jumping to a specified line, for finding the bracket which matches the one at the cursor and to get information about a particular keyword. It also has commands to set and recall bookmarks.

```
Find
Replace
Next
Previous
Set Bookmark
Goto Bookmark
Goto Line
Match Bracket
Find Reference
```

1.41 TDSEnglish.guide/Search-Find

Search/Find

Open a requester to enter the string to search for and with the following search options:

`'Case Sensitive'`

Distinguishes between upper and lower case.

`'Words Only'`

Finds only strings surrounded by spaces.

`'Wildcards'`

Uses `'?'` as a wildcard which matches any character.

e.g. `'t??t'` matches `'test'`, `'that'`, etc.

1.42 TDSEnglish.guide/Search-Replace

Search/Replace

Open a requester to enter the string to search for, the string to replace and the search options (See

```
Find
).
```

1.43 TDSEnglish.guide/Search-Next

```
Search/Next
-----
```

```
Repeat the last command (
    Find
    or
    Replace
) finding the next
occurrence.
```

1.44 TDSEnglish.guide/Search-Previous

```
Search/Previous
-----
```

```
Repeat the last command (
    Find
    or
    Replace
) finding the previous
occurrence.
```

1.45 TDSEnglish.guide/Search-Set Bookmark

```
Search/Set Bookmark
-----
```

```
Set a bookmark at position of the cursor.
```

1.46 TDSEnglish.guide/Search-Goto Bookmark

```
Search/Goto Bookmark
-----
```

```
Open a requester with all bookmarks set. To recall the selected
```

bookmark use the 'Goto' button, to delete it use the 'Delete' button.

1.47 TDSEnglish.guide/Search-Goto Line

Search/Goto Line

Open a requester with the line number to jump.

1.48 TDSEnglish.guide/Search-Match Bracket

Search/Match Bracket

Find the matching bracket to the bracket at the cursor.
e.g. '(' matches ')'

1.49 TDSEnglish.guide/Search-Find Reference

Search/Find Reference

Search the word at the cursor in the reference files and if it exists, load the file it references and moves the cursor to the line in which it has been defined. The reference files can be set with the

References
requester. The format of a reference file is described in

TRefs
.

1.50 TDSEnglish.guide/Menu Compile

Menu Compile
=====

This menu contains the commands to compile source files, to build an entire executable program and to run and debug it. All the commands use the project file defined with the commands of the

Project
menu.

The commands

- Compile
- ,
- Build
- and
- Build All

are not built into the editor, but their execution is demanded to TMake . When one of these commands has been selected, Ted starts TMake which executes the command and if it finds some errors, returns an error list to Ted . Using the multitasking facilities of the operating system TMake runs in background, so you can continue to edit your source files. Also these commands open a console window where it's possible to follow the compiling process and to interrupt it with Ctrl-C. This feature can be disabled with the 'No TMake Window' option of the Options requester.

- Compile
- Build
- Build All
- Stop
- Run
- Debug
- Next Error
- Previous Error
- Load Errors

1.51 TDSEnglish.guide/Compile-Compile

Compile/Compile

Compiles the source file in the current window.

1.52 TDSEnglish.guide/Compile-Build

Compile/Build

Builds the executable file compiling only the source files which has been modified.

1.53 TDSEnglish.guide/Compile-Build All

Compile/Build All

Builds the executable file compiling all the source files even if they have not been modified.

1.54 TDSEnglish.guide/Compile-Stop

Compile/Stop

Stops

TMake
. Useful when the 'No TMake Window' option is active and
you can't use CTRL-C to stop
TMake
.

1.55 TDSEnglish.guide/Compile-Run

Compile/Run

Runs the executable file.

1.56 TDSEnglish.guide/Compile-Debug

Compile/Debug

Runs the debugger.

1.57 TDSEnglish.guide/Compile-Next Error

Compile/Next Error

If

TMake

has reported some errors, use this command to find the next error in the error list.

1.58 TDSEnglish.guide/Compile-Previous Error

Compile/Previous Error

If

TMake

has reported some errors, use this command to find the previous error in the error list.

1.59 TDSEnglish.guide/Compile-Load Errors

Compile/Load Errors

Loads the error file as it has been created by the compiler or the linker.

1.60 TDSEnglish.guide/Menu Project

Menu Project
=====

This menu contains all the commands necessary to create, open and

save project files. The project file contains the names of the source files (modules) of the program, the options for the translators (compiler, assembler, etc.), linker and debugger and the work directories. Once you have created a project, you can use the commands

```
Compile
,
Build
and
Build All
to compile a single source file or to
rebuild the entire executable file.
```

```
New
Open
Save
Save As
Close
Translators
Linker
Debugger
Command
Modules
Options
```

1.61 TDSEnglish.guide/Project-New

Project/New

Creates a new project.

1.62 TDSEnglish.guide/Project-Open

Project/Open

Opens an existing project.

1.63 TDSEnglish.guide/Project-Save

Project/Save

Saves the project with the current name.

1.64 TDSEnglish.guide/Project-Save As

Project/Save As

Saves the project with a new name (the project file extension must be ``.prj'`).

1.65 TDSEnglish.guide/Project-Close

Project/Close

Closes the current project.

1.66 TDSEnglish.guide/Project-Translators

Project/Translators

Opens a requester which defines the translators used by the project. A translator is a compiler, assembler or any other program which `'translates'` a source file into an object file. When

 TMake

 tries to

compile a source file, it searches through the list of translators to find a source extension matching the extension of the source file. Once a source file has been compiled into an object file, the extension of the object file will be compared with object extension used by the linker. If the match fails, the object file becomes a source file and the iteration restarts at the search for a translator. This way you can use a compiler, which compiles a source file into an assembler file, then this assembler file will be translated by the assembler and finally linked by the linker.

Using the buttons 'Add', 'Delete', 'Edit', '+', '-', you can add, delete, modify and reorder the translators. To modify a translator use the 'Edit' button or double-click on the name of the translator. This will open the 'Translator' requester.

'Name'

Name of the translator.

'Command'

Command of the translator.
e.g. "sc" (for SAS C)

'Debug Opt.'

'Final Opt.'

'Debug Opt.' are the options used if the 'Use Debug Options' is set in the

Options

requester, otherwise 'Final Opt.' will be used.

The following strings have a special meaning:

'%src'

Name of the source file.

'%mod'

Name of the source file without extension.

'%base'

Name of the source file without extension and path.

'%obj'

Name of the object file.

'%opt'

Local options of the source file.

'%err'

Name of the error file (if not present, then the standard output will be used).

e.g.

'"-d -o%obj %src" and the source file "text.c"' becomes
'-d -otext.o text.c'.

'Source Ext.'

File extension of the source files.

'Object Ext.'

File extension of the object files.

'Object Dir.'

Directory of the object files.

'Ignore Warnings'

If set, ignores all warning messages.

'Check Headers'

Option used only for C source files: if set
 TMake
 checks for every
 source file if an include file has been modified. If so, it
 compiles the source file. The checking will be done only for
 include files in this format:

```
`#include "....."'
```

and not for:

```
`#include <.....>'
```

'Single Pass'

If set,

TMake

will use only one translator on the source file, and
 will not check if the object file has the extension required by
 the linker.

'Select Converter'

'Converter'

Use these gadgets to select the converter program for the
 compiler/assembler. The purpose of the converter is to translate
 the error messages coming from the compiler/assembler into a format
 readable by the editor. The list gadget displays all converters
 which are available in the directory 'TDS:converters'. If you want
 to use a compiler which doesn't have a converter, you can easily
 write your own one. All the converter has to do is to read from
 standard input the output of the compiler and to write to standard
 output the error messages with the following format:

```
MyConverter <compiler_error_file >ted_error_file source_file
```

```
'<test.c> 10 2 E <Error Message>' for an error  
'<test.c> 21 5 W <Error Message>' for a warning
```

where

```
<test.c>          : source file  
10                : row  
2                 : optional column  
E or W           : error or warning  
<Error Message> : error message
```

The converter program also receives the name of the source file as
 the first argument on the command line which sometimes is very
 helpful if the compiler didn't write the name of the source file
 in the error messages.

1.67 TDSEnglish.guide/Project-Linker

Project/Linker

Opens the requester with the options for the linker:

``Command'`

Command of the linker.
e.g. "slink" (for SAS C)

``Debug Opt.'`

``Final Opt.'`

``Debug Opt.'` are the options used if the ``Use Debug Options'` is set in the

Options requester, otherwise ``Final Opt.'` will be used.

The following strings have a special meaning:

``%obj'`

Names of the object files.

``%lnk'`

Name of the file containing the names of the object files.

``%lib'`

Names of the link libraries specified with the ``Libraries'` gadget.

``%exe'`

Name of the executable file.

``%err'`

Name of the error file (if not present, then standard output will be used).

e.g.

```
`FROM lib:c.o %obj TO %exe LIB %lib'
```

where

```
`test.o' and `sub.o' are the object files
```

```
`lib:lc.lib' and `lib:amiga.lib' are the libraries
```

```
`test' is the executable file
```

becomes

```
`FROM lib:c.o test.o sub.o TO test LIB lib:lc.lib lib:amiga.lib'
```

``Object Ext.'`

File extension of the object files.

``Libraries'`

List of link libraries. Use the ``Add'`, ``Delete'`, ``+'`, ``-'` buttons to add, delete and reorder the libraries files.

1.68 TDSEnglish.guide/Project-Debugger

Project/Debugger

Opens the requester with the options for the debugger:

``Command'`

Command name of the debugger.
e.g. "cpr" (for SAS C)

``Options'`

Command options for the debugger.

The following strings have a special meaning:

``%exe'`

Name of the executable file.

``%arg'`

Arguments line set with the
Options
requester.

``%src'`

Name of the current source file.

``%mod'`

Name of the current source file without extension.

``%base'`

Name of the current source file without extension and path.

``%screen'`

Name of the public screen used by the editor.

These options are very useful if you use the Amiga-E or TeX compilers. Therefore you can have more than one source file per project and run or display only the current one (see the example project files).

1.69 TDSEnglish.guide/Project-Command

Project/Command

Opens the requester with the options for the execution of the commands:

``Command Path'`

List of directories where to search the commands. If the list is empty, then the current path will be used.

``Stacksize'`

Stack size used by the commands.

``Window'`

Name of the console window used by the commands.

1.70 TDSEnglish.guide/Project-Modules

Project/Modules

Opens a requester with the list of the source files and precompiled object files. Use the 'Add', 'Delete', '+', '-' buttons to add, delete and reorder the source files. Use the 'Edit' button to set the local options for the module, while the 'Load' button will load the module into the editor.

1.71 TDSEnglish.guide/Project-Options

Project/Options

Opens a requester with the options for project:

'Program Name'

Name of the executable file.

The following strings have a special meaning:

'%src'

Name of the current source file.

'%mod'

Name of the current source file without extension.

'%base'

Name of the current source file without extension and path.

These options are very useful if you use the Amiga-E or TeX compilers. Therefore you can have more than one source file per project and run or display only the current one (see the example project files).

'Program Arguments'

Arguments line for the program (used by
Run
and
Debug
).

The following strings have a special meaning:

'%src'

Name of the current source file.

'%mod'

Name of the current source file without extension.

'%base'

Name of the current source file without extension and path.

'%screen'

Name of the the public screen used by the editor.

These options are very useful if you use the Amiga-E or TeX compilers. Therefore you can have more than one source file per project and run or display only the current one (see the example project files).

'Window'

Name of the console window used by the program, will be opened only if the 'Open Window' option is set.

'Source Directories'

List of directories where to search source and include files if an error has been found. Use the 'Add' and 'Delete' buttons to add and delete items from the list.

'Use Debug Options'

If set, the commands will use the debug options, otherwise the final options.

'No Linker'

If set,

TMake

will not call the linker (e.g. Amiga-E doesn't use a linker).

'No Requester'

If set,

TMake

will not display a requester after a file has been compiled or a project has been completed. Errors will always be reported.

'No TMake Window'

If set,

TMake

will not open a console window while working. Use the

Stop

command to interrupt it.

'Open Window'

If set,

Ted

will open a console window for the

Run

and

Debug

commands.

```
`Auto Open'
  If set,
      Ted
      will open all modules loaded the last time the project
      has been saved or closed.
```

1.72 TDSEnglish.guide/Menu Settings

Menu Settings

=====

This menu contains the commands to modify the settings of the program and to load and save them.

AutoIndent
WordWrap
OverStrike
Create Icons?
Editor
Display
Keyboard
References
Load Settings
Save Settings
Save Settings As

1.73 TDSEnglish.guide/Settings-AutoIndent

Settings/AutoIndent

Activates the automatic indentation.

1.74 TDSEnglish.guide/Settings-WordWrap

Settings/WordWrap

Activates the automatic wordwrap at the end of a line.

1.75 TDSEnglish.guide/Settings-OverStrike

Settings/OverStrike

Activates the overstrike mode.

1.76 TDSEnglish.guide/Settings-Create Icons?

Settings/Create Icons?

If set,

Ted

will create an icon for every file saved. Moreover it uses the ``.info'` files to store the position and size of the window and the last position of the cursor. The ``.info'` file used depends on the extension of the file to be saved.

Ted

will try to use a file called ``ENV:TDS/def_XXX.info'` or ``ENV:SYS/def_XXX.info'` where XXX is the extension of the file. So if you save a file called ``mydoc.txt'` which doesn't have an icon,

Ted

will try to add an ``.info'` file called ``ENV:TDS/def_TXT.info'` or ``ENV:SYS/def_TXT.info'`. There are already some icon files in the ``ENV:TDS'` directory, but you can add your own files or change the existing one if you don't like them.

1.77 TDSEnglish.guide/Settings-Editor

Settings/Editor

Opens a requester with the options for the editor:

``Requester'`

Defines the type of requester to use: ``ASL'` or ``ReqTools'`. If the

'reftools.library' is not installed, then it will always use the 'asl.library'.

'Tabwidth'

Sets the width of the tab.

'Left Margin'

'Right Margin'

Sets the left and right margin (used by
WordWrap
and
Format
).

'Max. Changes'

Sets the maximum number of changes recorded for every file.

'Autosave Delay'

Sets the time for the autosave mode in minutes.

'Priority'

Sets the priority of the editor.

'AutoIndent'

Activates the automatic indentation.

'WordWrap'

Activates the automatic wordwrap at the end of a line.

'OverStrike'

Activates the overstrike mode.

'WrapCursor'

Defines the behaviour of the cursor at the end of the line. If set, then the cursor will go to the start of the next line, otherwise it will continue to move to the right on the same line.

'Stripblanks'

Removes any blanks and tabs from the end of the line which has been modified.

'Autosave'

Activates the autosave mode.

'Backup'

Creates a backup file called '#?.bak' in the directory specified with 'Backup Dir' for every file saved.

'Backup Dir'

Sets the directory to use for backups. If no directory is specified then the backup file will be created in the same directory of the original file. Using a directory on the same volume of the original file is faster than using one on a different volume. In the first case the program has only to rename the file, whereas in the second case it has to copy the file.

'Guide'

Defines the guide to use for the on-line help.

'Hotkey'

Defines the hotkey used to deiconify
Ted
.

1.78 TDSEnglish.guide/Settings-Display

Settings/Display

Opens a requester with the options for the screen:

'Screen'

Selects the screen mode for the custom screen.

'Font'

Selects the font used to display the text files.

'Public Screen'

Defines the public screen used by
Ted
.

'Window Left'

'Window Top'

'Window Width'

'Window Height'

Sets the position and size of the first window and for any following window if 'Autosize' is not set. With 'Window Width' = 0 the window will open at the maximum width allowed, with 'Window Height' = 0 at the maximum height.

'Type'

Defines the type of screen used by
Ted
.

'Edit Palette'

Brings up a requester to modify the colours of the screen. This feature is available only if
Ted
is running on its own screen and the 'reqtools.library' is installed.

'Autosize'

If set, every new window will inherit the position and size of the current window.

'Hide Pointer'

If set, hides the mouse pointer while typing.

1.79 TDSEnglish.guide/Settings-Keyboard

Settings/Keyboard

Opens a requester with the list of all key bindings. Use the 'Add', 'Delete' and 'Edit' buttons to add, delete and edit them.

This requester describes the binding of a key to a command. The command can be of 3 types: 'Internal', 'ARexx Macro', 'AmigaDos'. If you want to define an internal command, you can choose it from the gadget 'Internal Commands'.

Here comes a list of the predefined bindings:

Binding	Command
Back	BACKSPACE
Delete	DELETE CHAR
Enter	SPLITLINE
Return	SPLITLINE
Ctrl-y	DELETE LINE
Ctrl-u	UNDO LINE
Ctrl-q	DELETE EOL
Ctrl-m	FIND BRACKET
Ctrl-h	HIDE
Ctrl-r	REVEAL
Ctrl-f	FORMAT
Ctrl-l	LOWERCASE
Ctrl-k	UPPERCASE
Ctrl-x	GOTOBOOKMARK
Ctrl-b	SETBOOKMARK
Left	CURSOR LEFT
Right	CURSOR RIGHT
Up	CURSOR UP
Down	CURSOR DOWN
Shift-Left	PREVIOUS WORD
Shift-Right	NEXT WORD
Shift-Up	PREVIOUS PAGE
Shift-Down	NEXT PAGE
Ctrl-Left	POSITION SOL
Ctrl-Right	POSITION EOL
Ctrl-Up	POSITION SOF
Ctrl-Down	POSITION EOF
F1	PREVIOUS FILE
F2	NEXT FILE
F10	ICONIFY
Shift-Help	FIND REFS

1.80 TDSEnglish.guide/Settings-References

Settings/References

Opens a requester with the list of the reference files. Use the 'Add', 'Delete' 'Edit', '+' and '-' buttons to add, delete, edit and rearrange the files.

1.81 TDSEnglish.guide/Settings-Load Settings

Settings/Load Settings

Loads the settings.

1.82 TDSEnglish.guide/Settings-Save Settings

Settings/Save Settings

Saves the settings with the current name.

1.83 TDSEnglish.guide/Settings-Save Settings As

Settings/Save Settings As

Saves the settings with a new name.

1.84 TDSEnglish.guide/ARexx Commands

ARexx Commands
=====

This is the list of the ARexx commands available:

ABOUT

BACKSPACE

BUILD

CLOSE

CMDSHELL

COMPILE

COPY

CURSOR

CUT

DEBUG

DELETE

DIR

ERASE

FIND

FIRSTCAPITAL

FORMAT

GOTOBOOKMARK

GOTOCOLUMN

GOTOFILE

GOTOLINE

HIDE

ICONIFY

INDENT

INSERT

KEYBOARD

LOAD

LOWERCASE

MARK

NEW

NEXT

OPEN

PASTE

POSITION

PREVIOUS

PROJECT

PROTECT

QUERY

QUIT

REDO

REPLACE

REQUESTFILE

REQUESTNOTIFY

REQUESTNUMBER

REQUESTRESPONSE

REQUESTSTRING

REVEAL

RUN

RX

SAVE

SAVEAS

SET

SETBOOKMARK

SETTINGS

SPLITLINE

STOP

TEXT

UNDO

UPPERCASE

1.85 TDSEnglish.guide/ABOUT

ABOUT

Command	Options	Description
-----	-----	-----
ABOUT	<no option>	open the 'About' requester

1.86 TDSEnglish.guide/BACKSPACE

BACKSPACE

Command	Options	Description
-----	-----	-----
BACKSPACE	<no option>	delete the character to the left of the cursor

1.87 TDSEnglish.guide/BUILD

BUILD

Command	Options	Description
-----	-----	-----
BUILD	<no option> ALL/S	rebuild the project recompile all modules even if they have not been modified

1.88 TDSEnglish.guide/CLOSE

CLOSE

Command	Options	Description
-----	-----	-----
CLOSE	FILE/S PROJECT/S	close the current file close the project

1.89 TDSEnglish.guide/CMDSHELL

CMLSHELL

Command	Options	Description
CMLSHELL	<no option>	open the ARexx command shell

1.90 TDSEnglish.guide/COMPILE

COMPILE

Command	Options	Description
COMPILE	<no option> NAME/K	compile the current file compile the specified file (STRING)

1.91 TDSEnglish.guide/COPY

COPY

Command	Options	Description
COPY	<no option>	copy the selected block to the clipboard

1.92 TDSEnglish.guide/CURSOR

CURSOR

Command	Options	Description
CURSOR	UP/S	move the cursor up one position
	DOWN/S	move the cursor down one position
	LEFT/S	move the cursor left one position
	RIGHT/S	move the cursor right one position

1.93 TDSEnglish.guide/CUT

CUT

Command	Options	Description
CUT	<no option>	remove the selected block and copy it to the clipboard

1.94 TDSEnglish.guide/DEBUG

DEBUG

Command	Options	Description
DEBUG	<no option>	start the debugger

1.95 TDSEnglish.guide/DELETE

DELETE

Command	Options	Description
DELETE	CHAR/S	delete the character to the right of the cursor
	LINE/S	delete the current line
	EOL/S	delete all characters to the end of the current line
	FILE/S	delete a file
	NAME/K	name of the file to delete (STRING)

1.96 TDSEnglish.guide/DIR

DIR

Command	Options	Description
DIR	PATH	change the current directory path
	ASK/S	open the 'Current Dir' requester

1.97 TDSEnglish.guide/ERASE

ERASE

Command	Options	Description
ERASE	<no option>	remove the selected block without copying it to the clipboard

1.98 TDSEnglish.guide/FIND

FIND

Command	Options	Description
FIND	STRING/K NEXT/S PREVIOUS/S BRACKET/S REFS/S	string to search for (STRING) find next occurrence find previous occurrence find matching bracket find reference of the current word

1.99 TDSEnglish.guide/FIRSTCAPITAL

FIRSTCAPITAL

Command	Options	Description
FIRSTCAPITAL	<no option>	convert the current word or block to first capital

1.100 TDSEnglish.guide/FORMAT

FORMAT

Command	Options	Description
FORMAT	<no option>	format a paragraph starting at the current line

1.101 TDSEnglish.guide/GOTOBOOKMARK

GOTOBOOKMARK

Command	Options	Description
GOTOBOOKMARK	<no option>	open the 'Goto Bookmark' requester

1.102 TDSEnglish.guide/GOTOCOLUMN

GOTOCOLUMN

Command	Options	Description
GOTOCOLUMN	COL/N/A	go to the specified column

1.103 TDSEnglish.guide/GOTOFILE

GOTOFILE

Command	Options	Description
GOTOFILE	NAME/A	go to the specified file (if the file is not in memory, it will be opened)

1.104 TDSEnglish.guide/GOTOLINE

GOTOLINE

Command	Options	Description
GOTOLINE	<no option> LINE/N	open the 'Goto Line' requester go to the specified line

1.105 TDSEnglish.guide/HIDE

HIDE

Command	Options	Description
HIDE	<no option>	hide the current file

1.106 TDSEnglish.guide/ICONIFY

ICONIFY

Command	Options	Description
ICONIFY	<no option>	iconify the program

1.107 TDSEnglish.guide/INDENT

INDENT

Command	Options	Description
INDENT	FORWARD/S	indent the selected block one position to the right
	BACKWARD/S	indent the selected block one position to the left

1.108 TDSEnglish.guide/INSERT

INSERT

Command	Options	Description
INSERT	NAME/K	insert the specified file into the current file

1.109 TDSEnglish.guide/KEYBOARD

KEYBOARD

Command	Options	Description
KEYBOARD	KEY/A CMD/F	key to map the ARexx command to ARexx command

The format for the key is:

[Ctrl-][Alt-][Shift-]<letter>

where letter is either a single character or one of:

LEFT, RIGHT, DOWN, UP, BACK, DELETE, ENTER, ESC, F1-F10, HELP, TAB

1.110 TDSEnglish.guide/LOAD

LOAD

Command	Options	Description
LOAD	FILE/S SETTINGS/S ERRORS/S NAME/K	load the file load the settings load the error file name of file or settings to load

1.111 TDSEnglish.guide/LOWERCASE

LOWERCASE

Command	Options	Description
LOWERCASE		convert the current word or block to lowercase

1.112 TDSEnglish.guide/MARK

MARK

Command	Options	Description
MARK	WORD/S	select the current word

LINE/S	select the current line
VERTICAL/S	start and stop the selection of a vertical block using the cursor
BLOCK/S	start and stop the selection of a horizontal block using the cursor
ALL/S	select the entire file

1.113 TDSEnglish.guide/NEW

NEW

Command	Options	Description
NEW	FILE/S	creates an empty file
	PROJECT/S	creates an empty project

1.114 TDSEnglish.guide/NEXT

NEXT

Command	Options	Description
NEXT	WORD/S	go to the next word
	PAGE/S	go to the next page
	FILE/S	go to the next file
	ERROR/S	go to the next error

1.115 TDSEnglish.guide/OPEN

OPEN

Command	Options	Description
OPEN	FILE/S	open a file
	PROJECT/S	open a project
	NAME/K	name of the file or project to open

1.116 TDSEnglish.guide/PASTE

PASTE

Command	Options	Description
PASTE	<no option>	insert the contents of the clipboard into the current file
	VERTICAL/S	insert the contents of the clipboard into the current file as a vertical block

1.117 TDSEnglish.guide/POSITION

POSITION

Command	Options	Description
POSITION	SOF/S	go to the start of the current file
	EOF/S	go to the end of the current file
	SOL/S	go to the start of the current line
	EOL/S	go to the end of the current line

1.118 TDSEnglish.guide/PREVIOUS

PREVIOUS

Command	Options	Description
PREVIOUS	WORD/S	go to the previous word
	PAGE/S	go to the previous page
	FILE/S	go to the previous file
	ERROR/S	go to the previous error

1.119 TDSEnglish.guide/PROJECT

PROJECT

Command	Options	Description
PROJECT	COMMAND/S	open the 'Command' requester
	DEBUGGER/S	open the 'Debugger' requester
	LINKER/S	open the 'Linker' requester
	MODULES/S	open the 'Modules' requester

OPTIONS/S	open the 'Options' requester
TRANSLATORS/S	open the 'Translators' requester

1.120 TDSEnglish.guide/PROTECT

PROTECT

Command	Options	Description
PROTECT	<no option>	open the 'Protect' requester

1.121 TDSEnglish.guide/QUERY

QUERY

Command	Options	Description
QUERY	NAME/A	query the value of some internal variable

Name	Result
FILE	name of the current file
ROW	current row
COLUMN	current column
LINES	length of the current file
CURSOR	position of the cursor in the format 'row,col'

1.122 TDSEnglish.guide/QUIT

QUIT

Command	Options	Description
QUIT	<no option>	quits the program

1.123 TDSEnglish.guide/REDO

REDO

Command	Options	Description
REDO	<no option>	redo the last action undone

1.124 TDSEnglish.guide/REPLACE

REPLACE

Command	Options	Description
REPLACE	FIND/K CHANGE/K ALL/S	string to find (STRING) string to replace (STRING) replace all occurrences

1.125 TDSEnglish.guide/REQUESTFILE

REQUESTFILE

Command	Options	Description
REQUESTFILE	TITLE/K PATH/K FILE/K PATTERN/K	open a file requester title (STRING) initial path (STRING) initial file (STRING) initial pattern (STRING)

1.126 TDSEnglish.guide/REQUESTNOTIFY

REQUESTNOTIFY

Command	Options	Description
REQUESTNOTIFY	PROMPT/A	open a notify requester prompt (STRING)

1.127 TDSEnglish.guide/REQUESTNUMBER

REQUESTNUMBER

Command	Options	Description
REQUESTNUMBER	PROMPT/K DEFAULT/K	open a number requester prompt (STRING) default number (INTEGER)

1.128 TDSEnglish.guide/REQUESTRESPONSE

REQUESTRESPONSE

Command	Options	Description
REQUESTRESPONSE	TITLE/K PROMPT/A	open a response requester (`OK`, `Cancel`) title (STRING) prompt (STRING)

1.129 TDSEnglish.guide/REQUESTSTRING

REQUESTSTRING

Command	Options	Description
REQUESTSTRING	PROMPT/K DEFAULT/K	open a string requester prompt (STRING) default string (STRING)

1.130 TDSEnglish.guide/REVEAL

REVEAL

Command	Options	Description
REVEAL	<no option>	open the `Reveal` requester

1.131 TDSEnglish.guide/RUN

RUN

Command	Options	Description
RUN	<no option>	run the program specified in the project

1.132 TDSEnglish.guide/RX

RX

--

Command	Options	Description
RX	COMMAND/A	execute an ARExx command

1.133 TDSEnglish.guide/SAVE

SAVE

Command	Options	Description
SAVE	FILE/S	save the current file
	PROJECT/S	save the current project
	SETTINGS/S	save the current settings
	CHANGED/S	save all files which have been changed

1.134 TDSEnglish.guide/SAVEAS

SAVEAS

Command	Options	Description
SAVEAS	FILE/S	save the current file with a new name
	PROJECT/S	save the current project with a new name
	SETTINGS/S	save the current settings with a new name
	BLOCK/S	save the selected block
	NAME/K	name of file, project, settings or block
(STRING)		

1.135 TDSEngish.guide/SET

SET

Command	Options	Description
SET	NAME/A VALUE/A	set an internal variable value of the variable
Name	Value	
AUTOINDENT	TRUE, FALSE, TOGGLE	
WORDWRAP	TRUE, FALSE, TOGGLE	
OVERSTRIKE	TRUE, FALSE, TOGGLE	
STRIPBLANKS	TRUE, FALSE, TOGGLE	
CREATEICONS	TRUE, FALSE, TOGGLE	
BACKUP	TRUE, FALSE, TOGGLE	
AUTOSAVE	TRUE, FALSE, TOGGLE	

1.136 TDSEngish.guide/SETBOOKMARK

SETBOOKMARK

Command	Options	Description
SETBOOKMARK	<no option>	insert the current position of the cursor in the bookmark list

1.137 TDSEngish.guide/SETTINGS

SETTINGS

Command	Options	Description
SETTINGS	EDITOR/S DISPLAY/S KEYBOARD/S REFS/S	open the 'Editor' requester open the 'Display' requester open the 'Keyboard' requester open the 'References' requester

1.138 TDSEngish.guide/SPLITLINE

SPLITLINE

Command	Options	Description
SPLITLINE	<no option>	splits the current line at the position of the cursor

1.139 TDSEnglish.guide/STOP

STOP

Command	Options	Description
STOP	<no option>	abort the last command sent to 'TMake'

1.140 TDSEnglish.guide/TEXT

TEXT

Command	Options	Description
TEXT (STRING)	STRING/A	insert a string into the current file

1.141 TDSEnglish.guide/UNDO

UNDO

Command	Options	Description
UNDO	<no option> LINE/S	undo the last action insert the last line deleted with the "DELETE LINE" command

1.142 TDSEnglish.guide/UPPERCASE

UPPERCASE

Command	Options	Description
---------	---------	-------------

UPPERCASE

convert the current word or block to
uppercase

1.143 TDSEnglish.guide/TMake

Twilight Make (TMake)

'TMake' is similar to the program 'make' used in the development of programs composed of more than one source file. It checks every source file if it has been modified and depending on the file extension (e.g. '.c' or '.asm') compiles or assembles it. Then it links all the object files together to obtain the executable file. 'TMake' doesn't use 'makefiles', but instead relies on project files created with

Ted

.

It has been designed to interface to the most popular compilers like SAS C, Lattice C, Aztec C, DICE C, PCQ, HCC, GNU-C, Oberon, and assemblers like DevPac, A68k and even programs like TeX, CatComp and MakeInfo. It's also possible to write a custom message converter if the compiler used is not supported. 'TMake' can also be used as a standalone program from Shell or Workbench to build projects created with

Ted

.

Usage: TMake PROJECT,FILE/K,ALL/S,PORTNAME/K,PRI=PRIORITY/K/N

'PROJECT'

name of the project file

'FILE/K'

if given, compiles only a single file

'ALL'

compiles all files, even if they have not been modified

'PORTNAME'

option used by

Ted

to set the name of the message port used by

'TMake'

'PRIORITY'

priority of 'TMake'

1.144 TDSEnglish.guide/TRefs

Twilight Reference Generator (TRefs)

'TRefs' generates reference files used by the Find Reference command. With this command it's possible to get information about a particular keyword, e.g. moving the cursor to the word 'Window' and selecting the Find Reference command will result in the loading of the file 'intuition.h' and the editor positioning the cursor to the start of the definition of the structure 'struct Window'. Currently 'TRefs' can be used to generate reference files from include files '#?.h' and autodocs files '#?.doc'.

Usage: TRefs REFS/K/A,FILES/M/A

'REFS/K/A'
name of reference file to create

'FILES/M/A'
list of files to search

Here comes the format of the reference files for anybody who wants to make his own reference generator:

```
[file]
keyword1=row1
keyword2=row2
...
```

Using 'TRefs' with the file 'intuition.h' generates the following reference file:

```
[intuition/intuition.h]
Menu=61
MenuItem=89
...
TabletHookData=1661
[intuition/intuitionbase.h]
IntuitionBase=66
[intuition/preferences.h]
Preferences=58
[intuition/screens.h]
DrawInfo=66
Screen=133
NewScreen=462
...
```

1.145 TDSEnglish.guide/Registration

Registration

This software is *SHAREWARE* and needs a keyfile to become completely functional. Without the keyfile

Ted

can't open more than 4 files at once and the length of a single file is limited. Moreover the project manager can't handle more than 8 modules per project and the 'About' requester will appear occasionally.

The price for the registration is:

Italy	Lire	30.000.-
Germany	DM	30.-
Other	US\$	20.-

The fastest, cheapest and easiest way to register is put the money together with the filled registration form into a letter and send it to:

Claudio Zani
Via Liuzzi 1
42020 Cadelbosco Sotto (RE)
ITALY

Please, do not send any kind of foreign cheques since the bank charges outrageous fees to change it and it takes a lot of time. If you really feel you must use such cheques, please include extra \$10.

In any case provide me with your name, address, phone number and E-Mail address for filing purposes. You can send this information via electronic mail, if you wish.

Once registered you will receive the newest version with the keyfile which permits you to use any further update of the software. You don't have to pay anything else to get an update. All you have to do is to download the newest version from a BBS or to copy it from a PD-Disk and install the keyfile.

1.146 TDSEnglish.guide/Enhancements

Enhancements

These are some of the features I would like to add to the next versions of the editor:

*Multiple windows per file

Edit the same file in different windows and bring in different views of the file at the same time.

*Folding

This feature gives the user the possibility to hide certain parts of a source file, like structure definitions and functions.

*AutoHighlight

Use boldface, italics and different colours to highlight the syntactical elements of a source file like reserved words, comments, strings and special characters. With a special requester the user can define what words are reserved, how comments start and end, how strings and characters are delimited.

*Message Browser

The message browser should facilitate the locating of the errors and warnings in the source files.

*Multiple Settings

With this feature the user can define the settings for every type of file. So when you edit a C file you have certain options, when editing an ASM file other options, and so on.

*Customizable Menus

Give the user the possibility to build his/her own menu structure.

*MUI Interface

Support for the MagicUserInterface (MUI) by Stefan Stuntz.

1.147 TDSEnglish.guide/Special Thanks

Special Thanks

Special thanks go to Enrico 'Fedro' Federigo for the Italian translation of the documentation and for his many suggestions to improve TDS and to Fredrik Lundström which helped me in finding and eliminating a lot of bugs and Enforcer hits from the programs and giving me many useful suggestions.

I also want to thank all of you who sent me the bug reports and suggestions to make the program better, and many thanks goes to all the registered users.

1.148 TDSEnglish.guide/Copyright

Copyright

All programs and files are Copyright ©1993-94 by

Claudio Zani
Via Liuzzi 1
42020 Cadelbosco Sotto (RE)

ITALY
Tel. 0522/911710
InterNet: zani@cs.unibo.it
FidoNet: Claudio Zani 2:332/516

License

This license applies to the product called "Twilight Development System" (short "TDS"), a collection of programs for the Amiga computer, published by Claudio Zani under the concepts of shareware, and the accompanying documentation. The terms "Program" and "TDS" below, refer to this product. The licensee is addressed as "you".

You may copy and distribute verbatim copies of the program's executable code and documentation as you receive it, in any medium, provided that you conspicuously and appropriately publish only the original, unmodified program, with all copyright notices and disclaimers of warranty intact and including all the accompanying documentation, example files and anything else that came with the original.

Except when otherwise stated in this documentation, you may not copy and/or distribute this program without the accompanying documentation and other additional files that came with the original. You may not copy and/or distribute modified versions of this program.

You may not copy, modify, sublicense, distribute or transfer the program except as expressly provided under this license. Any attempt otherwise to copy, modify, sublicense, distribute or transfer the program is void, and will automatically terminate your rights to use the program under this license. However, parties who have received copies, or rights to use copies, from you under this license will not have their licenses terminated so long as such parties remain in full compliance.

By copying, distributing and/or using the program you indicate your acceptance of this license to do so, and all its terms and conditions.

Each time you redistribute the program, the recipient automatically receives a license from the original licensor to copy, distribute and/or use the program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein.

You may not disassemble, decompile, re-source or otherwise reverse engineer the program.

You agree to cease distributing the program and data involved if requested to do so by the author.

Disclaimer

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDER AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A

PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.