

ImagedeskE

COLLABORATORS

	<i>TITLE :</i> ImagedeskE	
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>
WRITTEN BY		January 19, 2023

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	ImagedeskE	1
1.1	ImagedeskE.guide	1
1.2	ImagedeskE.guide/M1_INTRD	2
1.3	ImagedeskE.guide/M1_REQUI	3
1.4	ImagedeskE.guide/M1_INSTL	3
1.5	ImagedeskE.guide/M1_FASTE	4
1.6	ImagedeskE.guide/M1_TOUSE	6
1.7	ImagedeskE.guide/Starting ImageDesk	6
1.8	ImagedeskE.guide/Configuration	7
1.9	ImagedeskE.guide/System Prefs	8
1.10	ImagedeskE.guide/Viewer Prefs	10
1.11	ImagedeskE.guide/ThumbNail Prefs	12
1.12	ImagedeskE.guide/Menu	13
1.13	ImagedeskE.guide/M2_PROJ	13
1.14	ImagedeskE.guide/M21_OPCAT	14
1.15	ImagedeskE.guide/M21_GNCAT	14
1.16	ImagedeskE.guide/M21_RSING	15
1.17	ImagedeskE.guide/M21_SPATH	15
1.18	ImagedeskE.guide/M21_EXREX	15
1.19	ImagedeskE.guide/M21_ABOUT	15
1.20	ImagedeskE.guide/M21_INFMT	16
1.21	ImagedeskE.guide/M21_QUITP	16
1.22	ImagedeskE.guide/M2_VIEW	16
1.23	ImagedeskE.guide/M22_SFILE	17
1.24	ImagedeskE.guide/M22_PCONT	17
1.25	ImagedeskE.guide/M22_SELEC	17
1.26	ImagedeskE.guide/M2_THUM	17
1.27	ImagedeskE.guide/M23_RMSIN	18
1.28	ImagedeskE.guide/M23_CLEAN	18
1.29	ImagedeskE.guide/M23_MRKDL	18

1.30	ImagedeskE.guide/M2_PREF	18
1.31	ImagedeskE.guide/M24_SPWIN	19
1.32	ImagedeskE.guide/M24_VPWIN	19
1.33	ImagedeskE.guide/M24_TPWIN	19
1.34	ImagedeskE.guide/M24_ABCDK	20
1.35	ImagedeskE.guide/M24_LOADP	20
1.36	ImagedeskE.guide/M24_SAVEP	20
1.37	ImagedeskE.guide/M24_RESET	20
1.38	ImagedeskE.guide/Restrictions	20
1.39	ImagedeskE.guide/Hints on Usage	21
1.40	ImagedeskE.guide/M1_AREXX	23
1.41	ImagedeskE.guide/AREXX1	23
1.42	ImagedeskE.guide/AREXX2	24
1.43	ImagedeskE.guide/AREXX3	25
1.44	ImagedeskE.guide/M3_ABWIN	26
1.45	ImagedeskE.guide/M3_INWIN	27
1.46	ImagedeskE.guide/M3_SPWIN	27
1.47	ImagedeskE.guide/M3_VPWIN	28
1.48	ImagedeskE.guide/M3_TPWIN	28
1.49	ImagedeskE.guide/M3_IDREQ	29
1.50	ImagedeskE.guide/M3_ERMSG	29
1.51	ImagedeskE.guide/M3_CLEAN	30
1.52	ImagedeskE.guide/M3_VWIMG	30
1.53	ImagedeskE.guide/M3_VWPAT	31
1.54	ImagedeskE.guide/M3_LDPRF	31
1.55	ImagedeskE.guide/M3_SAPRF	32
1.56	ImagedeskE.guide/M3_MKTMB	32
1.57	ImagedeskE.guide/M3_GNTMB	33
1.58	ImagedeskE.guide/M3_DESKF	34
1.59	ImagedeskE.guide/M3_DESKB	34
1.60	ImagedeskE.guide/M3_OPCAT	35
1.61	ImagedeskE.guide/M3_GNCAT	35
1.62	ImagedeskE.guide/M3_QGCAT	36
1.63	ImagedeskE.guide/M3_IDGTF	36
1.64	ImagedeskE.guide/M3_IDGTP	37
1.65	ImagedeskE.guide/M3_GSPRF	37
1.66	ImagedeskE.guide/M3_SSPRF	38
1.67	ImagedeskE.guide/M3_GVPRF	39
1.68	ImagedeskE.guide/M3_SVPRF	40

1.69	ImagedeskE.guide/M3_GTPRF	41
1.70	ImagedeskE.guide/M3_STPRF	42
1.71	ImagedeskE.guide/M3_SYSIN	43
1.72	ImagedeskE.guide/M1_TOOLS	43
1.73	ImagedeskE.guide/M11_LIST	44
1.74	ImagedeskE.guide/M11_CPAT	44
1.75	ImagedeskE.guide/M11_REPK	45
1.76	ImagedeskE.guide/M11_JOIN	46
1.77	ImagedeskE.guide/M11_RMEN	47
1.78	ImagedeskE.guide/M1_REGIS	48
1.79	ImagedeskE.guide/M1_UPDAT	48
1.80	ImagedeskE.guide/M1_RIGHT	49
1.81	ImagedeskE.guide/Liability	49
1.82	ImagedeskE.guide/Distribution	49
1.83	ImagedeskE.guide/Trademarks	50
1.84	ImagedeskE.guide/Copyright	50
1.85	ImagedeskE.guide/M1_BUGRP	50
1.86	ImagedeskE.guide/M1_FUTUR	51
1.87	ImagedeskE.guide/M1_HISTO	51
1.88	ImagedeskE.guide/M1_THANX	55
1.89	ImagedeskE.guide/M1_AUTOR	56

Chapter 1

ImagedeskE

1.1 ImagedeskE.guide

ImageDesk

An utility for cataloging your picture directories

Version 1.6

(C) Copyright 1994-1995 Reinhard Haslbeck

SHAREWARE

Introduction

What is ImageDesk good for

System Requirements

Minimum requirements on your Amiga

Installation

...is really easy

Quick Start

For the impatient ones

Usage in General

Description of ImageDesk's functionality

AREXX Port

Conventions, command descriptions

Catalog Tools

Tools for touching up Catalog files

How to Register	How do I get my keyfile
Updates	Where can I get the latest releases
Legal Stuff	Copyright, Liability, Trademarks
Known Bugs	It's not a bug, it's ...
Future	Possible future enhancements
Releases	What has changed
Thanks	Do not forget to read this
Author	If you want to contact me

1.2 ImagedeskE.guide/M1_INTRD

Introduction

ImageDesk is a program to catalog picture directories by generating small representants of the pictures, so called thumbnails. Those thumbnails are internally being expanded to objects which will include all essential attributes of the represented pictures. Several thumbnail objects which corresponding pictures are in the same directory, could be saved together into a catalog file for being available immediately on request. These files could be saved packed, too provided XPK has been installed. The following picture formats are currently supported and will be recognized automatically:

- * IFF ILBM (color mapped, EHB, HAM, HAM8, DEEP, DCOL)
 - * GIF (87a, 89a)
 - * JPEG (1)
-

- * PCX (1 bit upto 32 bit)
- * BMP (4,8 and 24 bit, OS/2 and Windows formats, unpacked only)
- * PCD (upto BASE size)
- * PNM (P4, P5 und P6)
- * TARGA

The corresponding picture of a thumbnail object could be shown if requested. Therefore two internal viewers, the window- and the screen viewer, exists for each above mentioned format. The latter are able to view Images on CyberGraphics-, Picasso- or standard 8 bit screens, but it is also possible to specify external viewers or AREXX programs which ImageDesk will call on demand.

----- Footnotes -----

(1) ImageDesk needs the "Tower JPEG Codec Class" from Christoph Feck for its JPEG support.

1.3 ImagedeskE.guide/M1_REQUI

System Requirements

To figure a thumbnail image on the Desk, ImageDesk needs an Intuition Screen with 256 colors. Hence the minimum requirements on Kickstartversion is 3.0 (V39) or higher, and on the graphics hardware the ability to provide 8-bit Intuition screens.

This distribution contains two versions of ImageDesk. One is compiled for standard systems with a 68000 CPU the other version has been optimized for 68020 processors. but should run on 030 and 040 systems, too. A coprocessor is not required (ImageDesk makes no use of floating point arithmetics).

In quiet state the program allocates about 1MB of system memory, but during loading or generating catalogs the memory consumption will increase drastically. For calculating the thumbnail images it is necessary to extend all pixel data to a bitdepth of 24. Therefore at least 4MB of continous memory is recommended to have installed.

1.4 ImagedeskE.guide/M1_INSTL

Installation

The installation procedure is completely handled by the Commodore Installer. You just have to double-click one of the icons Install.Deutsch or Install.English in the drawer ImageDesk.

To install the "Tower JPEG Codec Class" (which is necessary for ImageDesk's JPEG support) just double-click the icon Install in the drawer JPEG Codec. If the JFIF DataType by Christoph Feck has been installed already, It is not necessary to do this installation procedure.

1.5 ImagedeskE.guide/M1_FASTE

Quick Start

ImageDesk can be started from Shell or from WorkBench. In both cases the same three arguments and tooltypes, resp., are supported.

- * PREFS=<Filename> - ImageDesk opens the prefs file <Filename>
- * CAT=<Filename> - ImageDesk opens the file <Filename> immediately after the program start
- * REXX=<Filename> - ImageDesk executes the AREXX program <Filename> immediately after the program start
- * VILLAGEMODE - For Picasso users only: ImageDesk starts in Village mode (default is CyberGrahpics mode).

If no prefs file were specified, ImageDesk is looking for the file ImageDesk.idprefs in the program directory. Should no valid prefs file be found, ImageDesk asks via requester for screen and font to be used. If it gets all required resources, the screen will be opened and all available functions are accessible by the menu (and partly by hotkeys, too).

Menu: Project

=====

Open Catalog (<R-Amiga>+<O>, <R-Amiga>+<U>)

Opens a requester which allows to select a former generated catalog file. If selected by Selectable, a window will be opened after confirmation by the OK-button, where the first catalog entry and the number of entries to load can be selected.

Generate Catalog (<R-Amiga>+<G>)

First of all a filename for the catalog file has to be specified in a requester. After this, another requester opens where path and pattern for the desired files has to be selected. Now ImageDesk checks every file if it is a supported picture format. In this case a thumbnail object will be created, which will appear as an intuition gadget on the screen.

Read Single Image (<R-Amiga>+<1>)

A thumbnail object for a single picture will be created.

Scan Path (<R-Amiga>+<2>)

Operates like Generate Catalog, but no catalog file will be saved.

Execute Arexx (<R-Amiga>+<X>)

Executes an Arexx script which has to be selected by a file requester

About

no comment

Information

Informs about the current program state

Quit (<R-Amiga>+<Q>)

Quits ImageDesk after a security request.

Menu: View Images

=====

Single File (<R-Amiga>+<V>)

Views a choosen picture, if its format is known by ImageDesk.

Path Contents (<R-Amiga>+<C>)

Works like View Single Image, but every file which filename is visible in the filerequesters listview will be processed.

Selected Thumbnails (<R-Amiga>+<T>)

First of all, the desired thumbnail objects have to be marked by a single click into its image. The marking will be visualized by a frame rendered around the thumbnail image. After that this menu item needs to be selected again. Now all pictures which belong to the marked objects will be viewed one by one.

Menu: Remove Thumbnails

=====

Remove Single (<R-Amiga>+<R>)

The next selected thumbnail object will be removed from the desk.

Clean Whole Desk (<R-Amiga>+<D>)

After an optional security request all thumbnail objects on the desk will be removed.

Mark & Delete (<R-Amiga>+<M>)

Thumbnail objects have to be selected exactly as described in Selected Thumbnails. If this menu item is selected again all marked Thumbnails will be removed from the screen.

Menu: Preferences

=====

System Prefs (<R-Amiga>+<?>)

Opens a window for changing the system preferences settings.

Viewer Prefs (<R-Amiga>+<!>)

Opens a window for changing change the viewer preferences settings.

ThumbNail Prefs (<R-Amiga>+<N>)

Opens a window for changing the thumbnail preferences settings.

Ask Before Cleaning Desk (<R-Amiga>+<A>)

If this menuitem is checked nearly everytime a Clean Whole Desk has to be made a security requester will prompt you for confirmation.

Load Prefs (<R-Amiga>+<L>)

Load an other preferences file.

Save Prefs (<R-Amiga>+<S>)

Saves the current preferences settings.

Reset to defaults

Overrides the current preferences settings and uses default values. Screen size and font will be asked by requester.

1.6 ImagedeskE.guide/M1_TOUSE

Usage in General

Starting ImageDesk

Stack, Arguments, Tooltypes

Configuration

Adjust ImageDesk to your own requirements

Menu

ImageDesk's menu structure

Restrictions

...without a keyfile

Hints on Usage

Tips and Hints

1.7 ImagedeskE.guide/Starting ImageDesk

Starting ImageDesk

=====

Due to my experiences, the stacksize is not growing much beyond the 2KB border. Therefore the default size of 4096 Bytes will be sufficient

in most cases. If you work mainly with images much wider than 1000 pixels its more secure to increase the stacksize to 8KB.

ImageDesk could be started from a shell or by Workbench. Currently there are four arguments and tooltypes, resp., allowed:

- PREFS=<Filename> - ImageDesk tries to load the prefs file <Filename> at programstart. If this file could not be found or it is not a valid ImageDesk prefs file, default values will be used. Prefs files created witch ImageDesk 1.3 or older are not supported any longer.
- CAT=<Filename> - ImageDesk opens the catalog file <Filename> immediately at the programstart.
- REXX=<Filename> - ImageDesk executes the AREXX program <Filename> immediately after the program start
- VILLAGEMODE - (for usage in conjunction with a picasso only)
If the CyberGraphics software is installed on the system, ImageDesk will use it for its specail screens in 8/15/16/24 bitdepth by default. if VILLAGEMODE is set, it is tried to use the standard Picasso drivers instead.

If no configuration file has been specified at programstart, ImageDesk will try to find the file ImageDesk.idprefs in the program directory. The first time you start ImageDesk, it won't find a configuration file, of course. In this case ImageDesk reports about it and you will be asked for screenmode and screenfont. The other values will be set to defaults. Before exiting, ImageDesk saves the last used preference settings. Nevertheless it is recommended to set all the preferences values to your own requirements by selecting the menu items System Prefs, Viewer Prefs and ThumbNail Prefs (see also Configuration) if ImageDesk has been started the first time.

1.8 ImagedeskE.guide/Configuration

Configuration

=====

The configuration adjustments in ImageDesk have been splitted in three major groups:

- * System preferences
- * Viewer preferences
- * Thumbnail preferences

Therefore, three preferences windows are available:

- System Prefs window - To configure ImageDesk's main environment
- Viewer Prefs window - To configure ImageDesk's handling of the

picture viewers

- Thumbnail Prefs window - To configure the thumbnail objects

These windows could be opened by selecting one of the menu items System Prefs, Viewer Prefs or ThumbNail Prefs.

System Prefs

Viewer Prefs

ThumbNail Prefs

1.9 ImagedeskE.guide/System Prefs

System Prefs

The data of the valid screenmode is displayed in the frame titled Screen. A mouse click on the ?-button opens a screenmode requester where a new screenmode can be selected. It is also possible to choose higher values for width and height than the screen's visible sizes. In this case it will be opened as an autoscroll screen.

The frame titled Font can be handled the same way. Here, the font for screen and windows of ImageDesk is displayed and can be changed.

Caution: If screen mode or font has been changed and you want to leave this window by pressing the USE or Save button, all thumbnail objects will be removed.

The third framed area of this window groups some gadgets where the xpkmode to use, an encryption password if supported and the efficiency of packing has to be specified. If XPK is not installed these gadgets are disabled.

Other preferences gadgets which could not be classified to a specific group are:

Save Project Icons

This gadget determines if an icon should be created for each generated catalog file. Creating project icons for catalog file has a big advantage. Later, it is possible start ImageDesk and load a catalog file with a single mouse click.

Use XPK for Catalogs

This gadget is displayed disabled if XPK has not been installed. Otherwise, it determines if XPK is used for saving catalog files.

Print Execution Command

This Gadget is significant if external viewers are used. If it is selected, the executed command will be printed in the output

window.

Default Action

This Cycle Gadget determines what has to happen if a thumbnail object has been clicked. Possible choices are:

- View Image - Views the corresponding image immediately.
- Execute AREXX - Runs an AREXX script, specified in Default AREXX Script. The script will receive file name and image type of the original picture.
- Requester - An information window opens which shows all essential attributes of the image represented by the clicked thumbnail object:
 - * Filename of the original image
 - * Path of the file
 - * Type of the image (IFF, JPEG, GIF...)
 - * Image width in pixels
 - * Image height in pixels
 - * Original bitdepth of the image
 - * Does the image file contain a color palette

Clicking the button Very Interesting will close the window and nothing else will happen. The buttons View Image and Execute AREXX will operate as described above.

Default AREXX Script

This string gadget is used to specify the AREXX script which has to be executed if Default Action is set to Execute AREXX. Clicking the ?-button opens a file requester for choosing the script name.

Output Window

Here the string for specifying the attributes of the external viewer console window has to be edited. It is very important for this string to contain SCREEN=IMAGEDESK at the end. Otherwise, this console window won't open on ImageDesk's screen.

Max. entries per catalog

This is a slider gadget which allows to change the entry limit of the catalog files. If a scanned directory contains of more entries than specified here, there will be generated as many catalog files as necessary to store all its thumbnails. Should more than one catalog file be used for a single scan, the files will be numbered and its filename will get this number as an filename extension.

There are four additional buttons, horizontally spreaded at the bottom of the window:

Save

The edited configuration is saved in the current directory and

gets the filename ImageDesk.idprefs. After this, the window will be closed and the changed values will be used in ImageDesk.

Use

The edited configuration is used immediately and the window will be closed.

Load

In a filerequester you are prompted for a prefsfile which is loaded afterwards. The window remains open to let the user make further changes to the loaded prefs.

Cancel

The window is closed, all changes will be dismissed.

1.10 ImagedeskE.guide/Viewer Prefs

Viewer Prefs

This window is used to select which viewer has to be taken for each supported image format. To select, click on one radio button of custom screen, external or window.

Remarks:

- * If the 'Tower JPEG Codec' has not been installed, the corresponding buttons are disabled.

To specify an external viewer, you have to type the viewer name and the arguments you want to use. Instead of a filename type %s. A small example:

Supposed you want to use the picture viewer called GigaView and usually you would call this viewer:

```
GigaView <filename> SCREENBEHIND
```

In the corresponding gadget you would have to type the following string:

```
GigaView %s SCREENBEHIND
```

Caution: you have to set the whole path instead of the viewer name only. Otherwise ImageDesk may not find it.

The preferences in the framed area named Internal Viewer Prefs are meaningless for external viewers and partly meaningless for the most image formats.

Display Screens

With this cycle gadget you tell ImageDesk how to determine the custom screens for displaying the images.

- autoscreen - ImageDesk tries to find optimal values for screen mode and screen size by itself.

- requester - Everytime an image has to be displayed, the user will be asked for a screen mode by a requester.
- global - Fixed screen ids will be used. The user is responsible for Global CLUT Screen and Global DCOL Screen to have valid values.

Display Size

Which size the images should be displayed has to be determined here. These values are meaningless for the external viewers.

- original - The image will be displayed in original size.
- small - The image will be displayed in half the hight and half the width.
- tiny - The image will be displayed in a quarter the hight and a quarter the width. Caution: The values in Display Size are only meaningful for the image formats PCD and JPEG, yet.

Orientation

These adjustments will cause the following:

- Auto - PCD only: Tries to find out the orientation by itself.
- Force Landscape - PCD only: Displays images in landscape mode.
- Force Portrait - PCD only: Displays images in portrait mode.
- Upside Down - all formats: Displays images mirrored to the x-axxis.
- Left to Right - PCD only: Displays images mirrored to the y-axxis.

Global CLUT Screen

After clicking on the ?-button a screenrequester appears where you have to choose an 8-bit screen. This selected screenmode is used for displaying all images containing upto 256 colors. This setting is only significant if Display Screens is set to global.

Global DCOL Screen

Same as Global CLUT Screen, with the difference that a screenmode for all images containing more than 256 colors has to be choosen.

Remark: it is quite possible to choose an 8-bit screenmode, but the display quality will be not very satisfying.

Dither 8-Bit Displays

If this gadget is checked, the images in 8 bit illustration (this is valid for the window viewers and for the 8-bit screen viewers) are displayed dithered. This improves the display quality of the image, but slows down the procedure a bit. Only images which contain more than 256 colors will be dithered. This means all 15/16/24/32 bit pictures and HAM images.

Use Original Palette

If checked, this gadget says that the windows viewer will use the original color palette of the pictures. Therefore, it is meaningful for images which contains up to 256 colors, only. If 'Use Original Palette' is activated, ImageDesk temporarily (to be more specific, for the duration a picture is displayed) switches its palette to the one of the picture. This will cause a somewhat strange looking user interface but it will decrease the the time for building up an image dramatically and will avoid quality losses. In the other case the image will be converted to 24-bit RGB row by row and scaled to 8-bit RGB, afterwards (for the insiders: RRRGGGBB).

Delay

The maximum duration time an image has to be displayed (in 1/10 seconds). After all, the display could be closed at any time (any keystroke or mouse button when screen viewers are used, ESC-key or CloseGadget when the Window viewers are used).

The four additional buttons SAVE, USE, LOAD and CANCEL have the same meaning as they have in the System Prefs window.

1.11 ImagedeskE.guide/ThumbNail Prefs

Thumbnail Prefs

In this window it has to be choosen how the thumbnail objects have to be presented or rendered.

The upper three gadgets are responsible for the font which is used for printing the file name below a thumbnail image (if desired). This font has to be selected the same way as described in System Prefs.

The next four gadgets have the following meaning:

Dither Thumbnail Images

Since ImageDesk has to deal with a limited number of colours, the thumbnail images are not always in best quality, especially if the images contain of fine colour runs. If this gadget is selected a bigger colourspace is simulated by the use of ordered dithering. However, using dithering not always results in a better quality of the thumbnail images as the pixelspace is to small to cheat the eyes perfectly. Another disadvantage is that dithered images could not be packed as effectively.

Show File Names

If selected, file names will be displayed below the thumbnail images.

HiQuality

This switch is just relevant for the formats PCD and JPEG, yet. If it is activated the original images will be used for calculating

the thumbnail images instead of reading them in, already scaled.

Remark: HiQuality requires much more memory and rendering time while calculating thumbnail images for the above mentioned formats.

Thumbnail Size

This cycle gadget determines which sizes the thumbnail images will get.

Remark: For performance and quality reasons the thumbnail images won't always get exactly the specified size.

The four additional buttons SAVE, USE, LOAD and CANCEL have the same meaning as they have in the other prefs windows.

Caution: If you have made changes in this window, it may be necessary to remove all active thumbnail objects from the screen. Otherwise all changes will be dismissed.

1.12 ImagedeskE.guide/Menu

```

====
                Menu

                Project

                View Images

                Remove Thumbnails

                Preferences

```

1.13 ImagedeskE.guide/M2_PROJ

```

-----
                Project

                Open Catalog

                Generate Catalog
                ~~~~~~

                Read Single Image

                Scan Path
                ~~~~~~

```

```

Execute Arexx
~~~~~

About...

Information
~~~~~

Quit

```

1.14 ImagedeskE.guide/M21_OPCAT

Open Catalog

This menu item branches in two subitems:

- * Selectable - opens a requester in which a former generated catalog file has to be chosen. If this file could not be identified as a catalog file, you will get an error message. In the other case, a window is opened, giving information about free space for thumbnail objects on the desk and the number of entries in the catalog file. The window contains two slider gadgets where the first entry to load and the number of thumbnail objects to load could be specified. Existing thumbnail objects on the desk won't be replaced, therefore it is sometimes necessary to remove all of them from the desk with Clean Desk First before new ones are loaded. Loading is started when the Load-button has been pressed. A process monitor will show approximately the current state of the loading procedure. It could be interrupted by pressing the ESC-key.
- * Quick - the selection window won't be opened. The catalog file is loaded immediately. There will be just as many thumbnails loaded as there will fit on the screen.

1.15 ImagedeskE.guide/M21_GNCAT

Generate Catalog

This menu item branches in two subitems:

- * Show Thumbnails - First of all a filename is requested for the catalogfile to be generated. After this another requester opens where path and a template for the picture files could be chosen. An additional selected file will be ignored. If the OK-button has been pressed, ImageDesk starts to examine all files listed in the requester for being a supported format. In this case, a thumbnail object will be generated which occurs as an intuition gadget on

the screen.

Caution: If there is no space left on the desk for a single thumbnail image, all existing objects will be removed from the desk without any demand. However, this will not influence the file which is generated.

The process monitor which occurs during the generation process helps by estimating the current state of the procedure. To stop the thumbnail generation, press the ESC-key and it will be interrupted on the next possible point of time.

Remark: If the generation process has been interrupted, all former generated objects will be saved correctly.

- * Don't show Thumbnails - Acts exactly like Show Thumbnails, but the generated thumbnail images won't occur on the desk.

1.16 ImagedeskE.guide/M21_RSING

Read Single Image

.....

A filename for a single image file is requested and a thumbnail object will be generated for it.

1.17 ImagedeskE.guide/M21_SPATH

Scan Path

.....

Acts nearly the same way like Generate Catalog, but no catalogfile is generated and saved.

1.18 ImagedeskE.guide/M21_EXREX

Execute Arexx

.....

Executes an Arexx script which has to be selected by a file requester

1.19 ImagedeskE.guide/M21_ABOUT

About

.....

Opens a information window which tells about program version, author and registered user.

1.20 ImagedeskE.guide/M21_INFMT

Information

.....

Opens a information window which tells:

- * Name of the public screen
- * Name of the AREXX port
- * Graphics board mode
- * Currently valid thumbnail sizes
- * Available memory
- * Thumbnail deskpace
- * Number of thumbnail objects used

1.21 ImagedeskE.guide/M21_QUITP

Quit

....

Exits ImageDesk after a security request. The current preference settings will be saved before.

1.22 ImagedeskE.guide/M2_VIEW

View Images

The menuitems contained here serve for viewing pictures. For the viewer's behaviour the adjustments made in the Viewer Prefs are responsible. All internal viewers could be interrupted at any time by pressing the <ESC>-Key.

Single File

Path Contents

Selected Thumbnails

1.23 ImagedeskE.guide/M22_SFILE

Single File

.....

You will be prompted for a filename of an imagefile. If it is a supported format it will be displayed.

1.24 ImagedeskE.guide/M22_PCONT

Path Contents

.....

Acts like Single File, but all in the filerequester's listview shown files will be processed. During this procedure, a process monitor is present to inform about the current process state. To interrupt it press the ESC-key.

1.25 ImagedeskE.guide/M22_SELEC

Selected Thumbnails

.....

First of all, ImageDesk turns into a marking mode. You will be prompted to mark all thumbnail objects you want by clicking them with the mouse. ImageDesk confirms this by rendering a frame around the object. At this point of time it is still possible to unmark selected objects by clicking it again. If the marking procedure is finished this menuitem has to be chosen again and all images which belong to the marked objects will be displayed one by one.

1.26 ImagedeskE.guide/M2_THUM

Remove Thumbnails

The contained menu items serve for removing a single or all thumbnail objects from the desk.

Remove Single

Clean Whole Desk

Mark & Delete

1.27 ImagedeskE.guide/M23_RMSIN

Remove Single

.....

The thumbnail object selected next will be removed from the desk.

1.28 ImagedeskE.guide/M23_CLEAN

Clean Whole Desk

.....

All thumbnail objects will be removed from the desk. Depending on the current preferences a security request is made before.

1.29 ImagedeskE.guide/M23_MRKDL

Mark & Delete

First of all, ImageDesk turns into a marking mode. You will be prompted to mark all thumbnail objects you want to remove by clicking them with the mouse. ImageDesk confirms this by rendering a frame around the object. At this point of time it is still possible to unmark selected objects by clicking it again. If the marking procedure is finished this menuitem has to be chosen again and all marked objects will be removed.

1.30 ImagedeskE.guide/M2_PREF

Preferences

System Prefs

Viewer Prefs

ThumbNail Prefs

~~~~~

Ask Before Cleaning Desk

~~~~~

Load Prefs

Save Prefs

~~~~~

Reset to defaults

### 1.31 ImagedeskE.guide/M24\_SPWIN

System Prefs

.....

Opens the window for changing the system preferences (see also System Prefs in Configuration).

### 1.32 ImagedeskE.guide/M24\_VPWIN

Viewer Prefs

.....

Opens the window for changing the viewer preferences (see also Viewer Prefs in Configuration).

### 1.33 ImagedeskE.guide/M24\_TPWIN

ThumbNail Prefs

.....

Opens the window for changing the thumbnail preferences (see also ThumbNail Prefs in Configuration).

---



### 1.34 ImagedeskE.guide/M24\_ABCDK

Ask Before Cleaning Desk  
.....

If this item is checked, everytime a Clean Whole Desk operation is made the user will be prompted for confirmation before (ignored during thumbnail generation).

### 1.35 ImagedeskE.guide/M24\_LOADP

Load Prefs  
.....

This menuitem serves for loading a former saved configuration. The filename for the prefsfile will be asked by a requester.

### 1.36 ImagedeskE.guide/M24\_SAVEP

Save Prefs  
.....

You will be prompted for a filename which will be used for saving the current configuration.

### 1.37 ImagedeskE.guide/M24\_RESET

Reset to defaults  
.....

The current configuration will be neglected to fix default values. Screenmode and font will be asked by requester.

### 1.38 ImagedeskE.guide/Restrictions

Restrictions  
=====

Without a personal keyfile, ImageDesk does not offer its whole functionality. The restrictions in particular:

\* Sometimes a 'NervRequester' will appear to remind on registering.

---

- \* The maximum number of entries in a catalog file is restricted to 15. But it is still possible to work on much larger directories.
- \* The maximum number of thumbnail objects to load is restricted to 13.
- \* The catalog tool CATJoin won't work at all.

I apply on your insight for these restrictions. How to get a personal keyfile you can read in How to Register.

## 1.39 ImagedeskE.guide/Hints on Usage

Hints on Usage

=====

Using XPK

-----

Of course, it is every users decision wether he use XPK or not. Despite a short delay while loading and saving catalogfiles, XPK provides nothing but advantages. The files will be shrunked to 35% of their original size in average. This shrink factor may be brought down to 25% if an according xpkmode and xpkefficiency has been choosen. Further more xpk provides password protection for catalog files. Yet, for all that it has to be considered, that your password ist stored unencrypted in the prefsfile and could be read by everyone who has access to the computer system. The following xpkmethods are very useful.

- SHRI - provides very high packing rates
- RDCN - provides very fast packing

Caution: Don't use xpack for packing or repacking catalog files, ImageDesk won't be able to read them then. Use CATRepack instead.

Online Help

-----

ImageDesk does not yet support an internal online-help function, but this could be done external very easily:

check the tooltypes in the icon of the hypertext document ImageDesk.guide. If it has not been done before, set a tooltype variable to PUBSCREEN=IMAGEDESK.

If you need help after ImageDesk has been started you have to switch to the Workbench Screen (<Left-Amiga>+<m>) and to double-click the icon ImageDesk.guide.

ImageDesk Windows

-----

Everytime the current configuration is saved, size and position of

---

certain ImageDesk windows are saved with it. The last used positions and sizes will be stored here. If font or screen size has changed in the meantime it may be necessary to override these values for opening the windows properly.

#### Screen Colors

-----

ImageDesk uses an optimized color palette. 255 out of 256 possible colors are reserved for figuring the thumbnail images. Therefore it is not possible to let the user choose custom colors for ImageDesk's user interface. Another consequence of this fixed palette are the unusual colors the mouse pointer will get.

#### AREXX scripts

-----

Since I am not what you call a great AREXX programmer, most of the contained AREXX scripts are thought to serve as examples. I leave the job of writing larger scripts to the user. Just a few suggestions of things might be possible for the Default AREXX script:

- Image conversion by the help of PBM
  
- Addressing a printing utility
  
- Addressing an image processor
  
- Dos action like copy, delete and so on

#### How to avoid memory short runs

-----

If you want to limit the memory consumption you should, first of all, avoid using very big screens. Furthermore, the max. number of entries per catalog should not be too high (see also System Prefs in the chapter Configuration). Thumbnail objects which won't be used anymore should be removed, this will give back some memory to the system.

#### PCD support

-----

The PCD support in ImageDesk is just rudimentary. I'm sorry, but I can't afford to spend thousands of Dollars to get a license and a toolbox for Windows(TM).

All the Information on the PCD format I used in ImageDesk, I got from studying pertinent source codes or I found out by myself. If you want to have a more professional Photo CD(TM) support you should consider to buy a commercial product. Thereby you'll get access to the larger formats 1536x1024, 3072x2048 (and partly bigger) and to image-converting and -processing functions.

#### Changing the 'default project' icon

-----

If you don't like the icons generated by ImageDesk (maybe you need 'MagicWB'-style icons), you just have to change the icon named

ID\_DefProjIcon(.info). This could be done with pertinent icon tools e.g. IconEd. But you should consider not to change the icon's attributes and also not to fix them.

## 1.40 ImagedeskE.guide/M1\_AREXX

AREXX Port

\*\*\*\*\*

Miscellaneous

Conventions

Command references

## 1.41 ImagedeskE.guide/AREXX1

Miscellaneous

=====

Since version 1.5 ImageDesk consists of an AREXX port. Such an AREXX port has several advantages.

- ImageDesk can be controlled by a script file
- ImageDesk is able to communicate with other programs
- ImageDesk can be controlled by other programs
- It is possible to extend ImageDesks command set

There are several possibilities for starting ImageDesk AREXX scripts.

- a. By executing the AmigaDos command "rx <Scriptfile>" in the command line
- b. Immediately on program start by using ImageDesk's command line arguments (ImageDesk R=<Scriptfile>)
- c. Immediately on program start by using ImageDesk's tooltypes (REXX=<Scriptfile>)
- d. By selecting the menu item "Execute AREXX" in the menu "Project"
- e. By clicking into a thumbnail object (if selected in System Prefs)

## 1.42 ImagedeskE.guide/AREXX2

### Conventions

=====

Each AREXX script for ImageDesk which has been started by a) to d) has to begin with the following lines:

```
/* ----- standard startup ----- */
OPTIONS RESULTS
if( ADDRESS() ~= "IDESK_REXXPORT" ) then
    ADDRESS IDESK_REXXPORT
/* ----- */
```

AREXX scripts which are thought to be executed on thumbnail click will receive two arguments from ImageDesk.

- \* file name of the corresponding image
- \* image type (IFF, GIF, JPG, PCX, BMP, PCD, PNM or TGA)

Therefore those AREXX programs should begin like this:

```
/* ---- standard startup II (if started via thumbnail click) ---- */
OPTIONS RESULTS
PARSE ARG iname itype
/* ----- */
```

All AREXX commands and keywords if supported have to be in uppercase letters. Up to four arguments are supported. Some of the commands show a different behaviour, depending on the number of arguments (for example OPENCAT). Arguments containing spaces have to be quoted. Since AREXX is filtering these quotation marks marks out of static strings, they have to be forced by embedding the quoted string in ""s in this case.

### Example

.....

```
OPENCAT ' "ram disk:pics.cat" '
```

If a string is stored in an AREXX variable the string has to be embedded explicitly in quotation marks.

### Example

.....

```
StringVar = "This is a requester"
IDREQUEST OK ' ""||StringVar||" "
```

Some of the AREXX commands will return a result string which can be found in the global AREXX variable "RESULT"

Example

.....

```
GETSYSINFO DESKPLACE
deskplace = RESULT
```

Besides a result string you will get a return code from from the commands. If a command has been executed properly without an error this will be the value 0. If the number of delivered arguments was not right for a specific command, the return code will be 10. If a command has been canceled by the user or an error occurred, you will get a return code of 5. The return code can be requested through the global AREXX variable "RC"

Example

.....

```
IDGETFILE "Select a file"
if RC > 0 then exit /* User has choosen "cancel" */
filename = RESULT
```

Boolean values have to be made available as one of the strings "TRUE" or "FALSE" (uppercase!). According commands will return boolean values as strings, too.

Example

.....

```
SETVPREFS DITHER TRUE
```

## 1.43 ImagedeskE.guide/AREXX3

Command references

=====

ABOUTWIN

INFOWIN

SPWIN

VPWIN

TPWIN

IDREQUEST

ERRORMSG

CLEANDesk  
VIEWIMAGE  
VIEWPATH  
LOADPREFS  
SAVEPREFS  
MAKETHUMBNAIL  
GENTHUMBNAILS  
DESKTOFRONT  
DESKTOBACK  
OPENCAT  
GENCAT  
QUIETGENCAT  
IDGETFILE  
IDGETPATH  
GETSPREFS  
SETSPREFS  
GETVPREFS  
SETVPREFS  
GETTPREFS  
SETTPREFS  
GETSYSINFO

## 1.44 ImagedeskE.guide/M3\_ABWIN

ABOUTWIN

-----

Syntax

.....

ABOUTWIN

Description

.....

---

Opens the "About" window

Result

.....

NULL

Example

.....

ABOUTWIN

## 1.45 ImagedeskE.guide/M3\_INWIN

INFOWIN

-----

Syntax

.....

INFOWIN

Description

.....

Opens the "Information" window

Result

.....

NULL

Example

.....

INFOWIN

## 1.46 ImagedeskE.guide/M3\_SPWIN

SPWIN

-----

Syntax

.....

SPWIN

Description

.....

---



Opens the "System Prefs" window

Result

.....

NULL

Example

.....

SPWIN

## 1.47 ImagedeskE.guide/M3\_VPWIN

VPWIN

-----

Syntax

.....

VPWIN

Description

.....

Opens the "Viewer Prefs" window

Result

.....

NULL

Example

.....

VPWIN

## 1.48 ImagedeskE.guide/M3\_TPWIN

TPWIN

-----

Syntax

.....

TPWIN

Description

.....

---

Opens the "Thumbnail Prefs" window

Result

.....

NULL

Example

.....

TPWIN

## 1.49 ImagedeskE.guide/M3\_IDREQ

IDREQUEST

-----

Syntax

.....

IDREQUEST <Gadget1>|<Gadgeet2>|...|<Gadget0> <Text>

Description

.....

Opens an intuition requester containing the body <Text> and the button texts <Gadget1>, <Gadget2>, ..., <Gadget0>.

Result

.....

Number of selected gadget (1,2,...,0) (Integer).

Example

.....

```
IDREQUEST "YES|NO" ' "Do you want to exit?" '
if( Result = 1 ) then exit
```

## 1.50 ImagedeskE.guide/M3\_ERMSG

ERRORMSG

-----

Syntax

.....

ERRORMSG <Text>

## Description

.....

Opens ImageDesk's standard error requester containing the error message <Text>

## Result

.....

NULL

## Example

.....

ERRORMSG "Last command failed!"

## 1.51 ImagedeskE.guide/M3\_CLEAN

CLEANDESK

-----

## Syntax

.....

CLEANDESK

## Description

.....

Removes all thumbnail objects from the desk.

## Result

.....

NULL

## Example

.....

CLEANDESK

## 1.52 ImagedeskE.guide/M3\_VWIMG

VIEWIMAGE

-----

## Syntax

.....

VIEWIMAGE [&lt;filename&gt;]

## Description

.....

If <filename> was given the corresponding image will be displayed. In the other case you will be prompted for an image file by a file requester.

## Result

.....

NULL

## Example

.....

VIEWIMAGE

### 1.53 ImagedeskE.guide/M3\_VWPAT

## VIEWPATH

-----

## Syntax

.....

VIEWPATH [&lt;path&gt; [&lt;pattern&gt;]]

## Description

.....

If <path> and <pattern> were given all known image files which match the pattern will be displayed. If <pattern> was not specified the default pattern "#?" will be used. Without any argument you will be prompted for path and pattern by a requester.

## Result

.....

NULL

## Example

.....

VIEWPATH "work:pics/gif" "#?.gif"

### 1.54 ImagedeskE.guide/M3\_LDPRF

## LOADPREFS

-----

## Syntax

.....

```
LOADPREFS [<filename>]
```

## Description

.....

Tries to read the configuration file <filename>. If <filename> is missing you will be prompted for one by a file requester.

## Result

.....

```
NULL
```

## Example

.....

```
LOADPREFS "ImageDesk.idprefs"
```

## 1.55 ImagedeskE.guide/M3\_SAPRF

## SAVEPREFS

-----

## Syntax

.....

```
SAVEPREFS [<filename>]
```

## Description

.....

Tries to save the current configuration under the name <filename> if specified. In the other case you will be requested for a file name.

## Result

.....

```
NULL
```

## Example

.....

```
SAVEPREFS
```

## 1.56 ImagedeskE.guide/M3\_MKTMB

---

## MAKETHUMBNAIL

-----

## Syntax

.....

```
MAKETHUMBNAIL [<filename>]
```

## Description

.....

Generates a single thumbnail object from the image file <filename>. If <filename> is missing you have to select one in a file requester.

## Result

.....

```
NULL
```

## Example

.....

```
MAKETHUMBNAIL
```

## 1.57 ImagedeskE.guide/M3\_GNTMB

## GENTHUMBNAILS

-----

## Syntax

.....

```
GENTHUMBNAILS [<path> [<pattern>]]
```

## Description

.....

If <path> and <pattern> were given for all known image files which match the pattern a thumbnail object will be generated. If <pattern> was not specified the default pattern "#?" will be used. Without any argument you will be prompted for path and pattern by a requester.

## Result

.....

```
NULL
```

## Example

.....

```
GENTHUMBNAILS "work:pics/gif" "#?.gif"
```

---

## 1.58 ImagedeskE.guide/M3\_DESKF

DESKTOFRONT

-----

Syntax

.....

DESKTOFRONT

Description

.....

Switches ImageDesk's screen into front.

Result

.....

NULL

Example

.....

DESKTOFRONT

## 1.59 ImagedeskE.guide/M3\_DESKB

DESKTOBACK

-----

Syntax

.....

DESKTOBACK

Description

.....

Switches ImageDesk's screen to back.

Result

.....

NULL

Example

.....

DESKTOBACK

---

## 1.60 ImagedeskE.guide/M3\_OPCAT

OPENCAT  
-----

Syntax  
.....

```
OPENCAT [<filename> [startindex num]]
```

Description  
.....

If a file name was given ImageDesk tries to open a thumbnail catalog file. Optionally it is possible to specify the first thumbnail object and the number of thumbnail objects to load. however, no more thumbnail objects will be loaded as will fit on the screen. If OPENCAT was called without any argument you will be prompted for file name, startindex and number to load.

Result  
.....

NULL

Example  
.....

```
OPENCAT "work:catalogs/gifpics.cat" 1 1000
```

## 1.61 ImagedeskE.guide/M3\_GNCAT

GENCAT  
-----

Syntax  
.....

```
GENCAT [<filename> [<path> [<pattern>]]]
```

Description  
.....

Generates a thumbnail catalog file with the name <filename> for all known images in <path> which match the pattern <pattern>. If <pattern> was not specified the default pattern "#?" will be used. If GENCAT is called with <filename> only, ImageDesk asks for path and pattern. Without any argument additionally you will be asked for a file name.

Result  
.....

NULL

---



Example

.....

```
GENCAT "work:catalogs/gifpics.cat" "work:pics/gif" "#?.gif"
```

## 1.62 ImagedeskE.guide/M3\_QGCAT

QUIETGENCAT

-----

Syntax

.....

```
QUIETGENCAT [<filename> [<path> [<pattern>]]]
```

Description

.....

Same behaviour than GENCAT but QUIETGENCAT will not display the generated thumbnail images on the desk.

Result

.....

```
NULL
```

Example

.....

```
QUIETGENCAT "work:cat/gifpics.cat" "work:pics/gif" "#?.gif"
```

## 1.63 ImagedeskE.guide/M3\_IDGTF

IDGETFILE

-----

Syntax

.....

```
IDGETFILE <title>
```

Description

.....

Opens a file requester with the title text <title>.

Result

.....

---

Chosen file name or NULL

Example

.....

```
IDGETFILE "Please choose a file"
```

## 1.64 ImagedeskE.guide/M3\_IDGTP

IDGETPATH

-----

Syntax

.....

```
IDGETPATH <title>
```

Description

.....

Opens a path requester with the title text <title>.

Result

.....

Chosen path or NULL

Example

.....

```
IDGETPATH "Please Choose a path"
```

## 1.65 ImagedeskE.guide/M3\_GSPRF

GETSPREFS

-----

Syntax

.....

```
GETSPREFS <keyword>
```

Description

.....

Supplies the value of a single system prefs adjustment. The result type depends on <keyword>. Valid keywords are:

- PROJECTICONS (-> Systemprefs "Save Project Icons")

- PRINTCOMMAND (-> Systemprefs "Print Execution Command")
- USEXPX (-> Systemprefs "Use Xpk for Catalogs")
- XPKPACKER (-> Systemprefs "Xpk")
- XPKPASSWD (-> Systemprefs "Password")
- XPKEFFIC (-> Systemprefs "Xpk Efficiency")
- OUTWIN (-> Systemprefs "Output Window")
- MAXENTRIES (-> Systemprefs "Max Entries per catalog")
- DEFAREXX (-> Systemprefs "Default AREXX Script")
- DEFACTION (-> Systemprefs "Default Action")

Result

.....

Depends on the keyword

- PROJECTICONS (BOOLEAN)
- PRINTCOMMAND (BOOLEAN)
- USEXPX (BOOLEAN)
- XPKPACKER (STRING)
- XPKPASSWD (STRING)
- XPKEFFIC (INTEGER)
- OUTWIN (STRING)
- MAXENTRIES (STRING)
- DEFAREXX (STRING)
- DEFACTION ("REQ", "VIW" or "REX")

Example

.....

GETSPREFS MAXENTRIES

## 1.66 ImagedeskE.guide/M3\_SSPRF

SETSPREFS

-----

Syntax

---

.....

```
SETSPREFS <keyword> <value>
```

Description

.....

Sets a single system prefs adjustment to <value> (see also GETSPREFS). The argument type of <value> depends on the argument <keyword>. Valid keywords are:

- PROJECTICONS (BOOLEAN)
- PRINTCOMMAND (BOOLEAN)
- USEXPK (BOOLEAN)
- XPKPACKER (STRING)
- XPKPASSWD (STRING)
- XPKEFFIC (INTEGER)
- OUTWIN (STRING)
- MAXENTRIES (STRING)
- DEFAREXX (STRING)
- DEFACTION ("REQ", "VIW" or "REX")

Result

.....

NULL

Example

.....

```
SETSPREFS MAXENTRIES 50
```

## 1.67 ImagedeskE.guide/M3\_GVPRF

GETVPREFS

-----

Syntax

.....

```
GETVPREFS <keyword>
```

Description

.....

---

Supplies the value of a single viewer prefs adjustment. The result type depends on <keyword>. Valid keywords are:

- DSCREENS (-> Viewerprefs "Display Screens")
- DSIZE (-> Viewerprefs "Display Size")
- DITHER (-> Viewerprefs "Dither 8-bit Displays")
- ORIGPAL (-> Viewerprefs "Use Original Palette")
- DELAY (-> Viewerprefs "Delay")
- VIEWERxxx (1) (-> Viewerprefs/MX Gadgets for choosing one of "custom screen", "external" or "window")
- EXTCOMxxx (-> Viewerprefs/String Gadgets for external viewers)

Result

.....

Depends on the keyword

- DSCREENS ("ASC", "REQ" oder "GLB")
- DSIZE ("ORIGINAL", "SMALL" oder "Tiny")
- DITHER (BOOLEAN)
- ORIGPAL (BOOLEAN)
- DELAY (INTEGER)
- VIEWERxxx ("CSC", "EXT" or "WIN")
- EXTCOMxxx (STRING)

Example

.....

```
GETVPREFS DITHER
```

```
----- Footnotes -----
```

(1) xxx stands for IFF, GIF, JPG, PCX, BMP, PCD, PNM or TGA

## 1.68 ImagedeskE.guide/M3\_SVPRF

SETVPREFS

-----

Syntax

.....

```
SETVPREFS <keyword> <value>
```

Description

.....

Sets a viewer prefs adjustment to <value> (see also GETVPREFS). The argument type of <value> depends on the argument <keyword>. Valid keywords are:

- DSCREENS ("ASC", "REQ" oder "GLB")
- DSIZE ("ORIGINAL", "SMALL" oder "Tiny")
- DITHER (BOOLEAN)
- ORIGPAL (BOOLEAN)
- DELAY (INTEGER)
- VIEWERxxx ("CSC", "EXT" or "WIN")
- EXTCOMxxx (STRING)

Result

.....

NULL

Example

.....

```
SETVPREFS DSIZE SMALL
```

## 1.69 ImagedeskE.guide/M3\_GTPRF

GETTPREFS

-----

Syntax

.....

```
GETTPREFS <keyword>
```

Description

.....

Supplies the value of a single thumbnail prefs adjustment. The result type depends on <keyword>. Valid keywords are:

- DITHER (-> Thumbnailprefs "Dither Thumbnail Images")
- SHOWNAMES (-> Thumbnailprefs "Show File Names")
- HIQUALITY (-> Thumbnailprefs "HiQuality")

- TSIZE (-> Thumbnailprefs "Thumbnail Size")

Result

.....

Depends on the keyword

- DITHER (BOOLEAN)  
- SHOWNAMES (BOOLEAN)  
- HIQUALITY (BOOLEAN)  
- TSIZE ("SMALL", "STD", "BIG", "HUGE" or "XLARGE")

Example

.....

GETTPREFS DITHER

## 1.70 ImagedeskE.guide/M3\_STPRF

SETTPREFS

-----

Syntax

.....

SETTPREFS <keyword> <value>

Description

.....

Sets a thumbnail prefs adjustment to <value> (see also GETTPREFS). The argument type of <value> depends on the argument <keyword>. Valid keywords are:

- DITHER (BOOLEAN)  
- SHOWNAMES (BOOLEAN)  
- HIQUALITY (BOOLEAN)  
- TSIZE ("SMALL", "STD", "BIG", "HUGE" or "XLARGE")

Result

.....

NULL

Example

.....

---

```
SETTPREFS TSIZE STD
```

## 1.71 ImagedeskE.guide/M3\_SYSIN

```
GETSYSINFO
```

```
-----
```

Syntax

```
.....
```

```
GETSYSINFO <keyword>
```

Description

```
.....
```

Supplies the value of a specified system state variable. The result type depends on <keyword>. Valid keywords are:

- VERSION (supplies ImageDesk's current version number)
- GFXMODE (tells the graphics mode e.g. "CyberGfx")
- DESKSPACE (tells how much thumbnails currently fits on the desk)
- THUMBSUSED (tells how much thumbnails are currently in use)

Result

```
.....
```

Depends on the keyword

- VERSION (STRING)
- GFXMODE (STRING)
- DESKSPACE (INTEGER)
- THUMBSUSED (INTEGER)

Example

```
.....
```

```
GETSYSINFO VERSION
```

## 1.72 ImagedeskE.guide/M1\_TOOLS

Catalog Tools

```
*****
```

This distribution contains of several CLI-only tools. They serve for

---



touching up catalog files created by ImageDesk. The templates for running such a tool do accord with the Commodore style guides. For further explanation take a look into your AmigaDos Manuals.

```
CATList  
  
CATChPath  
  
CATRepack  
  
CATJoin  
  
CATRemEntry
```

### 1.73 ImagedeskE.guide/M11\_LIST

```
CATList  
=====
```

```
Template:  
-----
```

```
CATFILE/A,P=PASSWORD/K,F=FULL/S
```

```
Description:  
-----
```

Lists all entries of an ImageDesk catalog file in the order of their occurrence. This command is very useful to find out which position a specific entry has. To remove an entry, for example, it is necessary to know its position in the catalog file.

```
CATFILE/A  
    Path and filename of an ImageDesk catalog file.
```

```
P=PASSWORD/K  
    If a catalog file was generated by using xpk-password encryption,  
    the corresponding password has to be specified here.
```

```
F=FULL/S  
    Besides position and filename, this switch directs CATList to print  
    further attributes of the pictures.
```

### 1.74 ImagedeskE.guide/M11\_CPAT

```
CATChPath  
=====
```

---

Template:

-----

CATFILE/A,P=NEUPATH/A

Description:

-----

To avoid a repeated thumbnail generation run if a path of an image directory has changed, you should use this program. It changes the content of the pathname in a catalog file to the choices given by the user. As only the header of a catalog file is changed, it is not necessary to specify a password even if it has been encrypted before. In opposition to most of the other catalog tools, CATChPath is a so called 'In Place'-operation. This means, you should better work on a copy of a catalog file to avoid damaging this file if an error occurs.

CATFILE/A

Filename of the ImageDesk catalog to work on.

P=NEUPATH

A string which describes the path to image directory. It won't be checked for validity, so the user is responsible for the correctness.

## 1.75 ImagedeskE.guide/M11\_REPK

CATRepack

=====

Template:

-----

CATFILE/A,O=OUTFILE/K,X=XPKMETHOD/K,F=EFFICENCY/N,P=PASSWORD/K

Description:

-----

If the packing method or packing efficiency of a former generated catalog file is to be changed, this command has to be used. For example, you could save your catalog files uncompressed in ImageDesk and pack them afterwards with CATRepack. For security reasons an OUTFILE should be specified.

CATFILE/A

Filename of the ImageDesk catalog to work on.

O=OUTFILE/K

Name for the resulting output file. If this argument ist missing, the original file will be overwritten.

X=XPKMETHOD/K

Packing method to be used for the catalog file. Referring to the XPK conventions, this has to be an uppercase fourletter string.

X=NUKE for example would mean, XPK method NUKE has to be used. If this argument is missing or XPK has not been installed the file will be saved without packing.

F=EFFICENCY/N

Efficiency the under XPKMETHOD specified packmethod should work with. This has to be a number in the range between 0 and 100. Default value is 50.

P=PASSWORD/K

If the catalog file has been saved key-encrypted here the password has to be specified. This password will also be used for the new output file if XPKMETHOD supports passwords.

## 1.76 ImagedeskE.guide/M11\_JOIN

CATJoin

=====

Template:

-----

CATFILE1/A,CATFILE2/A,AS=TO/K/A,X=XPKMETHOD/K,F=EFFICENCY/N,P=PASSWORD/K

Description:

-----

Joins two catalog files to a new one. Provided that you have generated more than one catalog file for a image directory in ImageDesk - maybe to save memory. For later assembly this command has to be used. It is very important for CATFILE1 and CATFILE2 to have the same path entry for the image directory. CATJoin won't work if ImageDesk has not been registered - it is the only one of the catalog tools which requires the keyfile.

CATFILE1/A

Filename of the first ImageDesk catalog file.

CATFILE2/A

Filename of the second ImageDesk catalog file.

AS=TO/K/A

Name for the output file.

X=XPKMETHOD/K

Packing method to be used for the output file. Referring to the XPK conventions, this has to be an uppercase fourletter string. If this argument is missing or XPK has not been installed the file will be saved without packing.

F=EFFICENCY/N

Efficiency the under XPKMETHOD specified packmethod should work with. This has to be a number in the range between 0 and 100. Default value is 50.

---

P=PASSWORD/K

If the catalog files has been password-encrypted, you have to specify the password here. Unless the two input files use the same password, CATJoin returns with an error. In this case, one of them has to be adjusted with CATRepack to the other one. This password will also be used for the output file.

## 1.77 ImagedeskE.guide/M11\_RMEN

CATRemEntry

=====

Template:

-----

CATFILE/A,E=ENTRY/N/A,O=OUTFILE/K,X=XPKMETHOD/K,F=EFFICENCY/N,P=PASSWORD/K

Description:

-----

CATRemEntry removes the entry with the position number ENTRY from a catalog file. This could be necessary to re-establish the consistence between the catalog file and the contents of the image directory. By help of CATList you can find out the entrynumber you want to know. The other arguments show the same behaviour as they do in CATRepack.

CATFILE/A

Filename of the ImageDesk catalog to work on.

E=ENTRY/N/A

Postition of the entry to remove.

O=OUTFILE/K

Name for the resulting output file. If this argument is missing the original file will be overwritten.

X=XPKMETHOD/K

Packing method to be used for the output file. Referring to the XPK conventions, this has to be an uppercase fourletter string. If this argument is missing or XPK has not been installed the file will be saved without packing.

F=EFFICENCY/N

Efficiency the under XPKMETHOD specified packmethod should work with. This has to be a number in the range between 0 and 100. Default value is 50.

P=PASSWORD/K

If the catalog file has been saved key-encrypted here the password has to be specified. This password will also be used for the new output file if XPKMETHOD supports passwords.

---

## 1.78 ImagedeskE.guide/M1\_REGIS

How to Register

\*\*\*\*\*

As you may have noticed, ImageDesk is a shareware product. Nearly all functions are available for testing without paying any money. If you think ImageDesk is worth the amount of 30,- DM or \$20,-, refer to me for your personal keyfile.

The keyfile method offers the advantage to enjoy the whole functionality of new ImageDesk releases immediately. You do not have to wait until I send you a new fully featured version.

Besides the keyfile, you'll get the latest release of the ImageDesk distribution and a printed manual.

To get registered for ImageDesk, please print the file OrderForm on your printer (if no printer is available, write off this text), fill up this form and send it to the given address. I will endeavour to act upon your registration within two weeks after I get the register form and the sharefee. In most cases it will be done faster. Prospectively the keyfiles will be shipped by (snail)mail.

The author reserves the right, not to accept register requests.

Special Conditions

=====

Since I had stopped developping for FLIcasso, FLImer and FLItina some month ago, I offer all former registered users of these programs the opportunity to become registered for ImageDesk.

1. Registered version of ImageDesk without a printed manual: Send me a floppy disk, a stamped envelope addressed to yourself and the register form.
2. Registered version of ImageDesk, including a printed manual: Send me 10,- DM (or \$10,-) in cash and the register form.

## 1.79 ImagedeskE.guide/M1\_UPDAT

Updates

\*\*\*\*\*

When you become a registered user, you will get the latest release of ImageDesk together with your personal keyfile. Thereby, you are independent from a direct support by the author. You'll get the latest releases from Aminet (eventually other PD archives, too) instead.

If you do not have the possibility to get ImageDesk this way you could get it directly from the author. In this case, send me a letter and include 5,-DM (\$5,- if you do not live within the EU). This offer

is valid for registered users only.

## 1.80 ImagedeskE.guide/M1\_RIGHT

Legal Stuff

\*\*\*\*\*

Liability

Distribution

Trademarks

Copyright

## 1.81 ImagedeskE.guide/Liability

Liability

=====

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDER AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

## 1.82 ImagedeskE.guide/Distribution

Distribution

=====

It is allowed to distribute ImageDesk on any data medium and to make

---

it available on bulletin boards or other network compounds if the directory structure of the original Aminet release will be kept. No file may be added, removed or exchanged.

It is of course allowed to distribute ImageDesk in a packed archive file. It is also allowed to levy copy charges for the distribution on floppy disks or CD-ROMs, as long as it has stated clearly for the user that he has not payed for the share fee, hereby. It is not allowed to copy, distribute or generate keyfiles for ImageDesk without a written permission from the author.

#### Special Versions

-----

If you want me to program a special version of ImageDesk e.g. for the management of commercial image archive CD-ROMs, you should try to contact me.

## 1.83 ImagedeskE.guide/Trademarks

### Trademarks

=====

Workbench (TM), Intuition(TM) and Amiga (TM) are registered trademarks of Commodore Amiga Inc., West Chester, USA.

GIF(TM) and "Graphics Interchange Format"(TM) are registered trademarks of Compuserv Inc., Ohio, USA.

PCD(TM) and "Photo CD"(TM) are registered trademarks of Kodak Corp.

Windows(TM) is a registered trademark of Microsoft Corp.

## 1.84 ImagedeskE.guide/Copyright

### Copyright

=====

ImageDesk, the accompanying files and the ImageDesk manual is Copyright (C) 1994-1995, Reinhard Haslbeck. All Rights reserved.

The JPEG codec is Copyright c 1994 Christoph Feck, TowerSystems. All Rights Reserved. It is based in part on the work of the Independent JPEG Group.

## 1.85 ImagedeskE.guide/M1\_BUGRP

## Known Bugs

\*\*\*\*\*

The following bugs are known:

- \* If 'MagicMenu' has been installed some menu colors will be displayed wrongly.
- \* It has been reported, ImageDesk is unable to open a screen requester, if ReqChange has been installed. I could not check this out, because ReqChange crashes on my system. It is recommended not to use ReqChange (startup program is named RCstart), but to use Nico Francois's RTpatch instead.

## 1.86 ImagedeskE.guide/M1\_FUTUR

## Future

\*\*\*\*\*

The following list should give a reference which features future releases of ImageDesk may have. The succession of this list does not say anything, at all.

- \* Add a catalog browser
- \* Add a Toolbar

## 1.87 ImagedeskE.guide/M1\_HISTO

## Releases

\*\*\*\*\*

## 0.97 Beta

-----

First beta release.

## 0.98 Beta

-----

- \* Now the default publicscreen ist left to the workbench as long as it is not neccessary for ImageDesk to declare its screen to the default publicscreen.
  - \* Before closing the screen, ImageDesk now checks if other applications have opened their windows on ImageDesk's publicscreen.
  - \* Don't try to load IFF-ILBM images with unknown compression type anymore.
-



- \* Filenames for the external viewers may contain spaces, yet.
- \* The slidergadgets in the Load Catalog control window are now managed correctly.
- \* A few catalog file tools have been added (CATList, CATChPath, CATRepack, CATJoin and CATRemEntry).

#### 1.0 - first public release

-----

- \* Added internal window viewer.
- \* Removed small bug in the BMP reader.
- \* System font will be opened correct, now.
- \* Added dither option for 8-bit displays.

#### 1.01

----

- \* Fixed bug: Village Screenmode requester sometime has been opened on the workbench screen.
- \* Fixed bug in the JPEG Picasso viewer: 8-bit JPEGs where displayed wrongly on the 8-bit screens.
- \* Fixed a wrong palette entry in the 8-bit Picasso viewer.
- \* Improved display speed of the window viewer for truecolor images.

#### 1.02

----

- \* Added Scrollbars to the window viewer.

#### 1.1

----

- \* Added Switch 'Use Original Palette' for the window viewers.
- \* Now supports and generates project icons for catalogs.

#### 1.11

----

- \* Thumbnail generation from 4-bit BMPs reported an error - Fixed.
- \* Now The name of the screen is displayed instead of the ID in the System Prefs window.

#### 1.12

----

- \* 'Default Public Screen' has not been set back to workbench if the
-

Picasso screenrequester has been used - Fixed.

## 1.2

---

- \* Fixed bug: If no complete path has been specified for a catalog file to be generated, some problems could have been arised while saving.
- \* CyberGraphics and standard 8 bit intuition screens are supported.
- \* The state of Show Image Infos is stored in the prefs file.
- \* The information window now shows the current graphics board mode.
- \* Added new menu item Ask Before Cleaning Desk.
- \* Open Catalog now branches into subitems: Selectable and Quick.
- \* Added new menu item Mark & Delete for multiple thumbnail removal.
- \* Changed (Improved?) most of the screen displaying routines.
- \* The image information window now shows the path of the file too.

## 1.21

----

- \* The number of entries per catalog is now selectable in the range of 3 and 600.
- \* Now it is possible to interrupt the internal viewers at any time.
- \* A few internal changes.

## 1.22

----

- \* Removed problems in conjunction with MFR.
- \* Fixed bug in the window viewers which caused a very high CPU-load factor.
- \* Compacted program code in the Picasso screen viewers.

## 1.23

----

- \* IFF DCOL (Direct COLor) chunks are supported now.

## 1.3

---

- \* Fixed bug: The ILBM decoder had problems reading truecolor images which contains additionally palette information.
  - \* Fixed problem of reading ILBMs containing ANNO Chunks with a wrong
-

Chunk length field.

- \* Now it is possible to have file names being rendered below the thumbnail images.

#### 1.4

---

- \* Added Thumbnail Prefs window.
- \* Now supports further thumbnail sizes.
- \* Uses own font for thumbnail text.
- \* New option: Print Execution Command.
- \* Prefs windows retouched.
- \* Changed prefs file structure.
- \* New catalog file structure.
- \* Adapted all Catalog Tools to the new structure.

#### 1.41

----

- \* Fixed size and alignment problems on temporary rastports.

#### 1.42

----

- \* Support for environment variable KEYPATH added which specifies the location of the key file.

#### 1.5

---

- \* Integrated AREXX Port.
- \* Increased GIF decoding speed (twice as fast).
- \* ImageDescriptor instead of ScreenDescriptor is used for size determination of GIF thumbnails, now.
- \* Removed several smaller bugs.

#### 1.6

---

- \* Now executes AREXX programs on thumbnail click.
  - \* Enhanced hotkey handling.
  - \* New option HiQuality.
  - \* Further AREXX commands.
-

- \* Enhanced slider gadget handling.
- \* File requester attributes are stored in the prefs, now.
- \* Larger thumbnail sizes possible.
- \* Config will be saved before ImageDesk exits
- \* Bug in the PCX reader removed.
- \* Reduced stack consumption.

## 1.88 ImagedeskE.guide/M1\_THANX

Thanks

\*\*\*\*\*

The following people I have to thank a lot. Without them, ImageDesk would not exist (at least not in this appearance).

- Christoph Feck for his great job on the JPEG Codec.
  - Matthias Meixner for gengui which enables ImageDesk's size sensitive GUI.
  - Markus Wild for porting the GNU-C compiler to the Amiga.
  - Urban Dominik Müller and all others who worked on XPK.
  - Reinhard Spisser and Sebastiano Vigna for the amiga release of MakeInfo.
  - Erik Gerl, Christian Herzinger, Thomas Kummer, Jernej Pecjak, Christian Rattei, Michael Böhmer for betatesting and their suggestions.
  - Martin Pflingstl for allowing me to test on his A4000/40.
  - Renate Valenta for her helping hand on the translation of the manual.
  - Frank Mariak for his help on my CyberGraphics problems.
  - Dan Zerkle for his corrections on my Announcement.
  - Jocelyn Levac for drawing MagicWB-styled icons and for being a nice guy.
  - Ignaz Kellerer for sending me IFFs ImageDesk had problems with.
  - Matthias Scheler for his work as Aminet-Admin and for his suggestions.
-

All these people could get a registered version of ImageDesk if they want (For this make a remark on the register form).

## 1.89 ImagedeskE.guide/M1\_AUTOR

Author

\*\*\*\*\*

Reinhard Haslbeck  
Spirknerstr. 7  
84137 Vilsbiburg

FR GERMANY

Tel. +49 (0)8741/91212

Fax. +49 (0)8741/7140

e-mail: Internet [haslbeck@informatik.tu-muenchen.de](mailto:haslbeck@informatik.tu-muenchen.de)  
or [haslbeck@leo.org](mailto:haslbeck@leo.org)

---