



## SENS™ PRO 500



### Notebook PC

---

<b>Microprocessor</b>	Intel Pentium® 100, 120, 133, 150MHz
<b>L2 Cache</b>	256K synchronous pipeline burst
<b>Display</b>	11.3" SVGA dual scan color 12.1" SVGA active matrix
<b>Video Sub-System</b>	32-bit PCI local bus with graphics acceleration 1 MB of video RAM
<b>RAM</b>	8MB EDO RAM standard 72 MB max 6MB EDO RAM standard 80 MB max
<b>Storage</b>	1.08 GB hard disk drive 1.44 GB hard disk drive 2.1 GB hard disk drive
<b>Multimedia</b>	Optional 6x CD-ROM (100MHz and 120MHz models), 6x CD-ROM drive (133MHz and 150MHz models)
<b>PC Cards</b>	2 Type II or Type III PCMCIA slots
<b>Pointing Device</b>	Integrated touch sensitive SENS pad
<b>Battery</b>	NIMH Battery Lithium Ion Battery
<b>Standard Interface</b>	1 Parallel (ECP, EPP mode), 1 Serial (16550A UART), PS/2 keyboard/mouse, external microphone jack and headphone jack

**Options** Spare lithium Ion/NIMH batteries  
memory upgrades (8MB, 16MB, 32MB)  
external quick charger,  
automobile adapter,  
carrying case,  
mini dock/port replicator

**Dimensions** 11.8" X 9.4" X 1.87"

**Weight** Under 7 lbs. with FDD