



# 1 Guide to using VVcode

- general introduction

## 1.1 VVencode command options

- described in a generic manner with operating system specifics at the end of the section

The general syntax of the VVencode command line is:

```
vvencode [options] input-file [options] [output-file] [options]
```

There are two *parameters* and many optional *qualifiers*. The parameters are:

**input-file**

**output-file**

The command qualifiers modify the behaviour of VVcode and are all optional. Qualifiers may appear before, between or after the parameters. The qualifiers acceptable to VVencode are:

**debug** Write copious debugging output to the standard error device or to the log file if the **+log** qualifier was specified. This qualifier would normally only be used when trying to report a VVencode problem and may indeed have been disabled for the version that you are using.

**encoding\_table file-spec**

Read the encoding table to be used from the file 'file-spec'. The file must contain the 64 characters to be used by VVencode. If this qualifier is not specified, the default VVencode encoding table will be used.

**format file-format**

Explicitly specify the file format that should be assumed by VVencode when it is reading the input file. The **file-format** value must be one of 'fixed', 'stream' and 'variable'. This qualifier would only be used if it was necessary to override the value determined automatically by VVencode.

**header\_filespec file-spec**

**help** VVencode will display a usage message on the standard error device and exit.

**log file-spec**

**mode file-mode**

Explicitly specify the file mode that should be assumed by VVencode when it is reading the input file. The **file-format** value must be one of 'binary' and 'text'. This qualifier would only be used if it was necessary to override the value determined automatically by VVencode.

**overwrite**

**record\_length**

**split\_size**

timestamp time

translation\_file file-spec

## 1.2 VVdecode command options

The general syntax of the VVdecode command line is:

```
vvdecode [options] input-file [options] [output-file] [options]
```

## 1.3 Operating system specific considerations

### 1.3.1 MS-DOS

- qualifiers introduced with '/' or '-' and must be separated from each other by whitespace
- values separated from qualifier by '=' or ':'
- optional values supported
- VVcode will act as a filter when '-' is specified as the input or output file
- optional file specification for 'log' qualifier
- examples of VVencode usage

### 1.3.2 OS/2

- qualifiers introduced with '/' or '-' and must be separated from each other by whitespace
- values separated from qualifier by '=' or ':'
- optional values supported
- VVcode will act as a filter when '-' is specified as the input or output file
- optional file specification for 'log' qualifier
- GCC 2.1 implementation does not support file timestamping
- HPFS file names supported
- OS/2 extended attributes not supported yet
- examples of VVencode usage

### 1.3.3 Unix

- qualifiers introduced with '-' or '+' and must be separated from each other by whitespace
- values separated from qualifier by whitespace
- optional values not supported
- VVcode will act as a filter when '-' is specified as the input or output file
- examples of VVencode usage

### 1.3.4 VAX/VMS

- qualifiers introduced with '/'
- values separated from qualifier by '='
- standard VMS CLD conventions
- optional values supported
- VVcode will act as a filter when '-' is specified as the input or output file though meaningless on VMS
- optional file specification for 'log' qualifier
- examples of VVencode usage

### 1.3.5 VM/CMS

- qualifiers introduced with '(' and must be separated from each other by whitespace
- values separated from qualifier by '=' or ':'
- command line driven through REXX EXEC
- optional values supported
- VVcode does not support input or output from/to standard I/O
- optional file specification for 'log' qualifier
- examples of VVencode usage

## 1.4 Transferring files between systems

- file type and format
- character set
- electronic mail
- timestamping

## 1.5 Unusual applications of VVcode

- character set conversion
- file type conversion
- VMS file format conversion vs. CONVERT

# Table of Contents

<b>1</b>	<b>Guide to using VVcode</b> .....	<b>2</b>
1.1	VVencode command options .....	2
1.2	VVdecode command options .....	3
1.3	Operating system specific considerations .....	3
1.3.1	MS-DOS .....	3
1.3.2	OS/2 .....	3
1.3.3	Unix .....	3
1.3.4	VAX/VMS .....	4
1.3.5	VM/CMS .....	4
1.4	Transferring files between systems .....	4
1.5	Unusual applications of VVcode .....	4