

[technical specifications]

eicon
technology
corporation

EiconCard C20

■ **Hardware Features**

- ISA 8-bit Plug-and-Play
- Motorola 68302 @ 15.36MHz
- RAM: 512K
- FLASH memory: 512K
- Interrupt level and I/O address: automatically assigned by Plug-and-Play
- V.24 serial interface port
- LED indicator

■ **Serial Port**

- DB-25 female connector (EIA RS-232-C)
- Line speed up to 64 Kbps
- Internal or external clocking
- Protocol support: X.25, Frame Relay, PPP, SDLC, HDLC
- Throughput:
 - X.25: 300 pps
 - Frame Relay: 350 pps

■ **Maximum Power Requirements**

- 1.5 A at +5 Volts
- 50 mA at +12 Volts
- 50 mA at -12 Volts

■ **Environment Requirements**

- Operating temperature: 0°C to 50°C
- Operating humidity: 0 to 90% (non-condensing)
- Barometric operating pressure: 86 to 106 kPascals
- Maximum tolerance in power supply variation: +5% to -5%



■ **Certification**

- FCC Class B, Part 15
- CE marking

■ **Warranty**

- 5-year

■ **Dimensions**

- 6.195" x 3.45" (15.74cm x 8.76cm)

■ **Supported OS platforms**

- UNIX

■ Packaging Contents

- EiconCard C20
- EiconCard C20 Installation Guide
- Hardware Diagnostic diskette
-

-
-
-
-



• Product Name	• Product Code
• EiconCard C20	• 310-198
• Related Accessories	
• V.24 RS-232 modem cable	• 310-007
• V.24 RS-232 null modem cable	• 310-022
• V.24 RS-232 gender-changed null modem cable	• 310-048

-

Eicon Technology Corporation

Tel.: (514) 745-5500
Fax: (514) 745-5588

In the United States, Canada, Latin America:

Tel.: 1-800-80-EICON
(214) 239-3270
Fax: (214) 239-3304

In Europe, Middle East, Africa:

Tel.: (44) 181 967-8000
Fax: (44) 181 967-8050

In Australia, New Zealand, Asia:

Tel.: (61) 2 9919-7200
Fax: (61) 2 9929-6300

Internet:

North America: sales@eicon.com
Europe: sales.europe@eicon.com
Asia Pacific:
sales.asiapac@eicon.com
Worldwide Web:
<http://www.eicon.com/>

