

[technical specifications]

eicon
technology
corporation

EiconCard C21

■ Hardware Features

- ISA 8-bit Plug-and-Play
- Motorola 68302 @ 15.36MHz
- RAM: 512K
- FLASH memory: 512K
- Interrupt level and I/O address: automatically assigned by Plug-and-Play
- V.24 serial interface port
- ISDN Basic Rate Interface port
- LED indicator

■ Serial Port

- DB-25 female connector (EIA RS-232-C)
- Line speed up to 64 Kbps
- Internal or external clocking

Protocol support: X.25, Frame Relay, PPP, SDLC, HDLC

- Throughput:
 - X.25: 300 pps
 - Frame Relay: 350 pps

■ ISDN Port

- DIN-4 female connector
- S/T interface using external cable assembly (RJ45)
- U interface using Eicon ISDN NT1
- Line speed up to 128 Kbps
- Channel support:
 - B-channel circuit switched
 - B-channel packet switched (X.31 case A, B)
 - D-channel circuit switched (X.31 case B)
- B-channel protocol support: X.25, Frame Relay, PPP, Multilink PPP, SDLC, HDLC
- D-channel protocol support: X.25

■ Maximum Power Requirements

- 1.5 A at +5 Volts

- 50 mA at +12 Volts
- 50 mA at -12 Volts

■ Environment Requirements

- Operating temperature: 0°C to 50°C
- Operating humidity: 0 to 90% (non-condensing)
- Barometric operating pressure: 86 to 106 kPascals
- Maximum tolerance in power supply variation: +5% to -5%

■ Certification

- FCC Class B, Part 15
- CE marking
- Industry Canada (formerly DOC)
- National ISDN-1 (NI-1)
- AT&T 5ESS Custom
- Euro-ISDN (including German, French and Swiss extensions)
- JATE (Japan)

■ Warranty

- 5-year

■ Dimensions

- 6.195" x 3.45" (15.74cm x 8.76cm)

■ Supported OS platforms

- DOS
- UNIX
- Windows 3.x
- Windows NT
-
-

■ Packaging Contents

- EiconCard C21
- EiconCard C21 Installation Guide
- Hardware Diagnostic diskette
- *with ISDN S/T interface cable*
 - ISDN S/T Interface cable
 - RJ45 cable
 - Terminating Resistor (except Europe and Japan)
- *with ISDN NT1*

- Eicon ISDN NT1 unit and associated cable
- power supply for NT1
- Eicon ISDN NT1 installation guide
- RJ45 cable

-
-
-
-
-

• Product Name	• Product Code
• EiconCard C21	• 310-150
• EiconCard C21 with ISDN S/T cable	• 310-118
• EiconCard C21 with ISDN NT1 unit	• 310-158
• Related Accessories	
• V.24 RS-232 modem cable	• 310-007
• V.24 RS-232 null modem cable	• 310-022
• V.24 RS-232 gender-changed null modem cable	• 310-048
• ISDN S/T1 cable - North America	• 310-090
• ISDN S/T1 cable - Europe, Japan	• 310-092
• ISDN NT1 unit	• 310-095
• ISDN N/T1 cable - North America only	• 310-097

Eicon Technology Corporation

Tel.: (514) 745-5500
Fax: (514) 745-5588

In the United States, Canada, Latin America:

Tel.: 1-800-80-EICON
(214) 239-3270
Fax: (214) 239-3304

In Europe, Middle East, Africa:

Tel.: (44) 181 967-8000
Fax: (44) 181 967-8050

In Australia, New Zealand, Asia:

Tel.: (61) 2 9919-7200
Fax: (61) 2 9929-6300

Internet:

North America: sales@eicon.com
Europe: sales.europe@eicon.com
Asia Pacific: sales.asiapac@eicon.com
Worldwide Web: <http://www.eicon.com/>

