

EiconCard C20

■ Hardware Features

- ISA 8-bit Plug-and-Play
- Motorola 68302 @ 15.36MHz
- RAM: 512K
- FLASH memory: 512K
- Interrupt level and I/O address: automatically assigned by Plug-and-Play
- V.24 serial interface port
- LED indicator

■ Serial Port

- DB-25 female connector (EIA RS-232-C)
- Line speed up to 64 Kbps
- Internal or external clocking
- Protocol support: X.25, Frame Relay, PPP, SDLC, HDLC

■ Maximum Power Requirements

- 1.5 A at +5 Volts
- 50 mA at +12 Volts
- 50 mA at -12 Volts

■ Environment Requirements

- Operating temperature: 0°C to 50°C
- Operating humidity: 0 to 90% (non-condensing)
- Barometric operating pressure: 86 to 106 kPascals
- Maximum tolerance in power supply variation: +5% to -5%

■ Certification

- FCC Class B, Part 15
- CE168X marking
- Microsoft HCL

■ Warranty

- 5-year

■ Dimensions

- 6.195" x 3.45" (15.74cm x 8.76cm)

■ Supported OS platforms

- DOS
- UNIX
- Windows® 3.x
- Windows® 95
- Windows NT®

■ Packaging Contents

- EiconCard C20
- EiconCard C20 Installation Guide
- Hardware Diagnostic diskette

Ordering Information	
Product Name	Product Code
EiconCard C20	310-198
Related Accessories	
V.24 DCE cable	300-007
V.24 null-modem cable	300-022
V.24 null-modem cable (gender-changed)	300-048

Eicon Technology Corporation

Tel.: (514) 745-5500
Fax: (514) 745-5588

**In the United States, Canada,
Latin America:**

Tel.: 1-800-80-EICON
(214) 239-3270
Fax: (214) 239-3304

In Europe, Middle East, Africa:

Tel.: +44 (0) 181 967-8000
Fax: +44 (0) 181 967-8050

In Australia, New Zealand, Asia:

Tel.: +61 (2) 9919-7200
Fax: +61 (2) 9929-6300

Internet:

North America: sales@eicon.com
Europe: sales.europe@eicon.com
Asia Pacific: sales.asiapac@eicon.com
Worldwide Web: <http://www.eicon.com/>



© 1997 Eicon Technology Corporation. All rights reserved.
All trademarks or registered trademarks are the property of their respective owners.