

EiconCard C30

■ **Hardware Features**

- PCMCIA Type II Release 2.1
- Motorola 68302 @ 15.36MHz
- RAM: 512K
- FLASH memory: 512K
- Interrupt level and I/O address:
automatically assigned by Plug-and-
Play
- V.24 serial interface port

■ **Serial Port**

- DB-25 female connector (EIA RS-
232-C) using external cable assembly
- Line speed up to 64 Kbps
- Internal or external clocking
- Protocol support: X.25, Frame Relay,
PPP, SDLC, HDLC

■ **Maximum Power Requirements**

- 200 mA at +5 Volts

■ **Environment Requirements**

- Operating temperature: 0°C to 50°C
- Operating humidity: 0 to 90% (non-
condensing)
- Barometric operating pressure: 86 to
106 kPascals
- Maximum tolerance in power supply
variation: +5% to -5%

■ **Certification**

- FCC Class B, Part 15
- CE68X marking

■ **Warranty**

- 5-year

■ **Dimensions**

- 2.918" x 2.015" (7.41cm x 5.12cm)

■ **Supported OS platforms**

- DOS
- Windows® 95

■ Packaging Contents

- EiconCard C30
- EiconCard C30 Installation Guide
- Hardware Diagnostic diskette
- V.24 DCE cable

Ordering Information	
Product Name	Product Code
EiconCard C30	310-199
Related Accessories	
PC Card V.24 DCE cable	300-084

Eicon Technology Corporation

Tel.: (514) 745-5500
 Fax: (514) 745-5588

In the United States, Canada, Latin America:

Tel.: 1-800-80-EICON
 (214) 239-3270
 Fax: (214) 239-3304

In Europe, Middle East, Africa:

Tel.: +44 (0) 181 967-8000
 Fax: +44 (0) 181 967-8050

In Australia, New Zealand, Asia:

Tel.: +61 (2) 9919-7200
 Fax: +61 (2) 9929-6300

Internet:

North America: sales@eicon.com
 Europe: sales.europe@eicon.com
 Asia Pacific: sales.asiapac@eicon.com
 Worldwide Web: <http://www.eicon.com/>



© 1997 Eicon Technology Corporation. All rights reserved.
 All trademarks or registered trademarks are the property of their respective owners.