

[technical specifications]

eicon
technology
corporation

DIVA

■ Hardware

- ISA bus
- 160mm x 73mm
- I/O address setting with software-based interrupt setting
- Digital Signal Processor with 40 MHz internal clock, 16 MIPS
- 96Kbyte on-board memory
- Basic Rate Interface

■ Connection Types

- Switched & Permanent

■ B-Channel Layer 2 Protocols

- PPP
- X.25 (LAPB)
- LAPB

■ B-Channel Layer 3 Protocols

- X.25 PLP
- T.90 NL
- T.70 NL

■ D-Channel Protocols

- NI-1 (North America National ISDN-1)
- 5ESS (North America - AT&T)
- ITR6 (Germany)
- DSS1
- ETSI (Euro-ISDN)
- Japan
- Belgium
- France
- ATEL (Australia)
- X.25 PLP

■ Workstation Requirements

- 80386 or higher
- Appropriate Operating System

-



■ **Packaging Contents**

- DIVA Hardware
- Cabling (RJ45)
- User Manual
- B and D Channel trace program
- IDI (ISDN Direct Interface)

-
-
-
-
-

• Product Name	• Product Code
• DIVA	• 310-182

• Related [items]	
• DIVA with Eicon NT-1	• 310-173
• DIVA for Windows 95	• 305-032
• DIVA for Windows 95 with Eicon NT-1	• 305-092
• DIVA for Windows NT	• 305-034
• DIVA for Windows NT with Eicon NT-1	• 305-093
• DIVA for Windows 3.x	• 305-033
• DIVA for Windows 3.x with Eicon NT-1	• 305-172
• DIVA MCA (Microchannel)	• 310-183
• DIVA MCA (Microchannel) with Eicon NT-1	• 310-171

-
-
-

Eicon Technology Corporation

Tel.: (514) 745-5500
 Fax: (514) 745-5588

In the United States, Canada, Latin America:

Tel.: 1-800-80-EICON
 (214) 239-3270
 Fax: (214) 239-3304

In Europe, Middle East, Africa:

Tel.: (44) 181 967-8000
 Fax: (44) 181 967-8050

In Australia, New Zealand, Asia:

Tel.: (61) 2 9919-7200
 Fax: (61) 2 9929-6300

Internet:

North America: sales@eicon.com
 Europe: sales.europe@eicon.com
 Asia Pacific: sales.asiapac@eicon.com
 Worldwide Web: http://www.eicon.com/



