

[technical specifications]

eicon
technology
corporation

DIVA PCM

- **Hardware**
 - PCMCIA Type II
 - 85mm x 54mm x 5mm
 - Plug and Play by card and socket services
 - Digital Signal Processor with 40 MHz internal clock, 16 MIPS
 - 96Kbyte on-board memory
 - Basic Rate Interface
- **Connection Types**
 - Switched & Permanent
- **B-Channel Layer 2 Protocols**
 - PPP
 - X.25 (LAPB)
 - LAPB
- **B-Channel Layer 3 Protocols**
 - X.25 PLP
 - T.90 NL
 - T.70 NL
- **D-Channel Protocols**
 - NI-1 (North America National ISDN-1)
 - 5ESS (North America - AT&T)
 - ITR6 (Germany)
 - DSS1
 - ETSI (Euro-ISDN)
 - Japan
 - Belgium
 - France
 - ATEL (Australia)
 - X.25 PLP
- **Workstation Requirements**
 - 80386 or higher
 - Appropriate Operating System
 -
-

■ **Packaging Contents**

- DIVA Hardware
- DAA Mouse cable
- Cabling (RJ45)
- User Manual
- Cardservice Enabler
- B- and D- Channel trace program
- IDI (ISDN Direct Interface)
-

-
-
-
-
-
-
-
-



• Product Name	• Product Code
• DIVA PCM	• 310-184
• Related [items]	
• DIVA PCM with Eicon NT-1	• 310-172
• DIVA for Windows 95	• 305-025
• DIVA for Windows 95 with Eicon NT-1	• 305-090
• DIVA for Windows NT	• 305-026
• DIVA for Windows NT with Eicon NT-1	• 305-091
• DIVA for Windows 3.x	• 305-024
• DIVA for Windows 3.x with Eicon NT-1	• 305-173

Eicon Technology Corporation

Tel.: (514) 745-5500
Fax: (514) 745-5588

In the United States, Canada, Latin America:

Tel.: 1-800-80-EICON
(214) 239-3270
Fax: (214) 239-3304

In Europe, Middle East, Africa:

Tel.: (44) 181 967-8000
Fax: (44) 181 967-8050

In Australia, New Zealand, Asia:

Tel.: (61) 2 9919-7200
Fax: (61) 2 9929-6300

Internet:

North America: sales@eicon.com
Europe: sales.europe@eicon.com
Asia Pacific: sales.asiapac@eicon.com
Worldwide Web: <http://www.eicon.com/>

