

*[technical specifications]*

eicon  
technology  
corporation

---

# ***Diva Pro 1.0***

## ■ Hardware

- ISA bus
- 260mm x 82mm
- Plug and Play
- Digital Signal Processor with 133 MHz internal clock, 33 MIPS
- 80Kbyte on-board memory
- Basic Rate Interface

## ■ Connection Types

- Switched & Permanent

## ■ B-Channel Protocols

- PPP
- V.32bis
- HDLC
- X.75
- T.30
- X.25 PLP
- X.25 (LAPB)
- LAPB
- T.90 NL
- T.70 NL
- V.110
- V.120

## ■ D-Channel Protocols

- NI-1 (North America National ISDN-1)
- 5ESS (North America - AT&T)
- ITR6 (Germany)
- DSS1
- ETSI (Euro-ISDN)
- Japan
- Belgium
- France
- ATEL (Australia)
- X.25 PLP



## ■ Workstation Requirements

- 80486 or higher
- Appropriate Operating System



■ **Packaging Contents**

- DIVA Pro hardware
- RJ45 Cable
- User Guide
- B and D Channel trace program
- IDI (ISDN Direct Interface)

• <b>Product Name</b>	• <b>Product Code</b>
• DIVA Pro 1.0	• 310-175

• <b>Related [items]</b>	
• DIVA Pro 1.0 with Eicon NT-1	• 310-218
• DIVA for Windows 95 (DIVA Pro)	• 305-101
• DIVA for Windows 95 (DIVA Pro) with Eicon NT-1	• 305-102
• DIVA for Windows NT (DIVA Pro)	• 305-103
• DIVA for Windows NT (DIVA Pro) with Eicon NT-1	• 305-104

- 
- 
- 
- 
- 

**Eicon Technology Corporation**

Tel.: (514) 745-5500  
 Fax: (514) 745-5588

**In the United States, Canada, Latin America:**

Tel.: 1-800-80-EICON  
 (214) 239-3270  
 Fax: (214) 239-3304

**In Europe, Middle East, Africa:**

Tel.: (44) 181 967-8000  
 Fax: (44) 181 967-8050

**In Australia, New Zealand, Asia:**

Tel.: (61) 2 9919-7200  
 Fax: (61) 2 9929-6300

**Internet:**

North America: sales@eicon.com  
 Europe: sales.europe@eicon.com  
 Asia Pacific: sales.asiapac@eicon.com  
 Worldwide Web: http://www.eicon.com/

