

*[technical specifications]*

eicon  
technology  
corporation

---

# ***EiconCard C20***

## ■ **Hardware Features**

- ISA 8-bit Plug-and-Play
- Motorola 68302 @ 15.36MHz
- RAM: 512K
- FLASH memory: 512K
- Interrupt level and I/O address: automatically assigned by Plug-and-Play
- V.24 serial interface port
- LED indicator

## ■ **Serial Port**

- DB-25 female connector (EIA RS-232-C)
- Line speed up to 64 Kbps
- Internal or external clocking
- Protocol support: X.25, Frame Relay, PPP, SDLC, HDLC
- Throughput:
  - X.25: 300 pps
  - Frame Relay: 350 pps

## ■ **Maximum Power Requirements**

- 1.5 A at +5 Volts
- 50 mA at +12 Volts
- 50 mA at -12 Volts

## ■ **Environment Requirements**

- Operating temperature: 0°C to 50°C
- Operating humidity: 0 to 90% (non-condensing)
- Barometric operating pressure: 86 to 106 kPascals
- Maximum tolerance in power supply variation: +5% to -5%



## ■ **Certification**

- FCC Class B, Part 15
- CE marking

## ■ **Warranty**

- 5-year

## ■ **Dimensions**

- 6.195" x 3.45" (15.74cm x 8.76cm)

## ■ **Supported OS platforms**

- UNIX

## ■ Packaging Contents

- EiconCard C20
- EiconCard C20 Installation Guide
- Hardware Diagnostic diskette
- 

- 
- 
- 
- 



• Product Name	• Product Code
• EiconCard C20	• 310-198
• Related Accessories	
• V.24 RS-232 modem cable	• 310-007
• V.24 RS-232 null modem cable	• 310-022
• V.24 RS-232 gender-changed null modem cable	• 310-048

- 

### Eicon Technology Corporation

Tel.: (514) 745-5500  
Fax: (514) 745-5588

### In the United States, Canada, Latin America:

Tel.: 1-800-80-EICON  
(214) 239-3270  
Fax: (214) 239-3304

### In Europe, Middle East, Africa:

Tel.: (44) 181 967-8000  
Fax: (44) 181 967-8050

### In Australia, New Zealand, Asia:

Tel.: (61) 2 9919-7200  
Fax: (61) 2 9929-6300

### Internet:

North America: sales@eicon.com  
Europe: sales.europe@eicon.com  
Asia Pacific:  
sales.asiapac@eicon.com  
Worldwide Web:  
<http://www.eicon.com/>

