

*[technical specifications]*

eicon  
technology  
corporation

---

# ***EiconCard EC/PC***

## ■ **Hardware Features**

- ISA 8-bit
- Motorola 68008 @ 10MHz
- RAM: 1 MB
- Interrupt levels selectable via software (2, 3, 4, 5, 6, 7)
- I/O address selectable via on-board switch (14 options)
- 4K shared memory access with a software selectable starting address (32 options between A000-DFFF)
- V.24 serial interface port

- DOS
- NetWare
- OS/2
- UNIX
- Windows 3.x
- Windows NT

## ■ **Serial Port**

- DB-25 female connector (EIA RS-232-C)
- Line speed up to 64 Kbps
- Internal or external clocking
- Protocol support: X.25, Frame Relay, PPP, SDLC, HDLC
- Throughput:
  - X.25: 50 pps
  - Frame Relay: 80 pps

## ■ **Maximum Power Requirements**

- 1.0 A at +5 Volts
- 45 mA at +12 Volts
- 45 mA at -12 Volts

## ■ **Environment Requirements**

- Operating temperature: 0°C to 50°C
- Operating humidity: 0 to 90% (non-condensing)

## ■ **Certification**

- FCC Class B, Part 15
- CE marking
- 

## ■ **Warranty**

- 5-year

## ■ **Dimensions**

- 7.8" x 4.2" (19.81cm x 10.67cm)

## ■ **Supported OS platforms**

## Packaging Contents

- EiconCard EC/PC
- EiconCard EC/PC Installation Guide
- Hardware Diagnostic diskette
- 

• <b>Product Name</b>	• <b>Product Code</b>
• EiconCard EC/PC	• 310-053
• <b>Related Accessories</b>	
• V.24 RS-232 modem cable	• 310-007
• V.24 RS-232 null modem cable	• 310-022
• V.24 RS-232 gender-changed null modem cable	• 310-048

•

•

•

•

•

### Eicon Technology Corporation

Tel.: (514) 745-5500  
Fax: (514) 745-5588

### In the United States, Canada, Latin America:

Tel.: 1-800-80-EICON  
(214) 239-3270  
Fax: (214) 239-3304

### In Europe, Middle East, Africa:

Tel.: (44) 181 967-8000  
Fax: (44) 181 967-8050

### In Australia, New Zealand, Asia:

Tel.: (61) 2 9919-7200  
Fax: (61) 2 9929-6300

### Internet:

North America: sales@eicon.com  
Europe: sales.europe@eicon.com  
Asia Pacific: sales.asiapac@eicon.com  
Worldwide Web: <http://www.eicon.com/>

