

*[technical specifications]*

eicon  
technology  
corporation

---

# ***ISDN Server for Windows NT***

## ■ Hardware

- SCOM
  - Basic Rate Interface (2B+D)
  - 8MHz microprocessor with 1MB of on-board RAM
- Quadro
  - Four Basic Rate Interfaces (8B+4D)
  - Four microprocessors: 8MHz each and 512KB of on-board RAM
- S<sub>2M</sub>
  - Primary Rate Interface (30B+D or 23B+D)
  - 33MHz i486 microprocessor with 4MB of on-board RAM

## ■ Connection Types

- Switched & Permanent

## ■ B-Channel Layer 2 Protocols

- PPP
- X.25 (LAPB)
- LAPB

## ■ B-Channel Layer 3 Protocols

- X.25 PLP
- T.90 NL
- T.70 NL

## ■ D-Channel Protocols

- NI-1 (North America National ISDN-1)
- 5ESS (North America - AT&T)
- ITR6 (Germany)
- DSS1
- ETSI (Euro-ISDN)
- Japan
- Belgium
- France
- ATEL (Australia)
- X.25 PLP



## ■ Installation & Configuration

- GUI-based

## ■ Workstation Requirements

- 80386 or higher
- Microsoft Windows NT™



■ **Packaging Contents**

- ISDN Adapter
- Cabling
- User Manual
- B- and D-channel trace program
- IDI (ISDN Direct Interface\_

- 
- 
- 
- 
- 



• <b>Product Name</b>	• <b>Product Code</b>
• ISDN Server for Windows NT (SCOM)	• 305-035
• ISDN Server for Windows NT (Quadro)	• 305-088
• ISDN Server for Windows NT (S <sub>2M</sub> )	• 305-089
• <b>Related [items]</b>	
• SCOM	• 310-185
• Quadro	• 310-187
• S <sub>2M</sub>	• 310-188

- 

**Eicon Technology Corporation**

Tel.: (514) 745-5500  
 Fax: (514) 745-5588

**In the United States, Canada, Latin America:**

Tel.: 1-800-80-EICON  
 (214) 239-3270  
 Fax: (214) 239-3304

**In Europe, Middle East, Africa:**

Tel.: (44) 181 967-8000  
 Fax: (44) 181 967-8050

**In Australia, New Zealand, Asia:**

Tel.: (61) 2 9919-7200  
 Fax: (61) 2 9929-6300

**Internet:**

North America: sales@eicon.com  
 Europe: sales.europe@eicon.com  
 Asia Pacific:  
 sales.asiapac@eicon.com  
 Worldwide Web:  
<http://www.eicon.com/>

