

MACHINE,C,\\$VAMACHNAME,C,		
ibmx	0	IBM XT
ibmat	0	IBM AT
ibm70	0	IBM Model 70
ibm90	0	IBM Model 90
Comp386N	0	Compaq 386N
comp25e	0	Compaq 25e

Sheet1

DESCRIPT,C,225

IBM XT, 8088-4.8, 640 K conventional memory, 1.6 MB expanded, IBM color EGA adapter (with 256K), ST-412 interface, 10
IBM AT, 286-8, 640K conventional memory, 2 MB extended, 1.9 MB expanded, IBM monochrome VGA, ST-506 disk interface
IBM Model 70, 386-25, 32K processor RAM cache, 2 MB RAM, VGA, IBM ESDI disk adapter, 120 MB disk, IBM DOS 5.0, EM
IBM Model 90, 486-33, 256K second level processor RAM cache, 8 MB RAM, XGA, IBM SCSI 32 with 512K cache, 157 MB d
Compaq Deskpro 386N , 386sx-16, 5MB, Mono VGA, IDE 40MB HD, Compaq DOS 5.0, CEMM providing 1 MB expanded me
Compaq Deskpro 386/25e, 32K processor RAM cache, 4 MB memory, VGA, Compaq ESDI controller, 320 MB hard disk, Cor

CPFP CPUSPEED,N,3,0

1	1	477
6	2	800
7	3	0
9	3	0
8	0	0
7	3	0