

Contents

[Introduction](#)

[Connecting to a server](#)

[Joining a channel](#)

[Chatting privately](#)

[Sending & receiving files](#)

[Changing colours](#)

[Setting options](#)

[Basic IRC commands](#)

[mIRC commands](#)

[Aliases, Popups, & Remote](#)

[Variables & Identifiers](#)

[Other features](#)

[The Author](#)

[License Agreement](#)

[How to Register](#)

[Acknowledgements](#)

Introduction

Welcome to **mIRC v5.0**, an Internet Relay Chat Client.

mIRC attempts to provide a user-friendly interface for use with the **Internet Relay Chat** network. The IRC network is a **virtual meeting place** where people from all over the world can meet and talk.

To IRC all you need to do is Connect to a server, Join a channel, and **Chat!**

mIRC will guide you through these initial stages and hopefully you'll be chatting in no time. If you get stuck or want to find out more about a certain feature, just click on a Help button eg. in the Setup dialog, and you should find some hints there to help you.

As you become more **experienced** you can also start **configuring** mIRC's features to suit your own needs and tastes, features such as colours, fonts, function keys, aliases, popup menus, scripts, sounds and many others.

Remember to visit the **mIRC homepage** or one of it's mirror sites regularly for the latest version information, as well as for links to other mIRC and IRC related information and websites.

United Kingdom <http://www.mirc.co.uk>

This website is owned by **Khaled Mardam-Bey**, the author of mIRC, and is maintained by **Tjerk Vonck**, the author of the mIRC homepage and FAQ.

Kuwait	http://www.moc.kw/mirc
USA	http://www2.axi.net/mirc
Brazil	http://www.conesul.com.br/mirc
South Africa	http://splash.ee.techpta.ac.za/~mirc
The Netherlands	http://www-2.nijenrode.nl/software/mirc
USA	http://www.geocities.com/SiliconValley/Park/6000

The above are **mirror sites** which are updated regularly with the same information as the main mIRC website.

Below you'll find a **selection** of additional mIRC and IRC related websites which are maintained by **IRC enthusiasts**. Keep in mind that websites come and go, so some of these addresses might become outdated at some time.

mIRC info provided by mIRC addicts and lovers:

mIRC Tricks	http://www.phoenix.net/~lsimon/mirc.html
mIRC Tips	http://leonardo.spidernet.net/Copernicus/831/mirc/home.html
mIRC Help	http://www.vvm.com/~tkaufman/mirc.html
mIRC Tutorial	http://kpt1.tricon.net/Personal/ewheeler/mirctut1.html
One Stop mIRC Shop	http://www.ctfire.com/
mIRC Scripts	http://www.indy.net/~trekkie/

IRC Intros:

IRC Intro	http://atpibm6000.tuwien.ac.at/~acvitkov/IRCIntro.html
New IRC Users page	http://www.neosoft.com/~biscuits/niu.html
Internet Chat	http://www.azstarnet.com/~emdee/chat/

IRC FAQs:

IRC FAQ <http://www.kei.com/irc.html>
IRC Info <http://www2.undernet.org:8080/~cs93jtl/irc.html>
Operators Guide <http://irchelp.org/irchelp/opguide.txt>

IRC Networks:

Undernet <http://www.undernet.org/>
Dalnet <http://www.dal.net/>
KidLink (IRC for Kids) <http://www.kidlink.org/IRC/>
KidsWorld (Kids IRC) <http://www.kidsworld.org/>
Lots of Nets <http://www2.undernet.org:8080/~cs93jtl/ircnets.html>

IRC Servers:

EFNet IRC Servers <http://users.hol.gr/~shadow/slists/efnet-servers.html>
Undernet IRC Servers <http://http2.brunel.ac.uk:8080/~cs93jtl/servers.html>
Dalnet IRC Servers <http://www.xmission.com/~dragon/dalnet/server.html>
IRCNet Servers <http://www.ludd.luth.se/irc/servers.html>
More Networks <http://users.hol.gr/~shadow/server-lists.html>

IRC Channels:

IRC Channels <http://www.funet.fi/~irc/channels.html>
Yahoo's list http://www.yahoo.com/Computers_and_Internet/Internet/Chatting/IRC/Channels/
Popular Channels <http://light.lightlink.com/irc/channels.html>
Dalnet Channels <http://service.dal.net/services/chan.html>

Books about IRC:

CTFire's book reviews <http://www.ctfire.com/books.shtml>

IRC History:

Undernet History http://www2.undernet.org:8080/~cs93jtl/unet_history.txt
EFNet History <http://www.the-project.org/history.html>

Technical IRC Docs:

Running a server <http://www.microserve.com/~joseph/wircsrv.html>
Microsoft Chat Server <http://backoffice.microsoft.com/product/chat/server.asp>
IRC RFC <http://ds.internic.net/rfc/rfc1459.txt>
CTCP Info http://www2.undernet.org:8080/~cs93jtl/irc_ctcp.txt
DCC Info http://www2.undernet.org:8080/~cs93jtl/irc_dcc.txt
DCC Resume Protocol <http://www.mirc.co.uk/dccresum.txt>
mIRC's Color Coding <http://www.mirc.co.uk/color.txt>
Undernet Development <http://www.wildstar.net/ircd-dev/>
EFnet Development <http://www.funet.fi/~irc/server/>
IRC3 <http://www.the-project.org/>
IRC Server Numerics <http://www.teleport.com/~jeepster/numeric.html>

Setting Options

You can change the various options in mIRC through the Setup and Options dialogs. The Setup dialog has options related to connecting to IRC Servers, whereas the Options dialog has general settings for various features in mIRC.

Setup

[IRC Servers](#)
[Local Info](#)
[Options](#)
[Identd](#)
[Firewall](#)

Options

[IRC Switches](#)
[Notify List](#)
[Control](#)
[Double-click](#)
[Event Beeps](#)
[Drag-Drop](#)
[Sound Requests](#)
[URL Catcher](#)
[Perform](#)
[Flood](#)
[Logging](#)
[DDE Control](#)
[Finger Server](#)
[Extras](#)

Options

Connect on startup

If this is turned on, mIRC tries to connect to the default IRC server automatically when it is run.

Reconnect on disconnection

If an IRC server disconnects you without you having typed /quit then checking this command will make mIRC reconnect automatically.

Popup setup dialog on startup

If enabled, this pops up the setup dialog when you run mIRC.

Move server to top of list on connect

If a single server is selected in the servers listbox, and you double-click on it, or you click the connect button, the server is moved to the top of the list.

On connection failure...

If you attempt to connect to a server and the connection fails, mIRC will retry the connection the specified number of times and will pause the specified delay inbetween each retry. If you selected multiple servers, mIRC will cycle through the list until a connection is made.

Note: Because of the way winsock works, this might cause problems. Winsock has it's own built-in timeout delay, so even if mIRC cancels a connection, winsock might still need to pause for 10 seconds.

Default Port

This allows you to specify a default server port that will be used in case you don't specify a port for a server.

DCC

DCC allows you to connect **directly** to another irc client, **bypassing** the IRC Network, to **DCC Send** and **DCC Get** files, and to **DCC chat** privately over a more secure connection.

DCC Send

DCC Send allows you to send a file to another user. Enter the nickname of user, select the file you want to send, and click on the Send button. mIRC will tell the user that you want to send them a file. The user then has to accept your send request, at which point the file transfer will begin.

Packet Size

The packet size is the number of bytes that mIRC will send to another client in one packet. The minimum is 512, the maximum is 4096. If you check minimize then the dcc send window(s) will be minimized automatically.

Fill Spaces

The fill spaces option is only available in the 32bit version and only under operating systems that allow spaces in filenames. It is highly recommended that you leave this option turned on. For more information read [this](#).

Fast Send

Turning on this option should speed up your DCC sessions. You can also change this setting with the **/fsend [on|off]** command.

Note: DCC Send needs to use your IP address to initiate a connection with another client. If you are having trouble initiating a connection then your IP address might be wrong. See the [Local Info](#) section for more information.

DCC Get

When someone tries to DCC Send you a file, the DCC Get dialog pops up and asks you if you want to accept the file.

If you choose to **accept** the file, mIRC will ask the sender to begin the file transfer, at which point you should begin receiving the file.

DCC Resume

This feature allows you to resume DCC transfers that failed to complete.

If a user tries to send you a file that already exists in your get directory then you will be shown a warning that the file exists. You then have the option to either overwrite, resume, or rename the file.

If you select overwrite then the whole file will be downloaded from the beginning and any existing file of the same name will be erased.

If you select resume then mIRC will attempt to negotiate a transfer resume to get the remaining part of the file. It will append this to the portion of the file you already have.

The mIRC DCC Resume Protocol is described [here](#).

DCC Chat

DCC Chat allows you to talk privately with another user. Enter the nickname of the user and

click on the chat button. mIRC will send information to the user telling them that you want to DCC Chat. The user then has to accept your chat request, at which point you can talk with them normally as if you were in a query window on IRC.

If a user sends you a chat request, a chat dialog will pop up asking you whether you want to talk accept their dcc chat. You can then accept or decline.

Note: DCC Chat needs to use your IP address to initiate a connection with another client. If you are having trouble initiating a connection then your IP address might be wrong. See the [Local Info](#) section for more information.

DCC Options

The DCC Options dialog allows you to change the way DCC windows and dialog appear.

Show Get Dialog/Auto-get file/Ignore all

By default, a send request must be accepted by you before a transfer begins. If you select the auto-get file option then mIRC will automatically accept a send request and begin receiving a file. If you select Ignore All then all incoming dcc send requests are ignored.

Show Chat Dialog/Auto-accept chat/Ignore all

By default, a chat request must first be accepted by you before chatting begins. If you select the auto-accept option then mIRC will automatically open a DCC chat window and accept the chat request. If you select Ignore All then all incoming dcc chats are ignored.

On Session Completion...

mIRC will perform the selected options once a transfer has been completed. mIRC will indicate in the status window whether the transfer was a success or a failure. The beep options depend on the settings in the [Event Beeps](#) dialog.

Get/Chat Dialog Time Out

When a user sends you a Send or Chat request, a dialog pops up and waits for you to accept or decline. The dialog will wait the specified number of seconds before disappearing.

Send/Get Transfer Time Out

During a transfer mIRC will wait the specified number of seconds for a response from the other client before closing the connection.

Fileserver Time Out

mIRC will close the fileserver window if a user has been idle for the specified number of seconds.

Max. DCC Sends

This limits the number of simultaneous remote DCC Sends. ie. it does not apply to you manually initiating a DCC Send but it does apply to users who request a DCC Send remotely.

Max. Fileservers

This limits the number of users that can be served simultaneously.

Auto-resume existing files

If someone tries to send you a file that already exists in your dcc get directory then mIRC usually pops up a dialog asking you if you want to overwrite/resume/rename the file. Checking this option forces mIRC to always resume a file automatically if it already exists.

Display fileserver warning

If this switch is checked then mIRC will pop up the filesaver warning dialog everytime a filesaver is initiated to someone. To learn more about filesavers see the [File Server](#) section.

DCC Get Directories

This allows you to specify dcc get directories where recieved files will be placed according to their extension. Files which don't match any of the extensions you specify are placed in the default get directory.

Window Menu

The Tile, Cascade, and Arrange Icons menu items work the same way they usually do in windows. If you want a **vertical** tiling of windows hold down the **Shift** key when you select tile.

The **MDI** window dialog allows you to specify how you want different types of windows to be opened. If a window is opened as an **MDI window** it will be contained **within** the main mIRC application window. If it is opened as a **Desktop window**, it can be placed **outside** and is independent of the main mIRC application window.

If the window is opened as a **Desktop window**, you can also choose to have it **stay on top** of all other windows by selecting its System Menu.

A list of currently open windows is shown beneath these items.

Help Menu

The mIRC help menu is **dynamic** which means that mIRC looks in its **current** directory for files ending in **.hlp** and **.txt** and adds them to the **help** menu for easy access. It also makes **aliases** for each of the files listed in the help menu, the aliases being the **name** of the file **excluding** the extension.

For example, if you put a help file by the name of **winsock.hlp** in your mIRC directory, mIRC would add the **winsock.hlp** item to your help menu, and would make an alias **/winsock**. You can then type **/winsock sometext** and mIRC would do a **context-sensitive** search in that help file for the text you specified.

You can **add/remove** files whenever you want from the mIRC directory, mIRC always **updates** the help menu whenever you open it.

If you download the mIRC FAQ in the **.hlp** format into the mIRC directory, it will appear in this menu.

Miscellaneous stuff

Saving options

mIRC saves the main window position and all other settings when you exit the program. Note that the sizes (and not positions) of the finger, dcc get/chat/send, channel list, etc. windows are saved. The next time one of these windows opens up, it will be the same size as the last time you used it.

Multiple Instances

You can only run multiple instances with the 32-bit mIRC. With the 16-bit mIRC, you cannot run multiple instances from the same EXE. However, you can have two copies of mirc, one mirc.exe and the other mirc2.exe, and you will then be able to connect to two different servers at the same time.

The Cookies

A squeaky sound, a multitude of silly comments, a faithful pet, and one bouncing dot. Where oh where can they be? :)

The Author (and part-time Human Bean)

Greetings! :)

I am **Khaled Mardam-Bey**, residing at 68 Melbury Court, London W8-6NJ, United Kingdom. I can be reached via email at khaled@mardam.demon.co.uk, and you can see my homepage at <http://www.mirc.co.uk/khaled>.

Well, it's been around **two** years since I started working on mIRC, and in that time it has grown **far** beyond what I expected, especially for something which was only meant to be a **hobby!** I've had many requests asking me to **continue** working on it and letters of **support** (thanks :) in a variety of languages that I decided to continue with it.

However, since I can't afford to work on it anymore without some kind of financial support, I've also decided to make mIRC **shareware**. I really hope that the original **spirit** and **intention** with which mIRC was **created** and **given** isn't diminished by this. Its purpose is still to help people communicate a little better :)

I've stuck a dollar **amount** on mIRC which I hope is fair and which I hope most people can afford. If you like mIRC please [register](#) as that will support my work on it. Thanks :)

I hope that mIRC has had, and will continue to have, a part to play in the making of new **friendships**, in the **keeping** of old ones, in the fostering of peaceful **communication**, and in the increased **understanding** and **respect** of other people and cultures, and that it has had a **positive** effect on people's lives.

I hope you enjoy using mIRC as much as I enjoyed creating it :)

Khaled

License Agreement

mIRC® v5.0 Internet Relay Chat Client
Copyright © 1995-1997 Khaled Mardam-Bey and mIRC Co. Ltd.
All rights reserved.

mIRC is **Shareware** which means that you can use it legally for **30 days** free of charge to evaluate it. If during, or at the end of, that period you decide that you would like to continue using it, please **register** your copy. Your single-user registration will license you to use your copy of mIRC, will support work on future versions, new features, and bug fixes, and will provide you with technical support via email.

Please see the [Registration](#) section to find out how you can register.

mIRC may be freely distributed subject to, but not limited to, the following terms: mIRC may not be sold or resold, distributed as a part of any commercial package, used in a commercial environment, used or distributed in support of a commercial service, or used or distributed to support any kind of profit-generating activity, even if it is being distributed freely.

If you would like to **distribute** mIRC as part of a shareware distribution, magazine, internet book, CD ROM, etc. contact me for written permission.

All **commercial** use interests in mIRC eg. site licensing, should be directed to **khaled@mardam.demon.co.uk**.

The integrity of the original mIRC distribution file as distributed by Khaled Mardam-Bey is essential. mIRC and all of its related files must be distributed together in the original format. The mIRC distribution file may not have files added to it or removed from it, and none of its contents may be modified, decompiled, or reverse engineered.

mIRC is provided **AS IS** without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose. In no event shall Khaled Mardam-Bey be liable for any damages whatsoever including direct, indirect, incidental, consequential, loss of business profits or special damages, even if Khaled Mardam-Bey has been advised of the possibility of such damages.

mIRC is a registered trademark of mIRC Co. Ltd.

Double-click

This feature allows you to enter a set of commands that will be executed whenever you double-click in the specified window type.

For example, for the **channel nickname listbox** you could enter:

/query \$1

which means that when you **double-click** on a nickname, a query window opens up and you can start talking with that nickname privately.

Aliases

mIRC allows you to create aliases and scripts to speed up your IRC session or to perform repetitive functions more easily. To create aliases you must know some [IRC commands](#).

Aliases can be called from the **command line**, from **other aliases**, and from **popup** and **remote** scripts. An alias **cannot** call itself recursively mainly because this seems to cause more problems for users than it solves.

Examples

The following examples show you how to create aliases that perform simple functions.

/gb /join #gb

If you now type `/gb` this is the same as typing `/join #gb`.

/j /join \$1

We have now added a parameter string. If we type `/j #gb` this is the same as typing `/join #gb`. The `$1` refers to the first parameter in the line that you supply.

/yell /me \$2 \$1

If you now type `/yell There! Hello` the action command will be `/me Hello There!` The number after `$` specifies the number of the parameter in the string that you entered.

/jj /join \$?

The question mark indicates that you should be asked to fill in this parameter. The parameter you supply will be inserted in the line at that point. So if you type `/jj` a dialog will pop up asking you for the channel you want to join. If you enter `#gb` then the final command will be `/join #gb`.

/jj /join # \$1

the `#` sign indicates that the parameter you specify should be prefixed with a hash indicating that it is a channel.

/jj /join \$?="Enter channel to join:"

This does the same thing but now the dialog will have the "Enter channel to join:" line displayed inside it.

/aw /away \$?="Enter away message:" | /say \$!

This is similar to the line above except for the addition of the `$!` parameter. This refers to the text you just typed into the parameter box. ie. the away message. This saves you having to type the same message twice.

/give /me gives \$ \$1 a \$ \$2

The double `$$` means that this command will only be executed if a parameter is specified. If you specify only one parameter in the above command it will not be executed. You can also do `$$?1` or `$?1` which means try to fill this value with parameter one if it exists. If

parameter one doesn't exist, ask for it. In the first case the parameter is necessary for the command to be executed, in the second case it isn't.

/slap /me slaps \$1 around with \$2-

The \$2- indicates that everything following (and including) parameter 2 should be appended to the command line. if you type `/slap Sheepy a large trout` the final line will be `/me slaps Sheepy around with a large trout`.

You can also specify \$2-5 which means use only parameters 2 to 5.

/laugh /me laughs at \$1's joke

Anything appended to a \$ parameter is appended to the final parameter. So if in the above example we type `/laugh mimi` the final command would be `/me laughs at mimi's joke`.

/silly /say Hel \$+ lo th \$+ ere \$+ !

Parameters are normally separated by a space. To make mIRC combine parameters you can use the \$+ identifier. The above line will say Hello there!.

/p /part #

The # sign refers to the channel you are currently on. So if you are on channel #blah, and you type `/p` then the client replaces the # sign with #blah, and the final command is `/part #blah`.

/op /mode # +o \$1

To op someone you can now just type `/op goat` instead of the whole `/mode` command.

/dop /mode # -ooo \$1 \$2 \$3

You can now depop three users by typing `/dop goat mike bongo`.

For multiple commands you should use a "|" (the shifted character usually under the \ key). So to write an alias that kicks and bans someone:

/dkb /kick # \$1 | /mode # +b \$1

The [] evaluation brackets

If you want greater control over the order of evaluation of identifiers, you can use the [] brackets. Identifiers within these brackets will be evaluated first, from left to right. You can nest brackets.

/say % [\$+ [\$1]]

You can also force a previously evaluated identifier to be re-evaluated by using extra [] brackets.

```
/set %x %y  
/set %y Hiya!  
/echo [ [ %x ] ]
```

The { } brackets

You can create multi-line scripts by using the { } brackets. This allows you to create an alias which performs several commands.

```
/poem {  
  /msg $1 A horse is a horse..  
  /msg $1 A duck is a duck..  
}
```

The If-then-else statement

You can use if-then-else statements to decide which parts of your script executes based on the evaluation of a comparison.

```
/number {  
  if ($1 == 1) echo The number ONE  
  elseif ($1 == 2) echo The number TWO  
  else echo Unknown number!  
}
```

This creates an alias which tests if the parameter you supplied is the number 1 or the number 2.

For more information, see the if-then-else section.

The Goto command

The goto command allows you to jump from one point in a script to another point.

```
/number {  
  if ($1 == 1) goto one  
  elseif ($1 == 2) goto two  
  else goto unknown  
  :one  
  echo The number ONE  
  halt  
  :two  
  echo The number TWO  
  halt  
  :unknown  
  echo Unknown number!  
  halt  
}
```

Using a **goto** incorrectly could lead to an **infinite loop**. You can **break** out of a currently running script by pressing **Control-Break**.

Note: I didn't prefix the above commands with the / command prefix. This is because the command prefix is really only needed when entering a command on the command line. In scripts, all lines are assumed to start with a command, so you don't need to use the / command prefix.

Identifiers and Variables

An **Identifier** returns the value of a built-in mIRC variable. For example, \$time would return the current time. Whenever mIRC finds an identifier in your command, it replaces it with the **current** value of that identifier.

For a list of identifiers, see the Identifiers section.

Variables are identifiers whose values you can create and change yourself and use later in your scripts.

For more information on variables, see the [Variables](#) section.

Custom Identifiers

A custom identifier is just an **alias** which returns a value, and you can use that aliases name with an identifier prefix.

For example, create an /add alias such as:

```
add {
  %x = $1 + $2
  return %x
}
```

And then use it in a command:

```
//echo Total is: $add(1,2)
```

You can supply as many parameters as you want to your identifier eg. \$add(1,2,...,N).

Built-in identifiers of the same name have priority.

Remote Scripts

You can add aliases to remote scripts by using the **alias** prefix and then entering your alias as usual.

```
alias add {
  %x = $1 + $2
  return %x
}
```

This is the same custom identifier as above, except it uses the **alias** prefix.

Function Key support

You can **redefine** function keys to perform certain commands, just like aliases. For example:

```
/F1 /say Hello!
/sF2 /query $1
/cF3 /ctcp $1 version
```

The **s** and **c** prefixes for **Shift** key and **Control** key respectively.

Note: A function key will behave **differently** depending on the window in which it is used. For example, when using it in a **query window** the \$1 parameter refers to the selected users nickname. If you're on a **channel** and the **nickname listbox** is active then the function key will work on the selected nicknames. If the listbox is **not** active, the function key will just work on the channel.

Command prefixes

If you are executing a command from the command line (ie. by typing it into an editbox),

you can force mIRC to evaluate identifiers in that command by prefixing it with two // instead of one /. For example:

/echo My nickname is \$me

Would print out "My nickname is \$me" and would not evaluate the \$me.

//echo My nickname is \$me

Would print out "My nickname is Pengy" if your nickname was Pengy.

If you want to force a command to perform **quietly** ie. without printing out any information, then you can prefix it with a "." fullstop. For example:

/ignore somenick

Would print out information telling you that you are now ignoring "somenick". If you don't want this information to be displayed, then you can use:

/.ignore somenick

Comments

You can add comments to your scripts by using the ; semi-colon at the start of a line.

;This is a comment

You can place comments anywhere in a script, they are ignored during processing.

Popups

mIRC allows you to create custom popup menus for the status window, query/chat windows, channel windows, the channel nickname listbox, and main menubar. To create these you must know how to use [Basic IRC commands](#), how to create [Aliases](#), and how to use [Identifiers](#) and [Variables](#).

If you click the right mouse-button in a window, the popup menu for that window will appear and you can select menu-items which you have defined to perform certain tasks, such as opping a user or joining a channel.

Examples

Popup menu definitions use the format:

```
<menuitem>:<commands>
```

Get Help:/join #irchelp

The words before the ":" colon are the name of the menuitem. The words after the ":" colon are the commands that are to be performed. In this case, the menuitem you would see is "Get Help". The command that would be performed if you select this menuitem would be "/join #irchelp", as if you had typed it.

The format of the commands follows precisely the same as those in normal aliases. See the [aliases](#) help section to understand how to write an alias.

To create a **Submenu**, use a "." fullstop.

```
Join a Channel
.Get IRC help!:/join #irchelp
.Visit the folks at #friendly:/join #friendly
.Who shall we join?:/join $?
```

In this case, the name of the submenu is "Join a Channel". All the commands following it beginning with a "." are part of this submenu.

To create **menus within a submenu**, you just add more fullstops:

```
Channels
.Help
..irchelp:/join #irchelp
..mIRC:/join #mirc
..newbies:/join #newbies
.Other Channels
..Visit #friendly:/join #friendly
..Wibble Wobble:/join #wibble
.Join?:/join #$$?="Enter a channel name:"
```

To **separate** menuitems, you can use a single "-" dash on a line by itself.

```
whois ?:/whois $?
-
Misc
.Edit Temp:/run notepad.exe temp.txt
```

```

.say?: /say $?
.action?:/me $?
Names
.#irchelp: /names #irchelp
.#friendly: /names #friendly
.names ?:/names $?
-
channel list:/list
-
Join a Channel
.Get IRC help!:/join #irchelp
.Visit the folks at #friendly:/join #friendly
.Who shall we join?:/join $?

```

To use the popup menu for a channel nickname listbox, you need to select a nickname before the menu will pop up. Here is a simple nickname listbox popup menu:

```

Who Is?:/whois $1
-
Modes
.Op:/mode # +o $1
.Deop:/mode # -o $1
.Kick, Ban:/kick # $1 | /ban $1
-
DCC Send:/dcc send $1
DCC Chat:/dcc chat $1
-
Slap!:/me slaps $1 around a bit with a large trout
Query:/query $1 Hey you! hello? are you there...?

```

If you want to create a popup menu item which performs **several commands**, you can use the { } brackets. See the [Aliases section](#) for more information on how to use these.

```

Cookie {
  if ($1 == $me) echo I give myself a cookie!
  else echo I give $1 a cookie!
}

```

The above menitem can be used in the channel nicknames listbox. The \$1 refers to the nickname of the user you have selected in the listbox. In this case, it checks to see if I've selected my own nickname, and if so displays the first message, otherwise it displays the second message.

The popup menus for the **Query/Chat** and the **MenuBar** work the same way as the channel listbox popup menu.

Extras

The options in this dialog are extra bits and pieces that don't fit anywhere else.

Fast screen update

For users with slower video cards, this updates the screen in batches instead of individually line by line. This should speed up screen updating for most users by quite a bit.

Multi-line editbox

In single line mode, the text scrolls to the right when you reach the end of the edit box. In multi-line mode, the text starts again at the left and scrolls downwards. It's probably easier to use multi-line mode since you can see what you've typed if the line is long. This mode also allows you to paste several lines of text into the editbox.

Note: The status window permanently has a single line edit box.

ESCAPE key minimizes window

To have a window minimize whenever you press the ESCAPE key select this option.

Toolbar and tooltips

You can choose to have the toolbar and it's tooltips hidden or shown.

Switchbar...

You can choose to have the switchbar shown or hidden. The switchbar shows all of your window's as buttons to allow quick access and switching between them.

If the **always highlight** option is turned on, mIRC will highlight a window's button when there is activity in the window and the window is open and non-active. If this option is turned off, mIRC will **only** highlight the window's button if there is activity in it and the window is iconized.

The **Show DCCs** switch allows you to show **DCC sends/gets** in the switchbar, otherwise they will appear as normal icons.

The **ontop** switch allows you to position the switchbar at the top or bottom of the main window.

Line separator

You can specify a line separator to be used in the status window. You can use a space to have a blank line. If you leave the box empty, lines in the status window will not be separated.

Command Prefix

The default standard prefix to a command is a / character, however you can specify another character if the / key is hard to access on your keyboard.

Note: Regardless of the character you choose here, mIRC still recognizes the / character and uses it internally.

Scrollbar buffer size

This limits the scrollbar buffer to the specified number of lines. Note that if a scrollbar buffer already contains more than the specified number of lines it will be shortened. You can always use the **/clear** command in a window to clear the scrollbar buffer completely. If you are scrolling back through the buffer, lines will not be removed until you return to the

bottom of the buffer.

Append this text to the application title bar

This allows you to specify text that will be shown in the mIRC application title bar.

Joining A Channel

Once you've connected to an IRC Server, you can join a channel to talk to other people. There are several ways to join a channel, each is explained below.

The Channels Folder

The easiest way to join a channel is to use the channels folder which holds a list of your favourite channels. mIRC **automatically** pops up this folder the moment you connect to an IRC Server. You can join one of the listed channels by selecting it and clicking the **Join** button.

You can also view the channels folder by clicking on the Channels Folder button in the toolbar.

The Channels List

Another way to join a channel is to retrieve the list of currently active channels by using the List Channels dialog. You can view the List Channels dialog by clicking on the List Channels button in the toolbar.

To retrieve the **entire** channels list, you can click on the **Get List** button. The list can be quite long, sometimes over 3000 channels, so it can take several minutes to retrieve it. mIRC will save this list once you have retrieved it, so if you wish to view it again later you can just click on the **Apply** button. However, if you want an updated list you will need to retrieve it again.

If you click your right mouse button in the channels list window, a popup menu with various options will appear.

The /join Command

The format of the /join command, which is a Basic IRC Command, is **/join #channel** where #channel is the name of the channel you want to join. So if you wanted to join channel #mIRC, you would type **/join #mIRC** and press enter, and a moment later the #mIRC window will open indicating that you have joined it.

Creating a new channel

You can create a new channel if it doesn't already exist just by joining it. So, let's say you want to create a channel called #bubbles, you would just type **/join #bubbles**, and if it doesn't exist it will be created for you. If it does exist, you will just join it as usual.

Talking on a channel

You can talk to other people by typing in a message and pressing the enter key. Your message will be sent to the channel and everyone on the channel will see it. A good first message is just to say hello with a smiley face :)

The **listbox** on the side of the channel window lists all of the people who are currently on that channel. If you click your right mouse button in the listbox, a popup menu with various options will appear.

Popup menus are actually used everywhere in mIRC, you can even click your right mouse button in the status window, or in the channel window itself, and a different popup menu will appear. These popup menus are configurable, you can change them in the popups dialog to perform whatever functions you require.

Leaving a channel

You can leave a channel by clicking its window's close button, or you can use the **/part** command, which is another basic IRC command similar to `/join`. The format of the `/part` command is **`/part #channel`** where `#channel` is the name of the channel you want to leave. If you type **`/part`** without a channel name and press enter, you will part the current channel.

Acknowledgements - Thank you, thank you, and thank you...

After two years of working on mIRC, it's hard to remember all of the people who've been involved with some aspect or other of its development; some I haven't heard from in a very long time, while others I still talk to today. They've all contributed in some way, whether through bug reports, suggestions, answering questions, beta-testing, helping out folks on IRC channels, or creating helpful scripts, documentation, and web pages.

I get emails about mIRC every day from people all over the world, emails which are often very touching and heartfelt, and I know that their kind words are as much a tribute to all of you who have helped to bring so many people together.

Thanks to...

Tjerk Vonck who created the first #mIRC channel, the mIRC homepage, and mIRC FAQ, and has contributed to mIRC in too many ways to mention.

The **mIRC Beta-testers**, past and present, for their hard work in catching bugs and suggesting features.

The folks who help out new users day after day on mIRC related channels, and who create helpful mIRC webpages, documentation, and scripts.

Nicolas Pioch for his short IRC primer, **Ramji, Bibbly, Stimps, Mike, James G., Edward, Bunster** for the queen-size futons, **Peeg** for the frequent *bonk*s over the head, and **Viv** :)

M.Hunnibell, M.Overtoom, Mark "Too Slick" Hanson, Ron R., and **Dan Lawrence** for their technical help.

All of the other kind folks who directed me at different people, places, source codes, and documents, discussed ideas with me, and in general both **supported** and **laughed** at my humble efforts :)

Basic IRC Commands

IRC commands allow you to perform functions such as maintaining control of a channel and the users on it. The following list of basic IRC commands should help you get started. There are also [mIRC Commands](#) you can look at.

General Commands

/JOIN #channel

Join the specified channel.

example: /join #irchelp

This will make you join the #irchelp channel. Once on a channel, anything you type will be seen by all the users on this channel. The #irchelp channel is very useful, so say hello and then ask any questions you want. If the channel you specified doesn't exist, a channel with that name will be created for you.

/PART #channel

Leave a channel.

example: /part #irchelp

/LIST [#string] [-MIN #] [-MAX #]

Lists currently available channels. You can also tell mIRC to show only channels with a minimum and a maximum number of people. If you specify a #string then mIRC will only list channels with that string in their title.

example: /list

example: /list -min 5 -max 20

example /list #love

/ME message

Tells the current channel or query about what you are doing.

/MSG nickname message

Send a private message to this user without opening a query window.

/QUERY nickname message

Open a query window to this user and send them a private message.

/WHOIS nickname

Shows information about someone.

/NICK nickname

Changes your nickname to a new nickname.

/QUIT [reason]

This will disconnect you from IRC and will give the optional message as the reason for your departure. (this message only appears to people who are on the same channels as you).

example: /quit That's all folks!

/AWAY [away message]

Leave a message explaining that you are not currently paying attention to IRC. Whenever someone sends you a MSG or does a WHOIS on you, they automatically see whatever message you set. Using AWAY with no parameters marks you as no longer being away.

example: /away off to get something to eat, back in a moment!

/TOPIC #channel newtopic

Changes the topic for the channel.

example: /topic #friendly Oh what a beautiful day!

/INVITE nickname #channel

Invites another user to a channel.

Channel and User Commands

If you have Op status, the following commands give you control over both a channel and the users on it.

/KICK #channel nickname

Kicks named user off a given channel.

example: /kick #gb Ed

/MODE #channel|nickname [[+|-]modechars [parameters]]

This is a powerful command that gives channel operators control of a channel and the users on it.

Channel modes

ModeChar	Effects on channels
b <person>	ban somebody, <person> in "nick!user@host" form
i	channel is invite-only
l <number>	channel is limited, <number> users allowed max
m	channel is moderated, (only chanops can talk)
n	external /MSGs to channel are not allowed
o <nickname>	makes <nickname> a channel operator
p	channel is private
s	channel is secret
t	topic limited, only chanops may change it
k <key>	set secret key for a channel

User modes

ModeChar	Effects on nicknames
i	makes you invisible to anybody that does not know the exact spelling of your nickname
o	IRC-operator status, can only be set by IRC-ops with OPER
s	receive server notices
v	gives a user a voice on a moderated channel

Here a few examples of the MODE command:

To give someone Op status: /mode #channelname +o nickname

Giving someone Op status means giving them control over the channel and the users on it. Give this out sparingly and to people you trust.

To op several people: /mode #channelname +ooo nick1 nick2 nick3

To de-op someone: /mode #channelname -o nickname

To ban someone: /mode #channelname +b nickname (or user address)

example: /mode #animals +b Jiminy

example: /mode #tree +b joe@bloggs.edu

To Unban someone: /mode #channelname -b nickname (or user address)

example: /mode #gb -b Ed

To Make a channel invite only: /mode #channelname +i

You must now **invite** a user for them to be able to join your channel.

There many more commands but this list should help you get started. To learn more about IRC commands you should download an IRC FAQ.

DDE Control

mIRC currently supports a limited **DDE** capability with enough DDE topics to make it useful.

All DDE transactions are **synchronous**, mIRC waits at most one second for a reply or acknowledgement to any dde poke or query it makes.

The /ddeserver command

As a server, mIRC's **default** service name is **mIRC**. The mIRC DDE Server defaults to **on** at startup unless it finds another mIRC or another application using it's current DDE Service name. You can use:

/ddeserver [[on [service name]] | off]

to manually turn on/off the dde server mode. If you have more than one mIRC acting as a DDE server then you should specify a different **service name** for each mIRC since if they all have the same service name you won't be able to predict which dde message will go to which server. For example:

/ddeserver on mIRCbot

If you try to use a service name which is **already** in use, mIRC will **warn** you but will still turn on the ddeserver.

For each of the following DDE topics, an example is given using mIRC's /dde command and \$dde identifier (both are explained after this section) which should help you understand how they work.

DDE Topics

Topic: **CHANNELS**

Transaction Type: XTYP_REQUEST

Item: None

Data (Arguments): None

Returns: A single line of text listing the channels which you are currently on separated by spaces. eg. "#mirc #mircremote #irchelp"

Example: This should only be called by an application, not from within an mIRC alias.

Description: The line of text that this returns could end up being quite long, maybe several k's worth of text, so an application should be prepared to handle this.

Topic: **COMMAND**

Transaction Type: XTYP_POKE

Item: None

Data (Arguments): One line of text containing the command to be performed.

Returns: Nothing

Example: /dde mirc command "" /server irc.demon.co.uk

Description: This is essentially the same as the remote DO ctcp command, it just executes whatever command you give it.

Topic: **CONNECT**

Transaction Type: XTYP_POKE

Item: None

Data (Arguments): one line of text in the form: address,port,channel,number

Returns:Nothing

Example: /dde mirc connect "" stork.doc.ic.ac.uk,6667,#mIRC,1

Description: This will tell mIRC to connect to the server stork.doc.ic.ac.uk, port 6667 and after it has connected it will automatically join channel #mIRC. If the number at the end is a 1 then the mIRC window will be activated, if it is a 0 it will not.

Topic: **CONNECTED**

Transaction Type: XTYP_REQUEST

Item: None

Data (Arguments): None

Returns:"connected" if you're connected to a server, "connecting" if you're in the process of connecting to a server, and "not connected" if you're not currently connected to a server.

Example: /say mIRC is currently \$dde mirc connected "" to a server

Topic: **EXENAME**

Transaction Type: XTYP_REQUEST

Item: None

Data (Arguments): None

Returns: The full path and name of the mIRC EXE file. eg. "c:\mirc\mirc.exe"

Example: /say The mIRC exe path and name is \$dde mirc exename ""

Description: This might be useful for applications that need to know the path and name of the exe file.

Topic: **INIFILE**

Transaction Type: XTYP_REQUEST

Item: None

Data (Arguments): None

Returns: The full path and name of the main INI file that is being used. eg. "c:\mirc\mirc.ini"

Example: /say mIRC's main ini file is \$dde mirc inifile ""

Description: This might be useful for applications that need to take a look at the INI file for various bits of information.

Topic: **NICKNAME**

Transaction Type: XTYP_REQUEST

Item: None

Data (Arguments): None

Returns: The nickname currently being used.

Example: /say My mIRCbot is using the nickname \$dde mirc nickname ""

Topic: **PORT**

Transaction Type: XTYP_REQUEST

Item: None

Data (Arguments): None

Returns: The port currently being used to connect to the irc server

Example: /say My mIRCbot is using port \$dde mirc port ""

Topic: **SERVER**

Transaction Type: XTYP_REQUEST

Item: None

Data (Arguments): None

Returns: The server to which you were last or are currently connected. eg. "irc.server.co.uk"

Example: /say My mIRCbot's irc server is \$dde mirc server ""

Topic: **SERVERPORT**

Transaction Type: XTYP_REQUEST

Item: None

Data (Arguments): None

Returns: The server and port to which you were last or are currently connected. eg.

"irc.server.co.uk:7000"

Example: /say My mIRCbot's irc server is \$dde mirc server ""

Topic: **USERS**

Transaction Type: XTYP_REQUEST

Item: Channel name, in the form #channel

Data (Arguments): None

Returns: A single line of text listing the users on the specified channel separated by spaces.

Example: This should definitely only be called by an application, not from within an mIRC alias.

Description: You can only request the names of users on a channel which mIRC has joined.

The line of text it returns could be very, very long, so any application that uses this must be prepared to handle a single line of several k's worth of text.

Topic: **VERSION**

Transaction Type: XTYP_REQUEST

Item: None

Data (Arguments): None

Returns: mIRC version number eg. "mIRC16 5.0" or "mIRC32 5.0"

Example: /say mIRC's version number is \$dde mirc version ""

To use the following /dde command and \$dde identifier you must know the DDE specifications of the application with which you want to communicate.

The /dde command

/dde [-r] <service> <topic> <item> [data]

The command defaults to sending an XTYP_POKE unless you specify the **-r** switch in which case an XTYP_REQUEST is sent. If you are sending an XTYP_POKE then all four arguments are mandatory, if you are sending an XTYP_REQUEST then the first three arguments are mandatory. This is why you can see a "" in the examples above, it acts as a filler and isn't actually used for anything. This filler is important because you might have the /dde or \$dde mixed with other commands, and mIRC has to know the exact number of parameters when parsing.

/dde monolog talk "" Greetings Earthling!

The \$dde identifier

\$dde <service> <topic> <item>

This sends an XTYP_REQUEST and retrieves any data returned by the specified service. All three arguments are mandatory (as explained in the above paragraph). Any retrieved data is inserted in the current position in an alias.

/say My other mIRC is \$dde mirc connected "" to \$dde mirc server ""

IRC Servers

Once you've entered a few **basic** pieces of information about yourself in the **Setup** dialog, you can **select an IRC Server** from the servers list and **click on the Connect button**.

You'll know you've connected when the irc server shows you it's **Message Of The Day**, which contains information about that server, and you'll then be able to join a channel to start talking to people.

Basic information

The following information is required before you can connect to a server.

Real Name

You can enter your real name here, however most people usually enter a witty one-liner or comment.

Email Address

You must enter a full email address eg. khaled@mardam.demon.co.uk.

Nickname and Alternative

Your nickname is the name people will know you by when you join IRC. Remember that there are many thousands of people on IRC, so it's possible that someone might already be using the nickname you've chosen, so you should try to pick something unique. You can enter an alternative nickname as well in case someone is using your first nickname. If both nicknames are in use, mIRC inserts "/nick" into the edit box so that all you have to do is enter a new nickname and press enter.

Invisible Mode

If you turn on the invisible mode switch, people will not be able to find you on IRC unless they already know your nickname, or if you join a channel or talk to them privately.

IRC Servers

You can manage your list of IRC servers by using the add, edit, and delete buttons. You can enter the following information for each IRC Server:

Description

This can be any text you want and serves only as a description.

Address

This is the IRC server address eg. irc.dal.net

Port Number

This is usually 6667. If the server allows connections on different ports, you can enter them all separated by commas eg. 6667,6668,6669 and mIRC will pick one randomly each time it connects to the server.

Group Name

This allows you to group servers together when they are sorted with the **Sort** button.

Password

This is **rarely** required, so you should not have to enter anything here unless you have been specifically told to.

Note: If you're having problems connecting to an IRC Server, see the [Connection Problems](#) section.

Identd

mIRC can act as an **ident server** and sends the specified **User ID** and **System** as identification. This server will be more useful to some people than others. In general it is better to leave it active as some systems might refuse a connection if there is no reply to an ident request.

User ID

This can be your account or user name on your system. For most people this will be the User ID portion of their email address (the text before the @ sign). Valid characters for a User ID are: **. 0-9 A-Z _ - a-z**

System

This identifies your operating system. For all intents and purposes, replying with a value other than UNIX would not be very useful for most people.

Port

This should usually be 113.

Note: This server will reply to **all** ident queries sent to the specified port ie. it is not limited to replying to an IRC server for mIRC. If you have turned on the identd server and it isn't replying to identd queries then it is probable that the type of internet account you have is preventing mIRC from replying, or that another program is running which has control of the identd port.

Finger

This allows you to finger a persons address to find out more information about them.

If a user has a personal email/machine address, this will only work if they are running a finger server. Most other addresses eg. school, government, etc. can usually be fingered sucessfully, though they will not necessarily give you any useful information. For some users this can be a way of checking if they have mail.

You can also type **/finger <nick/address>** at the command line.

If there's a . in the parameter you provide then it assumed to be an address and is immediately fingered, otherwise it is assumed to be a nickname, so mIRC looks up the users address with a /userhost and then fingers that address.

On a related note, check out the [Finger Server](#).

Online Timer

The **Online timer** is displayed in the titlebar of the status window next to your connection information.

You can choose to have the timer **reset to zero** every time you connect, so that you can tell how long you are on for that session, or if you select the second option, the timer will be **cumulative** and will show the **total** amount of time you have used IRC since the last reset.

Remote

The **remote** allows you to create scripts that react to IRC Server events, such as when a user joins a channel or sends you a message. This tool is the most complex part of mIRC and to use it you must already know how to use [IRC Commands](#), how to create [Aliases](#), and how to use [Variables](#) and [Identifiers](#).

The remote consists of **three** distinct sections:

The **Users** section, where user addresses with assigned access levels are listed. Each User in your Users section can be assigned one or more levels. These access levels dictate which events a user will be able to access.

The **Variables** section, where the currently active variables are listed.

The **Scripts** section, where the scripts that you create are listed. You can load **multiple** scripts which work **independently** of each other. This means that a single IRC Server event can trigger events in **one or more** scripts. Scripts consist of **events** which can only be triggered by **users** who have the **required** access levels. You can also place [aliases](#) in your scripts by using the **alias** prefix.

Since [Access Levels](#) play an important part in the way scripts work, you should read about them carefully before proceeding. You should also take a look at remote [commands](#), [identifiers](#), and the [internal address list](#).

All of the following **Events** use the same general format except for the **ctcp** and **raw** events. The sections below provide you with **information** on each event as well as **examples** and **tips** on how to use them.

Action	FileRcvd	Notice	SNotice
Ban	FileSent	Notify	Start
Chat	GetFail	Op	Text
ChatClose	Input	Part	Topic
ChatOpen	Invite	Quit	UnBan
Connect	Join	Raw	UNotify
Ctcp	Kick	SendFail	UserMode
CtcpReply	Load	Serv	Voice
DeOp	MidiEnd	ServClose	Wallops
DeVoice	Mode	ServerMode	
Dns	Nick	ServerOp	
Error	NoSound	ServOpen	

Note: You should never load or use a script that you don't understand.

Remote Commands

The following commands are used to modify settings in scripts and in the remote section.

General Commands

/ctcps [on|off]

This switches processing of ctcp events on/off.

/events [on|off]

This switches processing of named events on/off.

/dlevel <level>

This changes the default user level to the specified level.

/raw [on|off]

This switches processing of numeric events on/off.

/remote [on|off]

This switches processing of all scripts on/off.

Group Commands

These commands allow to turn groups on and off in remote scripts. You can find out about groups in the [Access Levels](#) section.

/enable <group1 group2 ... groupN>

This enables the specified groups in all scripts.

```
/enable #one #two #three
```

/disable <group1 group2 ... groupN>

This disables the specified groups in all scripts.

```
/disable #one #two #three
```

/groups [-e|d]

This displays a list of either all, enabled, or disabled groups in your scripts.

User and Level Commands

You can use the following three commands to add and remove users to the users list, as well as to add and remove levels from existing users.

/auser [-a] <levels> <nick|address>

This adds the specified nick/address exactly as it is given to the users list with the specified levels. If you specify [-a], then if the user already exists, the specified levels are added to the current levels the user has. Remember, if the first level is not preceded by an equal sign then it is a general access level.

```
/auser 1,2,3 Nick
```

This adds this nick with these access levels to the user list (replacing an existing user of the same name).

```
/auser -a 1,2,3 Nick
```

This adds the specified levels to this user. If the user doesn't exist, it is created.

```
/auser -a =1,2,3 Nick
```

This looks like the above command, however the =1 is very important. The =1 means that the initial general access level is **not** replaced. If you had used 1 then the initial access level would be replaced.

/flush [levels]

This clears the remote user list of nickname definitions that are no longer valid.

```
/flush 1,2,3
```

For each nick in the remote user list that matches the specified levels mIRC checks to see if that nick is on any of the channels that you are currently on. If not, the nick definition is removed from the remote user list. If you do not specify levels then mIRC clears all nicks from the remote user list that don't exist on channels you are on.

/guser [-a] <levels> <nick> [type]

This works the same as the /auser command except that it looks up address of the specified nick and adds it to the user list. It does this by doing a /userhost on the given nickname, and returning an address in the format specified by type. If no type is specified then a default address format is selected.

/ruser [levels] <nick | address> [type]

If used without specifying levels, this removes the specified user from the user list. If you specify levels then these levels are removed from the current access levels of this user. If all a user's levels have been removed, the user is removed. If you specify a type then the user's address is looked up with a /userhost and any users in the user list matching this address are removed.

```
/ruser Nick  
/ruser 1,2,3 Nick  
/ruser 1,2,3 Nick 1
```

If you use /ruser Nick! (with an exclamation mark at the end), it removes all users with an address beginning with Nick!.

/rlevel [-r] <levels>

This removes all users from the remote users list with the specified general access level.

```
/rlevel 20  
/rlevel =10
```

If the -r option is specified, then this applies to all the access levels for a user (not just the first general access level). Any matching levels are removed. If a user has no more levels left then the user is also removed.

```
/rlevel -r 1,5,7,8
```

/ulist [<|>] <level>

This lists users which have the specified access levels.

/ulist <10 lists users with access levels less than or equal to 10
/ulist >5 lists users with access levels larger than or equal to 5
/ulist 4 lists users with access level 4

Note: The /guser and /ruser commands do a /userhost on a nick to find the nick's address, thus they are delayed commands since they need to wait for a reply from the server. mIRC tries to get around this delay by maintaining it's own Internal Address List which will speed things up in certain situations.

Access Levels

Access levels are assigned both to a user and to an event and serve to limit a user's access to only certain events.

The **default access level** is 1 for users that are not listed in the Users list. All users can access level 1 events. The higher a user's access level is, the more events that user can access. You can change the default user level to allow unlisted users to access more commands.

Users

In the Users section you can specify a **list of users** and their access levels using the format:

```
<level1,level2,...,levelN>:<useraddress>
```

```
3,5,6:goat!khaled@mardam.demon.co.uk
```

The **first** level is a general access level, which means that the user can access all levels equal to or less than 3. All the **other** levels are levels that an event must specifically have to allow a user to access it.

If you want to **force** the first access level to be a specific level instead of a general access level, you can prefix it with an equal sign.

```
=3,5,6:goat!khaled@mardam.demon.co.uk
```

Now this user has access specifically to level 3, 5, and 6 event and to no other events.

Events

In general the format of an event is:

```
<prefix> <level>:<event>:<commands>
```

```
ctcp 1:HELP:/msg $nick No help is available for level 1 users
```

The above ctcp command can be accessed by all users because it is a level 1 command. So if a user with nickname goat sends you a /ctcp yournick HELP, your script will send them the above reply.

Only the **highest level** matching event is triggered for a user.

Named Levels

You can also use **named levels** which work the same way as a specific level but are easier to understand and read than a number.

```
friend:goat!khaled@mardam.demon.co.uk
```

```
on @friend:JOIN:#mIRC:/mode $chan +o $nick
```

This treats the word **friend** as a specific access level and matches the user with the event, and because the user is your friend, you give him ops.

Limiting Access

You can limit events to users with a certain access level by prefixing an event with a + **plus sign**.

```
10:goat!khaled@mardam.demon.co.uk
```

```
ctcp +5:HELP:/msg $nick You have accessed a level +5 event
```

The above user can't access this ctcp event even though he has an access level higher than 5 because the event is limited only to level 5 users.

You can prevent users with higher access levels from accessing **all** lower access level events by using an = **equal sign**.

```
10:goat!khaled@mardam.demon.co.uk
```

```
ctcp 2:HELP:/msg $nick You have accessed a level 2 event
ctcp 5:HELP:=
```

The above user can't access any of these events because the level 5 event prevents him from accessing all HELP events with access levels lower than 5.

You can prevent an event from reacting if it was initiated by you by using the ! **exclamation mark**.

```
ctcp !2:HELP:/msg $nick You have accessed a level 2 event
```

You would be unable to access the above event regardless of what access level you have.

You can limit events to being executed only when you have Ops on a channel by using the @ **at sign**.

```
10:goat!khaled@mardam.demon.co.uk
```

```
on @2:JOIN:#mIRC:/mode $chan +o $nick
```

When the above user joins channel #mIRC and you have Ops on #mIRC, the associated /mode command will be executed, in this case giving the user Ops. If you don't have Ops, the event will not trigger.

You can prevent commands for a certain event level from being processed by using a ! **exclamation mark** as the command.

```
ctcp 5:PING:echo PING!
ctcp 5:*:!
```

The ! at the end of the line tells the remote to halt any further processing of level 5 commands.

Creating Groups

You can create separate groups in scripts by using the # hash prefix.

```
#group1 on
...
[ list of events ]
```

```
...  
#group1 end
```

You can use the /enable and /disable commands to enable or disable groups. A group that is disabled will be ignored when processing events. A disabled group looks like this:

```
#group1 off  
...  
[ list of events ]  
...  
#group1 end
```

You cannot have groups within groups.

Ordering of definitions

Many of the prefixes and controls are sensitive to numerical order of the definitions. The safest thing is to order your definitions starting with the lowest access levels first and increasing numerically down the list, this makes it easier to keep track of which events should trigger first.

Remote Identifiers

You can use the following identifiers in scripts to refer to values relating specifically to events. There are also quite a few other identifiers which relate only to specific events, these are described with the events themselves in other parts of the help file. There are also other identifiers which can be used in both remote and non-remote scripts.

\$1-

You can use the \$1 \$2 ... \$N identifiers to refer to individual parameters in a line. You can also use \$N- to refer to parameters N and onwards, and \$N-M to refer to parameters \$N through to \$M. So to refer to a whole line, you would use \$1-.

\$address

Returns the address of the user associated with an event in the form userid@host.domain.

\$chan

Returns the name of the channel where an event took place. Only certain events occur specifically on a channel, for all other non-channel events \$chan will have no value.

\$clevel

Returns the matching event level for a triggered event.

\$dlevel

Returns the current default user level.

\$fulladdress

Returns the full address of the user triggering an event in the form nick!userid@host.domain.

\$group(N/#)

Returns the the name or status of a #group in a script.

Properties: status

\$group(0) returns the number of groups
\$group(1) returns the name of the first group
\$group(1).status returns on or off for the first group
\$group(#name) returns on or off for group #name

\$maddress(nick!userid@address)

Returns the first address in the Users list that matches the specified address.

\$nick

Returns the nickname of the user associated with an event.

\$numeric

Returns the numeric for the matching numeric event.

\$script

Returns the filename of the currently executing remote script.

\$scriptdir

Returns the directory of the currently executing remote script.

\$site

Returns the portion of \$address after the @ for the user associated with an event in the form userid@host.domain.

\$target

Returns the target of an event.

\$ulevel

Returns the user level that was matched for the currently triggered event.

\$wildsite

Returns the address of the user who triggered an event in the form *!*@host.domain.

DCC Resume Protocol

In it's current form the protocol is very simple.

User1 is sending the file.

User2 is receiving the file.

To initiate a DCC Send, User1 sends:

PRIVMSG User2 :DCC SEND filename ipaddress port filesize

Normally, if User2 accepts the DCC Send request, User2 connects to the address and port number given by User1 and the file transfer begins.

If User2 chooses to resume a file transfer of an existing file, the following negotiation takes place:

User2 sends:

PRIVMSG User1 :DCC RESUME filename port position

filename = the filename sent by User1.

port = the port number sent by User1.

position = the current size of the file that User2 has.

User1 then responds:

PRIVMSG User2 :DCC ACCEPT filename port position

This is simply replying with the same information that User2 sent as acknowledgement.

At this point User2 connects to User1 address and port and the transfer begins from the specified position.

Note: the newer versions of mIRC actually ignore the filename as it is redundant since the port uniquely identifies the connection. However, to remain compatible with older mIRC's, mIRC still sends a filename as **file.ext** in both RESUME and ACCEPT.

on CHAT/SERV

The **on CHAT** and **on SERV** events trigger when a message is sent to a dcc chat or dcc fserve window.

Format: on <level>:CHAT:<matchtext>:<commands>

Example: on 1:CHAT:*help*/:msg \$nick what's the problem?

For an explanation of **matchtext** see the [on TEXT](#) event.

Examples

on 1:CHAT:boo!:/msg =\$nick Boo back at ya!

This triggers when someone in a dcc chat window says boo! The equal sign in **=\$nick** is required to send the reply as a dcc chat message. If no equal sign is used, the message is sent as a private irc server message.

on 1:SERV:bye:/msg =\$nick Thanks for using my fileserver, bye!

This triggers when a user in a dcc fileserver session says the word bye to quit the fileserver.

Note: These events react to **all** users level 1 and above because of the way dcc chat works.

on TEXT

The **on TEXT** event triggers when you receive private and/or channel messages.

Format: on <level>:TEXT:<matchtext>:<*><?><#[,#]>:<commands>

Example: on 1:TEXT:*help*:#mirc,#irchelp:/msg \$nick what's the problem?

The **on ACTION** and **on NOTICE** events use exactly the same format as on TEXT, and trigger on an action and on a notice event respectively.

The **match text** can be a **wildcard** string, where:

- * matches any text
- & matches any word
- text matches if text contains only this word
- text* matches if text starts with this word
- *text matches if text ends with this word
- *text* matches if text contains this word anywhere

The **location** where this event occurs can be specified using:

- ? for any private message
- # for any channel message
- #mirc for any messages on channel #mirc
- * for any private or channel messages

Examples

```
on 1:TEXT:hello*:#:/msg $chan Welcome to $chan $nick!
```

This listens on any channel for any line beginning with the word hello and welcomes the user who said it to the channel.

```
on 1:TEXT:*cookie*:#food:/describe $chan gives $nick a cookie :)
```

This listens on channel #food for any message containing the word cookie and gives the user who said it a cookie.

```
on 1:ACTION:moo:#:/msg $chan Aha, I see we have a cow among us.
```

This listens on any channel for an action that contains the word moo and responds accordingly.

```
on 1:NOTICE:*?:/msg $nick I'm AFK, back in a moment!
```

This listens for any private notice and responds with the message that you're away from the keyboard.

For more flexibility, you can also use variables in place of both the matchtext and the channel parameters.

```
on 1:TEXT:%matchtext:%channel:/msg $nick You just said %matchtext on channel %channel
```

The value of %matchtext will be matched against whatever text the user sends, and the value of %channel will be matched against the channel to which the message was sent.

Note: You can't test out these events by typing text to yourself. They can only be initiated by someone else saying something in a channel or in a private message.

on JOIN/PART

The **on JOIN** and **on PART** events trigger when a user joins or parts a channel.

Format: on <level>:JOIN:<#[,#]>:<commands>

Example: on 1:JOIN:#mirc,#irchelp:/msg \$nick hiya!

Examples

on 1:JOIN:#:/msg \$chan Welcome \$nick!

This triggers when any user joins any channel which you are on.

on 5:PART:#mIRC,#newbies:/describe \$chan waves bye-bye to \$nick *sniff*

This triggers when a user with access level 5 leaves channels #mIRC or #newbies.

on KICK

The **on KICK** event triggers when a user is kicked from a channel.

Format: on <level>:KICK:<#[,#]>:<commands>

Example: on 1:KICK:#mirc,#irchelp:/msg \$nick Oops! ;)

Examples

on 5:KICK:#:/invite \$knick \$chan | /msg \$nick Hey, \$knick is my friend!

This triggers when when a user who has access level 5 is kicked out of any channel. **\$knick** refers to the nickname of the user who was kicked.

Comparing levels

You can **compare the levels** of the kicker and the kicked users by prefixing the line with <, >, <=, =, <>, or =, in the following way:

on >=2:KICK:#mIRC:/msg \$chan \$nick kicked \$knick (legal)

on 1:KICK:#mIRC:/msg \$chan \$nick kicked \$knick (illegal)

In this situation, if the kickers level is larger than or equal to the kicked users level, then it is a legal kick. Otherwise, it defaults to the second on KICK event which indicates that it is an illegal kick. Remember, this is comparing the **kickers and kicked users levels** and has nothing to do with with the level "2" in the definition.

Note: This event only works on a nickname because the IRC server only sends the nickname of the user being kicked and not an address.

on OP/DEOP

The **on OP** and **on DEOP** events trigger when a user on a channel is opped or deopped.

Format: on <level>:OP:<#[,#]>:<commands>

Example: on 1:OP:#mirc,#irchelp:/msg \$nick Please don't abuse your Op status

The **on SERVEROP** event uses exactly the same format and triggers when a user is opped by a server.

Examples

on 9:OP:#:/mode \$chan -o \$opnick | /msg \$nick Don't Op that person!

This triggers when a user with access level 9 is opped on any channel. **\$opnick** refers to the nickname of the person being opped/deopped.

on 1:DEOP:#beginner:/mode \$chan +o \$opnick

This triggers when any Op is deopped on channel #beginner.

on 1:SERVEROP:#:/mode \$chan -o \$opnick

This triggers when an irc server ops a user on any channel. You immediately deop them.

Comparing levels

You can **compare the levels** of the opper and the opped by prefixing the line with <, >, <=, =, >, or =, in the following way:

on >=2:DEOP:#mIRC:/msg \$chan \$nick deopped \$opnick (legal)

on 1:DEOP:#mIRC:/msg \$chan \$nick deopped \$opnick (illegal)

In this situation, if the deoppers level is larger than or equal to the deopped users level, then it is a legal deop. Otherwise, it defaults to the second ON DEOP line which indicates that it is an illegal deop. Remember, this is comparing the oppers and opped users levels and has nothing to do with with the level 2 in the definition.

Note: These events only work on nicknames because the IRC server only sends the nickname of the user being opped/deopped and not an address.

on CONNECT

The **on CONNECT** event triggers when mIRC connects to an IRC Server right after the MOTD is displayed.

Format: on <level>:CONNECT:<commands>

Example: on 1:CONNECT:/join #new2irc

Examples

on 1:CONNECT:/echo Connected to \$server at \$time with nickname \$nick

This triggers after mIRC connects to a server.

Note: This event is essentially the same as the Perform section.

mIRC Commands

The following commands are mostly unique to mIRC, though some are only modifications or extensions of standard IRC commands.

/alias [filename] <aliasname> <commands>

This adds, removes, replaces aliases, however it is limited to single line aliases and will not affect multiple line definitions. To add a new alias, you can use:

```
/alias /moo /me moos!
```

This will add the /moo alias to the top of the aliases list. To remove an existing alias:

```
/alias /moo
```

To add an alias to a specific alias file, you would use:

```
/alias moo.txt /moo /me moos!
```

If you don't specify a filename, it defaults to using the first filename in which the alias exists, or if it doesn't exist then it uses the first loaded aliases file.

/amsg <message>

This and the **/ame** command send the specified message or action to all channels which you are currently on.

/auser

This and remote-related commands are listed in the [remote](#) section.

/auto [-r] <nickname/address> [#channel1,#channel2,...] [type]

This adds someone to the auto-op list, see the [Control](#) section for a full description.

/ban [-uN] [#channel] <nickname> [type]

This bans someone from the current channel using their address. To do this, it first does a /userhost on the user, which gives it the user's address, and then it does a /mode # +b <user address>.

If you specify the **-uN** option then mIRC pauses N seconds before removing the ban.

If you do not specify a ban type, then mIRC uses the whole nick!*user@host.domain to do the ban. If you are banning an IP address then a wild card replaces the last number of the IP address. If you are on the channel then the #channel specification is not necessary.

For a list of ban types see the **\$mask** identifier in the [Identifiers](#) section.

Note: This command uses the [Internal Address List](#) maintained by mIRC.

/beep <number> <delay>

This beeps a number of times with a delay.

/channel

This pops up the channel central window (only works in a channel)

/clear [windowname]

This clears the entire scrollbar buffer of the current window. If you specify a window name, that window's buffer will be cleared.

/close [-icfgms] [nick1] ... [nickN]

This closes **all** windows of the specified type and nicknames. If **no** nicknames are given, **all** windows of the specified type are closed. The type of window is denoted by c for chat, f for fserve, g for get, i for inactive dcc windows, m for message (query), s for send.

If you wanted to close all **chat and fserve** windows for user **Nerp**:

```
/close -cf Nerp
```

/closemsg [windowname]

This closes the specified message window.

/creq [ask | auto | ignore]

This is the command line equivalent of setting the DCC Chat request radio buttons in the dcc options dialog (see /sreq below).

/dcc send <nickname> <filename>

This initiates a sending a file to another user. It can take multiple file names, the format is:

```
/dcc send <nickname> <file1> <file2> <file3> ... <fileN>
```

This will initiate multiple dcc send sessions to the specified user.

/dde [-r] <service> <topic> <item> [data]

This allows you to send information to other applications. See the [DDE Control](#) section for a full explanation.

/disconnect

This forces a hard and immediate disconnect from a server. This is different from the /quit command which sends a quit message to the server and waits for the server to disconnect you.

/dns <nick|address>

This is used to resolve an address. If mIRC sees a "." in the name you specify it assumes it's an address and tries to resolve it. Otherwise it assumes it's a nickname and does a /userhost to find the users address and then resolves it. If you give it an IP address, it looks up the host name.

/echo [colornumber] <-sa|#channel|[nick]> <text>

This prints text in the specified window using the specified colour (0 to 15).

```
/echo 3 #mIRC Testing
```

would print "Testing" in the colour green in channel window #mIRC, assuming it's already open.

To print in the status window use the -s switch, to print in the currently active window use the -a switch.

Note: This text is only printed in your window, it isn't sent to the server.

/exit

This forces mIRC to closedown and exit.

`/finger <nick/address>`

This does a finger on a user. If you specify an address then the address is immediately fingered. If you specify a nickname then the users address is looked up using a /userhost and then it is fingered.

`/flood [on|off|clear] <bytes> <maxlines> <maxmessages> <ignoretime>`

This allows you turn flood protection on and off. See the Flood section for a full description.

`/flushini <filename>`

This flushes the specified INI file to the hard disk. This is necessary because of the way INI files are cached in memory, so you might need to do this to make sure that your INI file doesnt lose information if you're updating the INI file frequently.

`/font`

This pops up the font dialog for the active window.

`/fsend [on | off]`

This allows you to turn fast send on or off.

`/fserve`

This initiates a fileserver session to another user. See the File Server section.

`/goto <name>`

This is used in a script definition to jump to different points in the script. See the aliases section.

`/halt`

This halts a currently executing script and prevents any further processing from continuing. You can use this in remote commands to prevent mIRC from replying to normal ctcp messages, or in aliases to halt an alias, and any calling aliases, completely.

`/help`

This brings up the Basic IRC Commands section in the mIRC help file. You can also do /help <keyword> and if the keyword matches a help topic you will be taken to it.

`/ial [on|off]`

Turns the Internal Address List on and off.

`/identd [on|off] [userid]`

Turns identd server on and off, and changes to a new userid if it is specified.

`/ignore [-rpcntiu#] <nickname/address> [type]`

This allows you to ignore messages from the specified nick, see the Control section for a full description.

`/links`

This retrieves the servers to which your current server is linked and lists them in a window for easy viewing and access.

`/load <-a|-pscqnm|-ruvs> <filename>`

This loads the specified alias, popup, or script.

/load -a aliases.ini loads an aliases file

/load -pc status.ini loads a channel popup
/load -pn status.ini loads a nickname list popup

/load -ru users.ini loads a users file
/load -rv vars.ini loads a variables file
/load -rs script.ini loads a scripts file

Note: You can only load one section at a time.

/loadbuf [lines] <window> <filename>

This allows you to load the specified number of lines from the end of the file of filename into the specified window.

/log [on|off] [windowname]

This allows you switch logging on and off for a window.

/nick <nickname> [alternate]

This allows you to change your current nicknames.

/notify <nickname> <note>

This allows you to add a nickname with a note to your notify list. If you don't specify a nickname, a notify request is sent to the irc server to update your notify list.

/omsg [#channel] <message>

This and the **/onotice** command sends the specified message to all channel ops on a channel. You must be a channel operator to use these commands. If the #channel isn't specified, then the current channel is used.

/partall [message]

This parts all of the channels you are currently on. On certain IRC Servers, you can also specify a message.

/perform [on|off]

This allows you to turn the "Perform these commands" section of the Perform dialog on and off.

/play [-cp q# m# rl# t#] [channel/nick] <filename> [delay]

This is a powerful command that allows you to send text files, or parts of them, to a user or a channel.

The **delay** is in milliseconds. If you play files too quickly to a server you will probably be disconnected for flooding. The default setting is 1000 ie. 1 second. Empty lines between text are treated as a delay.

```
/play c:\text\mypoeem.txt 1500
```

The **-c** switch forces mIRC to interpret lines as actual commands instead of plain text.

The /play command **queues** requests by users; it does this because if it tried to play all requests at the same time you would probably be disconnected from a server for flooding.

The **-p** switch indicates that this is a priority play request and should be placed at the head of the queue for immediate playing. The current play request will be paused and will resume once this play request is finished.

The **-q#** switch specifies the maximum number of requests that can be queued. If the queue length is already larger than or equal to the specified number then the play request is ignored.

```
/play -q5 c:\text\info.txt 1000
```

The **-m#** switch limits the number of requests that can be queued by a specific user/channel. If the user/channel already has or exceeds the specified number of requests queued then the play request is ignored.

```
/play -m1 info.txt 1000
```

The above line limits each user to a maximum of one request at a time and ignores all of their other requests.

Note: The **-q#** and **-m#** switches only apply to a /play initiated via a remote definition, not by you.

To combine the above switches you would do:

```
/play -cpq5m1 info.txt 1000
```

The **-r** switch forces a single line to be chosen randomly from a file and played.

```
/play -r action.txt 1500
```

The **-l#** switch forces the specified line-number to be read from a file and played.

```
/play -l25 witty.txt 1500
```

For both **-r** and **-l#** the first line in the file **must** be a single number specifying the number of lines in the file.

The **-t** switch forces mIRC to look up the specified topic in the file and play all lines under that topic. For example:

```
/play -thelp1 c:\help.txt
```

In the help.txt file you would have:

```
[help1]  
line1  
line2  
line3
```

```
[help2]
```

```
...
```

mIRC will play everything after [help1] and stop when it reaches the next topic header or the end of the file.

You can also use the **\$pnick** identifier in commands which identifies the nick/channel to which you are playing.

/pop <delay> [#channel] <nickname>

This performs a delayed Op on a nickname. The purpose of this command is to prevent a channel window filling up with Op mode changes whenever several users have the same nickname in their auto-op section.

mIRC will pause around <delay> seconds before performing the Op. If <delay> is zero, it does an immediate Op. Before performing the Op it checks if the user is already Opped. If you do not specify the #channel, the current channel is assumed.

/raw [-q] <command>

This sends any parameters you supply directly to the server. You **must** know the correct RAW format of the command you are sending. Useful for sending commands which mIRC hasn't implemented yet. The -q switch makes the raw work quietly without printing what it's sending. This command does the same thing as **/quote** in other IRC clients.

```
/raw PRIVMSG nickname :Hellooo there!
```

/remini <infile> <section> [item]

This allows you to delete whole sections or single items in an INI file.

```
/remini my.ini DDE ServerStatus
```

This would delete the ServerStatus item, and:

```
/remini my.ini DDE
```

Would delete the DDE section.

See the /writeini command below for a related example.

Warning: Do not use this command to modify any of the INI files currently being used by mIRC.

/remove <filename>

This deletes the specified file.

/return [value]

This halts a currently executing script and allows the calling routine to continue processing. You can also optionally return a **value** which will be stored in the **\$result** identifier. The \$result can then be used in the calling routine.

/run <filename> [parameters]

This allows you to run the specified program with parameters.

```
/run c:\net\ftp.exe sunsite.unc.edu
```

This runs the ftp program with the parameter sunsite.unc.edu.

```
/run notepad.exe $?
```

This asks you for a parameter and runs notepad using the parameter as the filename.

If you specify a **non-executable** file, mIRC tries to find the program associated with that file and then runs it.

/run info.txt

/save <-pscqnm|-ruv> <filename>

This saves the specified popup or remote users/variables file.

/save -ps status.inisaves the status popup to status.ini

/save -pn nick.ini saves the nickname list popup to nick.ini

/save -ru users.ini saves the user list to users.ini

/save -rv vars.ini saves the variables list to vars.ini

Note: You can only save one section at a time.

/savebuf [lines] <window> <filename>

This allows you to save the specified number of lines from the end of the buffer of the specified window into the specified filename.

/say <message>

This lets you define an alias that writes directly to a channel as if you were saying something. So "/say Hello there" would be the same as just typing "Hello there". This is useful in an alias when you want to ask the same question (or send the same information) again and again.

/info /say Please note that the games server is currently down and will be offline for a few hours...

Note: You can't use this command in the remote section. Use /msg #channel <message> instead.

/server <server/groupname> [port] [password]

This connects you to a server, first disconnecting you from the current server.

/server irc.server.co.uk 6667 mypassword

If you type /server with no parameters, mIRC will connect to the last server you used. If you use the server command while still connected, you will be disconnected with your normal quit message and will then connect to the specified server.

You can also use /server N which connects to the Nth server in the server list in the setup dialog.

You can also use /server groupname which will cycle through all the servers in the server list which have that group name until it connects to one of them.

/set and /unset

These allow you to define and undefine your own Variables.

/sound

This sends a sound request to another user. See the Sound Requests dialog for more information.

/speak <text>

This sends the specified text to Monologue (or Text Assist) which is a program that speaks whatever text is sent to it.

/splay <filename>

This plays the specified .wav or .mid file. If you do not specify a directory, the sounds directory from the Sound Requests options dialog is used. You can also use **/splay stop** to stop a .mid file from playing.

/sreq [ask | auto | ignore]

This is the command line equivalent of setting the DCC Send request radio buttons in the dcc options dialog (see /creq above).

/strip [+ -burc]

Turns control code stripping options in Options dialog on/off.

```
/strip +bur-c
```

would turn bold, underline, reverse stripping **on**, and turn color stripping **off**.

/timer[N] [-o] [time] <repetitions> <interval in seconds> <commands>

This activates the specified timer to perform the specified command at a specified interval, and optionally at a specified time.

If you are not connected to a server and you start a timer, it defaults to being an offline timer which means it will continue to run whether you are connected to a server or not.

If you are connected to a server and you start a timer, it defaults to being an online timer, which means that if you disconnect from the server, it will be turned off. You can specify the **-o** switch to force it to be an offline timer.

```
/timer1 0 20 /ame is AWAY!
```

Timer1 will repeat an all channel action every 20 seconds until you stop the timer.

```
/timer5 10 60 /msg #games For more info on the latest games do /msg GaMeBoT info
```

Timer5 will repeat this message to channel #games every sixty seconds and stop after 10 times.

```
/timer9 14:30 1 1 /say It's now 2:30pm
```

This will wait until 2:30pm and will then announce the time once and stop.

To see a list of active timers type /timers. To see the setting for timer1 type /timer1. To deactivate timer1 type /timer1 off. To deactivate all timers type /timers off. If you are activating a new timer you do not need to specify the timer number, just use:

```
/timer 10 20 /ame I'm not here!
```

And mIRC will allocate the first free timer it finds to this command.

You can force identifiers to be reevaluated when used in a /timer command by using the format \$!me or \$!time.

If you wish to turn off a range of timers, you can use a wildcard for the number, for example:

```
/timer3? off
```

Will turn off all timers from 30 to 39.

/timestamp [-s|a|e] [on|off] [windowname]

This turns time-stamping of events on/off, and attempts to timestamp **most** events that occur.

- s = for status window
- a = for active window
- e = for every window

If a windowname is not specified, then the global timestamp switch is turned on or off.

/titlebar <text>

This allows you to set the main application titlebar.

/unload <-a|-rs> <filename>

This unloads the specified alias or remote script file.

```
/unload -a aliases.ini      unloads the alias.ini file
/unload -rs script.ini      unloads the script.ini file
```

Note: You can only unload one section at a time.

/url [-d] [on|off|hide]

This pops up the URL list window. If you specify the [-d] then all "?" marked items will be deleted before showing the window.

You can also use **on|off** to turn URL catching on or off and **hide** to hide the URL window if it is currently showing.

See [URL Catcher](#) options for other settings.

/uwho [nickname]

This pops up a user window showing information about the specified user. It is the same information you would get if you did a "/whois nickname". You can also build up a list of nicknames and their associated real name and machine address. The format is: /uwho nickname

/window [-abcdelnorsx] <@name> [x y [w h]] [/command] [popup.txt] [font [size]]

This allows you to create and manipulate custom windows.

/write [-cid |# s#] <filename> [text]

This allows you to write lines to a file.

```
/write store.txt This line will be appended to the file store.txt
```

The **-c** switch clears the file completely before writing to it, so it allows you to start with a clean slate.

```
/write -c c:\info.txt This file will be erased and have this line written to it
```

The **-l#** switch specifies the line number where the text is to be written. If you do not specify a line number then the line is added to the end of the file.

`/write -i5 c:\info.txt` This line will overwrite the 5th line in the file

The **-i** switch indicates that the text should be inserted at the specified line instead of overwriting it. If you do not specify any text then a blank line is inserted. If you do not specify a line number then a blank line is added to the end of the file.

`/write -i5 c:\info.txt` This line will be inserted at the 5th line in the file

The **-d** switch deletes a line in the file. If you don't specify a line number then the last line in the file is deleted.

`/write -d15 c:\info.txt`

The above command will delete the 5th line in the file.

The **-s#** switch scans a file for the line beginning with the specified text and performs the operation on that line.

`/write -dstest c:\info.txt`

This will scan file info.txt for a line beginning with the word "test" and if found, deletes it.

If you do not specify any switches then the text is just added to the end of the file.

`/writeini <infile> <section> [item] [value]`

This allows you to write to files in a standard INI file format which should make storing and retrieving related bits of information a lot easier than with `/write`.

A part of the mirc.ini file looks like this:

```
[DDE]
ServerStatus=on
ServiceName=mirc
```

You could achieve this with `/writeini` by using:

```
/writeini my.ini DDE ServerStatus on
/writeini my.ini DDE ServiceName mirc
```

You can delete whole sections or items by using the `/remini` command.

Warning: Do not use this command to modify any of the INI files currently being used by mIRC.

Other features

System Menu

Help Menu

Window Menu

Text Copy and Paste

Bold, Underline, Reverse, Colour Text

File Server

Key Combinations

Command Line Parameters

Miscellaneous Stuff

The File Server

The mIRC fileserver allows other users to access files on your hard disk and is therefore **dangerous** since if used **improperly** it will allow them to access private/confidential information.

The /fserve command

A fileserver is initiated by using the **/fserve** command which initiates a DCC Chat to the specified user. You must specify a homedirectory. The user will be limited to accessing only files and directories within this homedirectory. The format is:

/fserve <nickname> <maxgets> <homedirectory> <welcomefile>

The **maxgets** is the maximum number of **simultaneous** dcc gets that a user can have during a fileserver session.

The **welcome file** is a text file that is sent to the user when they first connect. For example:

```
/fserve goat 5 c:\users\level1 level1.txt
```

This will initiate a fileserver session to user goat with his homedirectory as c:\users\level1 and will send goat the text in the level1.txt file (presumably informing him that he is a level1 user and what files he can access etc.). The user can only have 5 simultaneous gets.

In each directory, you can place a **dirinfo.srv** file which describes that directory. Everytime the user does a CD to change into a directory, mIRC will look for this file and if it finds it, the text in it will be sent to the user.

Fileserver commands

The commands available to a user once they're connected to your fileserver are:

cd - change directory.

dir [-b|k] [-#] [/w] - lists the name and size of each file in the current directory. The /w switch forces a wide listing. The [-b|k] selects bytes or k's. The [-#] specifies the number of files on each line in a horizontal listing.

ls [-b|k] [-#] - lists the name of each file in the current directory using a wide listing.

get <filename> - asks the fileserver to DCC Send the specified file.

read [-numlines] <filename.txt> - reads the specified text file. The user will be sent a default of 20 lines and then prompted whether to continue listing. The -numlines option changes the default number of lines to a value between 5 and 50.

help - lists the available commands.

exit or **bye** - terminates the connection.

Note:

1. It will improve performance a lot if you make sure that your directories are not too large. If a directory has a large number of files try to split them up into subdirectories.

2.If a user is idle too long the fileserver will automatically close the connection. You can set the idle time out in the DCC Options dialog.

3.A user is limited to opening a **single** fileserver session at any one time. If mIRC initiates a fileserver session to a user and that user doesnt respond then the fileserver session will have to time-out and close before that user can ask for another session.

System menu

If you click the **system menu** button in the top left hand corner of a window ie. the button you usually double-click to close a window, it will popup the usual system menu but with a few added functions (these vary depending on the type of window).

Position

You can tell mIRC to **remember** or **forget** the position/size of a window. If you select remember, the next time that window opens up it will do so in the saved position. If you choose **reset**, the window will be moved back to it's previously saved position.

Note: if a windows saved position lies outside the size of the main window then it will open in a default position and size. To force a window to open up in default positions assigned by windows, select **forget**.

Buffer

You can **clear** the text in the current window buffer or you can **save** the text to a file.

Font

This allows you to change the current or default font for a window. The font settings for each window will be remembered across sessions. The only fonts shown in the font dialog are those which mIRC can properly display.

Logging

If logging is turned on, any text displayed in a window will be logged to a file. This setting stays on across sessions until you switch it off. The filename is automatically taken from the name of the window.

Beeping

If beeping is turned on, mIRC will beep any time a message is sent to the window if it **isn't** active. This setting is remembered across sessions for each window.

Desktop

This allows you to position a window outside of the main mIRC window and onto the desktop.

Stay On Top

This appears only when a window is opened in Desktop mode and forces the window stay above all other windows.

Timestamp

This turns timestamping of events on/off for a window.

Text Copy and Paste

To copy text

You mark the text as usual with the mouse by pressing the left mouse-button and dragging it. The moment you release the left mouse-button, the text will be copied into the clipboard.

If you want to copy text **exactly** as it appears in the window, you can hold down the **Shift** key while you do the copy. Otherwise, text is copied in it's original format.

To paste text

You can then do the usual Shift-Insert key combination to paste the text any where you want.

The limitation

You can only copy the currently displayed text. To copy text from another page, you must scroll up/down to it and then copy it. If you want to store most of the text you see on a channel, you might want to use the logfile/buffer options in the System Menu.

The explanation

The use of colour in mIRC means that a simple text box cannot be used since text boxes can display only plain text (and they also have other limitations). However, text boxes also have built in cut/copy/paste routines which unfortunately are unavailable to a graphic window. This means that I had to code the mark/copy routine myself. I'm not sure which ran out first, my patience or my programming ability :-)

List Channels

The List Channels dialog allows you to retrieve the list of currently active channels. You can view the List Channels dialog by clicking on the List Channels button in the toolbar.

Apply

This allows you to respecify the list parameters without having to retrieve the whole list again from the IRC server. Just change the parameters and then click on apply to have them relisted according to your new criteria.

Get List

This retrieves a list of all of the active channels from the IRC server. This list can be quite long and depending on your connection it might take several minutes to download. The IRC Server actually sends the whole list, regardless of the filters you specify. You will not be able to do anything on IRC until this retrieval has been completed.

Match text

You can enter several words (separated by spaces) which mIRC will look for in channel names. Only those channels which match any of the words you specify will be listed. If you leave this **empty** then all channels will be listed.

Match topic

If this is turned on then mIRC will apply the Match Text procedure to channel topics as well. So only channel topics that match any of the words in the Match text editbox will be listed.

Do not sort

This prevents the channels list from being sorted.

Number of people

This allows you to limit the channels list to those channels which contain a number of people ranging between the specified minimum and maximum.

Lock/Unlock

This allows you lock the Hide parameters with a password thus preventing anyone from changing the Hide settings. The same password must be used to unlock this.

Hide channels which match...

You can enter several words (separated by spaces) which mIRC will look for in both channel names and topics. Any channels which match any of these words will be excluded from the channels list.

Hide non-alphanumeric channels

This will filter out any channels that begin with characters that aren't numbers or letters.

Note: Remember that you can right-click in the Channels List window to pop up the channels list menu.

URL Catcher

mIRC's URL feature currently works with the three major WWW Browsers.

Enable URL Catcher

If this option is turned on mIRC will catch references to URLs and store them in the URL listbox. Turning on this option slows down mIRC a bit since it has to scan each incoming line before printing it, so if you don't need this option it will speed things up if you turn it off.

mIRC looks for URLs beginning with "http://", "ftp://", "gopher://", "www.", and "ftp.". mIRC also checks to make sure addresses are not added to a list if they already exist. Addresses longer than 256 characters are ignored.

On View...

When you select View from the popup menu to view a URL, mIRC can ask your browser to open a new separate URL window and it will also activate it if required.

On Send...

When sending URLs to a channel, query, etc. mIRC can send only the URL or both the URL and it's description.

Place ? marked URLs at top of list

If this is checked then mIRC will place ? marked URLs at the top of the URL list, otherwise they will be placed at the bottom of the list.

Delete All ? marked URLs on exit

To prevent your URL list getting too long you can choose to have all ? marked items deleted when you exit mIRC. Any items whose marker has been changed to something other than ? will remain in your list for future reference.

Location and name of WWW browser

This specifies your WWW browser so that mIRC can run it (if it isn't already running) when you select view from the popup menu.

Note: You can click your right mouse-button in the URL window for a popup menu which provides various URL functions.

Sound Requests

Sound requests allow users to share the experience of playing sounds together. When someone uses the **/sound** command on a channel, all users on the channel who have that same sound will hear it play.

Accept sound requests

If this option is turned on, mIRC will listen for **/sound** requests from other users.

On Sound Request...

If a sound is already playing and a new sound request is received, you can either have mIRC halt the currently playing sound and play the new sound, or you can choose to have mIRC ignore the new sound.

mIRC can also **warn** you if a user has requested a sound that you don't have so that you can then ask the user for that sound.

Listen for "!nick file" get requests

If this is turned on mIRC will listen for requests from other users who don't have your sound and want to DCC Get it from you. The request must be of the form **!yournickname filename**, where filename is a .wav or .mid file that you have. mIRC will DCC Send the requested sound to the user automatically.

Send "!nick file" as private message

If this is turned on, then whenever you use the **!nick file** format to DCC Get a file from another user, mIRC will send the request as a private message instead of as a channel message. The purpose of this is to prevent such messages from cluttering the channel.

Location of wave/midi files

Whenever a sound is requested, mIRC will look in these directories and all of their **subdirectories** for it. These directories are also searched when you use the [/splay](#) command.

The **/sound** command

You can send a sound request to another user using the **/sound** command.

/sound [on|off|nick/channel] <file.wav|file.mid> <message>

If a **nick/channel** is not specified, the message is sent to the current channel or query window.

The sound file must end in **.wav or .mid**, and may be located in the default sounds directory or in any of the subdirectories in the sounds directory. You do not need to specify a directory for the filename unless the file is not in the sounds directory.

The **message** is optional, if you do provide one it appears exactly like an action command.

The Internal Address List

mIRC maintains an **internal address list** of all users who are currently on the same **channels** as you.

This address list is used by the /guser, /ruser, /ban, /ignore, /finger, and /dns commands to quickly find a user's address without resorting to a **/userhost** server lookup.

A user's address is **added** to the list either when they join the channel, send a message to a channel, or make a mode change.

A user's address is **removed** from the list when they are no longer on any of the channels which you are currently on.

The reason why only addresses for users on the **same channels** as you are stored is because this guarantees the **integrity** of the list. ie. that a specific nickname is associated with a specific address.

Note: Maintaining the integrity of the internal address list requires quite a bit of processing. For people with faster computers this won't make a difference but for others this might slow down IRCing quite a bit if you are on several channels with lots of people with many messages, modes, joins, parts, etc. mIRC has to keep checking it's internal list to make sure it is updated correctly.

You can turn the Internal Address List off in the remote dialog if you find that it is slowing down your IRC session too much.

Key Combinations

F1

Shows the help file and is context sensitive, so you can press it in a dialog and it will bring up the help file section describing that dialog. Remember that if this key is redefined as an alias it will no longer work as a help key.

Shift-F1

Displays the Keyword search dialog for the help file. If this is redefined as an alias it will no longer work as a help key.

Control-Tab

Switches quickly between windows.

Shift-Tab

Switches between the editbox and the nickname listbox in a channel window.

Control-Space

Cycles through channel windows.

Tab

Inserts a "/msg nickname" into the editbox of the window you are currently on, where **nickname** is the nickname of the last person that messaged you.

Cursor Up/Down

Browses the command line history buffer for a single-line editbox.

Control-Cursor Up/Down

Browses the command line history buffer for a multi-line editbox.

Page Up/Down

Browses the scrollback buffer of a window a page at a time.

Control-Page Up/Down

Browses the scrollback buffer of a window a line at a time.

ESCAPE key

Quickly minimizes the active window, it must be turned on in the Extras dialog.

Shift key

If you want to copy text exactly as it appears in a window, you can hold down the **Shift** key while you do the copy. Otherwise, text is copied in it's original format.

Control key

If you want to send information beginning with the / command prefix and you want it to be sent as normal text instead of **interpreted** as a command, just hold down the **Control** key when you press enter.

Control B/U/R/K

Inserts control characters for bold, underline, reverse and color in text.

Command Line Parameters

You can specify the following parameters on the command line:

-s<server:port> forces mIRC to connect to the specified server and port on startup.

-j<#chan1,...,#chanN> forces mIRC to join the specified channels on connect.

-p<password> specifies password required to join channel.

-n<nick1,nick2> sets your nickname and alternate nickname to these nicks.

-i<filename.ini> forces mIRC to use the specified INI file.

IRC Switches

Prefix own messages

If this is selected, your nickname will prefix any messages you type in a channel/query/chat.

Iconify query window

If someone sends you a query, the default is for the query window to open, ready for input. You can select this option to force mIRC to iconify the window preventing it from taking the focus from the window you are currently in.

Dedicated query window

This directs all private messages or notices from other users to one single message window. You will need to use the /msg command to reply. If you want to open a query window to a user, use the /query window.

Whois on query

Select this to have mIRC do a /whois nickname on any person that sends you a private message. The /whois will be done the first time the query window is opened.

Auto-join on invite

This will make you automatically join a channel when you are invited to it. mIRC will also try to minimize the window, however this might not always work.

Rejoin channel when kicked

If you are kicked from a channel, mIRC will immediately try to rejoin the same channel. It won't close the channel window unless it finds that you can't rejoin the channel.

Cancel away on keypress

If you set yourself as away (using /away <message>) then selecting this option cancels the away option automatically if you type a message to a channel or a query/chat window.

Timestamp events

This will prefix most events with the time of their occurrence.

Skip MOTD on connect

This makes mIRC hide any MOTD information which the server sends you when you first connect to it.

Show Alternate Join/Part/Quit

Checking this option makes mIRC display the join, part, and quit messages in a different, more compact format.

Show user addresses

Whenever a user joins/parts/quits/is kicked/etc. from a channel, you can choose to see their address by selecting this option.

Show quits in channel

Normally if a user on the same channel as you quits IRC, this message is only printed in the status window. If you want the quit message to be printed in the channel window as well then select this option.

Show joins/parts in channel

You can turn off this option if you are on channels that are very crowded and your channel

window is filling up with joins and parts. The joins and parts will instead be sent to the status window.

Show invites in active window

If this setting is turned off then invite messages will appear in the status window.

Show modes in channel

Normally all mode changes are shown in a channel window but you can turn this option off to dump these to the status window.

Show queries in active window

This shows all queries in the active channel window instead of opening up a query window. However, if you are not in a channel window, a query window will be opened.

Strip Codes

This allows you to strip out the Bold, Underline, Reverse, and Color codes from incoming private messages or channel messages.

Perform

Highlight text with these words

On a channel, any lines which contain words matching any words in your list will be highlighted in the highlight colour you've chosen in the [Colour dialog](#). This eases locating messages directed at you or about you eg. you could place your nickname in this box. The line you enter must consist of words separated by commas.

Beep on highlighted word

This works in conjunction with the highlight option. If a matching word appears and this option is checked then mIRC will beep.

On connect, perform these commands

You can enter a set of commands in this box which will be performed every time you connect to IRC. To understand how commands work, see the [Aliases](#) help section. A quick example:

```
/names #mirc,#irchelp | /join #winsock
```

Ctcp finger reply

The message a user receives when they /ctcp finger you.

Quit message

The message displayed to other users when you quit IRC.

Event Beeps

On event, beep...

Certain events cause a number of beeps to be made to alert you of their occurrence. It is possible to alter the number of beeps as well as how quickly they are sounded. The seconds value is in milliseconds. To turn off notification all together, specify zero beeps.

On event...

This allows you to turn on/off sounds for specific events. eg. for the disconnect event, if you are **disconnected** by the server without having typed /quit or selected the disconnect menu item, then mIRC will beep or play the specified sound to indicate that you are no longer connected to IRC.

Beep on channel message

Whenever a message is sent to a channel window that isn't currently the active window, mIRC will beep. Note that all this option does is automatically turn on the **Beep** setting in a channel window's System Menu when it first opens. So changing this setting doesn't affect windows which are already open.

Beep on query message

Whenever a message is sent to a query window that isn't currently the active window, mIRC will beep. Note that all this option does is automatically turn on the **Beep** setting in a query window's System Menu when it first opens. So changing this setting doesn't affect windows which are already open.

Beep on message while in buffer

Selecting this option will make mIRC beep if someone speaks on a channel while you are scrolling back through lines in the scrollback buffer.

Logging

Automatic logging

This allows you to automatically log **channel** and **chat** automatically whenever they open.

Strip control codes

This makes mIRC strip any Bold, Underline, Reverse, or Colour control codes from text that is being logged to a file.

Log files

You can view and delete any log files which are listed in your Logs and Buffers directory.

Log and Buffers directory

The directory in which all log files and buffer saves are stored.

Finger Server

The finger server listens for **finger requests** on port 79.

Enable finger server

This turns on the finger server.

Show finger requests

If this is turned on, finger requests are displayed in the status window.

Finger file

You can specify a finger file, which must be a plain text file, and this must be set up with **named sections** which will be used to reply to any finger requests. Each section begins in the following way:

```
[name]
line1
.
.
.
lineN
```

The section name corresponds to the **userid** that is being fingered. eg. if someone fingers khaled@mardam.demon.co.uk, then I will have a section named [khaled].

There should be at least one section named **[default]** which will be used to reply to a finger request which does not specify a user, or specifies a user that doesn't exist.

Therefore, for my own system I would have two sections:

```
[default]
etc.
```

```
[khaled]
etc.
```

This can, for example, allow you to setup a menu system, with various sections that can answer user finger queries, the default section being the main menu.

On a related note, check out the [/finger](#) command.

Local Info

Your **Local Host** and **IP Address** are needed if you want to use the DCC capabilities of mIRC.

mIRC will try to look up these values by itself and display them in the **Setup** dialog. However, if you see the message **Unable to resolve Local host** or you are unable to **initiate DCC sessions**, then changing the settings below might help.

If you see the message **Unable to resolve Local host** with the **32bit version of mIRC**, the problem might be related to using a **16bit winsock**, so you should try out the **16bit version of mIRC** to see if it works for you.

Local Host

This is used to register with the server and may be the part of your email address after the @ sign, eg. if my email address is khaled@mardam.demon.co.uk, then I would enter mardam.demon.co.uk here.

If you leave this box empty then mIRC will try to get your local hostname by itself. However, if mIRC replies with the message **Unable to get local hostname** then you will have to fill in your local hostname manually. mIRC will then use whatever you have entered to get your IP address...

IP Address

This will normally be filled in by mIRC and is here mainly for your information. mIRC looks up your IP address and stores it in the mirc.ini file for future reference. This way it doesn't have to look it up every time you want to connect.

If mIRC is having trouble getting your IP address then you can enter this value manually and mIRC will assume that it is correct. If this value is wrong you will still be able to log on to IRC but you will not be able to initiate DCC Send/Chat sessions (you will only be able to accept them).

On connect, always get...

These options are here because of the different types of internet connections people have. Some people have a fixed Local hostname and IP address, other have a dynamic Local Hostname, others a dynamic IP address, and yet others have both. If you don't know what kind of connection you have, leave both of these checked.

Selecting **Always get Local Host** automatically turns on the **Always get IP address** option. De-selecting the **Always get IP address** option automatically turns off the **Always get Local Host** option.

IP Method

If you find that mIRC is not resolving your IP address correctly you might try changing from **Normal** to **Server** or vice versa, which might solve the problem.

With the **Normal** method, mIRC relies on your winsock to reply with the correct information.

With the **Server** method, mIRC looks up your local host through the IRC Server, and then performs a dns on it to resolve it to an IP address.

The Server method will most likely be slower, you can tell when it has been completed

when you see your DCC Send/Chat toolbar buttons enabled, and also when your DCC Send/Chat menu items in the DCC menu become available.

Note: If changing the above switches **still** doesn't solve the problem, or you don't know what to enter for your local host or ip address, contact your **internet provider** or **system administrator**.

Long File Names With Spaces In Them

The DCC protocol doesn't take into account the possibility of a filename containing spaces, so most if not all IRC clients will incorrectly interpret the following DCC Send message:

PRIVMSG nick :DCC SEND This is a long file name with spaces in it ipaddress port filesize

Thus mIRC gives you the **Fill Spaces** option; this fills spaces in a filename with the underscore character `_`, which should then allow other clients to interpret the message correctly. So other clients would see:

PRIVMSG nick :DCC SEND This_is_a_long_file_name_with_spaces_in_it ipaddress port filesize

If the Fill Spaces option isn't selected then mIRC sends **"Long File Names with Spaces in them"** enclosed in quotes. For example:

PRIVMSG nick :DCC SEND "This is a long file name with spaces in it" ipaddress port filesize

As far as I know, only mIRC can send and receive messages of this form (and only versions 3.8 and onwards), so if you try using this dcc send message with other clients it probably won't work.

Moo! ;)

Firewall

mIRC can access an irc server through a **SOCKS firewall**.

The main purpose of this option is to allow someone to access IRC through a SOCKS server at work, or more rarely through a network set up at home. The majority of home users should keep this option turned off.

Hostname

The machine name of your SOCKS server, can be either a named address or an IP address.

User ID

Can be the account or user name on your system. For most people this will be the User ID portion of their email address (the text before the @ sign).

Password

The password required to access the firewall.

Port

This is usually be 1080.

Note: Only connecting to an IRC server is supported at this time. DCC Send/Chat, etc. through a firewall are not supported.

Control

The following settings are related to channel and user control.

Auto-Op

If a user joins a channel where you have Ops and that user's address is listed in the auto-op list, they will be given Op status. You can add an address to the list in the following format:

nick!userid@host.domain,#channel1,#channel2

On IRC, user addresses are specified in the format:

nick!userid@host.domain

So if my nickname is **MadGoat** and my address is **khaled@mardam.demon.co.uk** then to put me in your list, you would use:

madgoat!khaled@mardam.demon.co.uk

If I change nicknames a lot, then you would use:

***!khaled@mardam.demon.co.uk**

If I change my nickname and userid a lot, then:

***!*@mardam.demon.co.uk**

The /auto command

/auto [-r] <on|off|nickname/address> [#channel1,#channel2,...] [type]

The **-r** switch indicates that the address is to be removed.

If you do **not** specify a type then only the users nick is added to the op list. If you specify a type then the users address is looked up via the server and added to the list.

Random delay auto-op

This option introduces a random 1 to 7 seconds delay in the auto-op routine. This is to prevent channel windows from filling up with mode notifications whenever a nickname is in the auto-op list of several users. If at the end of the random delay the user has already been opped then mIRC does not perform an Op.

Ignore

If a user sends you a message, whether on a channel or in private, and that user's address is in the ignore list, the users message will be ignored and won't be displayed. You can add an address to the list in the following format:

nick!userid@host.domain,private,invite,ctcp

The /ignore command

/ignore [-rpcntiku#] <on|off|nickname/address> [type]

Where p = private, c = channel, n = notice, t = ctcp, i = invite, k = control codes.

The **-u#** switch specifies a delay in seconds after which the ignore is automatically removed.

The **-r** switch indicates that the address is to be removed.

If you do **not** specify a type then only the users nick is ignored. If you specify a type then the users address is looked up via the server and all messages coming from this address will be ignored.

Protect

If you are on a channel and you have channel Op status, any users that match the given nicknames will be automatically protected. mIRC does this by kicking or de-opping anyone who tries to kick or de-op your protected users. You can add an address to the list in the following format:

nickname,#channel1,#channel2

Note: This option is limited to using **nicknames** because of the way IRC servers work.

The /protect command

/protect [-r] <on|off|nickname> [#channel1,#channel2,...]

The **-k** switch ignores colour/bold/underline/reverse control codes in a message.

The **-r** switch indicates that the address is to be removed.

Notify List

The **notify** feature allows you to specify nicknames which you want mIRC to look for when you're connected to an IRC Server. mIRC will **inform** you whenever a nickname **joins** or **leaves** the IRC network you are on. You will also be informed if no users in your list are on IRC when you **first** connect.

mIRC checks the server and updates its notify list every **40 seconds or so** thereafter.

Adding a User

To add a user just enter the following information and click on the **Add** button.

Nickname

The nickname of a user that you want notify to look for.

Note

An optional note or reminder that will appear next to the users nickname.

Play sound

The sound that you want played whenever the user joins IRC.

Perform /whois

This option makes mIRC perform a **/whois** on the user when they join IRC to look up their address. You should only use this option if you really need to, if you use it with too many nicknames then the IRC server might disconnect you for flooding.

Add/Update/Delete

To add or delete users from the list. After you make a change to the settings of an existing user, you must click the **Update** button.

Show notifies in active window

The default is to show notifies in the status window, however checking this option will also show notifications in the current active window.

Only show notifies in notify window

This will make mIRC display notifies only in the notify window.

Pop up notify window on connect

This will pop up the notify list window when you connect to an irc server.

The /notify command

You can also add/remove nicknames from the notify list by using the /notify command.

/notify [-shr] <on|off|nickname> [note]

You can turn notify on and off by typing **/notify on or off** respectively.

The **-sh** switches can be used to **show or hide** the notify list window respectively

The **note** is optional and allows you to specify a little note for each nickname.

If you prefix a nickname with a **+** sign then mIRC will do a **/whois** on the nickname as part of the notify. However, if you do this on too many nicknames then the IRC server might

disconnect you for flooding, so it's best to use it only if you really need to.

You can manually force mIRC to update the notify list by typing **/notify** with no parameters.

Note: Some IRC networks might let you use a full address instead of just a nickname, the only way to see if it works is to try out.

Variables

Variables are temporary storage areas to which you can assign **values** which you can use later in your scripts. All **currently** defined variables are listed in the remote variables section and can be edited there.

If a variable is referred to and it doesn't exist, it returns the value **\$null**. The **\$null** value can be used in comparisons in if-then-else statements to control branching etc.

The following **commands** allow you to create and set the values of variables.

```
/set <%var> [value]
```

This sets the value of **%var** to **value**.

```
/unset <%var>
```

This **unsets and removes** the specified variables from the variables list. If you specify a variable with **wildcard** characters then all matching variables will be removed.

```
/unset %test*
```

This will **remove** all variables beginning with the word **%test**.

```
/unsetall
```

This **unsets and removes** all variables from the variables list.

```
/inc <%var> [value]
```

This **increases** the value of **%var** by **value**.

```
/dec <%var> [value]
```

This **decreases** the value of **%var** by **value**.

You can also use the **equal** sign to **assign** values to variables:

```
%i = 5
```

```
%count = $1
```

And you can perform the following **operations** on variables when using the **equal** sign:

```
%x = 5 + 1
```

```
%x = 5 - %y
```

```
%x = %x * 2
```

```
%x = %z / $2
```

```
%x = $1 % 3
```

```
%x = 2 ^ %w
```

You can only perform a **single** operation in an assignment at this time.

on BAN/UNBAN

The **on BAN** and **on UNBAN** events trigger when a user on a channel is banned or unbanned.

Format: on <level>:BAN:<#[,#]>:<commands>

Example: on 1:BAN:#mirc,#irchelp:/msg \$nick Sorry but you're not allowed on \$chan

Examples

on 9:BAN:#newbies:/mode \$chan -o \$nick | /mode \$chan -b \$banmask

This triggers when someone bans a user with access level 9. **\$banmask** refers to the banmask used to ban the user.

on 1:UNBAN:#:/msg \$bnick You have just been unbanned

This triggers when any user is unbanned from any channel. **\$bnick** refers to the banned users nickname, however this would actually only be filled if the banmask itself includes a nickname. If the banmask does not include a nickname, \$bnick is \$null.

Remember that **\$banmask** is usually a **wildcard string** which means that it will be matching wildcard strings in your remote users section. For example, if someone sets a ban of ***!k*d@*.uk** it will match users:

*!khaled@mardam.demon.co.uk

*!kha*d@*am.d*mo?.co.*

!k@*.u?

Comparing levels

You can **compare the levels** of the banner and the banned by prefixing the line with **<, >, <=, =, >, <>**, or **=**, in the following way:

on >=2:BAN:#mIRC:/msg \$chan \$nick banned \$banmask (legal)

on 1:BAN:#mIRC:/msg \$chan \$nick banned \$banmask (illegal)

In this situation, if the banners level is larger than or equal to the banned users level, then it is a legal ban. Otherwise, it defaults to the second ON BAN line which indicates that it is an illegal ban. Remember, this is comparing the banners and banned users levels and has nothing to do with with the level 2 in the definition.

Note: These events only work on nicknames because the IRC server only sends the nickname of the user being banned/unbanned and not an address. Also, IP addresses will not be matched against named addresses, and banmasks ending in **@*** will be ignored since this can match almost any user address.

How to Register

As described in the [License](#), mIRC is a **Shareware** program, which means that you can use it legally for 30 days free of charge to **evaluate** it. If during, or at the end of, that period you decide that you would like to continue using it, please **register** your copy. Your single-user registration will license you to use your copy of mIRC, will support work on future versions, new features, and bug fixes, and will provide you with technical support via email.

The **latest information** on how to register is always available on the [mIRC homepage](#).

The current registration amount is **US\$20.00** (or **UK£10.00** in Europe).

You can register mIRC either by:

1. Sending a **US** or **UK** personal **check** or **money/postal order** in my name to:

Khaled Mardam-Bey
68 Melbury Court,
London W8 6NJ,
Great Britain

Please make sure you send your **full name**, **postal address**, and **email address** with your registration.

If you are going to send anything **other** than a **UK** or **US** check or money/postal order, please email me first to make sure I can accept it. Note that if the postal order is not from the US or the UK, it should be made out in UK Pounds.

2. Registering **online** with your **Visa/Mastercard Credit Card** through CNET at:

<http://www.buydirect.com>

The registration amount is **US\$20.00** when registering with a credit card.

Once I **receive** your registration, either via snail-mail or via CNET, I will send you an **email** with your registration information. If you've submitted a registration and haven't received a reply, you can email me at khaled@mardam.demon.co.uk to check up on the status of your registration.

You can then **enter your registration information** in the **registration dialog** by going to the **Help menu** in the menubar (not the toolbar) in mIRC, and selecting **Register** at the bottom of the menu.

Drag and Drop

The **Drag and Drop** feature allows you to **pick up files** from other programs eg. a file manager, and **drop** them on either **Message** or **Channel** windows. Depending on the type of file you drop onto a window, a different action will be performed according to the commands you've defined for that file type.

You can define different actions for different types of files by **associating a command** with **a file ending**.

For example, if you wanted to mIRC to **read** a text file to another user whenever you drop files ending in **.txt** then you might make an association such as:

```
*.txt:/play $1 $2
```

In this case, **\$1** stands for the name of the user or channel where the file has been dropped, and **\$2** stands for the name of the file that was dropped. The /play command would send each line in the specified text file to the user.

You can also have different aliases executed for the same file type depending on whether you hold down the **shift key** or not when you drop the file.

Currently the **default** settings for dropping files with **no shift key** pressed are:

```
*.wav:/sound $1 $2  
*.*:/dcc send $1 $2
```

Which means that if you drop a Wave file, it will be played with the /sound command, and if you drop any other type of file it will initiate a dcc send to that user.

The **default** settings for dropping files with the **shift key** held down are:

```
*.*:/dcc send $1 $2
```

Which is the same as above, initiating a dcc send to the active user.

Note: if you drop a file which has a space in it, it is enclosed in "" quotes.

Raw Events

Raw events are special IRC Server messages that are identified only by a number. There are a large number of raw events, far too many to go into here, so it is recommended that you check out the links on the [mIRC Homepage](#) for technical information. The document you are looking for is called **RFC1459**. There is also a numerics help file available which is more up-to-date than this document.

Filtering and **handling** raw messages can be very **time-consuming** because of the large number of messages that a server can send, so you should try to make sure that your scripts process this information as quickly as possible. The format of the raw event definition is:

```
raw <numeric>:<matchtext>:<commands>
```

Examples

As a **quick** example, the following script filters out the **channels list** numeric when you use the /list command.

```
raw 322:*mirc*/:echo 5 $1-
```

The above script matches numeric 322 which is the channels /list numeric and if the line returned by this numeric has the word **mirc** in it, it is printed out in the status window.

Note: You can prevent most raw server messages from printing out their default text by using the /halt command.

on FILESENT/FILERCVD

The **on FILESENT** and **on FILERCVD** events trigger when a dcc send or dcc get succeeds.

Format: on <level>:FILESENT:<filename[,filename]>:<commands>

Example: on 1:FILESENT:*.txt:/msg \$nick I have successfully sent you the \$filename text file

The **on SENDFAIL** and **on GETFAIL** events use the same format as above, and trigger when a dcc send or dcc get fails.

Examples

on 1:FILESENT:*.txt,*.ini:/echo Sent \$filename to \$nick \$address

This triggers when a dcc send succeeds in sending a .txt or .ini file to a user. **\$filename** refers to the filename that was transmitted.

on 1:FILERCVD:*.txt,*.ini:/echo Received \$filename from \$nick | /run notepad.exe \$filename

This triggers when a dcc get succeeds in getting a .txt or .ini file from a user.

on 1:SENDFAIL:*.txt:/echo I failed to send the text file \$filename to \$nick

This triggers when a dcc send failed to send a .txt file to a user.

on 1:GETFAIL:*.zip:/echo I failed to get the zip file \$filename from \$nick

This triggers when a dcc get failed to get a .zip file from a user.

If-then-else statements

The **if-then-else** statement allows you to **compare** values and **execute** different parts of a script based on that comparison.

Basic format

```
if (v1 operator v2) { commands }  
elseif (v1 operator v2) { commands }  
else { commands }
```

The **() brackets** enclose **comparisons**, whereas the **{ } brackets** enclose the **commands** you want to be performed if a comparison is true. You must make sure that the number of **() and { }** brackets match to make sure that the correct comparisons are made, and that the correct commands are executed.

Using brackets **speeds up** processing. If an alias uses **too few** brackets then the statement might be **ambiguous** and the alias will take longer to parse, might be parsed incorrectly, or might not be parsed at all.

You can **nest** as many if-then-else statements as you want inside each other.

The Operators

==	equal to
!=	not equal to
<	less than
>	larger than
>=	larger than or equal to
<=	smaller than or equal to
//	is a multiple of
\\	is not a multiple of
isin	string v1 is in string v2
iswm	wildcard string v1 matches string v2
isnum	number v1 is a number in the range v2 which is in the form n1-n2 (v2 optional)
ison	nickname v1 is on channel v2
isop	nickname v1 is an op on channel v2
isvo	nickname v1 has a voice on channel v2
ischan	if v1 is a channel which you are on.
isauto	if v1 is a user in your auto-op list for channel v2 (v2 optional)
isignore	if v1 is a user in your ignore list with the ignore switch v2 (v2 optional)
isprotect	if v1 is a user in your protect list for channel v2 (v2 optional)
isnotify	if v1 is a user in your notify list.

To **negate** an operator you can prefix it with an **!** exclamation mark.

Combining comparisons

You can combine comparisons by using the **&& for AND** and **|| for OR** characters.

```

number {
  if (($1 > 0) && ($1 < 10)) {
    if ($1 < 5) echo Number is less than five
    else echo Number is greater than five
  }
  else echo Number is out of bounds
}

```

This alias checks if the number you specify, when you type `/number <value>`, lies within the required range.

Examples

```

listops {
  echo 4 * Listing Ops on #
  set %i 1
  :next
  set %nick $nick(%i,#)
  if %nick == $null goto done
  if %nick isop # echo 3 %nick is an Op!
  inc %i
  goto next
:done
  echo 4 * End of Ops list
}

```

This alias lists the Ops on the current channel. It does this the hard way since we could just use `$opnick()` instead but using `$nick()` serves as an example of how **isop** can be used and how **\$null** is returned once we reach the end of the list.

```

GiveOps {
  %i = 0
  %nicks = ""
  :nextnick
  inc %i
  if ($snick(%i,#) == $null) { if ($len(%nicks) > 0) mode # +oooo %nicks | halt }
  %nicks = %nicks $snick(%i,#)
  if (4 // %i) { mode # +oooo %nicks | %nicks = "" }
  goto nextnick
}

```

This is a popup definition which Ops the nicknames which are selected in the current channel nicknames listbox.

```

on 1:ctcpreply:PING* {
  if ($2 == $null) halt
  else {
    %pt = $ctime - $2
    if (%pt < 0) set %pt 0
    if (%pt < 5) echo 4 [PING reply] $nick is too close for comfort
    elseif (%pt < 20) echo 4 [PING reply] $nick is at just about the right distance
    else echo 4 [PING reply] Earth to $nick, earth to $nick
  }
  halt
}

```

```
}
```

This intercepts a ping reply and prints out a silly message based on how far away the person is.

Identifiers

Identifiers return specific values eg. **\$time** would return the **current time**. Whenever mIRC finds an identifier in your command, it **replaces** it with the **current value** of that identifier. Many identifiers also perform functions on data that you supply and then return a result. There are also remote identifiers for use with remote scripts.

Identifiers which cannot be evaluated or evaluate to no value return the value **\$null**. The **\$null** value can be used in comparisons in if-then-else statements to control branching etc.

For all of the following identifiers, you can place **other** identifiers or variables **inside** the brackets.

The identifiers are listed below according to group.

Time and Date identifiers

\$asctime(N)

Converts time values returned by \$ctime (also the ping reply) into a full date in text format.

\$ctime

Returns total number of seconds elapsed since 00:00:00 GMT, January 1, 1970.

\$date

Returns the current date in day/month/year format.

For the date in US format you can use \$adate.

\$day

Returns the name of the current day ie. Monday, Tuesday, etc.

\$duration(N)

Returns the specified number of seconds in a week/day/hour/minute/second format.

\$fulldate

Returns the current date in the format: Wed Jun 26 21:41:02 1996

\$idle

Returns your current idle time (same time as that returned by a ctcp finger).

\$online

Returns the number of seconds elapsed in the Timer dialog.

\$ticks

Returns the number of ticks since your O/S was first started.

\$time

Returns the current time in hour:minute:second format.

\$timer(N)

Returns the timer id of the Nth timer in the timers list.

Properties: com, time, reps, delay, type

`$timer(0)` returns the number of active timers
`$timer(1)` returns the timer id of the 1st timer in the list
`$timer(1).com` returns the command for the 1st timer in the list
`$timer(3).type` returns online/offline status for the 3rd timer in the list

\$timestamp

Returns the current time in [xx:xx] format.

Text and Number identifiers

\$abs(N)

Returns the absolute value of number N.

`$abs(5)` returns 5
`$abs(-1)` returns 1

\$asc(C)

Returns the ascii number of the character C.

`$asc(A)` returns 65
`$asc(*)` returns 42

\$chr(N)

Returns the character with ascii number N.

`$chr(65)` returns A
`$chr(42)` returns *

\$count(string,substring)

Returns the number of times substring occurs in string.

`$count(hello,el)` returns 1
`$count(hello,l)` returns 2

\$left(text,N)

Returns the N left characters of text.

`$left(goodbye,4)` returns good

\$len(text)

Returns the length of text.

`$len(#mIRC)` returns 5

\$lower(text)

Returns text in lowercase.

`$lower(HELLO)` returns hello

\$mid(text,S,N)

Returns the N characters starting at position S in text.

`$mid(othello,3,4)` returns hell

\$pos(string,substring)

Returns a number indicating the position of substring in string.

```
$pos(hello,el) returns 2  
$pos(hello,la) returns $null
```

\$longip

Converts an IP address into a long value and vice-versa.

```
$longip(158.152.50.239) returns 2660774639  
$longip(2660774639) returns 158.152.50.239
```

\$rand(v1,v2)

This works in two ways. If you supply it with numbers for v1 and v2, it will return a random number between v1 and v2. If you supply it with letters, it will return a random letter between letters v1 and v2.

```
$rand(a,z) returns a letter in the range a,b,c,...,z  
$rand(A,Z) returns a letter in the range A,B,C,...,Z  
$rand(0,N) returns a number in the range 0,1,2,...,N
```

\$remove(string,substring)

Removes any occurrence of substring in string.

```
$remove(abcdefg,cd) returns abefg
```

\$replace(string,substring,replacement)

Replaces any occurrence of substring in string with replacement.

```
$replace(abcdefg,cd,xyz) returns abxyzefg
```

\$right(text,N)

Returns the N right characters of text.

```
$right(othello,5) returns hello
```

\$str(text,N)

Returns text repeated N times.

```
$str(ho,3) returns hohoho
```

\$strip(text)

Returns text with all bold, underline, reverse, and colour control codes stripped out.

\$upper(text)

Returns text in uppercase.

```
$upper(hello) returns HELLO
```

File and Directory identifiers

\$dir, \$file, and \$hfile

Allow you to select a filename which is then inserted into an alias. The \$dir identifier pops up a full directory and file dialog, while the \$file just pops up a quick file dialog. The \$hfile is the same as \$file except that it lists files horizontally.

`$dir=["Select a file"] <path and filename>`
`$file=["Select a file"] <path and filename>`
`$hfile=["Select a file"] <path and filename>`

For example, in a popup definition:

Play A Wave:/splay \$file="Choose a wave!" c:\mywaves*.wav

Note: You should not use `$file` or `$dir` with the `/dcc send` command which has it's own built-in dcc send dialog.

\$exists(filename)

Returns `$true` if a file exists and `$false` if it doesn't.

`$exists(c:\mirc\mirc.exe)` returns `$true` or `$false`.

\$findfile(dir,filespec,N)

Searches the specified directory and its subdirectories for the Nth filename matching the filespec and returns the full path and filename if it is found.

`$findfile(c:\mirc*.exe,1)` returns `c:\mirc\mirc.exe`

\$getdir

Returns the DCC Get directory specified in the DCC Options dialog.

\$lines(filename)

Returns the total number of lines in the specified text file.

`$lines(c:\irc\kicks.txt)` returns the total number of lines in `c:\irc\kicks.txt`

\$lof(filename)

Returns the length of the specified file in bytes.

`$lof(c:\net\mirc\mirc32.exe)` returns `605694`

\$logdir

Returns the Logs directory as specified in the Logging section of the Options dialog.

\$mididir

Returns the Midi directory specified in the Sound Requests section of the Options dialog.

\$nofile(filename)

Returns the path in filename without the actual filename.

\$nopath(filename)

Returns filename without a path if it has one.

`$nopath(c:\mirc\mirc.exe)` returns `mirc.exe`

\$mirkdir

Returns the current directory of the mIRC program.

\$read

Reads a line from a file and inserts it into the current position in an alias command. The format is:

```
$read [-nl# -stext] <filename>
```

\$read will insert any text, even commands with identifiers, and these will work like normal commands.

```
/say $read c:\funny.txt
```

Reads a random line from funny.txt and inserts it at that position in the command.

```
/say $read -l24 c:\funny.txt
```

Reads line 24 from funny.txt and inserts it at that position in the command.

```
/kick # $1 $read kicks.txt
```

Reads a random kick line from kicks.txt and uses it in the kick command.

```
/say $read -smirc info.txt
```

Scans the file info.txt for a line beginning with mirc and uses the rest of the line in the alias.

If the **-n** switch is specified then the line read in will not be evaluated and will be treated as plain text.

Note: If the first line in the file is a single number, it must represent the total number of lines in the file. This speeds up the \$read considerably. If you don't specify the total number of lines in the file on the first line, then mIRC will need to count all of the lines itself which could slow down processing. For small files, this will make no difference, but for large files the delay will be noticeable.

\$readini

Reads information from an INI file and inserts into in the current position in an alias command. It works in conjunction with the /writeini command to read information from INI files. The format is:

```
$readini <-n> <filename> <section> <item>
```

```
/echo $readini mirc.ini mIRC nick
```

Reads your nickname from the mirc.ini file.

If the **-n** switch is specified then the line read in will not be evaluated and will be treated as plain text.

\$wavedir

Returns the Waves directory specified in the Sound Requests section of the Options dialog.

Nickname and Address Identifiers

\$address(nickname,type)

Searches the Internal Address List for the address associated with the specified nickname.

```
$address(nick,1) returns nick!userid@domain.host
```


If the Internal Address List doesn't contain a matching nickname, the identifier returns \$null.

See **\$mask()** for a list of types.

\$comchan(nick,N)

Returns the names of channels which both you and nick are on.

\$comchan(nick,0) returns the total number of common channels
\$comchan(nick,1) returns the first common channel name

\$ial(mask,N)

Returns the Nth address matching mask in the Internal Address List.

Properties: nick, user, host, addr

\$ial(*!*@*.demon.co.uk,0) returns the total number of address in the IAL matching *!
!@*.demon.co.uk
\$ial(*!*@*.demon.co.uk,3) returns the 3rd address in the IAL matching *!
!@*.demon.co.uk
\$ial(*!*@*.com,4).nick returns the nick of the 4th matching address ending in .com
\$ial(*!*@*.com,4).user returns the userid of the 4th matching address ending in .com

To scan each address in the IAL you can use \$ial(*,N).

\$level(address)

Finds a matching address in the remote users list and returns its corresponding levels list.

\$level(*!*@mardam.demon.co.uk) returns =5,10,20,21,32

\$mask(address,type)

Returns address with a mask specified by type.

\$mask(nick!khaled@mardam.demon.co.uk,1) returns *!*khaled@mardam.demon.co.uk
\$mask(nick!khaled@mardam.demon.co.uk,2) returns *!*@mardam.demon.co.uk

The available types are:

- 0: *!*user@host.domain
- 1: *!*user@host.domain
- 2: *!*@host.domain
- 3: *!*user@*.domain
- 4: *!*@*.domain
- 5: nick!user@host.domain
- 6: nick!*user@host.domain
- 7: nick!*@host.domain
- 8: nick!*user@*.domain
- 9: nick!*@*.domain

This standard set of masks is also used in other identifiers and commands.

\$me

Returns your current nickname.

\$nick(#,N)

Returns Nth nickname in the channels nickname listbox on channel #.

`$nick(#mIRC,0)` returns the the total number of nicknames on #mIRC

`$nick(#mIRC,1)` returns the 1st nickname on #mIRC

\$nopnick(#,N)

Returns the Nth non-Op nickname on channel #.

`$nopnick(#mIRC,0)` returns the the total number of non-Ops on #mIRC

`$nopnick(#mIRC,1)` returns the 1st non-Op nickname on #mIRC

\$notify(N)

Returns the Nth notify nick currently on IRC.

`$notify(0)` returns the total number of notify nicks on IRC.

`$notify(3)` returns the 3rd notify nick on IRC.

\$nvnick(#,N)

Returns the Nth non-voiced nickname on channel #.

`$nvnick(#mIRC,0)` returns the the total number of non-voiced nicknames on #mIRC

`$nvnick(#mIRC,1)` returns the 1st non-voiced nickname on #mIRC

\$opnick(#,N)

Returns the Nth Op nickname on channel #.

`$opnick(#mIRC,0)` returns the the total number of Ops on #mIRC

`$opnick(#mIRC,1)` returns the 1st Op nickname on #mIRC

\$snicks

Returns a string of the currently selected nicknames in the active channel listbox in the form:

nick1,nick2,nick3,...,nickN

\$snick(#,N)

Returns the Nth selected nickname in the channel listbox on channel #.

`$snick(#mIRC,0)` returns the the total number of selected nicknames on #mIRC

`$snick(#mIRC,1)` returns the 1st selected nickname on #mIRC

\$snotify

Returns the currently selected nickname in the notify list box.

\$vnick(#,N)

Returns the Nth voiced nickname on channel #.

`$vnick(#mIRC,0)` returns the the total number of voiced nicknames on #mIRC

`$vnick(#mIRC,1)` returns the 1st voiced nickname on #mIRC

Window identifiers

\$active

Returns the full name of the currently active window.

\$chan(N/#)

Returns information on channels that you are currently on.

Properties: topic, mode, key, limit

If you specify a number N, the Nth channel name is returned.

\$chan(0) returns the number of channels you are on
\$chan(2) returns the name of the 2nd channel you are on
\$chan(2).key returns the key of the 2nd channel you are on

If you specify a channel name, information on that channel is returned but only if you are on that channel already.

\$chan(#mIRC).mode returns the mode of channel #mIRC

\$chat(N/nick)

Returns the name of the Nth open dcc chat window.

Properties: ip, status

\$chat(0) returns the total number of open dcc chats.
\$chat(1) returns the nickname of the 1st dcc chat window.
\$chat(2).ip returns the ip address of the 2nd open dcc chat window.

\$fserv(N/nick)

Returns the name of the Nth open dcc chat window.

Properties: ip, status, cd

\$fserv(0) returns the total number of open fserves.
\$fserv(1) returns the nickname of the 1st fserve.
\$fserv(1).cd returns the current directory of the 1st fserve.

\$get(N/nick)

Returns the nickname and filename of the Nth open dcc get window.

Properties: ip, status, file, size, rcvd, cps, pc

\$get(0) returns the total number of open dcc gets.
\$get(2) returns the nickname of the 2nd dcc get.
\$get(2).rcvd returns the number of bytes recieved for the 2nd dcc get.
\$get(2).cps returns the character per second rate for the 2nd dcc get.
\$get(3).pc returns the percent complete of transfer for the 3rd dcc get.

\$query(N)

Returns the name of the Nth open query window.

\$query(0) returns the total number of open query windows.
\$query(2) returns the name of the 2nd open query window.

\$send(N/nick)

Returns the nickname and filename of the Nth open dcc send window.

Properties: ip, status, file, size, sent, lra, cps, pc

`$send(0)` returns the total number of open dcc sends.
`$send(2)` returns the nickname of the 2nd dcc send.
`$send(2).sent` returns the number of bytes sent for the 2nd dcc send.
`$send(2).lra` returns the last recieved ack for the 2nd dcc send.
`$send(3).pc` returns the percent complete of transfer for the 3rd dcc send.
`$send(3).status` returns active, inactive, or waiting for the 3rd dcc send.

Token identifiers

\$addtok(text,token,C)

Adds a token to the end of text but only if it's not already in text.

`$addtok(a.b.c,d,46)` returns a.b.c.d
`$addtok(a.b.c.d,c,46)` returns a.b.c.d

\$findtok(text,token,C)

Returns the Nth position of token in text.

`$findtok(a.b.c.d,c,46)` returns 3
`$findtok(a.b.c.d,e,46)` returns \$null

\$gettok(text,N,C)

Returns the Nth token in text.

`$gettok(a.b.c.d.e,3,46)` returns c
`$gettok(a.b.c.d.e,9,46)` returns \$null

You can also specify a range of tokens:

`$gettok(a.b.c.d.e,2-,46)` returns 2nd token onwards b.c.d.e
`$gettok(a.b.c.d.e,2-4,46)` returns tokens 2 through 4 b.c.d

\$instok(text,token,N,C)

Inserts token into the Nth position in text, even if it already exists in text.

`$instok(a.b.d,c,3,46)` returns a.b.c.d
`$instok(a.b.d,c,9,46)` returns a.b.d.c

\$remtok(text,token,C)

Removes one matching token from text.

`$remtok(a.b.c.d,b,46)` returns a.c.d
`$remtok(a.b.c.d,e,46)` returns a.b.c.d
`$remtok(a.c.c.d,c,46)` returns a.c.d

\$reptok(text,token,new,C)

Replaces one matching token with a new token in text.

`$reptok(a.b.c.d,b,e,46)` returns a.e.c.d
`$reptok(a.b.c.d,f,e,46)` returns a.b.c.d

Miscellaneous identifiers

\$away

Returns the value **\$true** or **\$false** depending on whether you are marked as away or not.

if (\$away) say I'm away! | else say I'm here!

\$cb

Returns the first 256 characters of the clipboard contents.

\$cr

Returns the **carriage return** character, the same as \$chr(13).

\$host

Returns your Local host name.

\$inmidi

Returns **\$true** if a midi file is currently playing, otherwise returns **\$false**.

\$ip

Returns your IP address.

\$lf

Returns the **linefeed** character, the same as \$chr(10).

\$port

Returns the **port number** of the server to which you're currently connected.

\$result

Stores the number value returned to a calling routine by the **/return** command.

\$server

Returns the name of the server to which you are currently connected.

If you're not currently connected to a server, it returns \$null.

\$server(N)

Returns the address of the Nth server in your irc servers list.

Properties: desc, port, group

\$server(0)	returns the total number of servers in the servers list
\$server(2)	returns the address of the 2nd server
\$server(2).desc	returns the description of the 2nd server
\$server(3).port	returns the port(s) of the 3rd server

\$url

Returns the **currently active** URL in your Web Browser.

\$url(N)

Returns the Nth address in your URL list.

Properties: desc, group

\$url(0)	returns the total number of items in the URL list
\$url(2)	returns the address of the 2nd item in the list
\$url(2).desc	returns the description of the 2nd item in the list
\$url(3).group	returns the group of the 3rd item in the list

\$usermode

Returns your current usermode on the irc server.

Flood

This turns on **flood protection** which attempts to prevent you from flooding a server and being disconnected. If this is turned on, mIRC will count the number of bytes you send to a server, and will initiate a flood check if you exceed a certain maximum number of bytes.

Trigger flood check after...

The number of bytes at which mIRC should check if it might be flooding the server or not. Setting this greater than 500 bytes isn't too helpful since that might be the maximum amount a server allows. The lower the number, the more sensitive mIRC will be, and the slower it will reply. Default 400.

Max. lines in buffer

The maximum number of lines mIRC will buffer.

Max. lines per person

The maximum number of messages a user can have in the buffer.

Ignore person for...

How long to ignore a user who has exceeded their maximum number of buffered messages. If zero, no ignore is done.

The **/flood** command also allows you to change these settings. Typing **/flood** with no parameters gives you the current flood status.

```
/flood 200 10 2 30
```

Here mIRC will check for flooding if it has sent 200 or more characters to the server, will buffer a maximum of 10 lines and ignore the rest, will only allow each user 2 buffered lines, and will ignore a user for 30 seconds if that user exceeded the maximum number of buffered messages.

The flood protection method also performs intelligent buffering in an attempt to satisfy the maximum number of users as possible as quickly as possible, so that no single user can hog the queue.

You can type **/flood on** to turn flood protection on with the default settings.

Bold, Underline, Reverse, and Colour

mIRC interprets control codes in text for **Bold, Underline, Reverse, and Colour** and displays text in the specified format.

You can use the following key combinations to insert control codes in text:

Control-B for **bold** text
Control-U for **underlined** text
Control-R for **reverse** text
Control-K for **coloured** text
Control-O for **plain** text

Examples

To **underline** a single word in a sentence:

- 1.Type Control-U
- 2.Type in the word
- 3.Type Control-U again

Only the text that is **enclosed** by the start and end codes will be affected. You can use this method with all of the other control codes.

The **Control-K** control code is slightly different because it allows you to specify a colour number. To **colour** a single word in a sentence:

- 1.Type Control-K
- 2.Type a number between 0 and 15
- 3.Type the word
- 4.Type Control-K again

If you also want to change the **background** colour of a word, you would need to type **two numbers** separated by a **comma** instead of just one number. The first number is the **text** colour, the second number is the **background** colour. The colours range from 0 to 15, and the indexes are:

0 white	8 yellow
1 black	9 lightgreen
2 blue	10 cyan
3 green	11 lightcyan
4 lightred	12 lightblue
5 brown	13 pink
6 purple	14 grey
7 orange	15 lightgrey

If you want to enclose **existing** text in control codes, just **select** the text with your cursor, and then type the Control code. This will insert both starting and ending control codes around the text you selected.

You can enclose text in multiple control codes, so for example you could have a bold, underlined, and coloured word.

If you want to strip out control codes that other people send you in private or channel

messages, you can either change the strip settings in the IRC Switches dialog, or you can use the /strip command.

on VOICE/DEVOICE

The **on VOICE** and **on DEVOICE** events trigger when a user on a moderated channel is voiced or devoiced.

Format: on <level>:VOICE:<#[,#]>:<commands>

Example: on 1:VOICE:#mIRC,#newbies:/msg \$vnick You can now speak on channel \$chan

Examples

on 9:VOICE:#:/mode \$chan -v \$vnick | /msg \$nick Don't voice that person!

This triggers when a user with access level 9 is given a voice on any channel. **\$vnick** refers to the nickname of the person given the voice.

on 1:DEVOICE:#mIRC:/mode \$chan +v \$vnick

This triggers when any user is devoiced on channel #mIRC.

Comparing Levels

You can **compare the levels** of the voicer and the voiced users by prefixing the line with <, >, <=, =, >, <>, or =, in the following way:

on >=2:DEVOICE:#mIRC:/msg \$chan \$nick devoiced \$vnick (legal)

on 1:DEVOICE:#mIRC:/msg \$chan \$nick devoiced \$vnick (illegal)

In this situation, if the voicer's level is larger than or equal to the devoiced users level, then it is a legal devoice. Otherwise, it defaults to the second on DEVOICE line which indicates that it is an illegal devoice. Remember, this is comparing the voicers and voiced users levels and has nothing to do with the level "2" in the definition.

Note: These events only work on nicknames because the IRC server only sends the nickname of the user being voiced/devoiced and not an address.

Ctcp Events

CTCP stands for **Client-To-Client-Protocol** which is a special type of communication between IRC Clients. By creating CTCP events, you can make your mIRC react to commands or requests from other users. CTCP events use the format:

```
ctcp <level>:<matchtext>:<commands>
```

The **level** is the access level required to access this event, the **matchtext** is the actual CTCP being sent, and the **commands** are the commands that will be performed if this event triggers successfully.

Examples

The following examples should give you an idea of how to create simple CTCP events.

A Basic CTCP event

```
ctcp 1:help:/msg $nick help yourself!
```

The above ctcp event would react to a **/ctcp yournick help** message. Since it has access level 1, this means that any user can access it because 1 is the lowest access level.

Giving Op status to a friend

```
=5:!*khaled@mardam.demon.co.uk
```

```
ctcp 5:opme:/mode $1 +o $nick  
ctcp 5:inviteme:/invite $nick $1
```

These definitions would allow the above level 5 user to send you the ctcp **/ctcp yournick opme #mIRC** and if you are on an Op on channel **#mIRC**, the above script would automatically Op him. The user can also send you the ctcp **/ctcp yournick inviteme #mIRC**, and you would invite him to channel **#mIRC**.

Note: By giving the user access level =5, the user is limited only to level 5 events. If I had given the user access level 5, then the user would be able to access all events which have access level 5 **and** below.

Changing a standard CTCP reply

```
ctcp 1:ping:/notice $nick Ouch! | /halt
```

This will react to the standard ping CTCP and will reply with "Ouch!". The /halt at the end of the line prevents the standard ping reply from being sent. If you don't use the /halt, the standard reply to PING will be sent.

```
ctcp 1:time:/notice $nick The time here is around $time | /halt
```

This will react to the standard time CTCP and will reply with the above message. Again, the /halt prevents the standard time reply from being sent.

Note: You can't prevent the standard version reply from being sent.

Controlling your mIRC remotely

```
100:*!khaled@mardam.demon.co.uk
```

```
ctcp 100:quit:/notice $nick Okay boss, I'm quitting... see you later! | /quit
```

The above definition shows how you can give yourself a high access level to access the quit event, and you can tell your mIRC to quit IRC from another IRC Client.

```
ctcp 100:send:/dcc send $nick $1-
```

This definition allows you to ask your mIRC to send you whatever file you specify to the IRC Client you're using from another location, for example by using the ctcp **/ctcp yournick send homework.txt**.

```
ctcp 100:*:$1-
```

This event definition allows you to execute any command remotely. So if you send a **/ctcp yournick echo Hi!**, your script will execute the command **echo Hi!**. This is a potentially dangerous event definition since if you allow anyone else to access it, they will be able to perform any command they want on your computer.

Wildcards and Variables

```
ctcp 1:*help*/notice $nick I can see that you need some help
```

By using the *** and ? wildcard characters**, you can match any text you want in a sentence. So if a user sends you a ctcp which has the word help in it anywhere, the above notice will be sent.

```
ctcp 1:%password:/notice $nick Your access has been authorized
```

By using variables in the matchtext section, you can change the value of %password whenever you want without having to change the event definition. So if you set %password to the value "moo" and someone sends you a "moo" ctcp, it will match %variable and the notice will the above message will be sent.

on SNOTICE

The **on SNOTICE** event triggers when you receive a server notice.

Format: on <level>:SNOTICE:<matchtext>:<commands>

Example: on 1:SNOTICE:*client connecting*/:halt

For an explanation of **matchtext** see the [on TEXT](#) event.

Examples

on 1:SNOTICE:*hack*/:splay hack.wav

This triggers when a server notice contains the word hack.

Note: You can prevent the default server notice from being displayed by using /halt.

on WALLOPS

The **on WALLOPS** event triggers when you receive a wallops message.

Format: on <level>:WALLOPS:<matchtext>:<commands>

Example: on 1:WALLOPS:*warning*/echo \$nick issued warning at \$time

For an explanation of **matchtext** see the [on TEXT](#) event.

Examples

on 1:WALLOPS:*oink*/splay oink.wav

This triggers when a wallops notice contains the word oink.

Note: You can prevent the default wallops message from being displayed by using /halt.

on CHATOPEN/CHATCLOSE

The **on CHATOPEN** and **on CHATCLOSE** events trigger when a dcc chat session first starts or when it ends.

Format: on <level>:CHATOPEN:<matchtext>:<commands>
Example: on 1:CHATOPEN:/msg =\$nick Welcome!

The **on SERVOPEN** and **on SERVCLOSE** events use the same format as above, and trigger when a dcc fserve session first starts or when it ends.

Examples

on 1:CHATOPEN:/msg =\$nick Hi! I'll be with you in a second...

This triggers when a dcc chat connection is first established. The equal sign in **=\$nick** is required to send the reply as a dcc chat message. If no equal sign is used, the message is sent as a private irc server message.

on 1:CHATCLOSE:/notice \$me \$nick just left the discussion!

This triggers when a dcc chat session ends.

Note: These events react to **all** users level 1 and above because of the way dcc chat works.

on NOTIFY/UNOTIFY

The **on NOTIFY** and **on UNOTIFY** events trigger when a user in your notify list joins or leaves IRC.

Format: on <level>:NOTIFY:<commands>

Example: on 1:NOTIFY:/msg \$nick Hiya! :)

Examples

on 1:NOTIFY:/msg \$nick Hi! I'm in #mIRC_Lounge, come over!

This triggers when a user in your notify list joins IRC.

on 1:UNOTIFY:/notice \$me \$nick just left IRC *sniff*

This triggers when a user in your notify list leaves IRC.

on INVITE

The **on INVITE** event triggers when a user invites to a channel.

Format: on <level>:INVITE:<#[,#]>:<commands>

Example: on 1:INVITE:#mIRC:/join \$chan

Examples

on 2:INVITE:#:/join \$chan | /timer 1 3 /describe \$chan appears in a puff of smoke!

This triggers when a user with access level 2 invites you to any channel.

Note: If you want to automatically join a channel when someone invites you, it's easier to turn on the auto-join option in the Options dialog.

on CTCPREPLY

The **on CTCPREPLY** event triggers when a user sends a standard ctcp reply to a ctcp that you initiated.

Format: on <level>:CTCPREPLY:<matchtext>:<commands>

Example: on 1:CTCPREPLY:VERSION:/echo \$nick is using IRC client: \$1-

For an explanation of **matchtext** see the [on TEXT](#) event.

Examples

on 1:CTCPREPLY:PING:/echo \$nick replied to my ping!

This triggers when a user replies to a ctcp PING that you sent.

on MODE

The **on MODE** event triggers when a user changes a channel mode.

Format: on <level>:MODE:<#[,#]>:<commands>

Example: on 1:MODE:#mIRC:/notice \$me \$nick changed \$chan mode to \$1-

The **on SERVERMODE** event uses the same format, and triggers when an IRC Server changes a channel mode.

Examples

on @1:MODE:#:/notice \$me \$nick changed \$chan mode to \$1-

This triggers when a user changes a mode on any channel where you have Ops (the @ at sign specifies the Op requirement, see the [Access Levels](#) section for more info). The actual parameters of the mode change are stored in **\$1-** which you would need to parse yourself to enforce a particular mode.

Note: This event only triggers on channel mode changes not user mode changes such as ops, bans, etc. It also does not trigger when **you** make a mode change.

on NICK

The **on NICK** event triggers when a user changes nickname while on the same channel as you.

Format: on <level>:NICK:<commands>

Example: on 1:NICK:/msg \$nick Hi \$newnick!

Examples

on 1:NICK:/describe \$newnick thinks \$nick was a nicer nickname!

This triggers when a user changes their nickname on a channel.

on QUIT

The **on QUIT** event triggers when a user quits IRC while on the same channel as you.

Format: on <level>:QUIT:<commands>

Example: on 1:QUIT:/notice \$me \$nick just quit IRC with the message \$1-

Examples

on 1:QUIT:/ame waves bye-bye to \$nick *sniff*

This triggers when a user quits IRC while on the same channel as you. The **\$1-** parameters hold the user's quit message.

on TOPIC

The **on TOPIC** event triggers when a user changes a channel topic.

Format: on <level>:TOPIC:<#[,#]>:<commands>

Example: on 1:TOPIC:#mIRC:/msg \$chan Hmm, odd topic!

Examples

on 1:TOPIC:#mIRC4Dummies:/describe \$chan admires \$nick's new topic!

This triggers when a user changes the topic on channel #mIRC4Dummies. The **\$1-** parameters hold the actual text of the new topic.

on NOSOUND

The **on NOSOUND** event triggers when a user sends a /sound request to play a sound and you don't have that sound.

Format: on <level>:NOSOUND:<commands>

Example: on 1:NOSOUND:/notice \$me Oops, \$nick has \$filename and I don't!

Examples

on 1:NOSOUND:/msg \$nick ! \$+ \$nick \$filename

This triggers when you don't have the requested sound. **\$filename** refers to the name of the file that was requested.

Note: You must have the accept sound requests option turned on for this event to trigger.

on DNS

The **on DNS** event triggers when a /dns query either succeeds or fails.

Format: on <level>:DNS:<commands>

Example: on 1:DNS:/notice \$me Resolved: \$raddress

Examples

on 1:DNS:/echo \$nick ip address: \$iaddress named address: \$naddress resolved address: \$raddress

This is triggered when a /dns completes. If **/dns <nick>** was used to initiate the DNS lookup then **\$nick** refers to the specified nickname otherwise it is \$null. **\$iaddress** refers to the ip address, and **\$naddress** refers to the named address. **\$raddress** is the resolved address. If **\$raddress** is \$null then that means that the address could not be resolved.

on ERROR

The **on ERROR** event triggers when an IRC Server sends an ERROR message, this usually occurs on a disconnection.

Format: on <level>:ERROR:<matchtext>:<commands>

Example: on 1:ERROR:*server full*/:echo Try another server!

For an explanation of **matchtext** see the [on TEXT](#) event.

Examples

on 1:ERROR:*banned*/:echo I'm banned from this server *mumble*!

This triggers when you try to connect to a server and it tells you you are banned. The **\$1-** parameters refer to the full error message.

Note: This event is not related to any kind of error reporting in mIRC itself.

on MIDIEND

The **on MIDIEND** event triggers when mIRC finishes playing a midi file.

Format: on <level>:MIDIEND:<commands>

Example: on 1:MIDIEND:/splay jazzy.mid

Examples

on 1:MIDIEND:/echo Finished playing midi file!

Triggers when a midi file finishes playing. There are no identifiers associated with this event.

Note: This event will not trigger if you use /splay to play another midi file or to stop the current one, it only triggers if the midi file finishes playing completely.

on INPUT

The **on INPUT** event triggers when you enter text in an editbox and press enter.

Format: on <level>:INPUT:<commands>

Example: on 1:INPUT:/echo You entered the text \$1-

Examples

```
on 1:INPUT:/echo I just mumbled " $1- "
```

Triggers when you enter text in an editbox and press enter. The **\$1-** parameters refer to the text that you entered. If you /halt this event, you can prevent mIRC itself from processing your message.

Note: You can use commands such as /say with on INPUT and they will send the message to the window in which you're typing, however other events don't work this way and require you to specify the actual destination of a message.

on USERMODE

The **on USERMODE** event triggers when you change your usermode.

Format: on <level>:USERMODE:<commands>

Example: on 1:USERMODE:/echo You changed your usermode to \$1-

Examples

on 1:USERMODE:/echo Usermode for \$nick is now \$1-

Triggers when your usermode changes. The **\$1-** parameters refer to the new usermode.

on LOAD/START

The **on LOAD** event triggers the first time a script file is ever loaded.

Format: on <level>:LOAD:<commands>

Example: on 1:LOAD:/echo mIRC Script Loaded!

The **on START** event uses the same format, and triggers the first time a script is ever loaded and also every time after that when scripts are loaded when mIRC is first run.

Examples

on 1:LOAD:/echo Performing one-time initialization for this script!

Triggers the first time a script is ever loaded. The purpose of this event is to perform a one-time initialization of settings.

on 1:START:/echo Performing regular initialization for this script!

Triggers the first time a script is ever loaded, and also every time after that when scripts are loaded when mIRC is first run. The purpose of this event is to perform general initialization settings.

Note: When a file is loaded in the remote dialog, it's initialization sections are not run until after the dialog is closed. Also, only **one** of each of these events is allowed in a script.

Chatting Privately

As well as being able to chat on public **channels**, mIRC also allows you to chat **privately** with someone.

If you're **on a channel**, and you see someone you'd like to chat with, you can **double-click** on their nickname in the nickname listbox and a private query window will open up. You can then start chatting privately to them through the query window. Alternatively, you can **click your right mouse button** in the nickname listbox and a **popup menu** will appear with various options, one of which will be to open a private query window to the person selected in the nickname listbox.

If you're **not on a channel**, you can type the command **/query nickname**, where nickname is the person you want to chat with. Press the enter key, and a query window will open up and you can start chatting privately, assuming of course that the person is on IRC. You can **find out** if a person is on IRC by using the **/whois nickname** command.

There is **another** way to chat privately called DCC Chat. This method is more secure and usually faster because it doesn't rely on the IRC Server to relay your messages. Instead it connects **directly** to the other person's IRC Client. However it does need to use the IRC Server to **initiate** the chat session.

To DCC Chat someone, you can click on the **Chat button** in the toolbar, and a DCC Chat dialog will pop up. Enter the person's nickname, and click on the Chat button, and if the person accepts your DCC Chat request, you will be able to start talking to them privately. For more information about DCC Chat you should read the DCC Chat Section.

Changing Colours

mIRC uses **black text** on a **white background** by default because this allows **coloured** text to appear clearly and crisply. However, if you find the colour scheme too bright, or if you want something a bit more fun, you can change the text and background, as well as other specific types of text eg. your own messages, to other colours.

To change the colour settings, select the **Colours dialog** from the **Tools Menu**. It will popup up and show you the different types of messages in their current colour settings.

To **change** the colour of an **item**, just **click** on it and you'll see it's **name** appear in the **listbox** at the bottom. Then **click** on any of the **coloured squares**, and you'll see the colour of the text for that item change accordingly.

To **change** the **background colour**, just **click** on the background itself and select a colour as usual. You can also click on the background of the **editbox** and the **listbox** to change their colours as well.

If you don't like the changes you've made you can either click **cancel** or you can click the **reset** button which will reset the colours back to the **default** mIRC colours.

Once you've **finished** making changes, click on the **Ok** button, and hey presto you should now feel a bit more colourful!

mIRC also allows you to **interactively** change the colour, as well as the **appearance**, of text as you type. You can find out how to do this in the [Bold, Underline, Reverse and Colour](#) section. However remember that other people might have a background colour that's **different** from yours, so what appears clearly on your background colour might be hard to read on someone else's.

Custom Windows

The **/window** command, along with a few **other** related commands listed below, allows you to **create** and **manipulate** custom windows. It's format is:

```
/window [-abcdelnorsx] <@name> [x y [w h]] [/command] [popup.txt] [font [size]]
```

Switches and Parameters:

You can specify the following switches and parameters either when first creating a window or to manipulate an existing window.

a = activate window
b = update horizontal scrollbar width for listbox
c = close window
d = open as desktop window
e = editbox
l = listbox
n = minimize window
o = if opened on desktop, place ontop
r = restore window
s = use a sorted list
x = maximize window

@name window name (must prefix with a @)
x,y,w,h left top width height
popup.txt popup filename, loaded when needed (must be a plain non-ini text file)
/command default command (executed whenever you enter text in an editbox)
font/size font name and size (defaults to status window font)

Commands:

The following commands allow you to manipulate the **lines** in a custom window.

```
/aline <@name> <text>    add line to list  
/dline <@name> <N>       delete Nth line  
/iline <@name> <N> <text>        insert line at Nth line  
/rline <@name> <N> <text>        replace Nth line  
/sline <@name> <N>        select Nth line
```

You can also specify a -cN switch for /aline, /iline, and /rline, to specify a line colour (text window only).

Identifiers:

The following identifiers return custom window information.

\$window(N).x left window position
\$window(N).y top window position
\$window(N).w width of window
\$window(N).h height of window
\$window(N).state minimized/maximized/normal

\$line(@name,N) returns Nth line
\$sline(@name,N) returns Nth selected line (listbox only)

Examples


```
/window @test
```

This would create a window named @test with all of the default settings.

```
/window -els @clones 10 10 clones.txt
```

This would create a window with a sorted listbox and an editbox, positioned near the top left of the mIRC window, and using the popup file clones.txt which would appear whenever you click the right mouse button in the listbox.

Connection Problems

The most **common** problems related to connecting to an IRC Server are described below.

Unable to resolve IRC Server

If you try to connect to a server and see this message, the problem could be:

Your Internet Provider's DNS isn't working

This happens occasionally and is a temporary problem with your Internet Provider. This problem would also result in your being unable to connect to other internet services such as web sites. You should try again later.

An Invalid or Non-working IRC Server address

You might be trying to connect to an IRC Server that is currently not working, or perhaps is an old address and doesn't exist anymore. You should try another IRC Server.

Trying to use the 32bit mIRC with a 16bit winsock

Try the 16bit mIRC to see if that solves the problem. If you are running Windows 95, NT, or another 32bit operating system, you may have an old version of winsock.dll on your machine. This causes all 32bit internet applications to stop working. You should have one file called winsock.dll, dated 1995-07-11 or later, probably 42k in size.

Unable to connect to IRC Server

If you try to connect to a server and see this message, the problem could be:

IRC Server isn't working

You might be trying to connect to an IRC Server that is currently not working. This is the most likely problem. You should try another IRC Server.

Invalid Port number

The IRC Server address might be correct but you've specified the wrong port. Most servers operate at least on port 6667, you should try that port to see if it solves the problem.

Other messages

If you try to connect to a server and get **Disconnected** and see the message **Closing Link** followed by a comment such as **No Authorization**, or **No More Connections**, etc., it might be that you're too far away geographically from that server, or that the server is full and can't handle anymore users, or there may be other reasons. You should try a different, closer IRC Server until one works for you.

Note: If you try to connect to a server and you get **Unable to resolve local host** then see the [Local Info](#) section.

