

**scout**

**COLLABORATORS**

	<i>TITLE :</i> scout		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		July 10, 2022	

**REVISION HISTORY**

NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>scout</b>	<b>1</b>
1.1	scout.guide	1
1.2	scout.guide/Introduction	2
1.3	scout.guide/Copyright	2
1.4	scout.guide/System Requirements	4
1.5	scout.guide/MUI	5
1.6	scout.guide/Identify	5
1.7	scout.guide/AmiTCP	5
1.8	scout.guide/Installation	6
1.9	scout.guide/Using Scout	6
1.10	scout.guide/Allocations	8
1.11	scout.guide/Assigns	9
1.12	scout.guide/BoopsiClasses	10
1.13	scout.guide/Commodities	11
1.14	scout.guide/Devices	12
1.15	scout.guide/Expansions	13
1.16	scout.guide/Fonts	15
1.17	scout.guide/InputHandlers	16
1.18	scout.guide/Interrupts	17
1.19	scout.guide/Libraries	18
1.20	scout.guide/Locks	19
1.21	scout.guide/LowMemory	20
1.22	scout.guide/Memory	21
1.23	scout.guide/Mounted Devs	22
1.24	scout.guide/Ports	23
1.25	scout.guide/Resident Cmds	24
1.26	scout.guide/Residents	25
1.27	scout.guide/Resources	26
1.28	scout.guide/ScreenMode	27
1.29	scout.guide/Semaphores	28

---

---

1.30	scout.guide/System . . . . .	29
1.31	scout.guide/Tasks . . . . .	29
1.32	scout.guide/Timer . . . . .	31
1.33	scout.guide/Vectors . . . . .	32
1.34	scout.guide/Windows . . . . .	33
1.35	scout.guide/Scout and AmiTCP . . . . .	34
1.36	scout.guide/Scout without MUI . . . . .	35
1.37	scout.guide/Options . . . . .	35
1.38	scout.guide/Commands . . . . .	38
1.39	scout.guide/Updates . . . . .	44
1.40	scout.guide/Credits . . . . .	44
1.41	scout.guide/Author Info . . . . .	45
1.42	scout.guide/Index . . . . .	46

---

# Chapter 1

## scout

### 1.1 scout.guide

Scout 37.204

Release 2.10

User's Manual

Copyright (C) 1994-97 Andreas Gelhausen, Richard Körber

Introduction

What is 'Scout'?

Copyright

Please read this first!

System Requirements

What your system should have

Installation

Installing 'Scout'

Using Scout

How to use 'Scout'

Scout and AmiTCP

'Scout' as 'AmiTCP' service

Scout without MUI

'MUI' is not necessary!

Options

You can set some variables.

Commands

ARexx and shell commands

---

Updates	How to get updates
Credits	Thanks are going to...
Author Info	How to reach the author
Index	Contents index

## 1.2 scout.guide/Introduction

What is Scout?

=====

'Scout' is a tool that allows you to monitor your computer system. It displays many different things -- like tasks, ports, assigns, expansion boards, resident commands, interrupts, etc. -- and you can perform some certain actions on them.

For example you can freeze tasks, close windows and screens, release semaphores or remove locks, ports and interrupts.

Through 'AmiTCP' it's also possible to use 'Scout' as an TCP/IP service.

Since version 2.0 of 'Scout' you can use nearly all implemented functions through shell parameters. Therefore it's not necessary to install 'MUI' for using 'Scout', but you will need 'MUI', if you want to use 'Scout' with its graphical user interface.

## 1.3 scout.guide/Copyright

Copyright

=====

Please read the following parts carefully. You accept the following terms by starting the software, even for a test drive only.

\*COPYRIGHT\*

Scout 37.204 (Release 2.10) - Copyright (C) 1994-97 by Andreas Gelhausen and Richard Körber, all rights reserved.

You only have the right to use the software, but no rights on the software itself. Disassembling, resourcing and all other ways of reverse engineering is forbidden.

---

\*FREEWARE\*

Scout is FreeWare. You are allowed to use the packet without paying a fee or similar to the authors. Of course we would appreciate a small donor! ;-)

\*COPYING\*

You can copy the packet as long as it remains entire and unchanged.

You are allowed to compress the packet using a customary compression software (as lha, lzh, lzx, dms). You must not compress single files of the packet (e.g. PowerPacker or Imploder).

\*DISTRIBUTION\*

You must not exceed an usual price on the market for your working and material. This means a maximum of 5 DM (or the equivalent amount in other currencies, including all taxes) for disks and 35 DM for CD-ROMs containing a PD software collection.

In any case, you need a written permission from us if you want to include Scout on a cover disk or in connection with a commercial product.

We explicitly permit the distribution via AmiNet, Meeting Pearls and Fred Fish.

\*LIABILITY\*

You are using the program as it is, with all flaws, and on your own risk! We grant no warranty for the software meeting a special purpose. This software may cause financial damage or harm people.

\*LIMITATIONS\*

You are not allowed to use this software and its results

- \* for fascism or military purposes

- \* if you do not agree to the copyright note

In this case you must delete the software and all related and generated files immediately!

\*CONTENTS OF THE PACKET\*

The Scout packet is *\*only\** entire with these files:

- Scout/arexx/activatetask.scout
- Scout/arexx/arexx.readme
- Scout/arexx/arexx.readme.info
- Scout/arexx/breaktask.scout
- Scout/arexx/freezetask.scout
- Scout/arexx/poptofront.scout
- Scout/arexx/settaskpri.scout
- Scout/arexx/startup.scout
- Scout/arexx.info
- Scout/help/deutsch/scout-39.guide
- Scout/help/deutsch/scout-39.guide.info
- Scout/help/deutsch/scout.doc
- Scout/help/deutsch/scout.doc.info
- Scout/help/deutsch/scout.dvi

---

Scout/help/deutsch/scout.guide  
Scout/help/deutsch/scout.guide.info  
Scout/help/deutsch.info  
Scout/help/english/scout-39.guide  
Scout/help/english/scout-39.guide.info  
Scout/help/english/scout.doc  
Scout/help/english/scout.doc.info  
Scout/help/english/scout.dvi  
Scout/help/english/scout.guide  
Scout/help/english/scout.guide.info  
Scout/help/english.info  
Scout/help.info  
Scout/icons/icons.readme  
Scout/icons/icons.readme.info  
Scout/icons/Scout.info  
Scout/icons/ScoutDock  
Scout/icons/ScoutDock.info  
Scout/icons.info  
Scout/libs/identify.library  
Scout/libs/identify.readme  
Scout/libs/identify.readme.info  
Scout/libs.info  
Scout/Product-Info  
Scout/Scout  
Scout/Scout.info  
Scout/scout.history  
Scout/Scout.history.info  
Scout/Scout.readme  
Scout/Scout.readme.info  
Scout.info

\*TRADEMARKS\*

All copyrights and trademarks are held by their owners.

## 1.4 scout.guide/System Requirements

### System Requirements

=====

'Scout' only requires Amiga operating system version 2.04. The 'identify.library' V8 is not required, but I strongly suggest to install it to give Scout its full power. See also

Identify

.

If you want to use 'Scout's' graphical user interface, you also have to install 'MUI' version 2.1 or higher. See also

MUI and where you can get it

.

The TCP/IP features of 'Scout' are only available, if you have installed the version 4.0 of 'AmiTCP'. See also

---



AmiTCP and where you can get it

.

## 1.5 scout.guide/MUI

MUI - MagicUserInterface

=====

(C) Copyright 1992-97 by Stefan Stuntz

MUI is a system to generate and maintain graphical user interfaces. With the aid of a preferences program, the user of an application has the ability to customize the outfit according to his personal taste.

MUI is distributed as shareware. To obtain a complete package containing lots of examples and more information about registration please look for a file called 'muiXXusr.lha' (XX means the latest version number) on your local bulletin boards or on public domain disks.

If you want to register directly, feel free to send DM 30.- or US\$ 20.- to

Stefan Stuntz  
Eduard-Spranger-Straße 7  
80935 München  
GERMANY

## 1.6 scout.guide/Identify

Identify

=====

Copyright (C) 1996-97 Richard Körber

'Identify' is a Shared Library that decodes expansion IDs, guru codes and library functions, and identifies your system.

'Identify' is FreeWare. You can find a complete package in the AmiNet ('util/libs/Identify.lha') or on the author's home page: <http://www.is-koeln.de/einwohner/shred/>. To get in contact, write to 'shred@chessy.aworld.de'.

## 1.7 scout.guide/AmiTCP

AmiTCP  
=====

'AmiTCP' is a TCP/IP protocol stack for the Amiga. The demo version 4.0 (or higher) should be available in greater public domain collections or on the AmiNet. Ask your preferred Amiga dealer. =:^)

## 1.8 scout.guide/Installation

Installing Scout  
=====

You only have to copy the program 'scout' to your favourite directory, and 'identify.library' to 'libs:'. Then you can start it.

## 1.9 scout.guide/Using Scout

How to use Scout

\*\*\*\*\*

This chapter describes the usage of 'Scout' through its graphical user interface. This graphical user interface is based on the 'Magic User Interface' ('MUI') and 'MUI' have to be installed in your system, if you want to use 'Scout' through windows and so on.

If you don't like 'MUI', you should see  
Scout without MUI

.

If you start the program, you will get the main window with these Gadgets:

Libraries

Devices

Resources

Semaphores

Allocations

Tasks

Ports

Commodities

Interrupts

Vectors  
ScreenMode  
Windows  
Fonts  
BoopsiClasses  
InputHandlers  
Assigns  
Locks  
Mounted Devs  
Resident Cmds  
Timer  
System  
Expansions  
Memory  
LowMemory  
Residents  
Every gadget you see represents a certain kind of system ←  
structures.

Click one of these gadgets and another window will be opened with a list of the structure type that is indicated on the pressed gadget.

*\*Example:\** Press the task gadget and you will get a window with the list of tasks and processes.

You can also select these functions by pressing the underlined key you see on each gadget or by using the right mousebutton menu.

If you wish to handle/remove a given structure, you should know what you do.

*\*Warning:\** Wrong handling of the showed structures can crash your system. At the worst you will lose your data.

*\*Please note:\** You should not be surprised, if you don't find a certain detail information in this manual, because it's too much work to explain each element of all the structures you could see in this program.

Many books are written about these things and if you want to have more information about them, you should have a look in the specialized literature.

---

## 1.10 scout.guide/Allocations

Allocations  
=====

This window informs about who allocated what hardware resource.

CIA  
---

The Amiga owns two CIA to control its hardware, the keyboard and the printer interfaces. Additionally, it contains a couple of timer. This window shows which parts of the CIA are not yet allocated, or which program allocated the resource.

`Timer A'  
`Timer B'

This are two 16bit timer. They can also be coupled to a 32bit timer.

`Alarm'

This resource informs if a third timer reached an alarm value.

`Serial'

This is a simple serial interface. Usually, the CIA-A one's is used for communicating with the keyboard. The CIA-B serial interface will not be allocated in most cases.

`Flag'

This is a special control line. It is connected from the CIA-A to the Index line of the floppy disk drives.

Note: newer DraCos do not contain the CIA chips. Thus, these hardware resources will be emulated or are even not offered.

Ports  
-----

This are the resources for the internal parallel and serial interfaces.

`Serial Port'

This are the plain data transfer registers (transmitting and receiving).

`Serial Control'

This are the serial control lines, as Carrier Detect.

`Parallel Port'

This are the data lines of the parallel port.

`Parallel Control'

This are the control lines of the parallel port, as Busy or Paper Out.

Actions

-----

'Update'

The window is updates each time you press this button.

'Print'

The window's contents are printed or saved to a file of your choice.

'Exit'

The window will be closed.

## 1.11 scout.guide/Assigns

Assigns

=====

This type of structure assigns a logical name to a directory.

If you assign the directory 'dh0:data/documents' the logical name 'texts:', you will also be able to choose a file FILENAME in that directory with the path 'texts:FILENAME'.

Column items

-----

'Address'

Address of the assign structure.

'Name'

Logical name of a directory

'Path'

Here you will find the path of the directory.

Actions

-----

'Update'

Selecting this gadget updates the list of assigns.

'Print'

This function allows you to send the list of 'Assigns' to printer or a selected file.

'Remove'

The selected assign will be removed with this function.

'Exit'

The 'Assigns' window will be closed.

---

## 1.12 scout.guide/BoopsiClasses

BoopsiClasses

=====

BOOPSI classes are object oriented classes. The classes in this list are all classes that are publically available from intuition.

Column items

-----

'Address'

This is the address of the 'IClass' structure, which contains all data of this class.

'Objects'

Shows the current amount of objects constructed by this class.

'Subclasses'

Shows the current amount of sub classes (public and private) which are derived from this class.

'Superclass'

A pointer to the 'IClass' structure of the parent class.

'Dispatcher'

A pointer to the dispatcher code, which realizes all methods of the class.

'Name'

The name of the class.

Actions

-----

'Update'

The list will be updated.

'Print'

This function allows you to send the list to printer or a selected file.

'Remove'

Removes the selected class from the system. This is only possible if neither objects nor sub classes exist from this class.

'More'

Opens a window with further information.

'Exit'

Closes the window.

## 1.13 scout.guide/Commodities

### Commodities

=====

Commodities are small utilities. Most of them react on the input stream, or manipulate it.

You can find some commodity examples in the 'Tools' drawer of your Workbench.

### Column items

-----

#### 'Address'

Points to the 'CxObj' structure of the commodity, containing all data about it.

#### 'ln\_Type'

Structure type. Usually, it will be 'Broker'.

#### 'ln\_Pri'

Priority of the commodity broker.

#### 'Flags'

Flags describing the broker.

#### 'Port'

All messages of the broker are sent to this MessagePort.

#### 'Name'

Name of the commodity.

### Actions

-----

#### 'Appear'

#### 'Disappear'

Let the selected commodity's GUI pop up or disappear. Some commodities do not have a GUI.

#### 'Enable'

#### 'Disable'

The commodity will be enabled or disabled.

#### 'Kill'

Let the selected commodity remove itself in a clean way.

#### 'ListChg'

#### 'Unique'

The commodity is notified that the list has been changed or that another commodity with the same name was about to be added. This is only useful for programmers to test out their commodities.

#### 'Update'

The list will be updated.

`'Print'`  
This function allows you to send the list to printer or a selected file.

`'Priority'`  
This function allows you to change the priority of a commodity.

`'Remove'`  
Removes the selected commodity from the system. Please try a friendly remove before, using `'Kill'`. Maybe the commodity removes itself voluntarily. =;^)

`'More'`  
Opens a window with further information.

`'Exit'`  
Closes the window.

## 1.14 scout.guide/Devices

### Devices

=====

A device is -- like a library (see Libraries) -- a collection of functions/procedures, which have to do certain jobs.

E.g. the `'trackdisk.device'` includes functions for the floppy disk handling.

### Column items

-----

`'Address'`  
Address of the device structure

`'ln_Name'`  
Name of a device

`'ln_Pri'`  
Priority of a device

`'OpenC'`  
This element shows how often the device was opened.

`'RPC'`  
`'RPC'` means `'RAM Pointer Count'` and shows how many jump addresses of the device point into RAM. In this way many programs -- like the `'setpatch'` command from Commodore -- patch the system.

Many viruses patch the system in this way too, but don't panic now. If you check your system in regular intervals with a current virus



killer, it should be out of danger.

If the whole program code of the device is located in RAM, you will find a dash (minus sign) here, because in this case it's unimportant how many jump addresses point into RAM.

``ln_Type'`

Type of this structure (usually `'device'`)

Actions

-----

`'Update'`

If you select this gadget, the list of devices will be updated.

`'Print'`

This function allows you to send the list of `'Devices'` to printer or a selected file.

`'Remove'`

The selected device will be removed with this function provided that no program uses this device anymore and the `'OpenC'` is zero.

`'Priority'`

Herewith the priority of the device can be changed. A little window will be opened, that asks you for a new priority. Through the new priority it can happen that the device gets a new place in the device list.

`'More'`

Another window will be opened and you will see more informations about the selected device.

You will have the same effect, if you doubleclick an element of the device list.

`'Functions'`

All device function offsets and addresses are shown up in a subwindow. If an appropriate `'.fd'` file exists and an `'FD:'` assign points to its directory, then you will also see the function names.

`'Exit'`

The `'Devices'` window will be closed.

## 1.15 scout.guide/Expansions

Expansions

=====

**\*IMPORTANT:\*** All Scout releases before 2.10 are not compatible to this release! So if you want to read this list using TCP/IP, make sure that the remote system runs the latest version as well!

---

This window shows a list about all your expansion boards (graphic boards, memory expansions and so on) too.

#### Column items

-----

##### 'Address'

The address of the expansion structure.

##### 'BoardAddr'

Usually you will find the ROM of the card here. If this address points into RAM, the card is a memory expansion.

##### 'Type'

Information about the board. See the More window for further information.

##### 'Manufacturer'

Name of the board manufacturer.

##### 'Product'

Name and class of the product.

#### Additional information

-----

If you select one item from the list, the text field below shows up some additional information:

##### 'Size'

If the entry belongs to a memory expansion, the size of the memory is displayed here. Otherwise it's the ROM size of the card.

##### 'Flags'

See the More window.

##### 'ID'

ManufacturerID, assigned by Commodore, followed by the Productnumber, assigned by the manufacturer of the board.

##### 'SN'

Serialnumber of the card (usually unused)

#### Actions

-----

##### 'Print'

This function allows you to send the list of 'Expansions' to printer or a selected file.

##### 'More'

Now a window will be opened, that includes more informations about the selected expansion board.

Doubleclick an element of the 'Expansions' list and you will have the same effect.

---

'Exit'

The 'Expansions' window will be closed.

Unknown expansion boards

-----

If you select an expansion board by selecting its list item, you will get the name of the manufacturer and the card in the textfield you find below the list, provided that the installed version of 'identify.library' knows about these data.

If no information is available in this textfield or the given information is wrong, you should send me the following data, please.

1. ManufacturerID (Manufacturer)
2. ProductID (Product)
3. Name of the company
4. Name of your expansion card
5. Function of your card

If you send me these data, the next version of 'Identify' will include your expansion boards. Please be as precise you can.

## 1.16 scout.guide/Fonts

Fonts

=====

This function will show you all fonts existing in your system.

Column items

-----

'YSize'

Vertical size of the font

'Count'

Here you can see how many programs use the font.

'Type'

'ROMFONT' means the font is located in ROM and 'DISKFONT' means the font was loaded from disk/harddisk.

'Name'

Name of the font

Actions

-----

'Update'

The list of fonts will be updated.

'Print'

---

This function allows you to send the list of 'Fonts' to printer or a selected file.

'Close'

The font will be closed by using this function.

'Remove'

It is possible to remove a font from system, provided that no program uses it and it's no 'ROMFONT'.

'Exit'

The 'Fonts' window disappears.

## 1.17 scout.guide/InputHandlers

InputHandlers

=====

Input handlers take care of all user input arriving in system (pressed keys, mouseclicks, inserted disks, etc.). They stand one behind the other like on a production line and analyze the user input. The input handler with the highest priority gets the 'events' first and if it doesn't know how to react on these 'events', the second input handler gets them, and so on.

Usually the system input handler has a priority of 50. Every input handler, that wants to get the user input before the system, must have a higher priority.

Column items

-----

'ln\_Name'

Name of the input handler

'ln\_Pri'

Its priority

'is\_Data'

This address points to some data needed by the input handler.

'is\_Code'

The program code starts here. If the code is located in RAM, the address is of different color. Otherwise you can find the code in ROM. Some viruses install an input handler in system. In this case the 'is\_Code' address points into RAM, but many other programs uses input handlers, too. Don't panic!

Actions

-----

'Update'

The list of input handlers will be updated when you select this gadget.

---

`'Print'`  
This function allows you to send the list of `'InputHandlers'` to printer or a selected file.

`'Remove'`  
Removes an input handler from system.

`'Priority'`  
Changes the priority of an input handler.

`'Exit'`  
The window will be closed.

## 1.18 scout.guide/Interrupts

### Interrupts

=====

Interrupts are important events the computer system has to react on. It exists a list of interrupt routines for each interrupt type. If a certain interrupt occurs, all these interrupt routines will be called. During their execution the running program will be interrupted.

### Column items

-----

`'ln_Name'`  
Name of the interrupt

`'ln_Pri'`  
Its priority

`'is_Data'`  
At this address you find the data of the interrupt.

`'is_Code'`  
Address of the interrupt code. If this address points into RAM, it's of a different color.

`'NUM'`  
This number represents the type of event the interrupt routine is called on. The `'IntName'` you find in the interrupt detail window gives you a little bit more information about it.

\*Example:\* Number 5 means that the interrupt is called at every vertical blank interval.

### Actions

-----

`'Update'`  
The list of interrupts will be updated.

**'Print'**

This function allows you to send the list of 'Interrupts' to printer or a selected file.

**'Remove'**

If the interrupt is a server you can remove it from system. An interrupt handler can't be removed by 'Scout'.

If you call 'avail flush' and the audio.device isn't used, the interrupt handlers of the audio.device will be removed.

**'More'**

Now a window will be opened that includes more details of the interrupt.

**'Exit'**

Selecting this gadget will close the 'Interrupts' window.

## 1.19 scout.guide/Libraries

### Libraries

=====

A library is a collection of functions/procedures, which have to do certain jobs. E.g. the 'graphics.library' includes routines for graphical display.

### Column items

-----

**'Address'**

Address of the library structure

**'ln\_Name'**

Name of a library

**'ln\_Pri'**

Priority of a library

**'OpenC'**

Here you see, how often the library was opened.

**'RPC'**

'RPC' means 'RAM Pointer Count' and shows how many jump addresses of the library point into RAM. In this way many programs -- like the 'setpatch' command from Commodore -- patch the system.

Many viruses patch the system in this way too, but don't panic now. If you check your system in regular intervals with a current virus killer, it should be out of danger.

If the whole program code of the library is located in RAM, you will find a dash (minus sign) here, because in this case it's unimportant how many jump addresses point into RAM.

**`ln\_Type'**

Type of this structure (usually 'library')

**Actions**

-----

**`Priority'**

Herewith the priority of the library can be changed. A little window will be opened, that asks you for a new priority. Through the new priority it can happen that the library gets a new place in the list of libraries.

**`Close'**

A library must be closed by all programs, if you want to remove it from system. In this case the 'OpenC' is zero.

If you select this function, you will be asked, how often you want to close it. You can choose between 'Once' and 'All'.

Select 'All' and the library will so often be closed till the 'OpenC' is zero.

**`Remove'**

The selected library will be removed with this function provided that no program uses this library anymore and the 'OpenC' is zero.

Some libraries can't be removed from system without a reset. So you shouldn't wonder about it, if this happens.

**`Functions'**

All library function offsets and addresses are shown up in a subwindow. If an appropriate '.fd' file exists and an 'FD:' assign points to its directory, then you will also see the function names.

**`Update'**

The list of libraries will be updated.

**`Print'**

This function allows you to send the list of 'Libraries' to printer or a selected file.

**`More'**

A window will be opened that includes more details of the library.

**`Exit'**

Selecting this gadget will close the 'library' window.

## 1.20 scout.guide/Locks

**Locks**

=====

---

A lock structure shows you, that a program reads from or perhaps write into a file or a directory. With this type of structure the system prevents, that a file will be deleted while another program gets some data from it.

Column items

-----

'Access'

Here you can see the type of access. This could be 'READ', 'WRITE' or 'OWN'. 'OWN' stands for a lock 'Scout' created to get the elements of this list.

'Path'

Path of the file or directory

Actions

-----

'Update'

The list of 'Locks' will be updated.

'Print'

This function allows you to send the list of 'Locks' to printer or a selected file.

'Remove'

A lock will be removed through dos.library's 'UnLock()' function.

'Pattern'

If you give 'Scout' a pattern, only the locks with a matching path will be shown.

'Exit'

The 'Locks' window will be closed.

## 1.21 scout.guide/LowMemory

LowMemory

=====

This list contains all low memory handler known to the system.

These handlers are called in their sequence if a memory allocation is about to fail due to missing resources. The handlers try to free as much unused memory space as possible.

'ramlib' is such a low memory handler removing unused libraries and devices from the system's memory. It is always present.

\*Note:\* Low memory handlers are only available since AmigaOS 3.0. On older systems this list will always be empty.

Column items

---



-----

`'Address'`

Address of the low memory handler structure.

`'ln_Name'`

Name of the handler.

`'ln_Type'`

Type of the handler.

`'ln_Pri'`

Priority of the handler. All handlers are called in their priority sequence.

`'is_Data'`

A pointer to some handler's private data.

`'is_Code'`

A pointer to the low memory handler code.

Actions

-----

`'Update'`

The list will be actualized.

`'Print'`

This function allows you to send the list to printer or a selected file.

`'Remove'`

The low memory handler will be removed from system.

`'Priority'`

Changes the priority of the selected handler.

`'Exit'`

The window will be closed.

## 1.22 scout.guide/Memory

Memory

=====

In this list you will find the segments of your memory. At least you will find an entry for your chip memory.

Column items

-----

`'ln_Name'`

Name of the memory segment (e.g. 'chip memory')

`ln\_Pri'  
Priority of memory

`mh\_Lower'  
First address of memory

`mh\_Upper'  
Last address of memory

#### Actions

-----

`Print'  
This function allows you to send the list of the memory segments to printer or a selected file.

`Priority'  
This function allows you to change the priority of a memory segment. The memory segment with the highest priority will be preferred from system, provided that no certain type of memory is demanded.

`More'  
Another window will be opened. This window includes more information about the memory segment.

`Exit'  
The window will be closed.

## 1.23 scout.guide/Mounted Devs

### Mounted Devices

=====

In this list you will find all your devices like disk drives, printer devices, etc.

#### Column items

-----

`Name'  
Name of the device

`Unit'  
Unit number

`Heads'  
Number of heads

`Cyl'  
Number of cylinders

`State'  
The state shows you for example, if a disk is in drive.

`'DiskType'`  
Type of a disk (e.g. OFS (OldFileSystem), FFS (FastFileSystem), ...)

`'Handler or Device'`  
The handler or the device you find here has to manage the stream of data from and to the device.

Actions  
-----

`'Update'`  
The list will be updated.

`'Print'`  
This function allows you to send the list of `'Mounted Devs'` to printer or a selected file.

`'Exit'`  
The window will be closed.

## 1.24 scout.guide/Ports

Ports  
=====

Programs are able to communicate together through ports.

Column items  
-----

`'Address'`  
Here you will find the port structure.

`'ln_Name'`  
Name of port

`'ln_Pri'`  
Priority of port

`'mp_SigTask'`  
The task is communicating through the port.

Actions  
-----

`'Update'`  
The ports list will be updated.

`'Print'`  
This function allows you to send the list of `'Ports'` to printer or a selected file.

---

'Remove'

The port will be removed.

'Priority'

Herewith the port priority can be changed.

'Exit'

The 'Ports' window will be closed.

## 1.25 scout.guide/Resident Cmds

Resident Commands

=====

This list includes all resident commands. That means all commands you find in ROM and the commands you made 'resident' through the 'resident' command.

Positions and sizes of their hunks you will find here, too.

Column items

-----

'Name'

Name of the command

'UseCount'

Here you can see, how often a command was being executed at the time the list was build.

'Lower'

First address of hunk in memory

'Upper'

Last address of hunk in memory

'Size'

Size of hunk (upper - lower - 8 bytes overhead)

Actions

-----

'Update'

The list of 'Resident Commands' will be updated.

'Print'

This function allows you to send the list of 'Resident Commands' to printer or a selected file.

'Remove'

The selected command will be removed with this function provided that no program uses this command anymore and the 'UseCount' is zero.

---

'Exit'  
The window disappears.

## 1.26 scout.guide/Residents

Residents

=====

Resident modules are reset-protected segments (code and data). In the list of 'Residents' you usually find libraries, devices and resources. A programmer has the possibility to make his own programs reset-protected. He has to initialize a resident structure for it and then he can link the program through the kick-vectors (see

Vectors

) to

the list of the resident modules. The residents you linked to system are usually located in RAM and are of a different color.

If you find a resident module that points into RAM and you don't know which program has created it, you should start your favourite virus detector and let it check your memory. Many viruses prefer this way to travel around.

Column items

-----

'Address'  
At this address the resident module is located.

'ln\_Name'  
Name of the resident module

'rt\_Pri'  
Priority

'rt\_IdString'  
Identity string of the resident module.

Actions

-----

'Update'  
The list of 'Residents' will be updated.

'Print'  
This function allows you to send the list of 'Residents' to printer or a selected file.

'More'  
Selecting this gadget opens a new window with more information about the selected resident module.

'Exit'  
The 'Residents' window will be closed.

## 1.27 scout.guide/Resources

### Resources

=====

Usually a resource is -- like a library (see  
Libraries  
) -- a  
collection of functions/procedures, which have to do certain jobs.

E.g. the 'filesystem.resource' includes functions for the filesystem handling.

### Column items

-----

#### 'Address'

Address of the resource structure

#### 'ln\_Name'

Name of a resource

#### 'ln\_Pri'

Priority of a resource

#### 'OpenC'

This element shows how often the resource was opened.

#### 'RPC'

'RPC' means 'RAM Pointer Count' and shows how many jump addresses of the resource point into RAM. In this way many programs -- like the 'setpatch' command from Commodore -- patch the system.

Many viruses patch the system in this way too, but don't panic now. If you check your system in regular intervals with a current virus killer, it should be out of danger.

If the whole program code of the resource is located in RAM, you will find a dash (minus sign) here, because in this case it's unimportant how many jump addresses point into RAM.

#### 'ln\_Type'

Type of this structure (usually 'resource')

### Actions

-----

#### 'Update'

The list of 'Resources' will be updated.

#### 'Print'

This function allows you to send the list of 'Resources' to

printer or a selected file.

**'Remove'**

The selected resource will be removed with this function, provided that no program uses it anymore and the 'OpenC' is zero.

**'Priority'**

Herewith the priority of the resource can be changed. A small window will be opened, that asks you for a new priority. Through the new priority it can happen that the resource gets a new position in the list of resources.

**'More'**

Select this gadget and you get a new window with more information about the selected resource.

**'Functions'**

All resource function offsets and addresses are shown up in a subwindow. If an appropriate '.fd' file exists and an 'FD:' assign points to its directory, then you will also see the function names. Note that some resources do not have functions.

**'Exit'**

The 'Resources' window will be closed.

\*Please note:\* If you should find three dashes (minus signs) at 'OpenC' and/or 'RPC', the resource has no typical library structure. This happens for example at the 'FileSystem.resource'.

## 1.28 scout.guide/ScreenMode

### ScreenMode

=====

Screen modes define all monitor resolutions that the system is able to show up.

You surely have already selected a screen mode before. In this list, you will find all available modes. Most of the programs filter out some of them when they do not meet their purpose.

### Column items

-----

**'ModeID'**

An identification number, unique to each mode.

**'Width'**

Nominal width of the resolution in pixeln.

**'Height'**

Nominal height of the resolution in pixeln.

**`Depth`**

Maximum number of planes. The amount of colors which can be simultaneously displayed depends on this.

**`ScreenMode`**

Name of the screen mode. Some modes do not have a real name, so Scout will generate it. Then it might differ from the name generated by other programs or screen mode requesters.

**Actions**

-----

**`Update`**

The list will be updated.

**`Print`**

This function allows you to send the list to printer or a selected file.

**`More`**

Further information about the screen mode are displayed in a subwindow. This includes the overscan resolutions and the frequencies. Due to an inaccuracy of the operating system, the real frequencies might be a little bit different to those displayed.

**`Exit`**

The window will be closed.

## 1.29 scout.guide/Semaphores

**Semaphores**

=====

The use of semaphores is a way of single-threading critical sections. For example only one program is allowed to use the printer at one time, otherwise the texts would be mixed.

**Column items**

-----

**`ln\_Name`**

Name of a semaphore

**`Nest`**

This item counts how often the semaphore has been obtained by the owner task.

**`Queue`**

This counter shows you, how many programs want to obtain the semaphore.

**`Owner`**

Here you will find the name of the task that owns the semaphore.



## Actions

-----

## 'Update'

The list of 'Semaphores' will be updated.

## 'Print'

This function allows you to send the list of 'Semaphores' to printer or a selected file.

## 'Obtain'

This function is used to gain access to a semaphore. The 'NestCnt' will be increased at one by this call.

## 'Release'

Herewith you can make a signal semaphore available to others.

## 'Exit'

The 'Semaphores' window will be closed.

### 1.30 scout.guide/System

## System

=====

## Actions

-----

## 'Print'

This function allows you to send the list to printer or a selected file.

## 'Exit'

The window will be closed.

## Entry items

-----

In this window you will find some (partially technical) information about your computer. Please excuse the ordinary look of the window, but it is very easy to add more lines this way.

### 1.31 scout.guide/Tasks

## Tasks

=====

In this window you find a list of all tasks and processes being in system. Each program you start will be executed as a task or process.

---

## Column items

-----

``ln_Name'`

Name of the task/process

``ln_Type'`

Type of the structure (`'task'` or `'process'`)

``ln_Pri'`

Priority of the task/process

``NUM'`

If a non detaching program was started from shell, you will find here the number of the process. Programs you started from Workbench have a dash here.

``State'`

Here you see the state of the task or process. You will find Scout's own process on the top of the list with a `'run'` at this place, because this process is always running when it gets the task list.

`'ready'` means the task wants to work, but it's interrupted by the execution of another task.

A task that is waiting for a certain signal is in the state `'wait'`. In this case it doesn't need processing time.

``SigWait'`

Signalmask the task is waiting for.

## Actions

-----

``Print'`

This function allows you to send the list of `'Tasks'` to printer or a selected file.

``Freeze'`

With this function you freeze the selected task. It can still be found in the list of tasks, but it gets no processing time from system.

**\*Warning:\*** If you try to freeze tasks essential to the system like `'input.device'`, you should have saved all important data, cause a RESET is the only way out!

``Activate'`

A frozen task can be activated here.

``CPU'`

Here you will find a text field and a cycle gadget. This text field displays -- dependent on the state of the cycle gadget -- the CPU load in percent.

For the cycle gadget you can choose between three states:

`'off'`

In this case the CPU load won't be displayed. If you select another state, `'Scout'` will patch some system functions to calculate the CPU load of all tasks.

`'full'`

If you select this state, `'Scout'` sets the real cpu load to 100%. That means the total of the CPU loads of all tasks and processes will be 100%. Therefore nothing will be displayed in the text field.

`'in %'`

`'Scout'` starts a task named `'« Scout's cheat task »'` to calculate the real CPU load and it will be displayed in the text field.

`'Secs'`

This string gadget allows you to set the intervall time for updating of the CPU load display.

`'Update'`

The list will be updated.

`'Remove'`

A task will be removed from the list. You should prefer the freeze function, if you perhaps need this task again.

See also `'Break'!`

`'Signal'`

If you select a signal mask, it will be send to the task.

`'Break'`

A signal mask that includes the signals CTRL-C and CTRL-D will be send to the task you selected. Many tasks and processes end, if they receive these signals.

`'Priority'`

The priority of a task can be changed with this function.

`'More'`

Selecting this gadget will open another window that displays more informations about the task or the process.

`'Exit'`

The window will be closed.

## 1.32 scout.guide/Timer

Timer

=====

This window lists all current requests of the timer.device.

---

## Column items

-----

## 'Address'

Address of the IO request structure.

## 'ReplyPort'

Address of the port the request will be replied to.

## 'Time'

Time that this request will stay in this list.

## 'Unit'

There are two different measures: VBlank (which has less overhead) and MicroHz (which is more accurate).

## 'Task'

Name of the requesting task.

## Actions

-----

## 'Print'

This function allows you to send the list to printer or a selected file.

## 'Update'

The list will be updated.

## 'Exit'

The window will be closed.

### 1.33 scout.guide/Vectors

## Vectors

=====

## Actions

-----

## 'Update'

The displayed vectors will be updated.

## 'Print'

This function allows you to send the list of 'Vectors' to printer or a selected file.

## 'Exit'

The window will be closed.

## Reset Vectors

-----

A program can make itself reset-protected by using the reset vectors. If the vectors are unused, they have a value of zero. The programs which use the Kick-Vectors (KickTagPtr, KickMemPtr and KickChecksum) can also be found in the list of resident structures. See also

Residents

.

Auto Vector Interrupts

-----

In a computer system with a MC68000 processor you will find the seven 'Auto Vector Interrupts' from address \$64 to address \$7c. Higher processors (MC68010, etc.) have the VBR (Vector Base Register) that allows you to move the interrupt table to FAST-MEM. The system will be a little bit faster then. 'Scout' uses the VBR if it exists.

Interrupt Vectors

-----

Here you see 16 interrupt vectors (IntVecs). These vectors are located in the 'ExecBase' (base structure of the exec.library).

## 1.34 scout.guide/Windows

Windows

=====

All screens with the windows opened on them are listed here. Screens are of a different color as windows.

Column items

-----

'Pos(x,y)'

x and y position of the screen/window

'Size(x,y)'

x and y size of the screen/window

'Title'

Title of the screen/window

Actions

-----

'Update'

The list will be updated.

'Print'

This function allows you to send the list of 'Windows' to printer or a selected file.

'Close'

With this function it is possible to close screens and/or windows. If you close a screen, all windows on it will be closed too.

'To Front'

The selected screen/window will be popped to front.

'More'

If you select this gadget another window will be opened that displays more informations about the window or the screen.

'Exit'

The window will be closed.

## 1.35 scout.guide/Scout and AmiTCP

Scout and AmiTCP

=====

This section will show you what you have to do for using 'Scout' as a TCP/IP service through 'AmiTCP'. Nearly all functions of 'Scout' can also be used via 'AmiTCP'.

Now some knowledge will be assumed. If you don't know, what kind of program 'AmiTCP' represents, you should read 'AmiTCP's' user's manual before. (See also

AmiTCP  
.)

If you have installed 'AmiTCP', you can use 'Scout' as client and server. Except the installed programs of 'AmiTCP' you don't need another program for using 'Scout' on networks.

If you want to make your computer available for other systems on the network, you have to do following two steps:

1. Add the line 'scout 6543/tcp' to file 'AmiTCP:db/services'.
2. Now please add the line 'scout stream tcp nowait root dh0:scout' to file 'AmiTCP:db/inetd.conf'. Make sure that the path at the end of this line is the right path for 'scout'.

That's it! If you start 'AmiTCP' now, your computer is available for other systems through using the options 'HOST', 'USER' and 'PASSWORD'.

\*Example:\* If I want perform some actions on some system structures of my own system for example, I have to start 'Scout' through something like:

```
1> scout HOST crash.north.de USER atte PASSWORD secret
```

If you leave out option 'PASSWORD', you will be asked for the correct password through the 'password:' prompt. In this case nobody can see your password, because it won't be displayed in shell.

---

If you don't use option 'USER', 'AmiTCP' takes the username that is actually available in system.

The usage of 'AmiTCP' doesn't provide the installation of 'MUI'. All of 'Scout's' shell commands (see also  
 Commands  
 ) can be used via network through 'AmiTCP'.

\*Example:\* If I want to get the task list of my system, I have to use something like:

```
1> scout HOST crash.north.de USER atte PASSWORD secret Tasks
```

You and all other users must always identify themselves through their usernames (option 'USER') and their passwords (option 'PASSWORD'). It's also possible to allow or deny certain systems the usage of some services through the file 'AmiTCP:db/inet.access'. See also the user's manual of 'AmiTCP'.

If you want to get more informations about the implemented options and commands, you should also see

```
Options  
and  
Commands  
.
```

\*NOTE:\* Please take care that the remote system runs the latest Scout version as well, to avoid incompatibilities.

## 1.36 scout.guide/Scout without MUI

Scout without MUI  
 =====

Nearly all through the graphical user interface available functions of 'Scout' are also available via shell. Therefore you don't really need 'MUI' for using 'Scout'. But if you want to use 'Scout's' graphical user interface, you must have 'MUI' in your system.

## 1.37 scout.guide/Options

Options

\*\*\*\*\*

There are some options for 'Scout' which you can use, when you start the program. The following options are available from shell and as tool types from Workbench.

---

``ICONIFIED'``*Usage:* `ICONIFIED'`

If this option is activ, 'Scout' starts iconified.

``PORTNAME'``*Usage:* `PORTNAME'=PORTNAME`

The name of Scout's ARexx port can be changed into PORTNAME. Without this option the ARexx port is called 'SCOUT.X'. The 'X' stands for a decimal number that will be incremented, if a so called port already exists.

``TOOLPRI'``*Usage:* `TOOLPRI'=VALUE`

This option allows you to change the priority of Scout's process into VALUE.

``STARTUP'``*Usage:* `STARTUP'=COMMAND`

The variable COMMAND should be an ARexx script or a single ARexx command. Both (script or command) will be executed, when 'Scout' will be started. In this way you can open more than only the main window by starting. Try for example the command 'OpenWindow Tasks' and you will get two windows by starting (the main window and the task list window).

(See also  
ARexx port  
.)

``INTERVALTIME'``*Usage:* `INTERVALTIME'=SECONDS`

This options allows you to save your preferred update time for the list of tasks. (See also  
Secs  
.)

``CPUDISPLAY'``*Format:* `CPUDISPLAY'=VALUE`

Through the variable VALUE you can select the state of the 'CPU' cycle gadget you find in the 'Tasks' window. (See also  
CPU  
.)

\* '1' means 'CPU: full'

\* '2' means 'CPU: in %'

``HOST'``*Format:* `HOST'=HOSTNAME`



This options allows you to specify the system (HOSTNAME) you want to manipulate via network through 'AmiTCP'.

#### 'USER'

\*Format:\* 'USER'=USERNAME

You have to use this option to identify yourself by using 'Scout' as a TCP/IP service.

#### 'PASSWORD'

\*Format:\* 'PASSWORD'=PASSWORD

Without a password 'Scout' can't connect to another system via network. This option allows you to set the correct password.

#### 'COMMAND'

\*Format:\* 'COMMAND'=COMMANDLINE

Nearly all of 'Scout's' implemented functions are available from shell through this option. You don't need the 'COMMAND' key to use this option. (See also  
Commands  
.)

#### 'SINGLEWINDOWS'

\*Format:\* 'SINGLEWINDOWS'

Some users don't like to handle the many windows of Scout. This option solves the problem of too many windows. If this option is selected, only one list window and only one detail window is opened at a time.

#### 'SORT#?TYPE'

\*Format:\* 'SORT#?TYPE'=NUMBER

Many of 'Scout's' lists have a cycle gadget below themselves. With these gadgets you can select, how a certain list will be sorted.

'SORT#?TYPE' stands for each of the following options:

'SORTLIBRARIESTYPE', 'SORTDEVICESTYPE',  
'SORTRESOURCESTYPE', 'SORTTASKSTYPE', 'SORTPORTSTYPE',  
'SORTCOMMANDSTYPE', 'SORTASSIGNSTYPE', 'SORTLOCKSTYPE',  
'SORTCOMMODITIESTYPE', 'SORTSCREENMODETYPE' and 'SORTCLASSESTYPE'.

'SORT#?TYPE' should follow a decimal number, which selects the kind of sorting.

Here are some examples for the list of tasks:

'SORTTASKSTYPE=1' the tasks will be sorted by their names.

'SORTTASKSTYPE=2' the tasks will be sorted by their priorities.

## 1.38 scout.guide/Commands

Scout's commands via ARexx and shell

\*\*\*\*\*

'Scout' supports two kinds of commands:

1. commands only available from shell
2. commands available from ARexx and shell

ARexx port

-----

It's a feature of 'MUI' to give each application its own ARexx port. Therefore 'Scout' also has an ARexx port that usually has the name 'SCOUT.X'. The 'X' stands for a decimal number that will be incremented, if a so called port already exists.

You will find the name of 'Scout's' ARexx port in the window you get, if you select the 'Project/About' menu.

Using tasknames:

-----

If a task or a process was started from shell and hasn't detached itself, you will find the name of the command being executed, where usually the taskname is displayed. The real name of those tasks usually is something like 'Background CLI', but such a taskname isn't useful.

\*Example:\* If you start a non detaching task like 'DH0:Debug/Sushi' from shell, you will see 'DH0:Debug/Sushi' as taskname.

Some ARexx commands need a taskname as parameter. You have to select those from CLI started self detaching tasks by using their command names like 'Scout' displays them in the lists of tasks.

Commands only available from shell

=====

'Help'

\*Format:\* 'Help'

This command is the most important one and it doesn't need parameters. If you try 'Help', 'Scout' prints a list of all available commands to shell. =:^)

Now 18 commands follow. These commands allow the user to get all lists of system structures from shell. Therefore you only need to install 'MUI' for using 'Scout's' graphical user interface.

Each of the following commands has a shortened form that stands behind the command in parentheses.

'Allocations' (a), 'BoopsiClasses' (b), 'Commands' (c), 'Devices' (d), 'Timer' (e), 'Fonts' (f), 'Assigns' (g), 'InputHandlers' (h), 'Interrupts' (i), 'LowMemory' (j), 'Commodities' (k), 'Libraries' (l), 'Memory' (m), 'Mounts' (n), 'Locks' (o), 'Ports' (p), 'Residents' (r), 'Semaphores' (s), 'Tasks' (t), 'Resources' (u), 'Vectors' (v), 'Windows' (w), 'Expansions' (x), 'System' (y) and 'ScreenMode' (z).

\*Example:\* To get the list of ports, you only have to use 'scout ports' or 'scout p' from shell.

Commands available from ARexx and shell

=====

#### 'FindTask'

\*Usage:\* 'FindTask' TASK

This command allows you to check, if task TASK exists in system or not. The result is the address of the task TASK, if it has been found. TASK can be the name or the address of a task.

#### 'FreezeTask'

\*Usage:\* 'FreezeTask' TASK

The task TASKNAME will be frozen. After that it will still be found in system's task list, but then it doesn't need processing time. You can choose the name or the address of a task for TASK.

#### 'ActivateTask'

\*Usage:\* 'ActivateTask' TASK

If task TASK was frozen, it will be activated, otherwise an error occurred. TASK is again a task's name or an address.

#### 'RemoveTask'

\*Usage:\* 'RemoveTask' TASK

This command removes the task TASK. It's lost forever.

#### 'BreakTask'

\*Usage:\* 'BreakTask' TASK

'Scout' sends the task TASK a certain signal mask that includes the signals CTRL-C and CTRL-D. Many programs support these signals and finish themselves, if they receive one of them.

#### 'SignalTask'

\*Usage:\* 'SignalTask' TASK HEXSIGNAL

This command allows you to send a signal HEXSIGNAL to the task TASK. The signal must be specified as a hexadecimal number.

\*Example:\*

SendSignal 'scout' 0x001000  
sends task 'scout' a CTRL-C and after that 'Scout' ends.

#### 'SetTaskPri'

\*Usage:\* `SetTaskPri` TASK PRIORITY

The task TASK gets a new priority (PRIORITY).

`RemovePort`

\*Usage:\* `RemovePort` PORT

The port PORT will be removed from `Scout`. PORT can be the name of a port or its address.

`GetLockNumber`

\*Usage:\* `GetLockNumber` LOCKPATTERN

This command returns the number of locks which have paths matching to the pattern LOCKPATTERN.

\*Example:\* Use the command

```
GetLockNumber 'WORK:Utilities/#?'
```

and you will know, how many locks are currently used for files in the directory `WORK:Utilities/`.

`RemoveLocks`

\*Usage:\* `RemoveLocks` LOCKPATTERN

Use this command and all locks which have paths matching to the pattern LOCKPATTERN will be removed. (See also `GetLockNumber`.)

`RemoveLock`

\*Format:\* `RemoveLock` LOCKADDRESS

The lock at adress LOCKADDRESS will be removed.

`FindNode`

\*Usage:\* `FindNode` NODETYPE NODENAME

This command allows you to find a certain node. You only have to know its name (NODENAME) and its type (NODETYPE).

NODETYPE can have following values: `LIBRARY`, `DEVICE`, `RESOURCE`, `MEMORY`, `SEMAPHORE`, `PORT` or `INPUTHANDLER`.

\*Example:\* If you want to get the address of the `disk.resource` you must use:

```
FindNode RESOURCE 'disk.resource'
```

`GetPriority`

\*Usage:\* `GetPriority` NODEADDRESS

This command allows you to check the priority of a certain node structure. This includes all following structure types: tasks, libraries, devices, resources, ports, residents, input handlers, interrupts, semaphores and the elements of the memory list.

You only have to know the address (NODEADDRESS) of that structure.

\*Example:\* The following ARexx commands store the priority of your chip memory in the variable `pri`:

```
FindName MEMORY 'chip memory'  
addr = result  
GetPriority addr  
pri = result
```

#### 'SetPriority'

\*Usage:\* 'SetPriority' NODETYPE NODENAME

If you want to change the priority of the node NODENAME, you can use this command. Again NODETYPE can have following values: 'LIBRARY', 'DEVICE', 'RESOURCE', 'MEMORY', 'SEMAPHORE', 'PORT' or 'INPUTHANDLER'.

#### 'CloseLibrary'

\*Format:\* 'CloseLibrary' LIBRARY

The library LIBRARY will be closed once. LIBRARY can be the name of the library or its address.

#### 'RemoveLibrary'

\*Format:\* 'RemoveLibrary' LIBRARY

The library LIBRARY will be removed, if no program uses it.

#### 'RemoveDevice'

\*Format:\* 'RemoveDevice' DEVICE

The selected device DEVICE will be removed. For DEVICE use the name or the address of the device.

#### 'RemoveResource'

\*Format:\* 'RemoveResource' RESOURCE

The resource RESOURCE will be removed.

#### 'ObtainSemaphore'

\*Format:\* 'ObtainSemaphore' SEMAPHORE

This command allows you to obtain the given semaphore. SEMAPHORE can be the semaphore's name or address.

#### 'ReleaseSemaphore'

\*Format:\* 'ReleaseSemaphore' SEMAPHORE

The semaphore SEMAPHORE will be once released.

#### 'RemoveSemaphore'

\*Format:\* 'RemoveSemaphore' SEMAPHORE

You are able to remove the semaphore SEMAPHORE by using this command.

#### 'RemoveInputhandler'

\*Format:\* 'RemoveInputhandler' INPUTHANDLER

The input handler INPUTHANDLER selected through name or address will be removed.

---

``FindResident'``*Usage:* `FindResident' RESIDENT`

This command returns the address of the resident structure RESIDENT.

``FindInterrupt'``*Usage:* `FindInterrupt' INTERRUPTNAME`

The address of the interrupt INTERRUPTNAME will be returned.

``RemoveInterrupt'``*Format:* `RemoveInterrupt' INTERRUPTNAME`

The interrupt you have selected through INTERRUPTNAME will be removed.

``FlushDevs'``*Usage:* `FlushDevs'`

All not used devices will be removed. The used memory will be freed.

``FlushFonts'``*Usage:* `FlushFonts'`

If a diskfont is in memory, but no program uses it, it will be removed.

``FlushLibs'``*Usage:* `FlushLibs'`

All not used libraries will be removed. The used memory will be freed.

``FlushAll'``*Usage:* `FlushAll'`

This function includes ``FlushDevs'`, ``FlushFonts'` and ``FlushLibs'`. All not used devices, libraries and fonts will be removed and the used memory will be freed.

``ClearResetVectors'``*Usage:* `ClearResetVectors'`

The six reset vectors will be cleared, if you select this function (see

Vectors  
).

``PopToFront'``*Usage:* `PopToFront' TITLE`

This command allows you to pop a screen or window to front. You only have to know its (TITLE).

---

``CloseOperation'``*Usage:* `CloseOperation' WINDOWTITLE`

This command closes the window that is specified through its title (WINDOWTITLE).

``CloseScreen'``*Usage:* `CloseScreen' SCREENTITLE`

If you select this command, the screen (SCREENTITLE) will be closed with all its windows.

``CloseFont'``*Format:* `CloseFont' ADDRESS`

The font at address ADDRESS will be closed once.

``RemoveFont'``*Format:* `RemoveFont' ADDRESS`

This command removes the font at address ADDRESS, if it's not used by any program.

``RemoveCommand'``*Format:* `RemoveCommand' ADDRESS`

'Scout' makes the resident command at address ADDRESS not resident.

``RemoveAssign'``*Format:* `RemoveAssign' NAME`

With this command you're able to remove the assign NAME.

``RemoveAssignList'``*Format:* `RemoveAssignList' NAME ADDRESS`

This command removes the directory at address ADDRESS from assign NAME. You will find the address of that directory in the list of assigns.

``PrintList'``*Format:* `PrintList' LISTCHARACTER FILENAME`

This command allows you to print a list (specified by the listcharacter) into the file FILENAME.

`*Example:*`

`PrintList t 'ram:tasklist'`  
will print the list of tasks into the file 'ram:tasklist'.

``OpenWindow'``*Usage:* `OpenWindow' WINDOWID`

All windows you get if you select a gadget of 'Scout's' main window, can be opened with this command. The WINDOWID is the same text you find on the main window gadgets.

---

\*Example:\*  
    OpenWindow 'Mounted Devs'  
will open the window with the list of mounted devices.

`CxAppear`  
`CxDisappear`  
`CxEnable`  
`CxDisable`  
`CxKill`  
`CxListChg`  
`CxUnique`  
    \*Format:\* `Cx...` NAME

Sends the command to the commodity named NAME.

`RemoveCx`  
    \*Format:\* `RemoveCx` COMMODITY

Removes the appropriate commodity from the list. Please consider this as 'emergency break'. Use it only if 'CxKill' failed.

`SetCxPri`  
    \*Format:\* `SetCxPri` COMMODITY PRIORITY

Sets the priority of a commodity.

`RemoveClass`  
    \*Format:\* `RemoveClass` CLASS

The appropriate BOOPSI class is removed, if no objects and no subclasses are existing.

## 1.39 scout.guide/Updates

How to get updates  
=====

The newest version of 'Scout' should always be available on AmiNet or Public Domain collections, which are up-to-date.

You can also find the latest version on my home page:  
<http://www.is-koeln.de/einwohner/shred/>

## 1.40 scout.guide/Credits

Credits  
=====

Now we have to thank some people for supporting the development of

---



'Scout' on many different kinds:

- \* Klaus 'gizmo' Weber, he was always available to Atte and his many questions (not a few) during the programming of 'Scout'.
- \* Christian 'cosinus' Stelter, he gave the permission to use his many manuals.
- \* Stefan Stuntz for his great 'MagicUserInterface'
- \* all (hopefully still) bug reporting and feature requesting people: Kai 'wusel' Siering, Martin Hauner, Peter Meyer, Karl 'Charly' Skibinski, Michael 'Mick' Hohmann, Thore Böckelmann, Bernardo Innocenti, Daniel Lundberg, ...

and last but not least

- \* all the others we've forgotten for reporting bugs, sending expansion boards data and so on.

## 1.41 scout.guide/Author Info

How to reach the author

=====

If you have questions, suggestions, bug reports or anything else, you can contact me at:

Richard Körber  
Hornstraße 20  
51465 Bergisch Gladbach  
- Germany -

E-Mail: [shred@chessy.aworld.de](mailto:shred@chessy.aworld.de)  
[richard.koerber@koeln.netsurf.de](mailto:richard.koerber@koeln.netsurf.de)

Send E-Mails whenever possible..

If you want to contact Andreas Gelhausen, you can reach him at:

Andreas Gelhausen  
Graf Spee Str. 23b  
26123 Oldenburg  
- Germany -

E-Mail: [atte@crash.north.de](mailto:atte@crash.north.de)

Please do not contact him for bug reports, suggestions and similar. But if you feel the urge to send a gift, then he is the right address!

That's it! =:^)

## 1.42 scout.guide/Index

Index	
*****	
Allocations	Allocations
AmiTCP	AmiTCP
ARexx	Commands
ARexx port	Commands
Assigns	Assigns
Author Info	Author Info
Boards	Expansions
BoopsiClasses	BoopsiClasses
Command	Commands
Command Line Options	Options
Commodities	Commodities
Contents	Copyright
Copying	Copyright
Copyright	Copyright
Copyright	Copyright
Credits	Credits

---

---

Device names, logical	
Assigns	
Devices	Devices
DISKFONT	Fonts
Distribution	Copyright
Expansions	Expansions
Fonts	Fonts
FreeWare	Copyright
Handler, LowMemory	LowMemory
Hardware	Expansions
Identify	Identify
Input events	InputHandlers
InputHandlers	InputHandlers
Installation	Installation
Interrupts	Interrupts
Introduction	Introduction
Legalities	Copyright
Liability	Copyright
Libraries	Libraries
Limitation	Copyright

---

---

Locks	Locks
Logical device names	Assigns
LowMemory	LowMemory
MagicUserInterface	MUI
Main Window	Using Scout
Manufacturer	Expansions
Memory	Memory
Mounted Devices	Mounted Devs
MUI	MUI
No Warranty	Copyright
Options	Options
Ports	Ports
Processes	Tasks
RAM Pointer Count	Devices
Resident Commands	Resident Cmds
Residents	Residents
Resource allocation	Allocations
Resources	Resources
ROMFONT	Fonts

---

---

RPC	Devices
ScreenMode	ScreenMode
Screens	Windows
Semaphores	Semaphores
System	System
System Requirements	System Requirements
Tasknames	Commands
Tasks	Tasks
TCP/IP	AmiTCP
Timer	Timer
Tool Types	Options
Trademarks	Copyright
Updates	Updates
Using Scout	Using Scout
VBR	Vectors
Vectors	Vectors
Vertical blank interrupt	
Interrupts	
What is Scout?	Introduction
Windows	Windows

---

