




Dual Enhancement-Mode MOSFET (N- and P-Channel)

Product Summary

	V _{DS} (V)	r _{DS(on)} (Ω)	I _D (A)
N-Channel	20	0.09 @ V _{GS} = 10 V	± 2.5
		0.175 @ V _{GS} = 4.5 V	± 1.8
P-Channel	-20	0.17 @ V _{GS} = -10 V	± 1.9
		0.32 @ V _{GS} = -4.5 V	± 1.3



N-Channel MOSFET



P-Channel MOSFET

Absolute Maximum Ratings (T_A = 25° C Unless Otherwise Noted)

Parameter	Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage	V _{DS}	20	-20	V
Gate-Source Voltage	V _{GS}	± 20	± 20	
Continuous Drain Current (T _J = 150°C) ^a	I _D	T _A = 25°C	± 2.5	± 1.9
		T _A = 70°C	± 2.0	± 1.5
Pulsed Drain Current	I _{DM}	± 20	± 15	A
Continuous Source Current (Diode Conduction) ^a	I _S	1.25	-1.25	
Maximum Power Dissipation ^a	P _D	T _A = 25°C	1.0	
		T _A = 70°C	0.64	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	-55 to 150		°C

Thermal Resistance Ratings

Parameter	Symbol	N- or P-Channel	Unit
Maximum Junction-to-Ambient ^a	R _{thJA}	125	°C/W

Notes

a. Surface Mounted on FR4 Board, t ≤ 10 sec.

Updates to this data sheet may be obtained via facsimile by calling Siliconix FaxBack, 1-408-970-5600. Please request FaxBack document #70171. A SPICE Model data sheet is available for this product (FaxBack document #70531).

Specifications ($T_J = 25^\circ\text{C}$ Unless Otherwise Noted)







Parameter	Symbol	Test Condition	Min	Typ	Max	Unit	
Static							
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$	N-Ch	1.0		V	
		$V_{DS} = V_{GS}, I_D = -250 \mu\text{A}$	P-Ch	-1.0			
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 20 \text{ V}$			± 100	nA	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 20 \text{ V}, V_{GS} = 0 \text{ V}$	N-Ch		1	μA	
		$V_{DS} = -20 \text{ V}, V_{GS} = 0 \text{ V}$	P-Ch		-1		
		$V_{DS} = 20 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 55^\circ\text{C}$	N-Ch		25		
		$V_{DS} = -20 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 55^\circ\text{C}$	P-Ch		-25		
On-State Drain Current ^a	$I_{D(on)}$	$V_{DS} = 5 \text{ V}, V_{GS} = 10 \text{ V}$	N-Ch	14		A	
		$V_{DS} = -5 \text{ V}, V_{GS} = -10 \text{ V}$	P-Ch	-10			
Drain-Source On-State Resistance ^a	$r_{DS(on)}$	$V_{GS} = 10 \text{ V}, I_D = 2.5 \text{ A}$	N-Ch		0.065	Ω	
		$V_{GS} = -10 \text{ V}, I_D = 1.9 \text{ A}$	P-Ch		0.13		
		$V_{GS} = 4.5 \text{ V}, I_D = 1.8 \text{ A}$	N-Ch		0.100		0.175
		$V_{GS} = -4.5 \text{ V}, I_D = 1.3 \text{ A}$	P-Ch		0.26		0.32
Forward Transconductance ^a	g_{fs}	$V_{DS} = 15 \text{ V}, I_D = 2.5 \text{ A}$	N-Ch		5	S	
		$V_{DS} = -15 \text{ V}, I_D = -1.9 \text{ A}$	P-Ch		3		
Diode Forward Voltage ^a	V_{SD}	$I_S = 1.25 \text{ A}, V_{GS} = 0 \text{ V}$	N-Ch		0.8	V	
		$I_S = -1.25 \text{ A}, V_{GS} = 0 \text{ V}$	P-Ch		0.8		-1.2
Dynamic^b							
Total Gate Charge	Q_g	N-Channel $V_{DS} = 10 \text{ V}, V_{GS} = 10 \text{ V}, I_D = 2.5 \text{ A}$ P-Channel $V_{DS} = -10 \text{ V}, V_{GS} = -10 \text{ V}, I_D = -1.9 \text{ A}$	N-Ch		7	10	nC
Gate-Source Charge	Q_{gs}		N-Ch		0.9		
			P-Ch		1.3		
Gate-Drain Charge	Q_{gd}	N-Ch		2.1			
		P-Ch		1.7			
Turn-On Delay Time	$t_{d(on)}$	N-Channel $V_{DD} = 10 \text{ V}, R_L = 10 \Omega$ $I_D \cong 1 \text{ A}, V_{GEN} = 10 \text{ V}, R_G = 6 \Omega$ P-Channel $V_{DD} = -10 \text{ V}, R_L = 10 \Omega$ $I_D \cong -1 \text{ A}, V_{GEN} = -10 \text{ V}, R_G = 6 \Omega$	N-Ch		11	20	ns
Rise Time	t_r		N-Ch		11	20	
			P-Ch		12	25	
Turn-Off Delay Time	$t_{d(off)}$		N-Ch		16	30	
			P-Ch		17	30	
Fall Time	t_f		N-Ch		6	15	
			P-Ch		6	15	
Source-Drain Reverse Recovery Time	t_{rr}		$I_F = 1.25 \text{ A}, di/dt = 100 \text{ A}/\mu\text{s}$	N-Ch		45	
		$I_F = -1.25 \text{ A}, di/dt = 100 \text{ A}/\mu\text{s}$	P-Ch		35	70	

Notes

- Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2\%$.
- Guaranteed by design, not subject to production testing.






Typical Characteristics (25°C Unless Noted)

N-Channel









Typical Characteristics (25°C Unless Noted)

N-Channel



Typical Characteristics (25°C Unless Noted)

P-Channel



Typical Characteristics (25°C Unless Noted)

P-Channel

