

## Printers

Description	Product No./ Option No.	PRICE
<b>HP 5000 Model F100 Page Printer--60Hz</b> Includes 16 Mb graphics memory.	<b>C2753A</b>	<b>\$175,000.</b>
<b>HP 5000 Model F100 Page Printer--50Hz</b> Includes 16 Mb graphics memory.	<b>C2754A</b>	<b>175,000.</b>
<b>HP 5000 Model F135XP Page Printer--60 Hz</b>	<b>C2755A</b>	<b>265,000.</b>
<b>HP 5000 Model F135XP Page Printer--50 Hz</b>	<b>C2756A</b>	<b>265,000.</b>
<b>16 Mb Graphics Memory Expansion Module</b> (Printer accommodates up to 3 expansion modules.)	<b>C2758A</b>	<b>10,000.</b>
<b>Voltage Selectable Transformer</b> Required in UK, Australia and some parts of Japan	<b>C2763A</b>	<b>2,700.</b>
<b>Return Credit for HP2680A</b> One credit per F100 ordered, expires October 31, 1992.	<b>2680AN</b>	<b>- 15,000.</b>
<b>420 LPM Tabletop Line Printer</b> Includes 7 character sets; must specify I/O.	<b>2562C</b>	<b>5,777.</b>
220 VAC, 50/60 Hz	Opt. 015	<b>N/C</b>
100 VAC, 50/60 Hz	Opt. 016	<b>N/C</b>
240 VAC, 50/60 Hz	Opt. 017	<b>N/C</b>
Graphics option - HP lable card	Opt. 024	<b>2,401.</b>
HP-IB I/O with 4m cable and documentation	Opt. 046	<b>362.</b>
Replaces standard with Katakana character sets	Opt. 047	<b>N/C</b>
U.S. Postal Barcode character set	Opt. 048	<b>375.</b>
RS-232 Interface (cable not included)	Opt. 049	<b>207.</b>
RS-422 Interface (cable not included)	Opt. 050	<b>207.</b>
Centronics interface	Opt. 053	<b>200.</b>
16.7 cpi character set. Will replace 13.3 cpi	Opt. 060	<b>500.</b>
Service documentation	Opt. 715	<b>77.</b>
<b>55 dBA Dot Matrix Line Printer (420 LPM)</b> Includes quietized cabinet, sound abatement & passive paper stacker	<b>2563C</b>	<b>8,717.</b>
Line Draw, Math and Block	Opt. 001	<b>196.</b>
Replaces Standard with Katakana 8	Opt. 002	<b>N/C</b>
OCR A & B	Opt. 003	<b>196.</b>
Near letter quality, HP Roman 8	Opt. 004	<b>196.</b>
Near letter quality, Italics HP Roman 8	Opt. 005	<b>196.</b>
Near letter quality, HP Katakana 8	Opt. 006	<b>196.</b>
Barcodes (3 of 9, 2 of 5, UPC, EAN)	Opt. 008	<b>258.</b>
12, 13.3 cpi Roman 8	Opt. 009	<b>196.</b>
12, 15 cpi Roman 8	Opt. 012	<b>196.</b>
13.3, 15 cpi Roman 8	Opt. 013	<b>196.</b>
220 VAC, 50/60 Hz	Opt. 015	<b>N/C</b>
100 VAC, 50/60 Hz	Opt. 016	<b>N/C</b>
240 VAC, 50/60 Hz	Opt. 017	<b>N/C</b>
HP Label card	Opt. 024	<b>2,401.</b>
Cyrillic - ECMA 113/86	Opt. 026	<b>196.</b>
Cyrillic high density - ECMA 113/86	Opt. 027	<b>196.</b>
Cyrillic - ECMA 113/88	Opt. 028	<b>196.</b>
Cyrillic high density - ECMA 113/88	Opt. 029	<b>196.</b>

Select a System Support Option. Refer to Table 4 on page 90.