

Monitors		
Physical Characteristics	19" Mono (GRX)	19" Color (CRX, CRX-24, CRX-24Z, TVRX, Dual CRX)
Screen Refresh	72Hz	72Hz
Video Signals	RS-343 A	RS-343 A
Resolution	1280x1024	1280x1024
Height	471mm (18.6 in.)	471mm (18.6 in.)
Width	500mm (20 in.)	500mm (20 in.)
Depth	505mm (20.2 in.)	505mm (20.2 in.)
Net Weight	30 Kg (66.5 lbs)	29 Kg (64.3 lbs)
Electrical Specifications		
Line Voltage	88-135 VAC 193-269 VAC	88-135 VAC 193-269 VAC
Line Frequency	47-63 Hz	47-63 Hz
Maximum Current	1.6A	2.7A
Power Consumption	100 Watts max.	175 Watts max.
Environmental Characteristics		
Operating Temperature	0°-40° C	0°-40° C
Non-operating Temperature	- 40°-71° C	- 40°-71° C
Humidity: Operating 40° C	15%-95% RH	15%-95% RH
Max. Altitude Operating	4570m (15,000 ft)	4570m (15,000 ft)
Max. Altitude Non-operating	15,240m (50,000 ft)	15,240m (50,000 ft)
Regulatory Compliance		
VDE level	B	B
FCC class	A	A
VCCI class	2	1
Safety	UL, CSA, EN 60, 950/6-88, DHHS 21, IEC 950	UL, CSA, EN 60, 950/6-88, DHHS 21, IEC 950