

MDARexx

COLLABORATORS

	<i>TITLE :</i> MDARexx		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		January 7, 2023	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	MDARexx	1
1.1	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	1
1.2	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	1
1.3	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	1
1.4	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	3
1.5	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	7
1.6	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	9
1.7	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	16
1.8	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	16
1.9	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	17
1.10	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	17
1.11	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	18
1.12	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	18
1.13	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	19
1.14	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	22
1.15	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	22
1.16	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	23
1.17	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	23
1.18	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	24
1.19	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	24
1.20	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	25
1.21	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	25
1.22	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	25
1.23	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	25
1.24	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	26
1.25	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	26
1.26	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	26
1.27	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	27
1.28	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	27
1.29	MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones	27

Chapter 1

MDARexx

1.1 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

=====

Read Me First, please...

Introduction

About this document

Index

Cross Reference

Examples

1.2 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Read Me First:

=====

This amigaguide file references another amigaguide file. For this handy feature to work, you must ensure two things:

- (1) The main MegaD amigaguide document is titled:

MegaD.Guide

- (2) That same file (MegaD.Guide) is located in the same directory as this file.

1.3 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

MegaD And ARexx

The major goal while writing MegaD 3.0 was to include ARexx support. I would like to think that I have achieved this goal. Every build-in command has an equivalent ARexx command, many have extended arguments or like commands that offer better control from the ARexx port.

This document describes all of the ARexx commands that may be used with MegaD. You will also find a number of ARexx programs found in the ARexx drawer of this archive. The usefulness of these programs vary from simple demonstrations of command uses, to powerful programs that can be used to backup directories to floppies. It would be wise to look through this directory to see if any are of use to you.

At last count there were 123 ARexx commands available for use be used with MegaD. As you add Program Controls to MegaD, the newly added Program Control becomes a new ARexx command. Lets say that you add the Program Control <LhaPack> to your preferences of MegaD. This Program control is designed to archive selected files in directory windows. Now if you should need Lha to Pack or archive a few files from within an ARexx program you only need to call it from the program as:

LhaPack

This is a little vague so I'll give you a short program using the "LhaPack" Program Control from an ARexx script.

```
-----  
/* example of LhaPack */  
  
OPTIONS RESULTS  
OPTIONS FAILAT 20  
  
ADDRESS MEGAD  
dbug           /* turn MegaD debug messages on */  
  
CloseWindows  /* close any open windows */  
Mark "Ram:"   /* open the ram disk */  
SAY RESULT    /* should display "Ram Disk:" */  
SelectAll     /* select everything */  
LhaPack       /* call the Program Control */  
-----
```

This would create an archive of all the files found in the Ram: disk at that given time.

It is very important that you understand MegaD and how it works before attempting to write an ARexx program for it. MegaD is unique and it is very powerful. You will find that it can be configured in ways that are only limited by your imagination. With this versatility come many ways that an ARexx program can be written to do the same thing. It is also very possible to write a program that will work fine on your machine, but if the program

is given to a friend with MegaD, it will fail due to the differences of the two machines.

John L. Jones
PO Box 292
Midvale, Utah 84047
USA

1.4 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

```
@{ " About this document " link "About this document" }

ABootAdd
FiltersMinus
SelSrcDir
ABootEdit
FiltersPlus
SelSrcFile
ActiveDir
Find
SetColor
AddFilter
FreeFilter
SetDefault
AddFind
FreeFind
SetDevice
AddPattern
FreePattern
SetDisplay
AddProCtrl
FreePC
SetExport
```

AllBytes
FreeSpace
SetFlag
AllDir
FreeVolumes
SetKeypad
AllFiles
GoDeep
SetMenuDev
Child
Iconify
SetMisc
ClearAll
Label
SetNumber
CloseMark
LabelAlign
SetPreferences
CloseWindows
LabelTimes
SetPrint
ClrABoot
LabModify
SetProtect
ClrDir
Lock
SetScreen
ClrFiles
Mark

SetString
ClrPattern
Menu
SourceBytes
ClrSrc
MenuCheck
SourceDir
ClrSrcDir
Move
SourceFiles
ClrSrcFile
MoveAs
TXClose
Copy
NextItem
TXCloseAll
CopyAs
Open
TxFind
CopyFormat
OpenWindows
TXHex
CreateDir
OutputFile
TXPrintAll
dbug
OutputPrt
TXPrintWindow

Delete
Parent
TXRepeatFind
DelProCtrl
PrintSpooler
TXScrollDown
Dest
PrtText
TXScrollUp
DirCloseWindows
Quit
TXSideToSide
DirOpenWindows
Relabel
XTopBottom
DiskIn
Rename
UnSelectItem
DiskOut
ResetAll
UpdateDir
DSelect
SaveAs
UseFilter
DumpPrefs
SavePreferences
UseFind
DUnselect
SearchText

UsePattern

Duplicate

SelABoot

ViewIcon

ExportFile

SelDir

ViewText

F7

SelectAll

VolPerScr

F8

SelectItem

VSelect

F9

SelFile

VUnselect

F10

SelPattern

FileComment

SelSrc

1.5 MegaD 3.1 AReXX Commands Copyright © 1993 John L. Jones

MegaD 3.1 AReXX Commands Copyright © 1993 John L. Jones

About this document

A few things are assumed in this document.

You are familiar with MegaD and the built in functions you wish to use within MegaD through the AReXX port.

You are familiar with the AReXX programing language.

Case Sensitivity

All commands and arguments are not case sensitive. So the call "dbug true" and "DBUG TRUE" will be interpreted the same.

Format The descriptions of the commands and with arguments format follow these conventions.

<> Angle brackets enclose arguments that must be provided. For Instance, <file name> means that you must enter the appropriate file name in that Position. Unless square brackets surround the argument (see below), the argument is required. The command will not work unless it is specified.

[] Square brackets enclose arguments and keywords that are optional. They will be accepted by the command but are not required.

The following is an example:

VolPerScr [<value> <value>]

This translates to:

VolPerScr may be called without arguments, But if arguments are supplied it requires two of them.

In this document, the ARexx command will be listed to the far left of the text. If any arguments are used with the command they will be listed on the next line to the far left of the text with command. The paragraph to the right of the command describes the functions if it is unique to to ARexx.

Common commands

If a command is not unique to ARexx it will have a simple description such as:

Same as "Copy As".

This tell the reader that this call will act the same as if you selected the function from a gadget or Menu selection. For more information on these types of commands, please refer to the MegaD.Guide file.

Errors

Errors will set the result variable to a brief description of the error and set the RC code to 20.

Returns

All commands that return a value, uses the result variable.

Debugging

A special calls can be made to the MegaD ARexx port.
This is:

dbug
TRUE

or:

```
    dbug
    FALSE
If "dbug TRUE" is sent, this will allow MegaD to open
requestors to complain about ARexx calls that it does
not understand. If possible it will supply a list of
values that it would understand. Also, it will
display the offending argument or command that has
confused MegaD. It is very helpful in writing and
debugging ARexx programs.
"dbug FALSE" will disable this feature.
```

MegaD ARexx Port

The MegaD ARexx port is titled MEGAD.

1.6 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

MegaD ARexx Commands cross reference to build-in commands.

ARexx Command	Corresponding Built-in Command
=====	=====

ABootAdd	ABoot Add
ABootEdit	ABoot Edit
ActiveDir	None
AddFilter	None
AddFind	None
AddPattern	None
AddProCtrl	None
AllBytes	None
AllDir	None
AllFiles	None

Child
None

ClearAll
Clear All

CloseMark
None

CloseWindows
Close Windows

ClrABoot
Clr ABoot

ClrDir
Clr Dir

ClrFiles
Clr Files

ClrPattern
Clr Pattern

ClrSrc
Clr Src

ClrSrcDir
ClrSrcDir

ClrSrcFile
ClrSrcFile

Copy
Copy

Copy/Format
Copy/Format

CopyAs
Copy As

CreateDir
Create Dir

dbug
None

Delete
Delete

DelProCtrl
None

Dest
None

DirCloseWindows
 DirCloseWindows

DirOpenWindows
 DirOpenWindows

DiskIn
 None

DiskOut
 None

DSelect
 None

DumpPrefs
 None

DUnselect
 None

Duplicate
 Duplicate

ExportFile
 Export File

F7
 None

F8
 None

F9
 None

F10
 None

FileComment
 File Comment

FiltersMinus
 Filters -

FiltersPlus
 Filters +

Find
 Find

FreeFilter
 None

FreeFind
None

FreePattern
None

FreePC
None

FreeSpace
None

FreeVolumes
Free Volumes

GoDeep
Go Deep

Iconify
Iconify

Label
Label

LabelAlign
Label Align

LabelTimes
Label Times

LabModify
Lab. Modify

Lock
None

Mark
None

Menu
None

MenuCheck
None

Move
Move

MoveAs
Move As

NextItem

None

Open
Open...

OpenWindows
Open Windows

OutputFile
Output File

OutputPrt
Output Prt

Parent
None

PrintSpooler
Print Spooler

PrtText
Prt Text

Quit
Quit

Relabel
Relabel

Rename
Rename

ResetAll
Reset All

SaveAs
Save As...

SavePreferences
Save Preferences

SearchText
Search Text

SelABoot
Sel ABoot

SelDir
Sel Dir

SelectAll
Select All

```
SelectItem
    None

SelFile
    Sel File

SelPattern
    Sel Pattern

SelSrc
    Sel Src

SelSrcDir
    SelSrcDir

SelSrcFile
    SelSrcFile

SetColor
    Set Color...

SetDefault
    Set Default...

SetDevice
    None

SetDisplay
    Set Display...

SetExport
    Set Export

SetFlag
    None

SetKeypad
    Set Keypad...

SetMenuDev
    Set MenuDev...

SetMisc
    Set Misc...

SetNumber
    None

SetPreferences
    Set Preferences

SetPrint
    Set Print...

SetProtect
    Set Protect
```

```
SetScreen
    Set Screen...

SetString
    None

SourceBytes
    None

SourceDir
    None

SourceFiles
    None

TXClose
    TX Close

TXCloseAll
    TX Close All

TxFind
    TX Find

TXHex
    TX Hex

TXPrintAll
    TX PrintAll

TXPrintWindow
    TX PrintWindow

TXRepeatFind
    TX RepeatFind

TXScrollDown
    TX ScrollDown

TXScrollUp
    TX ScrollUp

TXSideToSide
    TX SideToSide

TXTopBottom
    TX TopBottom

UnselectItem
    None

UpdateDir
    Update Dir
```

```
UseFilter
    None

UseFind
    None

UsePattern
    None

ViewIcon
    View Icon

ViewText
    View Text

VolPerScr
    VolPerScr

VSelect
    None

VUnselect
    None
```

1.7 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ABootAdd

Usage: ABootAdd

Description: Same as ABoot Add built-in.

Example: -

Built-In: ABoot Add

See Also:

AddProCtrl
for adding AutoBoots through ARexx.

1.8 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ABootEdit

Usage: ABootEdit [AutoBoot Title]

Description: Same as ABoot Edit built-in. If the Title of the AutoBoot is supplied as an argument, that AutoBoot will be deleted.

Example: -

Built-In: ABoot Edit

See Also: -

1.9 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ActiveDir

Usage: ActiveDir

Description: Will return the Active Directory name in the result variable or "" if none.

Example: -

Built-In: -

See Also: -

1.10 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: AddFilter

Usage: AddFilter <TYPE> <IN | OUT> <Pattern>

Description: Adds a filter to the current Filter list.
The TYPE argument can be one of four types::

Name
Size
Date
Protect

The IN | OUT argument can only be In or out.
The Pattern field must be the correct type of pattern to match the TYPE argument. All three arguments are required.

Example: -

Built-In: -

See Also:

FreeFilter

UseFilter

FiltersPlus

1.11 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: AddFind

Usage: AddFind <TYPE> <IN | OUT> <Pattern>

Description: Adds a filter to the current Find list.

The TYPE argument can be one of four types:

Name
Size
Date
Protect

The IN | OUT argument can only be In or out.

The Pattern field must be the correct type of pattern to match the TYPE argument. All three arguments are required.

Example: -

Built-In: -

See Also:

FreeFind

UseFind

Find

.

1.12 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: AddPattern

Usage: AddPattern <TYPE> <IN | OUT> <Pattern>

Description: Adds a filter to the current Pattern list.

The TYPE argument can be one of four types:

Name
Size
Date
Protect

The IN | OUT argument can only be In or out.

The Pattern field must be the correct type of pattern to match the TYPE argument.

All three arguments are required.

Example: -

Built-In: -

See Also:

FreePattern

UsePattern

SelPattern

ClrPattern

1.13 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: AddProCtrl

Usage: AddProCtrl <TYPE> <FLAGS> <SCREEN> <EXECUTE_TYPE> <TITLE>
<PATH:PROGRAM_NAME> <AFTER_NAME> <AFTER_LINE>
<OUT_FILE> <IN_FILE> <AUTOBOOT_EXTENSION>
<CONSOLE_WINDOW> <STACK_SIZE> <FUTURE>
<AUTOBOOT_CODE>

Description: A very powerful function to add all types of Program Controls. It requires 15 arguments in the above order.

TYPES:

Can be one of four possibilities:

MenuSet
AutoBoot
UserGadget
ARexx

FLAGS:

Can be NULL, one or a multiple of the following selections:

SkipDir
SkipFile
WorkWithout
SkipInfo
CombineAll
WorkbenchFront
MegadFront
ReloadDir
QueryEndName

Multiple FLAGS must be separated by a vertical bar <|> such as in:

SkipDir|SkipInfo

SCREEN:

Must be one of two possibilities:

MDScreen
WBScreen

EXECUTE_TYPE:

Must be one of three possibilities:

Execute
Hold
Workbench

TITLE:

This is a string identifyint this Program Control.
It must be a unique name not previously defined
as a built in command, ARexx command or as another
Program Control.

PATH:PROGRAM_NAME:

This is the actual program that MegaD is to
call during the execution of this Program
Control.

AFTER_NAME:

This is any information you want inserted into
the command line immediately after the program
name, or NULL if it is to be left blank.

AFTER_LINE:

This is any information you want appended to the
end of the command line, or NULL if it is to be
left blank.

OUT_FILE:

This is a valid file name for the output file, or
NULL if it is to be left blank.

IN_FILE:

This is a valid file name for the input file, or
NULL if it is to be left blank.

AUTOBOOT_EXTENSION:

This is a file extension to use for matching the
AutoBoot to. To use the extension, the
AUTOBOOT_CODE must be NULL.

CONSOLE_WINDOW:

The purpose of this is to set the size of the Console window. This MUST be the first of the actual console line that defines the device and the size. i.e.

CON:10/12/600/150

There is no error checking to see if this is correct. MegaD adds the rest of the Console line before launching the Program Control. If you wish to use the default size set this argument to NULL.

STACK_SIZE:

This is to set the stack size for the Program Control. MegaD will always guarantee that the launched program will have at least 4096 bytes of stack any setting less than this will be ignored. If this STACK_SIZE is not set MegaD will check to see if there is a Workbench Icon for the launched program and if this icon has a stack setting, if so it will use that setting. If the icon stack size is not available and STACK_SIZE was not set, MegaD will use its own stack size for the launched program. STACK_SIZE will override all other settings except for the minimum 4096 bytes.

FUTURE:

This is for future expansion. Leave NULL.

AUTOBOOT_CODE:

Set this to either:

NULL, or
a string of HEX number

If you set it to a string of HEX number, that hex number should be the same as the first bytes of the file to use for a match to execute an AutoBoot with.

Example:

```
/*
** Example of adding an AutoBoot with the ARexx port of
** MegaD.
**
** This will create the AutoBoot so that anytime an IFF
** graphic file is double clicked the program Display
** will be called from the Sys:Utilities drawer.
*/
```

```
/*
 ** If program is launched from MegaD the default address
 ** will be MEGAD. The next command must go to the REXX port.
 */

address REXX

option result /* All return values are done though
               the result variable */

address MEGAD /* Send commands to the MEGAD port */

@{ " dbug " link "dbug"} TRUE /* Let MegaD display
                                debugging messages
                                on the MegaD Screen */

/* test autoboot Hex codes */

"addproctrl autoboot skipinfo|skipdir|workwithout MDScreen ←
   workbench SysDisplay sys:Utilities/Display NULL NULL NULL NULL ←
   NULL NULL NULL NULL 464f524d"

-----
```

Built-In: -

See Also: For more information on Program Controls, see

Program Control Window

in the MegaD.Guide.

1.14 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: AllBytes

Usage: AllBytes

Description: Will return in the result variable, the total of all bytes selected in both source and destination windows.

Example: -

Built-In: -

See Also: -

1.15 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: AllDir

Usage: AllDir

Description: Will return in the result variable, the total of all directories selected in both source and destination windows.

Example: -

Built-In: -

See Also: -

1.16 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: AllFiles

Usage: AllFiles

Description: Will return in the result variable, the total of all files selected in both the source and destination windows.

Example: -

Built-In: -

See Also: -

1.17 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Child

Usage: Child <child_name>

Description: Will open a child directory window of the marked directory. Child must have one argument and that argument is the name of the child directory you wish to open. It will return the actual directory name of the directory opened or "" if the directory could not be found.

Example: -

Built-In: -

See Also:

Mark

Lock

Dest

Parent

SelectItem

UnSelectItem

CloseMark

1.18 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ClearAll

Usage: ClearAll

Description: Same as Clear All built-in.

Example: -

Built-In: Clear All

See Also: -

1.19 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: CloseMark

Usage: CloseMark

Description: Will close the marked directory window. Does not free the memory of that directory.

Example: -

Built-In: -

See Also:

Mark

Lock

Dest

Parent

Child

SelectItem

UnSelectItem

1.20 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: CloseWindows

Usage: CloseWindows

Description: Will Close all open directory windows.

Example: -

Built-In: Close Windows

See Also: -

1.21 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ClrABoot

Usage: ClrABoot [AutoBoot Title]

Description: Will unselect items in the open directory window that match the AutoBoot criteria. If no argument is supplied, the Clr AutoBoot function will be called in interactive mode requiring the user to define the AutoBoot to select by. If an argument is supplied it should be the Title of the AutoBoot to use to unselect by.

Example: -

Built-In: Clr ABoot

See Also: -

1.22 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ClrDir

Usage: ClrDir

Description: Same as Clr Dir built-in.

Example: -

Built-In: Clr Dir

See Also: -

1.23 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ClrFiles
Usage: ClrFiles
Description: Same as Clr Files built-in.
Example: -
Built-In: Clr Files
See Also: -

1.24 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ClrPattern

Usage: ClrPattern
Description: Same as Clr Pattern built-in.
Example: -
Built-In: Clr Pattern
See Also:
 AddPattern
 FreePattern
 UsePattern

1.25 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ClrSrc
Usage: ClrSrc
Description: Same as Clr Src built-in.
Example: -
Built-In: Clr Src
See Also: -

1.26 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ClrSrcDir

Usage: ClrSrcDir

Description: Same as ClrSrcDir built-in.

Example: -

Built-In: ClrSrcDir

See Also: -

1.27 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ClrSrcFile

Usage: ClrSrcFile

Description: Same as ClrSrcFile built-in.

Example: -

Built-In: ClrSrcFile

See Also: -

1.28 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Copy

Usage: Copy

Description: Same as Copy built-in.

Example: -

Built-In: Copy

See Also: -

1.29 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: CopyFormat

Usage: CopyFormat

Description: Same as Copy/Format built-in.

Example: -

Built-In: Copy/Format

See Also: -

1.30 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: CopyAs

Usage: CopyAs

Description: Same as Copy As built-in.

Example: -

Built-In: Copy As

See Also: -

1.31 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: CreateDir

Usage: CreateDir [directory_name]

Description: Same as Create Dir built-in if called without any arguments. If an argument is supplied, it will create new directories in the "Dest"ination directory windows with the [directory_name] argument.

Example: -

Built-In: Create Dir

See Also: -

1.32 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: dbug

Usage: dbug [TRUE | FALSE]

Description: To help in debugging ARexx commands sent to the MEGAD port. When a command fails, a small window will open

on the MegaD Screen giving the command or argument that failed and any possible information that might help. If called without arguments it will default to TRUE.

Example: -

Built-In: -

See Also: -

1.33 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Delete

Usage: Delete

Description: Same as Delete built-in.

Example: -

Built-In: Delete

See Also: -

1.34 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: DelProCtrl

Usage: DelProCtrl <Program_Control_Title>

Description: Must be supplied an argument that equals the title of one of the program controls set within MegaD. It will not allow you to delete an element of a Menu Set.

Example: DelProCtrl "LHA Pack"

Built-In: -

See Also: -

1.35 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Dest

Usage: Dest <TRUE | FALSE>

Description: Will select or unselect the "Dest"ination gadget of a marked window.

Example: -

Built-In: -

See Also:

Mark

Lock

Parent

SelectItem

UnSelectItem

CloseMark

Child

1.36 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: DirCloseWindows

Usage: DirCloseWindows

Description: Same as DirCloseWindows built-in.

Example: -

Built-In: DirCloseWindows

See Also: -

1.37 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: DirOpenWindows

Usage: DirOpenWindows

Description: Same as DirOpenWindows built-in.

Example: -

Built-In: DirOpenWindows

See Also: -

1.38 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: DiskIn

Usage: DiskIn

Description: Will open a small window that reads: "Waiting for disk insert message". This is for writing scripts that will wait for disk to be inserted into any floppy disk drive.

Should the user select the Window Close Gadget of this window "ABORT" will be returned in the result variable.

Example: -

Built-In: -

See Also: -

1.39 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: DiskOut

Usage: DiskOut

Description: Will open a small window that reads: "Waiting for disk removed message". This is for writing scripts that will wait for disk to be removed from any floppy disk drive.

Should the user select the Window Close Gadget of this window "ABORT" will be returned in the result variable.

Example: -

Built-In: -

See Also: -

1.40 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: DSelect

Usage: DSelect <Device_name>

Description: Requires an argument that will match an item in the Device List. If it is found it will select that item in the list. It will return the title of the selected item if found or it will return "" in the result variable if it is not found.

Example: -

Built-In: -

See Also: -

1.41 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: DumpPrefs

Usage: DumpPrefs [filename]

Description: Creates an actual ARexx Script that can be run to set preferences. The purpose for this function is to create a file that demonstrate the use of
AddProCtrl

,

SetNumber

,

SetString

,

SetDevice

and

FreePC

.

A user can also scan the output to get a visual idea of how the current preferences are set. An optional filename can be supplied to direct the output to a file, the default is to the "PRT:" device.

Example: -

Built-In: -

See Also: -

1.42 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: DUnselect

Usage: DUnselect <Device_name>

Description: Requires an argument that will match an item in the Device List. If it is found it will unselect that item in the list. It will return the title of the unselected item if found or it will return "" in the result variable if it is not found.

Example: -

Built-In: -

See Also: -

1.43 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Duplicate

Usage: Duplicate

Description: Same as Duplicate built-in.

Example: -

Built-In: Duplicate

See Also: -

1.44 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ExportFile

Usage: ExportFile

Description: Same as Export File built-in.

Example: -

Built-In: Export File

See Also: -

1.45 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: F7

Usage: F7

Description: Performs the same action as pressing the F7 key. This action will toggle through open Text Windows, if any.

Example: -

Built-In: -

See Also: -

1.46 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: F8

Usage: F8

Description: Performs the same action as pressing the F8 key. This action will toggle the Main Control Window forward or back of the screen. It will also set the display list in the control window to show "Devices, Assigns And Drives."

Example: -

Built-In: -

See Also: -

1.47 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: F9

Usage: F9

Description: Performs the same action as pressing the F9 key. This action will toggle the Main Control Window forward or back of the screen. It will also set the display list in the control window to show "Volumes In Memory."

Example: -

Built-In: -

See Also: -

1.48 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: F10

Usage: F10

Description: Performs the same action as pressing the F10 key. This action will toggle the Main Control Window forward or back of the screen. If "F10 Close Control Window" is checked in the Preferences, Set Defaults Window then this command will close or reopen the Main Control Window.

Example: -

Built-In: -

See Also: -

1.49 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: FileComment

Usage: FileComment

Description: Same as File Comment built-in.

Example: -

Built-In: File Comment

See Also: -

1.50 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: FiltersMinus

Usage: FiltersMinus

Description: Same as Filters - built-in.

Example: -

Built-In: Filters -

See Also: @{ "AddFilter" link "AddFilter"}
@{ "FreeFilter" link "FreeFilter"}
@{ "UseFilter" link "UseFilter"}.

1.51 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: FiltersPlus

Usage: FiltersPlus

Description: Same as Filters + built-in.

Example: -

Built-In: Filters +

See Also:

AddFilter

FreeFilter

UseFilter

.

1.52 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Find

Usage: Find

Description: Same as Find built-in.

Example: -

Built-In: Find

See Also:

AddFind

FreeFind

UseFind

.

1.53 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: FreeFilter

Usage: FreeFilter

Description: Will free all Filters created by the ARexx function AddFilter.

Example: -

Built-In: -

See Also:

AddFilter

UseFilter

FiltersMinus

.

1.54 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: FreeFind

Usage: FreeFind

Description: Will free all Find Filters created by the ARexx function AddFind.

Example: -

Built-In: -

See Also:

AddFind

UseFind

Find

.

1.55 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: FreePattern

Usage: FreePattern

Description: Will free all Pattern Filters created by the ARexx function AddPattern.

Example: -

Built-In: -

See Also:

AddPattern

UsePattern
.

1.56 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: FreePC

Usage: FreePC <Type>

Description: Frees the complete list of Program Controls from the version of MegaD which is currently running. A Type must be supplied. The types of Program Controls that can be sent are:

AutoBoot
ARexx
MenuSet
UserGadget

The main purpose of this command is to clear all Program Controls before resetting with the AddProCtrl command.

Example: -

Built-In: -

See Also:

DumpPrefs

1.57 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: FreeSpace

Usage: FreeSpace

Description: Will return the free disk space of the volume associated with the active directory in the result variable.

Example: -

Built-In: -

See Also: -

1.58 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: FreeVolumes

Usage: FreeVolumes

Description: Same as Free Volumes built-in.

Example: -

Built-In: Free Volumes

See Also: -

1.59 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: GoDeep

Usage: GoDeep

Description: Same as Go Deep built-in.

Example: -

Built-In: Go Deep

See Also: -

1.60 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Iconify

Usage: Iconify

Description: Will Iconify MegaD. If MegaD is already iconified, it will un-iconify. Any ARexx command to MegaD will un-iconify MegaD. MegaD is incapable of performing most task without its graphic interface open, it will un-iconify so that it can perform the command sent through the ARexx port.

Example: -

Built-In: Iconify

See Also: -

1.61 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Label

Usage: Label

Description: Same as Label built-in.

Example: -

Built-In: Label

See Also: -

1.62 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: LabelAlign

Usage: LabelAlign

Description: Same as Label Align built-in.

Example: -

Built-In: Label Align

See Also: -

1.63 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: LabelTimes

Usage: LabelTimes

Description: Same as Label Times built-in.

Example: -

Built-In: Label Times

See Also: -

1.64 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: LabModify

Usage: LabModify

Description: Same as Lab. Modify built-in.

Example: -

Built-In: Lab. Modify

See Also: -

1.65 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Lock

Usage: Lock <TRUE | FALSE>

Description: Will "Lock" the marked window.

Example: -

Built-In: -

See Also:

Mark

Dest

Parent

SelectItem

UnSelectItem

CloseMark

Child

.

1.66 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Mark

Usage: Mark <directory_name>

Description: Will do whatever is necessary to open a directory for the supplied directory name.

Mark requires one argument, the directory name to open. The actual name of the directory loaded will be

returned in the result variable.

Once the directory has been "Mark"ed, certain actions can be taken on the physical state of the directory window.

- The "Dest"ination gadget can be selected with the call "Dest TRUE" or it can be unselected with the call "Dest FALSE".
 - The "Lock" Gadget can be modified in the same manner with "Lock TRUE" or "Lock FALSE".
 - The parent directory of the Marked directory can be opened with a call to "Parent". The actual name of the Parent directory will be returned in the result variable.
 - A child directory can be opened from the Marked directory.
 - A single directory item can be selected or unselected from the marked window by name.
-

```
Example: /* Mark Demo
** This file demonstrates the uses of
**
  Mark
'
  Dest
'
  Lock
'
  Child
'
  Parent
'
**
  SelectItem
  and
  UnSelectItem
  */
options results

ADDRESS MEGAD
dbug TRUE

/* open window to the Ram Disk: and Mark it */

  Mark
  'ram:'

/* display actual name of opened directory */
SAY result
```

```
/* save name for later */
rootname = result

/* User select the Marked directory's 'Dest'ination gadget */

Dest
TRUE

/* Select the Marked directory's 'Lock' gadget */

Lock
TRUE

/* move to the subdirectory */

child
t

/* display actual name */
say result

/* save name for later */
childname = result

/* Mark the child directory */

Mark
""result"""

/* User select the Marked directory's 'Dest'ination gadget */

Dest
TRUE

/* Select the Marked directory's 'Lock' gadget */

Lock
TRUE

/* Move to the parent directory */

parent
        /* display actual name */
say result

/* Mark the Parent directory */

Mark
""result"""

/* Flash the T directory 40 times */
DO 40

SelectItem
t
```

```
UnSelectItem  
t  
END  
  
Mark  
"/"childname"/"  
  
/* close the child */  
  
CloseMark  
  
Mark  
"/"rootname"/"  
  
/* close the parent */  
  
CloseMark
```

Built-In: -

See Also:

Parent

Dest

Lock

SelectItem

UnSelectItem

CloseMark

Child

1.67 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Menu

Usage: Menu <Menu_Path>

Description: Will let you select any MegaD non-ViewText menu item by its titles.

You must supply one argument for <Menu>. This will not work on on "Checkable" menus, for those see MenuCheck. The argument must read exactly as the menu reads, and must be in the following format:

MenuItem,MenuItem

- or -

MenuTitle, MenuItem, MenuSubItem

Example: "Menu Project,Color..."
"Menu 'Output,Disk Label,Alignment'"

NOTE: The extra single quotes are needed due to the space found in "Disk Label".

Built-In: -

See Also: -

1.68 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: MenuCheck

Usage: MenuCheck <Menu_path> <Check | UnCheck>

Description: Will let you select any MegaD non-text menu item by its titles.

You must supply two arguments for <MenuCheck>. The first argument is the title of the menu. The second argument is either Check or UnCheck.

Example: "Menu 'Windows,Use Snapshot' Check"
"Menu 'Show,Sort on,Name' UnCheck"

Built-In: -

See Also:

1.69 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Move

Usage: Move

Description: Same as Move built-in.

Example: -

Built-In: Move

See Also: -

1.70 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: MoveAs

Usage: MoveAs

Description: Same as Move As built-in.

Example: -

Built-In: Move As

See Also: -

1.71 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: NextItem

Usage: NextItem <Attribute> [Clear]

Description: This will find the next selected item in any of the open directory windows, and will return the file attribute of that file item in the result variable.

<NextItem> requires one argument and can use a second argument. The first argument must be one of the following:

Filename	(returns filename only)
Path	(return path only)
Name	(return full path and filename)
Size	(return size)
Date	(return date)
Protection	(return protection flags)
Comment	(return comment)
Type	(return Directory or File)

The second optional argument will UnSelect that item in the list. This argument can be anything to trigger the unselecting of the directory item.

Example: do forever

```
NextItem Name
if result = "" then leave
Say result

NextItem Size
Say result

NextItem Comment
Say result

/* Clear the item */
NextItem Type clear
Say result

end
```

Built-In: -

See Also: -

1.72 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Open

Usage: Open [filename]

Description: If no argument is sent, MegaD will open the ASL requestor for selection of a new .pf file. If the [filename] argument is supplied, MegaD will open and use the preference file. Only valid .pf files should be sent to this function.

Example: -

Built-In: Open...

See Also: -

1.73 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: OpenWindows

Usage: OpenWindows

Description: Same as Open Windows built-in.

Example: -

Built-In: Open Windows

See Also: -

1.74 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: OutputFile

Usage: OutputFile

Description: Same as Output File built-in.

Example: -

Built-In: Output File

See Also: -

1.75 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: OutputPrt

Usage: OutputPrt

Description: Same as Output Prt built-in.

Example: -

Built-In: Output Prt

See Also: -

1.76 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Parent

Usage: Parent

Description: Will move to the parent of the marked windows. It will return the actual directory name of the directory opened or "" if there was not a parent directory.

Example: -

Built-In: -

See Also:

Mark

Dest

Lock

SelectItem

UnSelectItem

CloseMark

Child

1.77 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: PrintSpooler

Usage: PrintSpooler

Description: Same as Print Spooler built-in.

Example: -

Built-In: Print Spooler

See Also: -

1.78 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: PrtText

Usage: PrtText

Description: Same as Prt Text built-in.

Example: -

Built-In: Prt Text

See Also: -

1.79 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Quit

Usage: Quit

Description: Will quit MegaD. It will fail if other program have been lunched with MegaD or if there are visitors on MegaD's public screen.

Example: -

Built-In: Quit

See Also: -

1.80 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Relabel

Usage: Relabel

Description: Same as Relabel built-in.

Example: -

Built-In: Relabel

See Also: -

1.81 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: Rename

Usage: Rename [filename]

Description: If no argument is sent, this will operate the same as the "Rename" built-in command.

If an argument is sent, the argument must be the filename you wish to rename the first selected item to. Once it is renamed, the item will be unselected.

If Keep .info is selected, the .info file will be renamed also.

Example: DO FOREVER

 NextItem Filename

```
if result = "" then leave

ELSE DO
    /* add underscore for new name */
    name = '_' || result

    /* Rename will unselect the first
       selected item */
    Rename name
END

/* skip the next selected item */
END
```

Built-In: Rename

See Also: RenameOther.rexx script

1.82 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ResetAll

Usage: ResetAll

Description: Same as Reset All built-in.

Example: -

Built-In: Reset All

See Also: -

1.83 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SaveAs

Usage: SaveAs [filename]

Description: If no argument is sent, MegaD will open the ASL requestor for selection of a new .pf file. If the [filename] argument is supplied, MegaD will save the current preference file as the filename supplied. MegaD preference files should be saved with a .pf extension.

Example: -

Built-In: Save As...

See Also: –

1.84 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SavePreferences

Usage: SavePreferences

Description: Same as Save Preferences built-in.

Example: –

Built-In: Save Preferences

See Also: –

1.85 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SearchText

Usage: SearchText

Description: Same as Search Text built-in.

Example: –

Built-In: Search Text

See Also: –

1.86 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SelABoot

Usage: SelABoot

Description: Will select items in the open directory window that match the AutoBoot criteria.

If no argument is supplied, the Sel ABoot function will be called in interactive mode requiring the user to define the AutoBoot to select by.

If an argument is supplied it should be the TITLE of the AutoBoot to use to select by.

Example: -

Built-In: Sel ABoot

See Also: -

1.87 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SelDir

Usage: SelDir

Description: Same as Sel Dir built-in.

Example: -

Built-In: Sel Dir

See Also: -

1.88 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SelectItem

Usage: SelectItem <Directory_item_name>

Description: This requires one argument, which should match one of the directory items in the marked window.

If a match is found, the actual name will be returned in the result variable. If no match is found, the result will be set to "".

Example: -

Built-In: -

See Also:

Mark

Dest

Lock

UnSelectItem

CloseMark

Child

Parent

1.89 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SelectAll

Usage: SelectAll

Description: Same as Select All built-in.

Example: -

Built-In: Select All

See Also: -

1.90 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SelFile

Usage: SelFile

Description: Same as Sel File built-in.

Example: -

Built-In: Sel File

See Also: -

1.91 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SelPattern

Usage: SelPattern

Description: Same as Sel Pattern built-in.

Example: -

Built-In: Sel Pattern

See Also:

FreePattern

AddPattern

UsePattern
.

1.92 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SelSrc

Usage: SelSrc

Description: Same as Sel Src built-in.

Example: -

Built-In: Sel Src

See Also: -

1.93 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SelSrcDir

Usage: SelSrcDir

Description: Same as SelSrcDir built-in.

Example: -

Built-In: SelSrcDir

See Also: -

1.94 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SelSrcFile

Usage: SelSrcFile

Description: Same as SelSrcFile built-in.

Example: -

Built-In: SelSrcFile

See Also: -

1.95 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetColor

Usage: SetColor

Description: Same as Set Color... built-in.

Example: -

Built-In: Set Color...

See Also: -

1.96 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetDefault

Usage: SetDefault

Description: Same as Set Default... built-in"

Example: -

Built-In: Set Default...

See Also: -

1.97 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetDevice

Usage: SetDevice <subscript> <Path String> <Title String>

Description: Sets one of the Device Gadget's path and title elements for the version of MegaD which is currently running.

A subscript and two strings are required to set this. There are 45 possible Device Gadgets. If the element needs to be blanked send "NULL" as String.

Example: -

Built-In: -

See Also:

ARexxPrefsList.txt
file for possible subscripts and valid Values for the elements.

1.98 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetDisplay

Usage: SetDisplay

Description: Same as Set Display... built-in"

Example: -

Built-In: Set Display...

See Also: -

1.99 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetExport

Usage: SetExport

Description: Same as Set Export built-in.

Example: -

Built-In: Set Export

See Also: -

1.100 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetFlag

Usage: SetFlag <subscript> <value>

Description: Sets one of the preferences flags for the version of
MegaD which is currently running.

Example: -

Built-In: -

See Also:

 ARexxPrefsList.txt
 file for a complete
 list of valid subscripts and the possible values.

1.101 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetKeypad

Usage: SetKeypad

Description: Same as Set Keypad... built-in.

Example: -

Built-In: Set Keypad...

See Also: -

1.102 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetMenuDev

Usage: SetMenuDev

Description: Same as Set MenuDev... built-in.

Example: -

Built-In: Set MenuDev...

See Also: -

1.103 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetMisc

Usage: SetMisc

Description: Same as Set Misc... built-in.

Example: -

Built-In: Set Misc...

See Also: -

1.104 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetNumber

Usage: SetNumber <subscript> <Value>

Description: Sets one of the number elements of preferences for the version of MegaD which is currently running.

A subscript and the value to set this to must be supplied. Values are not range checked so the ARexx script should guarantee that only valid values are sent.

Example: -

Built-In: -

See Also:

 ARexxPrefsList.txt
 file for possible subscripts
 and valid Values for the elements.

1.105 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetPreferences

Usage: SetPreferences

Description: Same as Set Preferences built-in.

Example: -

Built-In: Set Preferences

See Also: -

1.106 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetPrint

Usage: SetPrint

Description: Same as Set Print... built-in.

Example: -

Built-In: Set Print...

See Also: -

1.107 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetProtect

Usage: SetProtect

Description: Same as Set Protect built-in.

Example: -

Built-In: Set Protect

See Also: -

1.108 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetScreen

Usage: SetScreen

Description: Same as Set Screen... built-in.

Example: -

Built-In: Set Screen...

See Also: -

1.109 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SetString

Usage: SetString <subscript> <String>

Description: Sets one of the string elements of preferences for the version of MegaD which is currently running.

A subscript and the a string to set this to must be supplied. If the element needs to be blanked send "NULL" as the String.

Example: -

Built-In: -

See Also: ARexxPrefsList.txt file for possible and valid Values

for the elements.

1.110 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SourceBytes

Usage: SourceBytes

Description: Will return the total bytes of source files selected.
It will also return the bytes selected in directories if the
GoDeep
commands has been issued. The total will be
returned in the result variable.

Example: -

Built-In: -

See Also: -

1.111 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SourceDir

Usage: SourceDir

Description: Will return the total number of directories selected
in source windows in the result variable.

Example: -

Built-In: -

See Also: -

1.112 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: SourceFiles

Usage: SourceFiles

Description: Will return the total number of files selected in the
source windows in the result variable.

Example: -

Built-In: -

See Also: -

1.113 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: TXCloseAll

Usage: TXCloseAll

Description: Same as TX Close All built-in.

Example: -

Built-In: TX Close All

See Also: -

1.114 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: TXClose

Usage: TXClose

Description: Same as TX Close built-in.

Example: -

Built-In: TX Close

See Also: -

1.115 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: TXFind

Usage: TXFind

Description: Same as TX Find built-in.

Example: -

Built-In: TX Find

See Also: -

1.116 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: TXHex

Usage: TXHex

Description: Same as TX Hex built-in.

Example: -

Built-In: TX Hex

See Also: -

1.117 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: TXPrintAll

Usage: TXPrintAll

Description: Same as TX PrintAll built-in.

Example: -

Built-In: TX PrintAll

See Also: -

1.118 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: TXPrintWindow

Usage: TXPrintWindow

Description: Same as TX PrintWindow built-in.

Example: -

Built-In: TX PrintWindow

See Also: -

1.119 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: TXRepeatFind

Usage: TXRepeatFind

Description: Same as TX RepeatFind built-in.

Example: -

Built-In: TX RepeatFind

See Also: -

1.120 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: TXScrollDown

Usage: TXScrollDown

Description: Same as TX ScrollDown built-in.

Example: -

Built-In: TX ScrollDown

See Also: -

1.121 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: TXScrollUp

Usage: TXScrollUp

Description: Same as TX ScrollUp built-in.

Example: -

Built-In: TX ScrollUp

See Also: -

1.122 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: TXSideToSide

Usage: TXSideToSide

Description: Same as TX SideToSide built-in.

Example: -

Built-In: TX SideToSide

See Also: -

1.123 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: TXTopBottom

Usage: TXTopBottom

Description: Same as TX TopBottom built-in.

Example: -

Built-In: TX TopBottom

See Also: -

1.124 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: UnSelectItem

Usage: UnSelectItem <Directory_item_name>

Description: This requires one argument, which should match one of the directory items in the marked window.

If a match is found, the actual name will be returned in the result variable. If no match is found the result will be set to "". The item will be left unselected.

Example: -

Built-In: -

See Also:

Mark

Dest

Lock

SelectItem

CloseMark

Child

Parent

1.125 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: UpdateDir

Usage: UpdateDir

Description: Same as Update Dir built-in.

Example: -

Built-In: Update Dir

See Also: -

1.126 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: UseFilter

Usage: UseFilter [Dest]

Description: This will use the filters created by AddFilter.

An optional argument, <Dest>, can be supplied.
If this argument is supplied. The filter will
be attached to all "Dest"ination windows only.

If the "Dest" argument is not supplied. The
filters will become global to all windows
(source and "Dest"ination).

Example: -

Built-In: -

See Also:

AddFilter

FreeFilter

FiltersPlus

1.127 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: UseFind

Usage: UseFind [DirFile | File | Dir] <Save_file_name>

Description: This will use the Find Filters created by AddFind.

It requires one argument, and an optional argument can be supplied. The required argument must be one of the following:

DirFile
File
Dir

This argument will set what types of directory items to find.

The optional argument is for a file name to save the found directory items names to. If supplied this should be a full Path and file name.

Example: -

Built-In: -

See Also:

AddFind

FreeFind

1.128 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: UsePattern

Usage: UsePattern [Select | UnSelect] <Dest>

Description: This will use the Pattern Filters created by AddPattern.

It requires one argument, and an optional argument can be supplied. The required argument must be one of the following:

Select
UnSelect

This will select or unselect matches to the patterns.

The optional argument is to limit the selection to "Dest"ination directories only. The optional argument for this is <Dest>

Example: -

Built-In: -

See Also:

AddPattern
FreePattern
SelPattern
ClrPattern

1.129 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ViewIcon
Usage: ViewIcon
Description: Same as View Icon built-in.
Example: -
Built-In: View Icon
See Also: -

1.130 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: ViewText
Usage: ViewText
Description: Same as View Text built-in.
Example: -
Built-In: View Text
See Also: -

1.131 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: VolPerScr
Usage: VolPerScr <Value> <Value>
Description: This will set the limits for the Volumes Per Screen and the limits for the Windows Per Volume.
If called without arguments, it will call the built in function VolPerScr .

If arguments are supplied, there needs to be Two values. The two values must be greater than 0 and less than 10. The first value will set the Volumes Per Screen limit. The Second value will set the Windows Per Volume limit.

Example: VolPerScr 3 4

This would set the Volumes Per Screen limit to 3, and the Windows Per volume to 4.

Built-In: VolPerScr

See Also: -

1.132 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: VSelect

Usage: VSelect <Volume_Name>

Description: This requires one argument. That argument should match one of the items listed in the Volumes In Memory list.

If the item is found, it will be marked selected and the name of the volume will be returned in the result variable.

If it is not found the result variable will be set to "".

Example: -

Built-In: -

See Also: -

1.133 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Command: VUnselect

Usage: VUnselect <Volume_Name>

Description: This requires one argument. That argument should

match one of the items listed in the Volumes In Memory list.

If the item is found, it will be marked unselected, and the name of the volume will be returned in the result variable.

If it is not found the result variable will be set to "".

Example:

Built-In:

See Also: -

1.134 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

Examples:

=====

```
@{ " BackupMD.rexx      " link "backupMD.rexx"}  
@{ " ChangePreferences.rexx " link "ChangePreferences.rexx"}  
@{ " DLPrint.rexx        " link "DLPrint.rexx"}  
@{ " MarkDemo.rexx       " link "MarkDemo.rexx"}  
@{ " MDARexxStart.rexx   " link "MDARexxStart.rexx"}  
@{ " NextItem.rexx       " link "NextItem.rexx"}  
@{ " OpenSE.rexx         " link "OpenSE.rexx"}  
@{ " Parse.rexx          " link "Parse.rexx"}  
@{ " RenameOther.rexx    " link "RenameOther.rexx"}  
  
@{ " ARexxPrefsList.txt  " link "ARexxPrefsList.txt"}
```

1.135 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

backupMD.rexx:

=====

```
/* This script will back up my 5 source code directories to a floppy disk.  
 I keep the source code for MegaD in MD: MDP: COM: SP: and RX:.  
 If you should want to use this script to backup a directory you should  
 change the directory names to something more useful. The script expect  
 a blank disk or a disk that has only been used by this script.  
 Do not create your own directory on this disk or the script will fail.  
*/
```

```
lhaFileName = "odds&ends:commands/lha" /* where to find the LHA program */  
  
arguments = "md mdp com rx sp" /* Back up assign directories */  
  
options results
```

```
signal on syntax
if ~show("L","rexxsupport.library") then call addlib"rexxsupport.library",0,-30

address MEGAD

        dbug
        TRUE

        freevolumes
        /* clear out the directory buffers and close directory windows */

/* be sure that the sort is on Name */
"
        MenuCheck
        'show,sort on,name' Check"

        diskin
        /* wait for a disk to be inserted into a drive.  The script  ←
           expect DF0: */
if result = "ABORT" then exit /* user closed window */

"
        Mark
        DF0:" /* Load the disk in drive DF0: and keep track of it for  ←
                  ARexx calls */
if result == "" then exit /* the root disk directory did not load */
volumename = result      /* keep track of the real volume name */

        dest
        TRUE          /* Select the Dest gadget of the Marked window */
dirname = date(s)      /* get the current date from ARexx to use as a directory  ←
name   */

        unselectItem
        "'dirname'"    /* check for directory with this name */
if result ~= "" then do /* The directory already exist */
    say dirname "exist, can not create directory"
    exit 0
end

/* before we add this directory lets find out what the last date was */

        selDir
        /* select all directories in all open directory windows */
lastdir = ""
do forever

        nextItem
        name clear      /* get the next selected item and unselect it */
if result = "" then leave /* no more selected directories */
lastdir = result      /* Save the last directory name */
end

if lastdir ~= "" then do /* The name of the directory are sorted dates */
    lastdir = right(lastdir,8) /* grab the last 8 characters of the directory name  ←
*/
```

```
year = substr(lastdir,3,2) /* Pull the pieces out of the name to make */
month = substr(lastdir,5,2) /* a date filter */
day = substr(lastdir,7,2)
end

CreateDir
""dirname""           /* create a directory with the sorted date ←
string */

child
""dirname""           /* move to child */
dirname = insert(volumename,dirname)

mark
""dirname""           /* mark the child directory */

lock
TRUE                 /* lock the window so we can't lose it,
it is still set as "Dest" */

/* set up the patterns for selecting files */

FreePattern
/* start with a blank list */

AddPattern
name in md#?.c

AddPattern
name in md#?.h

AddPattern
name in #?.lnk

AddPattern
name in #?.rexx

AddPattern
name in smakefile

AddPattern
name out #?protos.h /* Please note: You may create as many ←
filters
as you wish with ARexx */

/* if lastdir is not "" then we have already backed up to this disk
I usually back up everything to the first directory of the new backup disk
then each future backup is only of the files changed since the first backup
This way I can recover from one disk and usually have 5 or 6 backup on one disk
*/
if lastdir ~= "" then do
/* we need to move the last sorted directory string around into a
date filter which is the opposite format */
string = insert('-',day) /* add '-' to define Less Than date */
string = insert(string,'-')
```

```
string = insert(string,month)
string = insert(string,'-')
string = insert(string,year) /* by now the string should look like -18-12-99 */

        AddPattern
        date out string
/* another note about patterns and ARexx. At this point we have a total of
   7 filters, 5 IN type, 2 OUT type, 6 are name filters,
   one is a date filter. There is one that will select only the "smakefile"
   should one exist. There are no limits to the number of Filters you
   wish to use with ARexx.
*/
end

do while arguments ~= ""
PARSE VAR arguments filename arguments /* pull one of the arguments */
filename = STRIP(filename)      /* strip the spaces */
arguments = STRIP(arguments)
assign = insert(filename,':')    /* add the ':' for the assigned name */

        mark
        assign           /* Open and Mark the Assigned directory */

        UsePattern
        select          /* use all of the patterns to select items
                           in the open directory window */

        sourcebytes
        /* get how many bytes were selected */
bytes = result
if bytes ~= 0 then do          /* files were selected by the filters */
/* create a special User gadget to call */
/* A special "Flags to add after Program Name" field to create the .lha ←
   flagname
   this will create a string that looks somewhat like this:
   'a "df0:19921218/md"'
*/
flagname = insert(dirname,'/')
flagname = insert(flagname,filename)
string = insert("a ',''flagname''")
string = insert("UserGadget combineAll MDscreen Execute LHAPACK odds&ends: ←
   commands/lha ","'"string"'");
string = insert(string," NULL NULL NULL NULL NULL NULL NULL NULL");

        addproctrl
        string /* this creates LHAPACK */

LHAPACK      /* Call the program control we have just added */

        delproCtrl
LHAPACK /* remove this Program Control */

bytes = bytes%110
Call delay(bytes)/* LHA packs 110 bytes to a floppy per tick (1/50 sec) */
/* or 420 bytes to the ram disk on an A3.10/25 */
```

```
        /* This was added to prevent multiple LHA running trying */
        /* to write to one floppy at one time.*/
end

        CloseMark
        /* close the Marked directory */
end

        UpdateDir
        /* update the current Dest directory */
exit 0

syntax:
if(rc ~= 0) then do
    say "at syntax"
    say "rc = " rc
    end
exit 0
```

1.136 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

```
ChangePreferences.rexx:
=====

/* */
options results

ADDRESS MEGAD
dbug TRUE

/* See
   ARexxPrefsList.txt
   for Subscript definitions and possible values */

/* Set PF_CONFIRM_QUIT (16) to TRUE (1) */

        SetFlag
        16 1

/* Set PF_TAB_WIDTH (9) to the value of 4 */

        SetNumber
        9 4

/* Set PF_CREATE_DIR_NAME (21) to "A_New_Directory_Name" */

        SetString
        21 "A_New_Directory_Name"

/* Set first device gadget (0) to Path of "'Ram Disk:T'" and
   set Title to "'Temp Dir'" */
```

```
SetDevice
0 "'Ram Disk:T'" "'Temp Dir'"'

/* free All ARexx Program Controls */
/* Commented out to prevent lost or your ARexx Program Controls */
/*
    freePC
    ARexx */
```

1.137 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

ARexxPrefsList.txt:

=====

```
/*
    SetString
    position values */

NOT_USED                                0
PF_SOURCE_ICON_NAME                      1
NOT_USED                                2
PF_FILTER_1                             3
PF_FILTER_2                             4
PF_FILTER_3                             5
PF_FILTER_4                             6
PF_FILTER_5                             7

PF_DIR_OUTPUT_NAME                      8
PF_EX_OUTPUT_NAME                      9

PF_PATTERN_1                           10
PF_PATTERN_2                           11
PF_PATTERN_3                           12
PF_PATTERN_4                           13
PF_PATTERN_5                           14

PF_FIND_1                               15
PF_FIND_2                               16
PF_FIND_3                               17
PF_FIND_4                               18
PF_FIND_5                               19

PF_FIND_FILENAME                        20

PF_CREATE_DIR_NAME                      21
PF_SEARCH_TEXT_NAME                     22
PF_SEARCH_TEXT_FILE                     23
PF_PACK_QUERY_NAME                      24
PF_DICTIONARY_NAME                     25
PF_PATH_FILENAME                        26

/* SPOOL ARexx commands */
PF_SP_QUIT                            27
```

```
PF_SP_ADDJOB                                28
PF_SP_ADDJOBDEL                             29
PF_SP_STOP_CURRENT                          30
PF_SP_STOP_ALL                             31
PF_SP_PORT_NAME                            32

/* Communicate to MDPrefs the current Save As filename */
PF_SAVE_PATH                                 33 /* will not work in ARexx */
PF_SAVE_FILE                                 34 /* will not work in ARexx */

/*
   SetFlag
   values */

/* FALSE = 0, TRUE = any non-zero value */
PF_ACTIVE_WINDOW_TO_FRONT                  0 /* TRUE or FALSE */
PF_AUTO_COLOR_SWITCH                      1 /* TRUE or FALSE */
PF_AUTO_RESIZE                            2 /* TRUE or FALSE */
PF_AUTO_UPDATE                           3 /* TRUE or FALSE */
PF_COL_GADGET_BACK                       4 /* Valid Pen Number */
PF_COL_BORDER1                           5 /* Valid Pen Number */
PF_COL_BORDER2                           6 /* Valid Pen Number */
PF_COL_GADGET_TEXT                       7 /* Valid Pen Number */
PF_COL_DIRECTORY                         8 /* Valid Pen Number */
PF_COL_FILE                              9 /* Valid Pen Number */
PF_COL_INFO                               10/* Valid Pen Number */
PF_COL_SELECTED                          11/* Valid Pen Number */
PF_COL_TEXT1                             12/* Valid Pen Number */
PF_COL_TEXT2                             13 /* Valid Pen Number */
PF_COL_TITLE                            14 /* Valid Pen Number */
PF_COL_UNSELECTED                        15 /* Valid Pen Number */
PF_CONFIRM_QUIT                          16 /* TRUE or FALSE */
PF_DATE_TYPE                            17 /* TRUE or FALSE */
PF_DECIMAL_IS_COMA                       18 /* TRUE or FALSE */
PF_ICONIZED_AT_START                     19 /* TRUE or FALSE */
PF_MESSAGES_OFF                          20 /* TRUE or FALSE */
PF_APP_ICON_ON_WORKBENCH                 21 /* TRUE or FALSE */
PF_PANIC_BUTTON                         22 /* TRUE or FALSE */
PF_SAVE_WIN_POSITIONS                   23 /* TRUE or FALSE */
PF_SAVE_AT_CLOSING                      24 /* TRUE or FALSE */
PF_WARN_IF_REPLACEING                   25 /* TRUE or FALSE */
PF_SCREEN_TYPE                           26

/* "Workbench Screen" = 0 */
/* "Hires" = 1 */
/* "Hires-Interlace" = 2 */
/* "SuperHires" = 3 */
/* "SuperHires-Lace"= 4 */

PF_SIMPLE_REFRESH_WINDOWS                27 /* TRUE or FALSE */
PF_THOUSAND_SEPARATOR                   28

/* "1,000,000" = 0 */
/* "1.000.000" = 1 */
/* "1 000 000" = 2 */
/* "1000000" = 3 */
```

```

PF_TODAY_YESTERDAY           29      /* TRUE or FALSE */
PF_TWELVE_HOUR_CLOCK         30      /* TRUE or FALSE */
PF_WARN_BEFORE_COPY          31      /* TRUE or FALSE */
PF_WARN_BEFORE_DELETE        32      /* TRUE or FALSE */
PF_WARN_BEFORE_MOVE          33      /* TRUE or FALSE */
PF_WARN_IF_DELETING_PROTECTED 34      /* TRUE or FALSE */
PF_WARN_IF_REPLACEING_LARGER   35      /* TRUE or FALSE */
PF_WARN_IF_REPLACEING_NEWER    36      /* TRUE or FALSE */

PF_DISPLAY_ORDER              37

/* "List directories first" = 0 */
/* "List files first" = 1 */
/* "List items mixed" = 2 */

PF_DISPLAY_PRI_NAME           38      /* 0 - 4 */
PF_DISPLAY_PRI_SIZE            39      /* 0 - 4 */
PF_DISPLAY_PRI_DATE            40      /* 0 - 4 */
PF_DISPLAY_PRI_PROTECTION      41      /* 0 - 4 */
PF_DISPLAY_PRI_COMMENT         42      /* 0 - 4 */

/* used from MegaD only flags */
PF_ICON_HIDE_COMMAND_GAD       43      /* TRUE or FALSE */
PF_ICON_HIDE_FILE_INFO         44      /* TRUE or FALSE */
PF_ICON_HIDE_DEV_GAD           45      /* TRUE or FALSE */
PF_GRID_DOWN                   46      /* 1 - 255 */
PF_GRID_ACROSS                  47      /* 1 - 255 */
PF_LIMIT_VOLUME                  48      /* 1 - 255 */
PF_LIMIT_WINDOWS                  49      /* 1 - 255 */
PF_DEST_CONTROL                  50      /* TRUE or FALSE */

/* system Filters */
PF_FILTER_OUT_1                 51      /* TRUE or FALSE */
PF_FILTER_OUT_2                 52      /* TRUE or FALSE */
PF_FILTER_OUT_3                 53      /* TRUE or FALSE */
PF_FILTER_OUT_4                 54      /* TRUE or FALSE */
PF_FILTER_OUT_5                 55      /* TRUE or FALSE */
PF_FILTER_ACTIVATE_1             56      /* TRUE or FALSE */
PF_FILTER_ACTIVATE_2             57      /* TRUE or FALSE */
PF_FILTER_ACTIVATE_3             58      /* TRUE or FALSE */
PF_FILTER_ACTIVATE_4             59      /* TRUE or FALSE */
PF_FILTER_ACTIVATE_5             60      /* TRUE or FALSE */

PF_FILTER_TYPE_1                  61
PF_FILTER_TYPE_2                  62
PF_FILTER_TYPE_3                  63
PF_FILTER_TYPE_4                  64
PF_FILTER_TYPE_5                  65

/* "Name" = 0 */
/* "Size" = 1 */
/* "Date" = 2 */
/* "Protect" = 3 */

/* export flags */
PF_EX_SEND_FILENAME               66      /* TRUE or FALSE */
PF_EX_SEND_VOLUMENAME              67      /* TRUE or FALSE */
PF_EX_SEND_PATHNAME                68      /* TRUE or FALSE */
PF_EX_SEND_TYPE                     69      /* TRUE or FALSE */

```

```
PF_EX_SEND_DATE          70      /* TRUE or FALSE */
PF_EX_SEND_SIZE          71      /* TRUE or FALSE */
PF_EX_SEND_BLOCKS         72      /* TRUE or FALSE */
PF_EX_SEND_PROTECTION     73      /* TRUE or FALSE */
PF_EX_SEND_COMMENT        74      /* TRUE or FALSE */
PF_EX_APPEND              75      /* TRUE = append */
PF_EX_SEND_FILE_DIR       76      /* 0 = send both, *
                                /* 1 = send files */
                                /* 2 = send directories */

PF_EX_FIELD_SEPARATOR     77      /* character value */
PF_EX_RECORD_SEPARATOR     78      /* character value */

PF_TWO_WINDOW_MODE        79      /* TRUE or FALSE */

/* system Patterns */
PF_PATTERN_OUT_1           80      /* TRUE or FALSE */
PF_PATTERN_OUT_2           81      /* TRUE or FALSE */
PF_PATTERN_OUT_3           82      /* TRUE or FALSE */
PF_PATTERN_OUT_4           83      /* TRUE or FALSE */
PF_PATTERN_OUT_5           84      /* TRUE or FALSE */
PF_PATTERN_ACTIVATE_1       85      /* TRUE or FALSE */
PF_PATTERN_ACTIVATE_2       86      /* TRUE or FALSE */
PF_PATTERN_ACTIVATE_3       87      /* TRUE or FALSE */
PF_PATTERN_ACTIVATE_4       88      /* TRUE or FALSE */
PF_PATTERN_ACTIVATE_5       89      /* TRUE or FALSE */
PF_PATTERN_TYPE_1           90
PF_PATTERN_TYPE_2           91
PF_PATTERN_TYPE_3           92
PF_PATTERN_TYPE_4           93
PF_PATTERN_TYPE_5           94

/* "Name" = 0 */
/* "Size" = 1 */
/* "Date" = 2 */
/* "Protect" = 3 */

/* system Finds */
PF_FIND_OUT_1                95      /* TRUE or FALSE */
PF_FIND_OUT_2                96      /* TRUE or FALSE */
PF_FIND_OUT_3                97      /* TRUE or FALSE */
PF_FIND_OUT_4                98      /* TRUE or FALSE */
PF_FIND_OUT_5                99      /* TRUE or FALSE */
PF_FIND_ACTIVATE_1            100     /* TRUE or FALSE */
PF_FIND_ACTIVATE_2            101     /* TRUE or FALSE */
PF_FIND_ACTIVATE_3            102     /* TRUE or FALSE */
PF_FIND_ACTIVATE_4            103     /* TRUE or FALSE */
PF_FIND_ACTIVATE_5            104     /* TRUE or FALSE */
PF_FIND_TYPE_1                 105
PF_FIND_TYPE_2                 106
PF_FIND_TYPE_3                 107
PF_FIND_TYPE_4                 108
PF_FIND_TYPE_5                 109

/* "Name" = 0 */
/* "Size" = 1 */
/* "Date" = 2 */
/* "Protect" = 3 */
```

PF_FIND_WHAT	110
/* "Find Directory & Files" = 0 */	
/* "Find Files only" = 1 */	
/* "Find Directories only" = 2 */	
PF_F10_CLOSE_CONTROL	111 /* TRUE or FALSE */
PF_SCREEN_DEPTH	112
/* "4 color screen" = 0 */,	
/* "8 color screen" = 1 */,	
/* "16 color screen" = 2 */	
PF_MAIN_CYCLE_CURRENT	113 /* cannot use in ARexx */
PF_USE_SYSTEM_ICON	114 /* TRUE or FALSE */
PF_RETURN_KEYPAD	115 /* TRUE or FALSE */
PF_WARN_IF_REPLACE_PREFS	116 /* TRUE or FALSE */
PF_DISPLAY_SOURCE_INFO	117 /* TRUE or FALSE */
PF_DISPLAY_MEMORY	118 /* TRUE or FALSE */
PF_DISPLAY_SELECTED	119 /* TRUE or FALSE */
 SetNumber values	
PF_CURRENT_MENU_SET	0
PF_LABEL_HEIGHT	1
PF_LABEL_WIDTH	2
PF_SCREEN_HEIGHT	3 /* not used */
PF_SCREEN_WIDTH	4 /* not used */
PF_ASL_LEFT	5 /* ASL Requestor */
PF_ASL_TOP	6 /* ASL Requestor */
PF_ASL_WIDTH	7 /* ASL Requestor */
PF_ASL_HEIGHT	8 /* ASL Requestor */
PF_TAB_WIDTH	9 /* 1 - 20 */
PF_WORD_WRAP_WIDTH	10 /* 0 or 20 - 999 */

1.138 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

```
DLPprint.rexx:
=====
/* Automate printing labels for each disk inserted into drive DF0: */

address REXX

options results

address MEGAD
```

```
        dbug
        do forever

        diskin
            if result == "ABORT" then leave
        "
        mark
        df0:"

        selectall

        NextItem
            Name /* will test for at lease one item on the disk to print ←
                  label for */
        if result ~= "" then
            label

            freeVolumes
        end
```

1.139 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

```
MarkDemo.rexx:
=====

/* Mark Demo
   This file demonstrates the uses of

      Mark
      '
      Dest
      '
      Lock
      '
      Child
      '
      Parent
      '

      SelectItem
      and
      UnSelectItem

      .
      .
      .
      Outside of this, this program is pretty much useless
*/
options results

ADDRESS MEGAD

        dbug
        TRUE

/* open window to the Ram Disk: and Mark it */
```

```
Mark
'ram:'

/* display actual name of opened directory */
SAY result
/* save name for later */
rootname = result
/* User select the Marked directory's 'Dest'ination gadget */

Dest
TRUE

/* Select the Marked directory's 'Lock' gadget */

Lock
TRUE
/* move to the subdirectory */

child
t
/* display actual name */
say result
/* save name for later */
childname = result
/* Mark the child directory */

mark
""result"""

/* User select the Marked directory's 'Dest'ination gadget */

Dest
TRUE

/* Select the Marked directory's 'Lock' gadget */

Lock
TRUE
/* Move to the parent directory */

parent
/* display actual name */
say result
/* Mark the Parent directory */

mark
""result"""

/* Flash the T directory 40 times */
DO 40

SelectItem
t

UnSelectItem
t

END

mark
""childname"""

/* close the child */
```

```
        CloseMark

        mark
        /* "rootname" */

/* close the parent */

        CloseMark
```

1.140 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

```
MDARexxStart.rexx:
=====

/* MegaD will look for the MDARexxStart.rexx file in its home directory
when it is first run. If it is found it will be executed.

This ARexx program will clear all of the internal strings to NULL.
*/
ADDRESS REXX

OPTION RESULT

ADDRESS MEGAD

        dbug
        TRUE

/* Send output to a console window on the MegaD Screen */
call close 'STDOUT'
call open 'STDOUT', 'con:0/12/640/100/MegaD RX/SCREEN MEGAD', 'W'

subscript = 0
DO 40
    SAY 'Clearing string 'subscript' to NULL'

        SetString
        subscript NULL
subscript = subscript + 1
END
```

1.141 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

```
NextItem.rexx:
=====

/* example of NextItem */

ADDRESS REXX
```

```
CALL CLOSE 'STDOUT'
CALL OPEN 'STDOUT','con:0/12/640/100/MegaD RX/SCREEN MEGAD', 'W'

OPTIONS RESULTS
OPTIONS FAILAT 20
SIGNAL ON FAILURE

ADDRESS MEGAD

        dbug

        CloseWindows
        /* close any open windows */

        Mark
        "Ram:"    /* open the ram disk */

SAY RESULT

        SelectAll
        /* select everything */

DO FOREVER

        NextItem
        Name
IF RESULT = "" THEN LEAVE
SAY RESULT

        NextItem
        Filename
SAY RESULT

        NextItem
        Path
SAY RESULT

        NextItem
        Size
SAY RESULT

        NextItem
        Date
SAY RESULT

        NextItem
        Comment
IF RESULT ~= "" THEN SAY RESULT

        NextItem
        Type clear /* Clear the item */

SAY RESULT
END
EXIT

failure:
IF RC ~= 0 THEN SAY "Script Failed, RC = " RC
EXIT
```

1.142 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

```
OpenSE.rexx:  
=====/* Open file from Arguments */  
/* this is an example of how to modify '  
Parse.rexx  
'  
to perform a more useful task, it will open files to the SAS/C editor.  
I call this from an ARexx Program Control. The Program Control has the  
following items checked.  
  
Skip selected directories  
Work without selected items  
Skip .info files  
Combine all selected on one line  
Workbench screen to front at start  
  
*/  
  
IF ~SHOW("L","rexxsupport.library") THEN CALL ADDLIB"rexxsupport.library",0,-30  
OPTIONS RESULTS  
  
/*********************************************/  
/* set specific for the program that we will use this script with */  
/********************************************/  
open_command = 'OW'  
port_name = 'SC_SE'  
program_name = '"SC:C/SE"'  
  
arguments = ARG(1)  
/* if no arguments were sent test for the port and if it is  
not available run the program without an argument */  
if arguments = "" then do  
  if ~show("P",port_name) then do  
    ADDRESS COMMAND 'run' || program_name  
    END  
  EXIT  
END  
DO WHILE arguments ~= ""  
/* test for quote at first of name */  
/* if it starts with a Quote it ends with a Quote */  
delim = " " /* default to space as a delimiter */  
IF LEFT(arguments,1) = '"' THEN delim = '''  
ELSE arguments = " " || arguments /* add space to front */  
PARSE VAR arguments (delim) filename (delim) arguments  
filename = STRIP(filename)  
arguments = STRIP(arguments,L)  
if ~show("P",port_name) then do  
  ADDRESS COMMAND 'run' || program_name || ' ' || filename  
  ADDRESS COMMAND 'WaitForPort' || port_name  
  END
```

```
else do
  ADDRESS (port_name)
  open_command filename || d2c(13) /* return character require for SE */
  END
END
```

1.143 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

```
Parse.rexx:
=====
/* parse command line */
/* To use this with MegaD, add an ARexx Program Control that will call this
   Drag select a few files in an open directory window, select a ARexx button
   that will call this script.

It will display each selected item in the console window that will open.
The program has little value except for demonstrating how to parse
information sent from MegaD. See
  OpenSE.rexx
  for
another example.
*/
/* open output to MegaD screen */
CALL CLOSE 'STDOUT'
CALL OPEN 'STDOUT','con:0/12/640/100/MegaD RX/SCREEN MEGAD', 'W'

arguments = ARG(1)
/* test for quote at first of name */
DO WHILE arguments ~= ""

  /* if it starts with a Quote it ends with a Quote */
  delim = " " /* default to space as a delimiter */
  IF LEFT(arguments,1) = '"' THEN delim = ''
  ELSE arguments = " " || arguments /* add space to front */
  PARSE VAR arguments (delim) filename (delim) arguments
  filename = STRIP(filename)
  arguments = STRIP(arguments,L)
  SAY filename
END

value = Delay(5 * 50) /* Five second delay to see window on MegaD screen */
```

1.144 MegaD 3.1 ARexx Commands Copyright © 1993 John L. Jones

```
RenameOther.Rexx:
=====
/* example of Rename */
```

```
/*
This program will rename every other item in a selected directory
to the same name with an underscore at the front. If you want to
test this out use the AReXX program MakeLikeFiles.rexx, it will create
a number of files in the T: directory with the name likeFile1, likeFile2...
```

```
A user wanted a quick way to rename a number of animation frames so that he
could use every other file, and so, this program was written.
```

```
*/
ADDRESS REXX
```

```
OPTIONS RESULTS
OPTIONS FAILAT 20
SIGNAL ON FAILURE
```

```
ADDRESS MEGAD
```

```
        dbug
/* First, we need to make sure that the items are sorted by Name ←
 */
"
```

```
        MenuCheck
        'show,sort on,name' Check"
```

```
directory = ARG(1)
```

```
if directory = '' then exit
```

```
*****
```

```
The directory argument can be sent in one of two ways
```

```
Selected Directory in MegaD window
```

```
AReXX Gadget Program Control should have only the below two items checked
```

```
    Skip selected files
    Skip .info files
```

```
and the Path and Program name should be the correct path to this script.
```

```
This will require the user to select at least one directory to rename
every other file to have an underscore in front of it.
```

```
User Input required
```

```
AReXX Gadget Program Control should have only the below five items checked
```

```
    Skip select4d directories
    Skip selected files
    work without selected items
    skip .info files
    Query for 'Flags to add'
```

```
and the Path and Program name should be the correct path to this script.
```

```
This method will require a valid Path to the correct directory to
be typed by the user.
```

```
*****
```

```
        CloseWindows
        /* close any open windows */
```

```
        Mark
        directory /* open the ram disk */
```

```
IF RESULT = '' then exit
```

```
        SelectAll
        /* select everything */
```

```
/* disable directory sorting or we will be rename files renamed once before */
"
    MenuCheck
    'show,sort on,none' Check"

DO FOREVER

    NextItem
    Filename
if result = "" then leave
ELSE DO
    name = '_' || result

    Rename
    name /* Rename will unselect the first selected item */
END
/* skip the next selected item */

    NextItem
    Filename clear /* unselect the next item too */
IF RESULT = "" then leave
END

/* re-enable the sorting on Name */
"
    MenuCheck
    'show,sort on,name' Check"
/* force and update of the window */
"
    Menu
    'show,Reset All'"

exit

failure:
if RC ~= 0 then say "Script Failed, RC = " RC
exit
```