

PGL.HEL

Copyright © 1995 Soft-Logik Publishing Corporation

COLLABORATORS

| | | | |
|---------------|---------------------------|-----------------|------------------|
| | <i>TITLE :</i> PGL.HEL | | |
| <i>ACTION</i> | <i>NAME</i> | <i>DATE</i> | <i>SIGNATURE</i> |
| WRITTEN BY | | August 23, 2022 | |

REVISION HISTORY

| NUMBER | DATE | DESCRIPTION | NAME |
|--------|------|-------------|------|
| | | | |

Contents

| | | |
|----------|--|----------|
| 1 | PGL.HEL | 1 |
| 1.1 | PAGELINER2 HELP SYSTEM ©1995 Soft-Logik Publishing Corp. | 1 |
| 1.2 | PageLiner Startup Options | 1 |

Chapter 1

PGL.HEL

1.1 PAGELINER2 HELP SYSTEM ©1995 Soft-Logik Publishing Corp.

PAGELINER2 HELP SYSTEM

Menus & Menus

Macros Macro Command Index

Topics System Requirements to use PageLiner2

Startup Options

How to Contact Soft-Logik Publishing
Information on other Soft-Logik products

License, Copyrights, Trademarks & Credits

©1995 Soft-Logik Publishing Corporation

PageStream, BME, PageLiner, Art Expression and TypeSmith are trademarks or registered trademarks of Soft-Logik Publishing Corporation.

1.2 PageLiner Startup Options

PageLiner Startup Options

If the PageLiner.prefs file exists in the same directory as PageLiner, startup options entered in the file will be used when PageLiner is started.

A PageLiner preferences file should start with:

```
;PageLiner Preferences File
```

The syntax of all options is COMMAND=data. The case is irrelevant. The commands which can be used are:

PORTNAME=name the ARexx port name. (Default=PAGELINER)

| | |
|----------------|---|
| | ie: PORTNAME=PLPORT |
| FILES=path | the default path used in the file requester ie: FILES=Work:Text |
| SPACE=char | the character displayed for a space for Show Invisibles ie: SPACE=? |
| SHOWINV=yes no | the default Show Invisibles setting ie: SHOWINV=no |
| LF=char | the character displayed for a line feed for Show Invisibles ie: LF=¶ |
| TAB=char | the character displayed for a tab for Show Invisibles ie: TAB=» |
| MARGIN=o,i | the margins: o=outside, i=inside or AUTO or SET ie: MARGIN=5,AUTO |
| PAPER=pen | the paper color ie: PAPER=2 |
| EDGE=pen | the edge color ie: EDGE=3 |
| TEXT=pen | the text color ie: TEXT=1 |
| HILITE=pen | the highlight text color ie: HILITE=3 |
| WINDOW=l,t,w,h | the default window position: l=left edge, t=top edge, w=width, h=height ie: WINDOW=-1,-1,640,389 |
| FLASH=x | the interval between cursor flashes 0=no flash ie: FLASH=3 |
| TABSPACES=x | the number of spaces to show per tab ie: TABSPACES=8 |
| CURSORWIDTH=x | the width of the cursor in pixels ie: CURSORWIDTH=2 |
| PUBSCREEN=name | the name of the existing public screen to open on (screen names are case sensitive) ie: PUBSCREEN=PAGESTREAM3 |
| SPELLPATH=path | the directory containing the dictionary files ie: SPELLPATH=softlogik:Engines |
| FONT=name,size | the name and of the display font ie: FONT=topaz.font,11 |
| STARTUP=script | the name of the ARexx script to run at startup ie: STARTUP=PageStream3:Macros/PLstartup.rexx |

PARENTWIN=1,t the left and top position of the title bar
 ie: PARENTWIN=0,11

F1-F10=action,string the action and text for a function key (action=AREXX|
 TEXT)
 ie: F1=AREXX;PageStream3:macros/PLcmdshell.rexx
 ie: F6=TEXT;desktop publishing

SETTINGS=file the name of the preferences file to load (when
 starting PageLiner from a shell)
 ie: SETTINGS=PageStream3:PageLiner.prefs

The following is an example of a common preferences file:

```
;PageLiner Preferences File
FONT=topaz.font,8
FILES=Text:
PAPER=2
TEXT=1
EDGE=3
HILITE=3
SPELLPATH=softlogik:Engines
FLASH=3
CURSORWIDTH=2
TABSPACES=8
SHOWINV=NO
MARGIN=5,AUTO
SPACE=?
LF=¶
TAB=»
WINDOW=-1,-1,640,389
PARENTWIN=0,0
PORTNAME=PAGELINER
F1=AREXX;PageStream3:macros/PLcmdshell.rexx
F2=AREXX;PageStream3:macros/PLdate.rexx
F3=AREXX;PageStream3:macros/PLmath.rexx
F4=AREXX;PageStream3:macros/PLtime.rexx
F5=TEXT;PageLiner
F6=TEXT;desktop publishing
F7=TEXT;<N>
F8=TEXT;<B>
F9=TEXT;<I>
F10=AREXX;pgsm:test.rexx
PUBSCREEN=PageStream3
```