

# **Localizer**

Massimiliano Origi Scholling

Copyright © (c)1996-98 Massimiliano Origi, 1999-2001 Carsten Scholling. All Rights Reserved.

**COLLABORATORS**

	<i>TITLE :</i> Localizer		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY	Massimiliano Origi Scholling	January 13, 2023	

**REVISION HISTORY**

NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1 Localizer</b>	<b>1</b>
1.1 Localizer Guide	1
1.2 Introduction	2
1.3 System Requirements	3
1.4 Installation	3
1.5 Main Window	3
1.6 Info Window	3
1.7 Edit Project	3
1.8 Load Project	4
1.9 Save Project	5
1.10 Scan Sources	5
1.11 Edit Strings	5
1.12 Translate Strings	7
1.13 Search Window	10
1.14 Preview Window	10
1.15 History	11
1.16 Credits	13
1.17 Legal stuff	13
1.18 Author info	14
1.19 Supported Escape Sequences	14
1.20 Supported keys for the string gadget	15
1.21 Index	16

---

# Chapter 1

## Localizer

### 1.1 Localizer Guide

Localizer 1.39

The Locale Development Tool.

Copyright ©1996-98 Massimiliano Origgi.

Copyright ©1999-2001 Carsten Scholling.

All Rights Reserved.

Massimiliano stopped the Localizer project in 1998. I have taken over the project in 2000. Now, in 2001, i finally have the time to do some bug fixes.

```
~Introduction~~~~~  
  What is it?  
  
~System~Requirements~  
  What you need  
  
~Installation~~~~~  
  Where do I put it?  
  
~Main~Window~~~~~  
  The Main Window  
  
~Info~Window~~~~~  
  The Information Window  
  
~Edit~Project~~~~~  
  Edit Project Settings  
  
~Load~Project~~~~~  
  Load New Project  
  
~Save~Project~~~~~  
  Save Current Project
```

---

```
~Scan~Sources~~~~~  
    Scan Source Code  
  
~Edit~Strings~~~~~  
    Edit CD Files  
  
~Translate~Strings~~~  
    Edit CT Files  
  
~Search~Window~~~~~  
    The search engine  
  
~Preview~Window~~~~~  
    Quickly preview your strings  
  
~History~~~~~  
    A look into the past  
  
~Credits~~~~~  
    I wish to thank...  
  
~Legal~stuff~~~~~  
    Boring but necessary  
  
~Author~Info~~~~~  
    How to reach me  
  
~Escape~sequences~~~~~  
    Supported escape sequences  
  
~String hotkeys ~~~~  
    Supported keys for the string gadget
```

## 1.2 Introduction

Localizer has been created to help both programmers and translators.

Here is a brief list of what Localizer can do:

- scans source files, extracts locale IDs and builds a .cd file;
- merges old and new .cd and .ct files and hilights differences for fast ↔ editing;
- builds C source files to handle locale stuff;
- can add comments to each .cd ID, useful for translators;
- builds .catalog files;
- fast load/save of projects;
- bubble help for each gadget;
- quickly moves among new/changed entries for fast update of .cd and .ct files ↔  
;
- and even more...

## 1.3 System Requirements

Localizer needs:

- A 68020 or better
- AmigaOS 3.0 or better
- MUI 3.8 or better

## 1.4 Installation

Installing Localizer is really easy: just launch the supplied installer script!  
If you don't want to use the script you can just copy the Localizer drawer ↔  
wherever  
you want and copy the files in the libs drawer to the MUI:libs/mui/ one.

## 1.5 Main Window

This is the main window of Localizer, you can access all functions from here.

Localizer does not use any menu.

All gadgets have an associated bubble help with a brief description of their use.  
All time consuming operations will be noticed with the usual busy pointer.

The window title bar will show the name of the currently loaded project or "---" ↔  
if no  
project is currently loaded or the project has no name.

## 1.6 Info Window

This window displays copyright notes about Localizer and MUI and  
my~addresses  
.

## 1.7 Edit Project

Here you can edit all the necessary options to work with Localizer .

Project name.

This name will be used as a prefix for .cd, .ct and .catalog files.

For example if you write 'test', Localizer will read and write test.cd,  
test.ct, ~test.catalog.

Scanner.

From version 1.24 Localizer offers 2 different source scanners.

The ID scanner is the same of the previous Localizer version; it scans the source ↔  
code

to look for strings starting with the characters specified in the string gadget ↔  
besides

---

the scanner cycle gadget.

Remember: ALL AND ONLY the locale IDs MUST use this prefix.

For example if you write 'MSG\_', Localizer will get strings like MSG\_OK,~MSG\_GADGET\_CONTINUE, etc.

The Func scanner, instead, will look for fake functions whose name is specified in the above mentioned string gadget.

If you specify 'STRING' as the fake function name, the scanner will look at functions

with this syntax: STRING(<locale ID>,<default string>).

So you can have functions like: STRING(MSG\_OK,"OK").

Thanks to this syntax Localizer can completely build the .cd file from your source

code, both the IDs and the default strings! You don't have to write the strings by hand

in the .cd file anymore, everything is inside your source, saving a lot of time and

boring work!

Locale source dir.

In this directory Localizer will save the C source code it generates.

Localizer generates source code for both type of scanners.

Source files.

Here you can specify the source file Localizer will scan.

The list supports multiselection and you can sort the entries with drag & drop.

The Add button opens a standard asl requester where you can select one or more source~files.

The Del button removes all selected files from the list.

The Clear button will remove all files from the list.

Catalogs dir.

This is the directory which contains all the .cd, .ct and .catalog files in the~standard locale structure.

That is, if you write 'RAM:' and the project name is 'test', Localizer will search,~for example, RAM:test.cd, RAM:italiano/test.ct or RAM:italiano/test.~catalog.

The catalogs directory contains the .cd file and the directories named after their~language. These directories contain the .ct and .catalog files.

## 1.8 Load Project

Here you can load a new project.

The list displays all the currently available projects.

You can select a project in the list or write its name in the string gadget below

Press OK to load the project or Cancel to abort the operation.

From Localizer 1.24 there is also a Del gadget besides the string gadget. It will be

enabled only when the string gadget contains the name of an existing project file

The close window gadget acts just like the Cancel button.



## 1.9 Save Project

Here you can save the project you are currently working on. The list displays all the currently available projects. You can select a project in the list or write its name in the string gadget below ↔

If a project with the selected name already exists, it will be overwritten. From Localizer 1.24 there is also a Del gadget besides the string gadget. It will ↔ be enabled only when the string gadget contains the name of an existing project file ↔

Press OK to save the project or Cancel to abort the operation. The close window gadget acts just like the Cancel button.

## 1.10 Scan Sources

As soon as you press the Scan Sources button in the main window, ↔ Localizer will start scanning your source files. A small window will display the status of the operation: number of scanned files and total number of files. You can't currently abort this operation, sorry. The scanner function generates a file with the .newcd extension in your catalogs directory. This file will be read when you use the EditStrings function.

## 1.11 Edit Strings

Here you can finally edit your .cd file. Localizer will look at both a .newcd file and a .cd file. If only a .newcd file exists, it will load it and sort entries alphabetically. If only a .cd file exists, it will simply load it. If both a .newcd and a .cd file exist, it will merge them, unless the .newcd file ↔ has the archive bit set. If an entry is present only in the .newcd file, it will be marked as NEW. If an entry is present only in the .cd file, it will be removed. If an entry is present in both files, it will be marked as OK.

Author.  
Enter here the author name.

Language.  
Select the language for this .cd file.  
Either enter it in the string gadget or select one from the popup list.

Version.  
Enter the version number of this .cd file.

IDs list.  
This list displays all available IDs.

---

It's divided in 4 columns: they contain the ID name, the id~number,~the~status of ←  
~  
this~ID(see below) and the text of this ID.

There are 4 possible status codes:

- New (the ID has just~been~added~after~the~last~scan),
- Updated (the entry was updated/changed in this session)
- Empty (no text),
- OK (self explanatory :-).

You can change the size of the columns by clicking on the vertical separator bar which divides the columns in the list title bar and moving the mouse.

Or you can change their order by clicking on the column title and moving the ←  
mouse.

You can also drag sort the entries.

In all cases(add, delete, copy or sort) the ID numbers will be correclty updated ←  
to

avoid errors suh s two entries with the same ID value.

ID String.

You can change the ID name here.

Add.

Adds a new id before the currently selected entry.

Del.

Deletes the currently selected entry.

Copy.

Makes a copy of the currently selected entry.

Text String.

In this text editor you can enter the text of the currently selected ID.

When this gadget is active, yuo can move through the entries of~the~list~with~the ←  
~~

left amiga + cursor up or down keys.

You can enter

escape~sequences  
here.

Min Lenght.

Here you can select the min lenght that the~translated~text(in~the~corresponding~  
.ct~file) must have.

You can enable and disable this option with the checkbox gadget on the left.

Max Lenght.

Here you can select the max lenght that the~translated~text(in~the~corresponding~  
.ct~file) must have.

You can enable and disable this option with the checkbox gadget on the left.

ID Value.

Here you can choose the numeric value associated with this ID.

If the checkbox is disabled a default value will be chosen by Localizer.

Next.

When you press this gadget Localizer will jump to the next New or Empty entry if ←  
any,

---

unless the current entry is still New or Empty.

Prev.

When you press this gadget Localizer will jump to the Previous New or Empty entry ←  
if  
any, unless the current entry is still New or Empty.

Search.

When you press this gadget Localizer will open the  
search~window  
.

Preview.

When you press this gadget Localizer will open the  
preview~window  
(if not already  
open) and display a preview of the current entry.

Comment String.

Here you can enter a comment string for the current ID. It's useful when~you~ ←  
have~to~ ←  
send the .cd file to traslators.

Save CD.

It saves the .cd file over the old one. If a .newcd file exists, it will set its  
archive bit, so it won't be loaded again next time.  
When you're using the function scan mode and have updated entries, Localizer asks ←  
you if he should  
change the contents of the dummy functions in the source files to reflect the ←  
current string value  
you've given. Answer "no" to leave the sources untouched.

Build Source.

It generates 2 C source files to handle the .cd file: Locale.c and Locale.h.  
They will be saved in the source dir you have selected in the  
Edit~Project~window  
or you can change both the path and file name in the file ←  
requester Localizer will  
display before generating the files.  
There are 3 functions to open the catalog, close it and get a string.

Cancel.

Just cancels all changes and closes the window.  
The close gadget does the same function.  
If any string has been modified, it will put up a requester asking for ←  
confirmation  
before closing the window.

## 1.12 Translate Strings

Here you can select the language of the .ct file you want to edit ←  
or create.

Select Language window.

The list displays the languages a .ct file exists for.  
You can select a language in the list, type its name in the string gadget~or~ ↔  
select~  
it~from the popup list.  
If you press Cancel or the close window button, the operation is cancelled.  
If you press OK, the Translate window opens.  
It's not too much different from the Edit Strings window.

Translate strings window.

Localizer will look at both a .cd file and a .ct file.  
If only a .cd file exists, it will simply load it.  
If only a .ct file exists, it will simply load it, if the .ct file has not been  
generated by Localizer, it won't contain enough information to make it usable, so ↔  
you  
really need the .cd file. If, instead, the .ct file has been generated by ↔  
Localizer you  
won't need the .cd file anymore, because the .ct file contains all necessary  
informations.  
If both a .cd and a .cd file exist, it will merge them, unless the .cd file has ↔  
the  
archive bit set.  
If an entry is present only in the .cd file, it will be marked as NEW.  
If an entry is present only in the .ct file, it will be removed.  
If an entry is present in both files, it will be marked as OK if the default ↔  
string is  
the same in both files, as Changed if it is different.

Author.

Enter here the author name. it will be saved in the .catalog file.

Language.

Displays the language of this .ct file.

Version.

Enter the version and revision number of this .ct file.

IDs list.

This list displays all available IDs.

It's divided in 4 columns: they contain the ID name,~the~id~number,~the~status~  
of~this~ID(see below) and the ttranslated text of this ID.

There are 5 possible status codes:

- new (the ID~has~just~been~added~after~the~last~scan),
- Empty (no text),
- Changed (the original text in~the~.cd~file~has ben changed),
- WrongSize (the string lenght is not within the min/max values),
- OK (self explanatory :-).

You can change the size of the columns by clicking on the vertical separator bar  
which divides the columns in the list title bar and moving the mouse.

Or you can change their order by clicking on the column title and moving the ↔  
mouse.

Text String.

In the list below the original text of this ID is displayed. You can mark ↔  
portions

---

of text with the mouse and they will be copied to the clipboard automatically.

Translation String.

In the text editor below you can enter the translation for the current ID.

When this gadget is active, you can move through the entries of the list with the ← →  
~~

left amiga + cursor up or down keys.

You can enter

escape~sequences  
here.

Min Size.

Min size allowed for current entry.

Current Size.

Current size of selected entry.

Max Size.

Max size allowed for current entry.

Next.

Goes to the next New, Changed, Empty or WrongSize entry if any, unless the ← →  
current  
entry is not OK.

Prev.

Goes to the previous New, Changed, Empty or WrongSize entry if any, unless the ← →  
current  
entry is not OK.

Search.

When you press this gadget Localizer will open the  
search~window  
.

Preview.

When you press this gadget Localizer will open the  
preview~window  
(if not already open)  
and display a preview of the current entry.

Comment String.

Displays the comment for the current ID.

Save CT.

It saves the .ct file over the old one. If the .cd file exists, it will set its  
archive bit, so it won't be loaded again next time.

Build Catalog.

It generates the .catalog file.

If one or more entries status is not OK, a requester will popup asking if you ← →  
want to  
generate the .catalog file anyway.

If one or more entries are empty another requester will popup asking if you want ← →  
to  
generate these empty entries anyway or if you want to skip them. this is ← →  
particularly

---

useful for catalog translators, because they can partially translate the .cd file ←  
and  
see the original string and not an empty one for the not yet translated strings. ←  
This  
is possible because the AmigaOS locale system simply returns the default string ←  
to  
the application if it can't find the corresponding translated string in the . ←  
catalog  
file.

Cancel.

Just cancels all changes and closes the window.

The close gadget does the same function.

If any string has been modified, it will put up a requester asking for ←  
confirmation

before closing the window.

## 1.13 Search Window

The search window is available both when you edit cd and ct files and it's fully asynchronous.

The search window in ct mode will offer you a cycle gadget at the top, so you can decide if you want to perform the search among the original strings or the ←  
translated  
ones.

In the string gadget you can enter the string you want to search; the search ←  
engine  
fully supports ALL standard AmigaOS wildcards (just like AmigaDOS programs).  
Due to this usefull feature, if you want to search a substring inside your ones, ←  
you  
have to surround it with the '#?' sequence. For example to search for 'prog' you ←  
have  
to type '#?prog#?'.  
With the case cycle gadget you can perform a case sensitive or insensitive search ←

.  
The 3 bottom gadgets finally perform the search operation:  
the 'All' button searches from the first string in the list;  
the 'Next' button searches forward from the currently selected entry in the list;  
the 'Prev' button searches backward from the currently selected entry in the list ←  
.

You can close and reopen the window at any time and it will preserve its contents ←  
.

## 1.14 Preview Window

The preview window is available both when you edit cd and ct files and it's fully asynchronous.

The preview window in ct mode will offer you a cycle gadget at the top, so you ←  
can

---

decide if you want to preview the original strings or the translated ones. You ↔  
can so  
quickly switch between a preview of the original string and of its translation ↔  
with a  
simple click on this button!

The text area below will display the parsed string(as saved in the catalog file) ↔  
of  
the currently selected entry.

## 1.15 History

### Version 1.41

- project ported to storm gcc
- increase the maximum size of one catalog sting from 8192 bytes to 81920 ↔  
bytes

### Version 1.40

- some bugfixes of Carsten for Tales of Tamar

### Version 1.39

- Reworked source scanning code. No more empty strings or Enforcer/CyberGuard hits while scanning
- Now the date is written correctly to the CD/CT files
- Added Updated-Flag to CD entries
- Added automatic changing of source code when using func definitions and changing the original strings inside Localizer
- Added some more languages
- Added some nice and worthless menus

### Version 1.38

- fixed an evil bug in the ct loading code, which could corrupt the ID numbers ↔  
;
- changed the shortcut keys in the cd and ct windows;
- added 2 new shortcut keys which perform the same action of the next and prev gadgets;
- now the cd and ct gadgets in the main window will always be ghosted when no newcd or cd file is available, thus avoiding possible dead locks fi they are pressed and no file exists.

### Version 1.37

- the author string gadget is bigger, 120 characters;
- the preview window in both the cd and ct windows is updated automatically ↔  
when  
you edit the text;
- sped up opening of both the cd and ct windows;
- performed various code optimizations and cleanups.

### Version 1.36

- the ID string gadget is now wider;
- avoids merging .newcd and .cd files or .cd and .ct files when not necessary;
- added installer script.

### Version 1.35beta (public beta)

---

- fixed a couple of lame bugs in the cd window which could cause enforcer hits ←  
and  
general slow down while editing;
- now uses the BetterString class by Allan Odgaard instead of the old plain ←  
string  
gadget;
- now you can't make the min lenght of the string bigger than max lenght or  
viceversa any more;
- now you can add, delete, copy and drag sort entries in the edit cd window;
- when generating the catalog file, it asks if you want to skip empty entries ←  
in  
the ct file. This is useful to test partially translated ct files, because ←  
you  
won't get empty text for the untraslated entries, but the default strings.

#### Version 1.34beta (public beta)

- opening of the cd and ct edit windows is now faster;
- now uses TextEditor class by Allan Odgaard for editing strings;
- you can now change the active entry in both the cd and ct edit windows with ←  
the  
left Amiga + cursor up/down keys.

#### Version 1.33beta (public beta)

- now uses the NList classes by Gilles Masson.

#### Version 1.32beta (public beta)

- fixed a couple of bugs in the function scanner;
- changed the shortcut key for the search function, due to conflict with ←  
another  
key;
- changed 'string' in 'pattern' in the search window;
- now checks when no text is in the pattern string gadget;
- now the scan function reports an error when it can't find anything in the  
source files.

#### Version 1.31

- Now if you save the cd or ct file after modifying it and then close the ←  
window,  
Localizer won't put up the 'strings have been modified' requester anymore.
- Fixed conversion of exadecimal escape sequences(\xHH) in both the preview ←  
window  
and the catalog generator.

#### Version 1.30

- Now saves comment lines in .cd and .ct files only when present.
- Fixed a bug when loading comments from .cd and .ct files.
- Puts up a requester before closing the .cd or .ct edit windows if the ←  
strings  
have been modified.
- Checks the format of the version string before generating a .catalog file.
- NEW home page!

#### Version 1.29

- Added context sensitive AmigaGuide help.
- Performs some optimizations on the generated catalog files, they will be a ←  
bit  
smaller often.



- Faster cd and ct loading in most cases.
- Added search window.
- Added preview window.

Version 1.25 to 1.28

- Internal versions

Version 1.24

- Removed a couple of bugs which caused a lot of generated .catalog files to be unreadable.
- New layout of the main window.
- The project name is now displayed in the main window title bar.
- Cycle chain now works in the edit ct window.
- Revised some parts of this doc.
- No more problems when saving .ct files.
- Revised several parts of the program.
- Does not quit anymore when the iconify gadget gets pressed.
- Added cancel button in the Edit Project window.
- Handles correctly strings starting with the '#' or ';' characters.
- Added del button in the load/save windows.
- Removed a couple of bugs in the cd and ct parsers.
- Added several error requesters.
- Added a new source scanner.
- You can now generate source code or the .catalog file even if not all ↔ entries are ok.

Version 1.1 to 1.23

- Internal versions

Version 1.0

- First release

## 1.16 Credits

I want to thank:

Ole Friis, Paolo Menichetti, Laurent Kempè for their ideas and for beta ↔ testing.  
Krister Larsson, Peter Eriksson and Rune Jacobsen for bug reports.  
Oliver Wagner for his interesting suggestions.  
Stefan Stuntz for his great MUI package.  
Dietmar Eilert for Golded.  
Gilles Masson for the NList classes.  
Allan Odgaard for the BetterString and TextEditor classes.

And all the ones I forgot to mention!

## 1.17 Legal stuff

Localizer is Copyright (c)1996-98 Massimiliano Origgi, (c)1999-2001 Carsten Scholling and it has changed from Giftware to Freeware because i do

---

not want gifts for Massimilanos hard work.

You can freely distribute it as long as all of its files are included in their original form without additions, deletions or modifications of any kind, and only a nominal fee is charged for its distribution to cover media and expedition costs. This software is provided as is without warranty of any kind either expressed or implied. By using Localizer you agree to accept the entire risk as to the quality and performance of the program.

Of course it was extensively tested before it was released...

I hope you'll enjoy it and find it useful!

## 1.18 Author info

Send comments, bug reports, complaints and ideas to:

cs@aphaso.de (Carsten Scholling)

Watch my home page for bug fixes and updates at:

<http://www.aphaso.de>

## 1.19 Supported Escape Sequences

Both catalog description and catalog translation strings can contain the following escape sequences:

<code>\b</code>	Backspace (Ascii 8)
<code>\c</code>	Control Sequence Introducer (Ascii 155)
<code>\e</code>	Escape (Ascii 27)
<code>\f</code>	Form Feed (Ascii 12)
<code>\g</code>	Display beep (Ascii 7)
<code>\n</code>	Line Feed, newline (Ascii 10)
<code>\r</code>	Carriage Return (Ascii 13)

---

```

\t
    Tab (Ascii 9)

\v
    Vertical tab (Ascii 11)

\
    The backslash itself

\xHH
    A character expressed in hex digits.

\000
    A character expressed in octal digits.

```

## 1.20 Supported keys for the string gadget

These are the keys currently supported by the BetterString gadget used by Localizer:

```

Amiga + c    = Copy, either what is selected or the complete string.
Amiga + x    = Cut, either what is selected or the complete string.
Amiga + v    = Paste from clipboard.
Amiga + z    = Undo until the last deletion (only one level)
Amiga + Z    = Redo the last undo.
Amiga + q    = Revert to original string, press it again to go back to the ←
               modified
               string.
Amiga + g    = Toggle case on current character.
Amiga + G    = Toggle case from cursor to start of next word.
Amiga + i    = Increase the nearest number.
Amiga + d    = Decrease the nearest number.
Amiga + #    = Convert current hexadecimal number to decimal.
Amiga + $    = Convert nearest number to hexadecimal.
Amiga + Tab  = Complete the current volume, assign or paths name.
               You can step thru the various matches by pressing Amiga+Tab again ←
               .
               Use Amiga+Shift+Tab to go backwards.

Ctrl + left  = Start of line.
Ctrl + right = End of line.
Alt  + left  = Start of next word.
Alt  + right = Start of current or previous word.

Delete      = Delete the marked block, or current character.
Backspace   = Delete the marked block, or the character to the left.
Ctrl + Delete = Delete to start of line.
Ctrl + Backspace = Delete to end of line.
Alt  + Delete  = Delete to start of next word.
Alt  + Backspace = Delete to start of current or previous word.

```

## 1.21 Index

Index of Localizer Guide

Load~Project

Author~info

Credits

Edit~Project

Edit~Strings

Escape~Sequences

History

Info~Window

Introduction

Legal~stuff~and~Author~info

Localizer~Guide

Main~Window

Preview~Window

Save~Project

Scan~Sources

Search~Window

String hotkeys

System~Requirements

Translate~Strings

---