

Date

COLLABORATORS

	<i>TITLE :</i>		
	Date		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		March 24, 2022	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	Date	1
1.1	Date.doc	1
1.2	Date/--background--	3
1.3	Date/--history--	5
1.4	Date/GregorianDayDiff	8
1.5	Date/GregorianDayGreater	9
1.6	Date/GregorianDaysAfterWeekday	10
1.7	Date/GregorianDaysBeforeWeekday	11
1.8	Date/GregorianDaySmaller	12
1.9	Date/GregorianDiffDate	12
1.10	Date/GregorianEaster	13
1.11	Date/GregorianLeapYear	14
1.12	Date/GregorianMonthDays	15
1.13	Date/GregorianMoonAge	16
1.14	Date/GregorianToJD	16
1.15	Date/GregorianWeek	17
1.16	Date/GregorianWeekday	18
1.17	Date/GregorianYearDays	19
1.18	Date/GSYearToJD	20
1.19	Date/GYearToScaliger	21
1.20	Date/HeisDayDiff	22
1.21	Date/HeisDayGreater	23
1.22	Date/HeisDaysAfterWeekday	23
1.23	Date/HeisDaysBeforeWeekday	24
1.24	Date/HeisDaySmaller	25
1.25	Date/HeisDiffDate	26
1.26	Date/HeisLeapYear	27
1.27	Date/HeisMonthDays	28
1.28	Date/HeisToJD	29
1.29	Date/HeisWeek	29

1.30	Date/HeisWeekday	30
1.31	Date/HeisYearDays	31
1.32	Date/HSYearToJD	32
1.33	Date/HYearToScaliger	33
1.34	Date/JDtoMJD	34
1.35	Date/JDToTime	34
1.36	Date/JSYearToJD	35
1.37	Date/JulianDayDiff	36
1.38	Date/JulianDayGreater	37
1.39	Date/JulianDaysAfterWeekday	38
1.40	Date/JulianDaysBeforeWeekday	38
1.41	Date/JulianDaySmaller	39
1.42	Date/JulianDiffDate	40
1.43	Date/JulianLeapYear	41
1.44	Date/JulianMonthDays	42
1.45	Date/JulianToJD	43
1.46	Date/JulianWeek	44
1.47	Date/JulianWeekday	44
1.48	Date/JulianYearDays	45
1.49	Date/JYearToScaliger	46
1.50	Date/LMT	47
1.51	Date/MJDtoJD	47
1.52	Date/ScaligerYearToG	48
1.53	Date/ScaligerYearToH	49
1.54	Date/ScaligerYearToJ	49
1.55	Date/SecToTime	50
1.56	Date/TimeToJD	51
1.57	Date/TimeToSec	52
1.58	Date/TimeZoneFactor	52

Chapter 1

Date

1.1 Date.doc

```
--background--  
  
--history-- ()  
  
GregorianDayDiff ()  
  
GregorianDayGreater ()  
  
GregorianDaysAfterWeekday ()  
  
GregorianDaysBeforeWeekday ()  
  
GregorianDaySmaller ()  
  
GregorianDiffDate ()  
  
GregorianEaster ()  
  
GregorianLeapYear ()  
  
GregorianMonthDays ()  
  
GregorianMoonAge ()  
  
GregorianToJD ()  
  
GregorianWeek ()  
  
GregorianWeekday ()  
  
GregorianYearDays ()  
  
GSYearToJD ()  
  
GYearToScaliger ()  
  
HeisDayDiff ()
```

HeisDayGreater ()
HeisDaysAfterWeekday ()
HeisDaysBeforeWeekday ()
HeisDaySmaller ()
HeisDiffDate ()
HeisLeapYear ()
HeisMonthDays ()
HeisToJD ()
HeisWeek ()
HeisWeekday ()
HeisYearDays ()
HYearToJD ()
HYearToScaliger ()
JDtoMJD ()
JDToTime ()
JYearToJD ()
JulianDayDiff ()
JulianDayGreater ()
JulianDaysAfterWeekday ()
JulianDaysBeforeWeekday ()
JulianDaySmaller ()
JulianDiffDate ()
JulianLeapYear ()
JulianMonthDays ()
JulianToJD ()
JulianWeek ()
JulianWeekday ()
JulianYearDays ()

```
JYearToScaliger()  
  
LMT  
  
MJDtoJD()  
  
ScaligerYearToG()  
  
ScaligerYearToH()  
  
ScaligerYearToJ()  
  
SecToTime()  
  
TimeToJD()  
  
TimeToSec()  
  
TimeZoneFactor()
```

1.2 Date/--background--

NAME

Date -- This module was designed to help calc. calendar dates (V33)

FUNCTION

I know about the date routines in the Amiga-OS(TM), but I decided not to use them, because of their limited functionalities and of the portability of this module!

NOTES

A tropical year is 365.2422 days! / 365d, 5h, 48min, 46sec

A moon month is 29.53059 days! / 29d, 12h, 44min, 2.9 sec

A moon phase is 7.38265 days!

(German) Books which helped me creating this library:

Kleine Naturwissenschaftliche Bibliothek, Band 23

Ewige Kalender

A.W. Butkewitsch & M.S. Selikson

5. Auflage

Teubner, Leipzig 1974

ISBN 3-322-00393-0

Tag und Woche, Monat und Jahr: eine Kulturgeschichte des
Kalenders

Rudolf Wendorff

Westdeutscher, Opladen 1993

ISBN 3-531-12417-X

Kalender und Chronologie: Bekanntes & Unbekanntes aus der
Kalenderwissenschaft

Heinz Zemanek

4. Auflage

Oldenbourg, München 1987

ISBN 3-486-20447-5

Meyers Handbuch
über das Weltall
Karl Schaifers & Gerhard Traving
5. Auflage
Bibliographisches Institut Mannheim 1973
ISBN 3-411-00940-3

Meyers Handbuch
über das Weltall
Karl Schaifers & Gerhard Traving
5. Auflage
Bibliographisches Institut Mannheim 1973
ISBN 3-411-00940-3

(English) Books which helped me creating this library:

Mathematical Astronomy with a Pocket Calculator
Aubrey Jones Fras
unknown(first) Edition
David & Charles Newton Abbot, London 1978
ISBN 0-7153-7675-6

COPYRIGHT

This module is Copyright 1994 by Kai Hofmann - all rights reserved!
For private use, Public Domain, Gift Ware, Freeware and Shareware
you could use this module under following conditions:

- You send me a little gift (money is very welcome :)
For Bank Account see below - but *ONLY* send in DM
to this Bank Account!!!

Other nice gifts: all Amiga hardware, and I am searching for a
good old 1541 (C64 floppy)

- You include a notice in your product, that you use this library
and that it is Copyright by Kai Hofmann!

If you want to redistribute this library read the following points:

- Redistribution warranty is given to:

Fred Fish for his great Amiga-Software-Library
The German SAAR AG PD-Library
The German AMOK PD-Library

All public accessible INTERNET servers and PHONE boxes!

All other who NOT take more than DM 5.- for one disk

ALL other who NOT take more than DM 50.- for one CD

For commercial use send me DM 200.-

But if you are Apple or Microsoft you have to send (20000.- US\$)

DISCLAIMER

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDER AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE
COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY REDISTRIBUTE THE

PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

ADDITIONAL INFORMATIONS

I have tried to make portable/usefull and I hope bugfree software for eternity - but this seems to be impossible (sorry!) :)
So I hope you will pay a fee for this.

AUTHOR

Kai Hofmann
Arberger Heerstraße 92
28307 Bremen
Germany
EMail: i07m@alf.zfn.uni-bremen.de
(no phone - I hate it!)

Bank account : 1203 7503
Account owner: Kai Hofmann
Bank code : 290 501 01
Bank name : Sparkasse in Bremen
Bank address : 28307 Bremen / Germany

THANK

Thanx are going to the following people:
Danial Armor - For his hint about the Oberon-2 SHORT
command
Heinz Zemanek - For his great book
Christian Schaefer - For spending time on this lib with his
Borland C++ 4.0 compiler
Rita Reichl - For correcting my bad english ;-)
Jim Rickman - For reporting a bug

1.3 Date/--history--

NAME

history -- This is the development history of the Date module

VERSION

\$VER: Date 33.089 (30.11.1994)

HISTORY

16.01.1994 - Procedures: JulianLeapYear, GregorianLeapYear &
HeisLeapYear initiated.
22.01.1994 - Procedures: JulianMonthDays, GregorianMonthDays,
HeisMonthDays, JulianYearDays, GregorianYearDays,
HeisYearDays, JulianDayDiff, GregorianDayDiff,
HeisDayDiff, JulianDaySmaller, GregorianDaySmaller,
HeisDaySmaller, JulianWeekday, GregorianWeekday,
HeisWeekday, JulianDaysBeforeWeekday,
GregorianDaysBeforeWeekday, HeisDaysBeforeWeekday,

- JulianDaysAfterWeekday, GregorianDaysAfterWeekday,
HeisDaysAfterWeekday JulianDiffDate, FreeDate
initiated.
Types: Weekdays, Date, DatePtr initiated.
Vars of Gregorian reform initiated
(for changing to different countries)
- 23.01.1994 - Procedures: JulianDiffDate finished,
GregorianDiffDate, HeisDiffDate, JYearToScaliger,
GYearToScaliger, HYearToScaliger, ScaligerYearToJ,
ScaligerYearToG, ScaligerYearToH, JSYearToJD,
GSYearToJD, HSYearToJD, JDtoMJD, MJDtoJD, JulianToJD,
GregorianToJD, HeisToJD, TimeToJD, JDToTime, FreeTime
initiated.
Types: Time, TimePtr initiated.
- 28.01.1994 - Procedures: GregorianMoonAge, MoonMonthAge,
GregorianEaster initiated.
- 30.01.1994 - Procedures: JulianDiffDate, GregorianDiffDate,
HeisDiffDate, JDtoTime, GregorianEaster edited
(changing return value from ptr to VAL variables).
Procedures: FreeDate, FreeTime deleted.
Types: Date, DatePtr, Time, TimePtr deleted (not
longer needed, because of the procedure changes).
Procedures: GregorianMoonAge, GregorianEaster changed
year parameter from CARDINAL to INTEGER (this is more
consistent to the rest of the library).
Bugs removed: GregorianWeekday, HeisWeekday
(before removing, the weekday for leapyears was
wrong)
Procedure: GregorianEaster finished.
- 30.01.1994 - Ported to Oberon-2
- 31.01.1994 - Compiled with Oberon-2 V3.11
- 12.02.1994 - Procedures: TimeZoneFactor,
LMT
, TimeToSec, SecToTime
initiated.
Version-String installed :)
- 12.02.1994 - Starting translation to SAS C 6.51
Date.h translated
- 13.02.1994 - Continuation of C translation
- 17.02.1994 - New Oberon-2 Port, because yesterday Daniel Armor
gives me a small hint about the SHORT command
(I did not know about this!)
- 17.02.1994 - Small bug in Autodocs removed
making this text as Date/--history-- autodoc
- 17.02.1994 - Continuation of C translation
- 18.02.1994 - Finished with C translation
- 19.02.1994 - C bugs removed (thanx to SAS for helping a C Lamer
like me!), some optimizations done too.
- 19.02.1994 - Oberon-2 version compiled with V40.17 includes
- 21.02.1994 - Starting to write Modula-II testmodule
Vars for the begining of Heis calculation initiated.
Fixed small bugs in GregorianWeekday, HeisWeekday,
TimeToSec, SecToTime
Return-value of
LMT
changed to LONGINT!
Converting testmodule to Oberon-2
-

- 22.02.1994 - Converting testmodule to C
- 23.02.1994 - I noticed, that I forgot the 3 functions
JulianWeek, GregorianWeek, HeisWeek
- 24.02.1994 - Initiated the 3 forgotten functions
- 26.02.1994 - Initiating new GregorianEastern with Gauß-algorithms
but ONLY for 1900-2099!
- 27.02.1994 - Bug fixed in JulianWeekday
Bugs fixed in JulianDayDiff, GregorianDayDiff,
HeisDayDiff
JulianDayGreater, GregorianDayGreater,
HeisDayGreater Initiated.
- 02.03.1994 - Small bug fixed in HeisdayDiff
Bugs from 27.02. fixed in Modula-II and Oberon-2
versions
I found the way to extend Gregorian Easter!
Small bug fixed in JulianWeek, GregorianWeek,
HeisWeek (~(M2) is not !(C))
- 05.03.1994 - Some internal bugs removed
New internal procedures GregorianSB,
GregorianJHSB, GregorianJHStartSB!
Extending GregorianEaster :)
- 11.03.1994 - Things from 05.03. done in Modula-II and Oberon
- 12.03.1994 - If __SASC is defined autoinitalization instead of
_DateInit will be used!
- 13.03.1994 - After studying the SAS C Manual again I decided to
check for __SASC_650 instead of __SASC because of
the available priorities!
Setting the priority of _DateInit for
autoinitalization to 600!
- 15.03.1994 - Making Date as library
- 16.03.1994 - Some work on the Autodocs was done
Eleminating OldGregorianEaster by comments
(ANSI: STOP bad standards like that there are NO
nested comments possible in C!!!)
- 19.03.1994 - Some work on the Autodocs was done in the M2 Code
- 20.03.1994 - Some work on the Autodocs was done in the Oberon Code
- 22.03.1994 - In JDtoMJD, MJD to JD an L was added to the constant
In
GregorianWeekday()
,
HeisWeekday()
,

JulianDiffDate()
,
GregorianDiffDate()
,

HeisDiffDate()
,
JDToTime()
I have inserted
conversions (found with Borland C++ 4.0)
- 24.03.1994 - Making SunOS4.1.3, SunOS5.3(Solaris2.3) &
RS6000 AIX3.2.? binaries with gcc
Eliminating nested commends by inserting a space
between / and * (I hate this ANSI C standard

```

feature for commends :(
27.03.1994 - Adding library register assignments to the autodocs
03.04.1994 - Small fixes for the SAS C++ Compiler
    Small bug fixed in the M2 version of GregorianEaster
04.04.1994 - Adding some 'static' keywords
10.04.1994 - Changing from Shareware to Gift Ware ;- )
02.08.1994 - Small fixes in the Autodocs (thanks to Rita Reichl
    for correcting my bad english ;- )
11.08.1994 - Again small fixes in the Autodocs!
13.11.1994 - Small fix in
    JulianWeek()
    ,
    GregorianWeek()
    ,
    HeisWeek()
    .
    Thanks to Jim Rickman for reporting the bug!
    Small changes in the Autodocs!
30.11.1994 - Fix the bug from 13.11. in M2 and Oberon code.

```

1.4 Date/GregorianDayDiff

NAME

GregorianDayDiff -- Calculates the days between 2 dates. (V33)

SYNOPSIS

```
days := GregorianDayDiff(day1,month1,year1,day2,month2,year2);
```

```
PROCEDURE GregorianDayDiff(day1,month1 : SHORTCARD; year1 : INTEGER;
    day2,month2 : SHORTCARD; year2 : INTEGER) : LONGINT;
```

FUNCTION

GregorianDayDiff gives you back the number of days between two specified dates.

INPUTS

```

day1    - day of the first date
month1  - month of the first date
year1   - year of the first date
day2    - day of the second date
month2  - month of the second month
year2   - year of the second date

```

RESULT

days - The number of days between the two dates
(positive if date1 <= date2).

EXAMPLE

```

...
days := GregorianDayDiff(18,9,1970,22,1,1994);
WriteString("Age of Kai Hofmann in days : ");
WriteInt(days,10); WriteLn;
...

```

NOTES

It is better only to use this function for years from -7 to 3200!

BUGS

If you use on of the dates 5.10.1582 to 14.10.1582 you will get a wrong output, because this days don't exist!

SEE ALSO

```

    JulianDayDiff()
    ,
    HeisDayDiff()
    ,
    GregorianDaySmaller()
    ,
    GregorianDayGreater()
    ,
    GregorianMonthDays()
    ,
    GregorianYearDays()

```

1.5 Date/GregorianDayGreater

NAME

GregorianDayGreater -- Checks if date1 is greater than date2. (V33)

SYNOPSIS

```
greater := GregorianDayGreater(day1,month1,year1,day2,month2,year2);
```

```

PROCEDURE GregorianDayGreater(day1,month1 : SHORTCARD;
    year1 : INTEGER; day2,month2 : SHORTCARD;
    year2 : INTEGER) : BOOLEAN;

```

FUNCTION

GregorianDayGreater test if date1 is greater than date2.

INPUTS

```

day1    - day of the first date
month1  - month of the first date
year1   - year of the first date
day2    - day of the second date
month2  - month of the second month
year2   - year of the second date

```

RESULT

greater - This is TRUE is date1 > date2 otherwise it's FALSE.

EXAMPLE

```

...
IF GregorianDayGreater(18,9,1970,22,1,1994) THEN
    WriteString(">"); WriteLn;
ELSE
    WriteString("<="); WriteLn;

```

```
END;
...

NOTES
It is better only to use this function for years from -7 to 3200!

BUGS
No known bugs.

SEE ALSO
JuliandayGreater(),
HeisDayGreater()
```

1.6 Date/GregorianDaysAfterWeekday

```
NAME
GregorianDaysAfterWeekday -- Returns the diff to wday after. (V33)

SYNOPSIS
days := GregorianDaysAfterWeekday(day,month,year,weekday);

PROCEDURE GregorianDaysAfterWeekday(day,month : SHORTCARD;
    year : INTEGER; weekday : Weekdays) : SHORTCARD;

FUNCTION
Returns the days to the weekday after the specified date.
So if you specify the 22.1.1994 (Saturday) and Thursday
you get back 5!
If you specify the 22.1.1994 and Saturday you get back 0
(the same day)!

INPUTS
day      - day of the date
month    - month of the date
year     - year of the date
weekday  - weekday to search for building difference

RESULT
days - The days after to the searched weekday.

EXAMPLE
...
days := GregorianDaysAfterWeekday(22,1,1994,Thursday);
...

NOTES
It is better to use this function only from -7 to 3200!

BUGS
See GregorianWeekday()!

SEE ALSO
JulianDaysAfterWeekday()
```

```

    ,
    HeisDaysAfterWeekday()
    ,
    GregorianWeekday()

```

1.7 Date/GregorianDaysBeforeWeekday

NAME

GregorianDaysBeforeWeekday -- Returns the diff to wday before. (V33)

SYNOPSIS

```
days := GregorianDaysBeforeWeekday(day,month,year,weekday);
```

```
PROCEDURE GregorianDaysBeforeWeekday(day,month : SHORTCARD;
    year : INTEGER; weekday : Weekdays) : SHORTCARD;
```

FUNCTION

Returns the days to the weekday before the specified date.
 So if you specify the 22.1.1994 (Saturday) and Thursday
 you get back 2!
 If you specify the 22.1.1994 and Saturday you get back 0
 (the same day)!

INPUTS

```

day      - day of the date
month    - month of the date
year     - year of the date
weekday  - weekday to search for building difference

```

RESULT

```

days - The days back to the searched weekday (1-7)
      - If you get back 8 an error occurs!

```

EXAMPLE

```

...
days := GregorianDaysBeforeWeekday(22,1,1994,Thursday);
...

```

NOTES

It is better to use this function only from -7 to 3200!

BUGS

See GregorianWeekday()!

SEE ALSO

```

    JulianDaysBeforeWeekday()
    ,
    HeisDaysBeforeWeekday()
    ,
    GregorianWeekday()

```

1.8 Date/GregorianCalendarSmaller

NAME

GregorianCalendarSmaller -- Checks if date1 is smaller than date2. (V33)

SYNOPSIS

```
smaller := GregorianCalendarSmaller(day1,month1,year1,day2,month2,year2);
```

```
PROCEDURE GregorianCalendarSmaller(day1,month1 : SHORTCARD;
    year1 : INTEGER; day2,month2 : SHORTCARD;
    year2 : INTEGER) : BOOLEAN;
```

FUNCTION

GregorianCalendarSmaller test if date1 is smaller than date2.

INPUTS

```
day1    - day of the first date
month1  - month of the first date
year1   - year of the first date
day2    - day of the second date
month2  - month of the second month
year2   - year of the second date
```

RESULT

smaller - This is TRUE is date1 < date2 otherwise it's FALSE.

EXAMPLE

```
...
IF GregorianCalendarSmaller(18,9,1970,22,1,1994) THEN
    WriteString("<"); WriteLn;
ELSE
    WriteString(">="); WriteLn;
END;
...
```

NOTES

It is better only to use this function for years from -7 to 3200!

BUGS

No known bugs.

SEE ALSO

```
JulianDaySmaller()
,
HeisDaySmaller()
```

1.9 Date/GregorianCalendarDiffDate

NAME

GregorianCalendarDiffDate -- Returns the diff date to another date. (V33)

SYNOPSIS


```
GregorianDiffDate(day,month,year,diffdays,dday,dmonth,dyear);
```

```
PROCEDURE GregorianDiffDate(day,month : SHORTCARD;  
    year,days : INTEGER; VAR dday,dmonth : SHORTCARD;  
    VAR dyear : INTEGER);
```

FUNCTION

Returns the date wich lies diffdays before/after the specified date.

INPUTS

day - day of the date
month - month of the date
year - year of the date
diffdays - difference to the date in days

RESULT

dday - Destination day
dmonth - Destination month
dyear - Destination year

EXAMPLE

```
...  
GregorianDiffDate(23,1,1994,7,dday,dmonth,dyear);  
...
```

NOTES

It is better to use this function only from -7 to 3200!

BUGS

unknown.

SEE ALSO

```
GregorianDayDiff()  
,  
JulianDiffDate()  
,  
HeisDiffDate()
```

1.10 Date/GregorianEaster

NAME

GregorianEaster -- Returns the date of eastern in a year (V33)

SYNOPSIS

```
GregorianEaster(year,dday,dmonth);
```

```
PROCEDURE GregorianEaster(year : INTEGER;  
    VAR dday,dmonth : SHORTCARD);
```

FUNCTION

Returns the date of eastern for a specified year.

INPUTS

year - eastern is calculated for this year

RESULT

dday - day of easter-Sunday
dmonth - month of easter-Sunday

EXAMPLE

```
...
GregorianEaster(1994, dday, dmonth);
...
```

NOTES

Use this only for 1900 to 2099!
Tested for 1977-1994! But this formula is from Gauß - so it must be correct :)

BUGS

None.

SEE ALSO

GEP(), GregorianJHSB()

1.11 Date/GregorianLeapYear

NAME

GregorianLeapYear -- Checks if a year is a leap year. (V33)

SYNOPSIS

```
leapyear := GregorianLeapYear(year);
```

```
PROCEDURE GregorianLeapYear(year : INTEGER) : BOOLEAN;
```

FUNCTION

GregorianLeapYear checks if a year is a leap year.
For years after 1582 all years devideable by 4 are leap years,
without years devideable by 100, but years devideable by 400
are leap years again!
For years before 1582 see

```
JulianLeapYear()
```

.

INPUTS

year - The year which should be checked (from -32768 to 32767)
I think only values from -7 to 3200 are valid, because of
the variant that was done on -8 by Augustus and other things!

RESULT

leapyear - TRUE if the year is a leap year, otherwise false.

EXAMPLE

```
...
IF GregorianLeapYear(1994) THEN
  WriteString("leap year!");
ELSE
  WriteString("no leap year!");
```

```
END;
WriteLn;
...
```

NOTES
 A year is 365.2425 days long!
 Use this function only for values from -7 to 3199

BUGS
 No known bugs.

SEE ALSO

```
JulianLeapYear()
,
HeisLeapYear()
```

1.12 Date/GregorianMonthDays

NAME

GregorianMonthDays -- Gives back the number of days of a month. (V33)

SYNOPSIS

```
days := GregorianMonthDays(month,year);
```

```
PROCEDURE GregorianMonthDays(month : SHORTCARD;
  year : INTEGER) : SHORTCARD;
```

FUNCTION

GregorianMonthDays gives you back the number of days a month in a specified year has.

For the year 1582 and the month 10 there are only 21 days, because of the Gregorian-reform 10 days are delete from the month (for more - look out for books about this!)

INPUTS

month - The month from wich you want to get the number of days.
 year - The year in which the month is.

RESULT

days - The number of days the month uses, or 0 if you use a wrong month.

EXAMPLE

```
...
days := GregorianMonthDays(1,1994);
WriteString("Days of January 1994 : ");
WriteCard(days,2); WriteLn;
...
```

NOTES

Use this function only for years from -7 to 3199!

BUGS

If the reform in a country is not in the same month an error will occur!

SEE ALSO

```
GregorianLeapYear()  
,  
JulianMonthDays()  
,  
HeisMonthDays()
```

1.13 Date/GregorianMoonAge

NAME

GregorianMoonAge -- Returns the age of the moon (V33)

SYNOPSIS

```
ep := GregorianMoonAge(day,month,year);
```

```
PROCEDURE GregorianMoonAge(day,month : SHORTCARD;  
    year : CARDINAL) : SHORTCARD;
```

FUNCTION

Returns the age of the moon on a specified date.

INPUTS

day - For this day the age is calculated.
month - For this month the age is calculated.
year - For this year the age is calculated.

RESULT

ep - The age of the moon on the specified date.

EXAMPLE

```
...  
ep := GregorianMoonAge(18,9,1994);  
...
```

NOTES

Use this only for 1582 to 4100!
This is only a experimental version!

BUGS

unknown.

SEE ALSO

MoonMonthAge(),GregorianEP()

1.14 Date/GregorianToJD

NAME

GregorianToJD -- Returns the JD for a date. (V33)

SYNOPSIS

```
jd := GregorianToJD(day,month,year);
```

```
PROCEDURE GregorianToJD(day,month : SHORTCARD;
    year : INTEGER) : LONGCARD;
```

FUNCTION

Returns the JD for a Gregorian date.

INPUTS

```
day      - day of the date to convert
month    - month of the date to convert
year     - year of the date to convert
```

RESULT

jd - This is the JD

EXAMPLE

```
...
jd := GregorianToJD(23,1,1994);
...
```

NOTES

It is better to use this function only from -7 to 3200!

BUGS

unknown.

SEE ALSO

```
JulianToJD()
,
HeisToJD()
,
GSYearToJD()
,
GYearToScaliger()
,
GregorianDayDiff()
```

1.15 Date/GregorianWeek

NAME

GregorianWeek -- Gets the weeknumber of a specified date. (V33)

SYNOPSIS

```
weeknr := GregorianWeek(day,month,year);
```

```
PROCEDURE GregorianWeek(day,month : SHORTCARD;
```

```
year : INTEGER) : SHORTCARD;
```

FUNCTION

GregorianWeek gets the weeknumber for a specified date.

INPUTS

```
day   - day of the date
month - month of the date
year  - year of the date
```

RESULT

week - This is the number of the week the specified date lies in.
 If the first day in a new year is a Friday, Saturday or Sunday, this would be the last week of the last year!
 If the 29.12. is a Monday, the 30.12. is a Monday or a Tuesday, the 31.12. is a Monday, Tuesday or a Wednesday this is the first week of the next year!

EXAMPLE

```
...
weeknr := GregorianWeek(4,10,1582);
...
```

NOTES

It is better only to use this function for years from 0 to 3000!

BUGS

For years < 0 errors could occur.

SEE ALSO

```
JulianWeek()
,
HeisWeek()
,
GregorianDaySmaller()
,
GregorianWeekday()
,
GregorianDayDiff()
```

1.16 Date/GregorianWeekday

NAME

GregorianWeekday -- Gets the weekday of a specified date. (V33)

SYNOPSIS

```
weekday := GregorianWeekday(day,month,year);
```

```
PROCEDURE GregorianWeekday(day,month : SHORTCARD;
year : INTEGER) : Weekday;
```

FUNCTION

GregorianWeekday gets the weekday for a specified date.

INPUTS

day - day of the date
 month - month of the date
 year - year of the date

RESULT

weekday - This result is of type:
 Weekdays = (dayerr, Monday, Tuesday, Wednesday, Thursday, Friday,
 Saturday, Sunday);
 dayerr will show you, that an error occurs!

EXAMPLE

```
...
weekday := GregorianWeekday(22,1,1994);
IF weekday = dayerr THEN
...
END;
...
```

NOTES

It is better only to use this function for years from -7 to 3200!
 In this version dayerr will only occur for the 10 lost days :)

BUGS

It's not possible to use years < 0 (for more see
 JulianWeekday()
).

SEE ALSO

```
JulianWeekday()
,
HeisWeekday()
,
GregorianDaySmaller()
,
GregorianLeapYear()
```

1.17 Date/GregorianYearDays

NAME

GregorianYearDays -- Gives back the number of days in a year. (V33)

SYNOPSIS

```
days := GregorianYearDays(year);
```

```
PROCEDURE GregorianYearDays(year : INTEGER) : CARDINAL;
```

FUNCTION

GregorianYearDays gives you back the number of days in a specified year.

INPUTS
 year - The year in which to count the days.

RESULT
 days - The number of days the year uses.

EXAMPLE
 ...
 days := GregorianYearDays(1994);
 WriteString("Days of 1994 : ");
 WriteCard(days,3); WriteLn;
 ...

NOTES
 It is better only to use this function for years from -7 to 3199!

BUGS
 No known bugs.

SEE ALSO

GregorianMonthDays()
 ,
 JulianYearDays()
 ,
 HeisYearDays()

1.18 Date/GSYearToJD

NAME
 GSYearToJD -- Calcs the JD from a Scaliger year. (V33)

SYNOPSIS
 jd := GSYearToJD(syear);

PROCEDURE GSYearToJD(syear : CARDINAL) : LONGCARD;

FUNCTION
 Returns the Julianday of a Scaliger year.

INPUTS
 syear - Scaliger year

RESULT
 jd - The Julianday

EXAMPLE
 ...
 jd := GSYearToJD(4800);
 ...

NOTES
 It is better to use this function only from 4707 to 7981!

BUGS
unknown.

SEE ALSO

```
JSYearToJD()  
,  
HYearToJD()  
,  
GregorianDayDiff()  
,  
ScaligerYearToG()
```

1.19 Date/GYearToScaliger

NAME

GYearToScaliger -- Returns the year as Scaliger year. (V33)

SYNOPSIS

```
syear := GYearToScaliger(year);
```

```
PROCEDURE GYearToScaliger(year : INTEGER) : CARDINAL;
```

FUNCTION

Returns the Scaliger year.

INPUTS

year - Gregorian year

RESULT

syear - The Scaliger year

EXAMPLE

```
...  
syear := GYearToScaliger(1994);  
...
```

NOTES

It is better to use this function only from -7 to 3200!

BUGS
unknown.

SEE ALSO

```
JYearToScaliger()  
,  
HYearToScaliger()
```

1.20 Date/HeisDayDiff

NAME

HeisDayDiff -- Calculates the days between 2 dates. (V33)

SYNOPSIS

```
days := HeisDayDiff(day1,month1,year1,day2,month2,year2);
```

```
PROCEDURE HeisDayDiff(day1,month1 : SHORTCARD; year1 : INTEGER;
    day2,month2 : SHORTCARD; year2 : INTEGER) : LONGINT;
```

FUNCTION

HeisDayDiff gives you back the number of days between two specified dates.

INPUTS

day1 - day of the first date
month1 - month of the first date
year1 - year of the first date
day2 - day of the second date
month2 - month of the second month
year2 - year of the second date

RESULT

days - The number of days between the two dates
(positive if date1 <= date2).

EXAMPLE

```
...
days := HeisDayDiff(18,9,1970,22,1,1994);
WriteString("Age of Kai Hofmann in days : ");
WriteInt(days,10); WriteLn;
...
```

NOTES

It is better only to use this function for years from -7 to 8000!

BUGS

If you use on of the dates 5.10.1582 to 14.10.1582 you will get a wrong output, because this days don't exist!

SEE ALSO

```
JulianDayDiff()
,
GregorianDayDiff()
,
HeisDaySmaller()
,
HeisDayGreater()
,
HeisMonthDays()
,
HeisYearDays()
```

1.21 Date/HeisDayGreater

NAME

HeisDayGreater -- Checks if date1 is greater than date2. (V33)

SYNOPSIS

```
greater := HeisDayGreater(day1,month1,year1,day2,month2,year2);
```

```
PROCEDURE HeisDayGreater(day1,month1 : SHORTCARD; year1 : INTEGER;
    day2,month2 : SHORTCARD; year2 : INTEGER) : BOOLEAN;
```

FUNCTION

HeisDayGreater test if date1 is greater than date2.

INPUTS

```
day1    - day of the first date
month1  - month of the first date
year1   - year of the first date
day2    - day of the second date
month2  - month of the second month
year2   - year of the second date
```

RESULT

greater - This is TRUE is date1 > date2 otherwise it's FALSE.

EXAMPLE

```
...
IF HeisDayGreater(18,9,1970,22,1,1994) THEN
    WriteString(">"); WriteLn;
ELSE
    WriteString("<="); WriteLn;
END;
...
```

NOTES

It is better only to use this function for years from -7 to 8000!

BUGS

No known bugs.

SEE ALSO

```
    JulianDayGreater()
    ,
    GregorianDayGreater()
```

1.22 Date/HeisDaysAfterWeekday

NAME

HeisDaysAfterWeekday -- Returns the diff to the wday after. (V33)

SYNOPSIS

```
days := HeisDaysAfterWeekday(day,month,year,weekday);
```

```
PROCEDURE HeisDaysAfterWeekday(day,month : SHORTCARD;
    year : INTEGER; weekday : Weekdays) : SHORTCARD;
```

FUNCTION

Returns the days to the weekday after the specified date.
So if you specify the 22.1.1994 (Saturday) and Thursday
you get back 5!
If you specify the 22.1.1994 and Saturday you get back 0
(the same day)!

INPUTS

day - day of the date
month - month of the date
year - year of the date
weekday - weekday to search for building difference

RESULT

days - The days after to the searched weekday.

EXAMPLE

```
...
days := HeisDaysAfterWeekday(22,1,1994,Thursday);
...
```

NOTES

It is better to use this function only from -7 to 8000!

BUGS

See HeisWeekday()!

SEE ALSO

```
JulianDaysAfterWeekday()
,
GregorianDaysAfterWeekday()
,
HeisWeekday()
```

1.23 Date/HeisDaysBeforeWeekday

NAME

HeisDaysBeforeWeekday -- Returns the diff to wday before. (V33)

SYNOPSIS

```
days := HeisDaysBeforeWeekday(day,month,year,weekday);
```

```
PROCEDURE HeisDaysBeforeWeekday(day,month : SHORTCARD;
    year : INTEGER; weekday : Weekdays) : SHORTCARD;
```

FUNCTION

Returns the days to the weekday before the specified date.
So if you specify the 22.1.1994 (Saturday) and Thursday
you get back 2!

If you specify the 22.1.1994 and Saturday you get back 0
(the same day)!

INPUTS

day - day of the date
month - month of the date
year - year of the date
weekday - weekday to search for building difference

RESULT

days - The days back to the searched weekday (1-7)
If you get back 8 an error occurs!

EXAMPLE

```
...
days := HeisDaysBeforeWeekday(22,1,1994,Thursday);
...
```

NOTES

It is better to use this function only from -7 to 8000!

BUGS

See HeisWeekday()!

SEE ALSO

```
JulianDaysBeforeWeekday()
,
GregorianDaysBeforeWeekday()
,
HeisWeekday()
```

1.24 Date/HeisDaySmaller

NAME

HeisDaySmaller -- Checks if date1 is smaller than date2. (V33)

SYNOPSIS

```
smaller := HeisDaySmaller(day1,month1,year1,day2,month2,year2);
```

```
PROCEDURE HeisDaySmaller(day1,month1 : SHORTCARD; year1 : INTEGER;
    day2,month2 : SHORTCARD; year2 : INTEGER) : BOOLEAN;
```

FUNCTION

HeisDaySmaller test if date1 is smaller than date2.

INPUTS

day1 - day of the first date
month1 - month of the first date
year1 - year of the first date
day2 - day of the second date
month2 - month of the second month
year2 - year of the second date

RESULT
smaller - This is TRUE is date1 < date2 otherwise it's FALSE.

EXAMPLE
...
IF HeisDaySmaller(18,9,1970,22,1,1994) THEN
 WriteString("<"); WriteLn;
ELSE
 WriteString(">="); WriteLn;
END;
...

NOTES
It is better only to use this function for years from -7 to 8000!

BUGS
No known bugs.

SEE ALSO

 JulianDaySmaller()
 ,
 GregorianDaySmaller()

1.25 Date/HeisDiffDate

NAME
HeisDiffDate -- Returns the date for a diff to another date. (V33)

SYNOPSIS
HeisDiffDate(day,month,year,diffdays,dday,dmonth,dyear);

PROCEDURE HeisDiffDate(day,month : SHORTCARD; year,days : INTEGER;
 VAR dday,dmonth : SHORTCARD; VAR dyear : INTEGER);

FUNCTION
Returns the date wich lies diffdays before/after the specified date.

INPUTS
day - day of the date
month - month of the date
year - year of the date
diffdays - difference to the date in days

RESULT
dday - Destination day
dmonth - Destination month
dyear - Destination year

EXAMPLE
...
HeisDiffDate(23,1,1994,7,dday,dmonth,dyear);
...

NOTES

It is better to use this function only from -7 to 8000!

BUGS

unknown.

SEE ALSO

```

HeisDayDiff()
,
JulianDiffDate()
,
GregorianDiffDate()

```

1.26 Date/HeisLeapYear

NAME

HeisLeapYear -- Checks if a year is a leap year. (V33)

SYNOPSIS

```
leapyear := HeisLeapYear(year);
```

```
PROCEDURE HeisLeapYear(year : INTEGER) : BOOLEAN;
```

FUNCTION

HeisLeapYear checks if a year is a leap year.

For years after 1582 see

```
GregorianLeapYear()
```

```
,
```

The correction from N. Heis says, that all years devideable by 3200 are no longer leap years!

For years before 1582 see JulianLeapYear

INPUTS

year - The year which should be checked (from -32768 to 32767)

I think only values from -7 to 8000 are valid, because of the variant that was done on -8 by Augustus and other things!

RESULT

leapyear - TRUE if the year is a leap year, otherwise false.

EXAMPLE

```
...
```

```
IF HeisLeapYear(1994) THEN
```

```
  WriteString("leap year!");
```

```
ELSE
```

```
  WriteString("no leap year!");
```

```
END;
```

```
WriteLn;
```

```
...
```

NOTES

A year is now 365.2421875 days!

Use this function only for values from -7 to 8000!

BUGS
No known bugs.

SEE ALSO

```
JulianLeapYear()  
,  
GregorianLeapYear()
```

1.27 Date/HeisMonthDays

NAME

HeisMonthDays -- Gives back the number of days of a month. (V33)

SYNOPSIS

```
days := HeisMonthDays(month,year);
```

```
PROCEDURE HeisMonthDays(month : SHORTCARD;  
    year : INTEGER) : SHORTCARD;
```

FUNCTION

HeisMonthDays gives you back the number of days a month in a specified year has.

For the year 1582 and the month 10 there are only 21 days, because of the Gregorian-reform 10 days are delete from the month (for more - look out for books about this!)

INPUTS

month - The month from wich you want to get the number of days.
year - The year in which the month is.

RESULT

days - The number of days the month uses, or 0 if you use a wrong month.

EXAMPLE

```
...  
days := HeisMonthDays(1,1994);  
WriteString("Days of January 1994 : ");  
WriteCard(days,2); WriteLn;  
...
```

NOTES

Use this function only for years from -7 to 8000!

BUGS

See GregorianMonthDays!

SEE ALSO

```
HeisLeapYear()  
,  
JulianMonthDays()
```



```

GregorianMonthDays ()

```

1.28 Date/HeisToJD

```

NAME
HeisToJD -- Returns the JD for a date. (V33)

```

```

SYNOPSIS
jd := HeisToJD (day, month, year);

```

```

PROCEDURE HeisToJD (day, month : SHORTCARD;
year : INTEGER) : LONGCARD;

```

```

FUNCTION
Returns the JD for a Heis date.

```

```

INPUTS
day      - day of the date to convert
month    - month of the date to convert
year     - year of the date to convert

```

```

RESULT
jd - This is the JD

```

```

EXAMPLE
...
jd := HeisToJD (23, 1, 1994);
...

```

```

NOTES
It is better to use this function only from -7 to 3268!

```

```

BUGS
unknown.

```

```

SEE ALSO

```

```

JulianToJD ()
,
GregorianToJD ()
,
HSYearToJD ()
,
HYearToScaliger ()
,
HeisDayDiff ()

```

1.29 Date/HeisWeek

```

NAME
HeisWeek -- Gets the weeknumber of a specified date. (V33)

SYNOPSIS
weeknr := HeisWeek(day,month,year);

PROCEDURE HeisWeek(day,month : SHORTCARD;
    year : INTEGER) : SHORTCARD;

FUNCTION
HeisWeek gets the weeknumber for a specified date.

INPUTS
day - day of the date
month - month of the date
year - year of the date

RESULT
week - This is the number of the week the specified date lies in.
    If the first day in a new year is a Friday, Saturday or
    Sunday, this would be the last week of the last year!
    If the 29.12. is a Monday, the 30.12. is a Monday or a Tuesday,
    the 31.12. is a Monday, Tuesday or a Wednesday this is the
    first week of the next year!

EXAMPLE
...
weeknr := HeisWeek(4,10,1582);
...

NOTES
It is is better only to use this function for years from 0 to 8000!

BUGS
For years < 0 errors could occur.

SEE ALSO
    JulianWeek()
    ,
    GregorianWeek()
    ,
    HeisDayDiff()
    ,
    HeisDaySmaller()
    ,
    HeisWeekday()
```

1.30 Date/HeisWeekday

```

NAME
HeisWeekday -- Gets the weekday of a specified date. (V33)
```

SYNOPSIS

```
weekday := HeisWeekday(day,month,year);
```

```
PROCEDURE HeisWeekday(day,month : SHORTCARD;  
    year : INTEGER) : Weekday;
```

FUNCTION

HeisWeekday gets the weekday for a specified date.

INPUTS

day - day of the date
month - month of the date
year - year of the date

RESULT

weekday - This result is of type:
Weekdays = (dayerr,Monday,Tuesday,Wednesday,Thursday,Friday,
Saturday,Sunday);
dayerr will show you, that an error occurs!

EXAMPLE

```
...  
weekday := HeisWeekday(22,1,1994);  
IF weekday = dayerr THEN  
...  
END;  
...
```

NOTES

It is better only to use this function for years from -7 to 8000!
In this version dayerr will only occur for the 10 lost days :)

BUGS

It is not possible to use year < 0 (see
JulianWeekday()
for more).

SEE ALSO

```
JulianWeekday()  
,  
GregorianWeekday()  
,  
HeisDaySmaller()  
,  
HeisLeapYear()  
,  
HeisDayDiff()
```

1.31 Date/HeisYearDays

NAME
HeisYearDays -- Gives back the number of days in a year. (V33)

SYNOPSIS
days := HeisYearDays(year);

PROCEDURE HeisYearDays(year : INTEGER) : CARDINAL;

FUNCTION
HeisYearDays gives you back the number of days in a specified year.

INPUTS
year - The year in which to count the days.

RESULT
days - The number of days the year uses.

EXAMPLE
...
days := HeisYearDays(1994);
WriteString("Days of 1994 : ");
WriteCard(days,3); WriteLn;
...

NOTES
It is better only to use this function for years from -7 to 8000!

BUGS
No known bugs.

SEE ALSO

HeisMonthDays()
,
JulianYearDays()
,
GregorianYearDays()

1.32 Date/HSYearToJD

NAME
HSYearToJD -- Calcs the JD from a Scaliger year. (V33)

SYNOPSIS
jd := HSYearToJD(syear);

PROCEDURE HSYearToJD(syear : CARDINAL) : LONGCARD;

FUNCTION
Returns the Julianday of a Scaliger year.

INPUTS
syear - Scaliger year

RESULT
jd - The Julianday

EXAMPLE
...
jd := HYearToJD(6700);
...

NOTES
It is better to use this function only from 4707 to 7981!
In this version only
 GYearToJD()
 is called, because the
Scaliger period is only valid to 3268

BUGS
unknown.

SEE ALSO

 JYearToJD()
 ,
 GYearToJD()

1.33 Date/HYearToScaliger

NAME
HYearToScaliger -- Returns the year as Scaliger year. (V33)

SYNOPSIS
syear := HYearToScaliger(year);

PROCEDURE HYearToScaliger(year : INTEGER) : CARDINAL;

FUNCTION
Returns the Scaliger year.

INPUTS
year - Heis year

RESULT
syear - The Scaliger year

EXAMPLE
...
syear := HYearToScaliger(1994);
...

NOTES
It is better to use this function only from -7 to 8000!

BUGS
The Scaliger period is defined to 3268!!!.

SEE ALSO

```
JYearToScaliger()  
,GYearToScaliger()
```

1.34 Date/JDtoMJD

NAME

JDtoMJD -- Switches from JD to MJD. (V33)

SYNOPSIS

```
mjd := JDtoMJD(jd);
```

```
PROCEDURE JDtoMJD(jd : LONGCARD) : LONGCARD;
```

FUNCTION

Returns the Modified Julianday of a Julianday.

INPUTS

jd - Julianday

RESULT

mjd - The Modified Julianday

EXAMPLE

```
...  
mjd := JDtoMJD(2449354);  
...
```

NOTES

none

BUGS

Only use this function for $jd > 2400001$, because mjd is only defined for this, otherwise system will crash!

SEE ALSO

```
MJDtoJD()
```

1.35 Date/JDToTime

NAME

JDToTime -- Returns the real time for a JD time. (V33)

SYNOPSIS

```
JDToTime(jd, rhour, rmin, rsec);
```

```
PROCEDURE JDToTime(jd : REAL; VAR rhour, rmin, rsec : SHORTCARD);
```

```
FUNCTION
Returns the real time for a JD time.

INPUTS
jd - JD time

RESULT
rhour - 24 hour real time
rmin  - real minutes
rsec  - real seconds

EXAMPLE
...
JDToTime(0.76543, rhour, rmin, rsec);
...

NOTES
none.

BUGS
If jd is > 0 (including days) there will be occur arithmetic bugs!

SEE ALSO

        TimeToJD()
```

1.36 Date/JSYearToJD

```
NAME
JSYearToJD -- Calcs the JD from a Scaliger year. (V33)

SYNOPSIS
jd := JSYearToJD(syear);

PROCEDURE JSYearToJD(syear : CARDINAL) : LONGCARD;

FUNCTION
Returns the Julianday of a Scaliger year.

INPUTS
syear      - Scaliger year

RESULT
jd - The Julianday

EXAMPLE
...
jd := JSYearToJD(4800);
...

NOTES
It is better to use this function only from 4707 to 6295!
```

BUGS
unknown.

SEE ALSO

```
GSYearToJD()
'
HSYearToJD()
```

1.37 Date/JulianDayDiff

NAME

JulianDayDiff -- Calculates the days between 2 dates. (V33)

SYNOPSIS

```
days := JulianDayDiff(day1,month1,year1,day2,month2,year2);
```

```
PROCEDURE JulianDayDiff(day1,month1 : SHORTCARD; year1 : INTEGER;
    day2,month2 : SHORTCARD; year2 : INTEGER) : LONGINT;
```

FUNCTION

JulianDayDiff gives you back the number of days between two specified dates.

INPUTS

```
day1    - day of the first date
month1  - month of the first date
year1   - year of the first date
day2    - day of the second date
month2  - month of the second month
year2   - year of the second date
```

RESULT

days - The number of days between the two dates
(positive if date1 <= date2).

EXAMPLE

```
...
days := JulianDayDiff(18,9,1970,22,1,1994);
WriteString("Age of Kai Hofmann in days : ");
WriteInt(days,10); WriteLn;
...
```

NOTES

It is better only to use this function for years from -7 to 1582!

BUGS

No known bugs.

SEE ALSO

```
GregorianDayDiff()
'
HeisDayDiff()
```



```
,  
JulianMonthDays()  
,  
JulianYearDays()
```

1.38 Date/JulianDayGreater

NAME

JulianDayGreater -- Checks if date1 is greater than date2. (V33)

SYNOPSIS

```
greater := JulianDayGreater(day1,month1,year1,day2,month2,year2);
```

```
PROCEDURE JulianDayGreater(day1,month1 : SHORTCARD; year1 : INTEGER;  
    day2,month2 : SHORTCARD; year2 : INTEGER) : BOOLEAN;
```

FUNCTION

JulianDayGreater test if date1 is greater than date2.

INPUTS

```
day1    - day of the first date  
month1  - month of the first date  
year1   - year of the first date  
day2    - day of the second date  
month2  - month of the second month  
year2   - year of the second date
```

RESULT

greater - This is TRUE is date1 > date2 otherwise it's FALSE.

EXAMPLE

```
...  
IF JulianDayGreater(18,9,1970,22,1,1994) THEN  
    WriteString(">"); WriteLn;  
ELSE  
    WriteString("<="); WriteLn;  
END;  
...
```

NOTES

It is better only to use this function for years from -7 to 1582!

BUGS

No known bugs.

SEE ALSO

```
GregorianDayGreater()  
,  
HeisDayGreater()
```

1.39 Date/JulianDaysAfterWeekday

NAME

JulianDaysAfterWeekday -- Returns the diff to the wday after. (V33)

SYNOPSIS

```
days := JulianDaysAfterWeekday(day,month,year,weekday);
```

```
PROCEDURE JulianDaysAfterWeekday(day,month : SHORTCARD;
    year : INTEGER; weekday : Weekdays) : SHORTCARD;
```

FUNCTION

Returns the days to the weekday after the specified date.
So if you specify the 22.1.1994 (Saturday) and Thursday
you get back 5!
If you specify the 22.1.1994 and Saturday you get back 0
(the same day)!

INPUTS

```
day      - day of the date
month    - month of the date
year     - year of the date
weekday  - weekday to search for building difference
```

RESULT

days - The days after to the searched weekday.

EXAMPLE

```
...
days := JulianDaysAfterWeekday(22,1,1994,Thursday);
...
```

NOTES

It is better to use this function only from -7 to 1582!

BUGS

See JulianWeekday()!

SEE ALSO

```
GregorianDaysAfterWeekday()
,
HeisDaysAfterWeekday()
,
JulianWeekday()
```

1.40 Date/JulianDaysBeforeWeekday

NAME

JulianDaysBeforeWeekday -- Returns the diff to the wday before. (V33)

SYNOPSIS

```
days := JulianDaysBeforeWeekday(day,month,year,weekday);
```

```
PROCEDURE JulianDaysBeforeWeekday(day,month : SHORTCARD;
    year : INTEGER; weekday : Weekdays) : SHORTCARD;
```

FUNCTION

Returns the days to the weekday before the specified date.
 So if you specify the 22.1.1994 (Saturday) and Thursday
 you get back 2!
 If you specify the 22.1.1994 and Saturday you get back 0
 (the same day)!

INPUTS

day - day of the date
 month - month of the date
 year - year of the date
 weekday - weekday to search for building difference

RESULT

days - The days back to the searched weekday (0-6)
 If you get back 8 an error occurs!

EXAMPLE

```
...
days := JulianDaysBeforeWeekday(22,1,1994,Thursday);
...
```

NOTES

It is better to use this function only from -7 to 1582!

BUGS

See JulianWeekday()!

SEE ALSO

```
GregorianDaysBeforeWeekday()
,
HeisDaysBeforeWeekday()
,
JulianWeekday()
```

1.41 Date/JulianDaySmaller

NAME

JulianDaySmaller -- Checks if date1 is smaller than date2. (V33)

SYNOPSIS

```
smaller := JulianDaySmaller(day1,month1,year1,day2,month2,year2);
```

```
PROCEDURE JulianDaySmaller(day1,month1 : SHORTCARD; year1 : INTEGER;
    day2,month2 : SHORTCARD; year2 : INTEGER) : BOOLEAN;
```

FUNCTION

JulianDaySmaller test if date1 is smaller than date2.

```

INPUTS
day1    - day of the first date
month1  - month of the first date
year1   - year of the first date
day2    - day of the second date
month2  - month of the second month
year2   - year of the second date

RESULT
smaller - This is TRUE is date1 < date2 otherwise it's FALSE.

```

```

EXAMPLE
...
IF JulianDaySmaller(18,9,1970,22,1,1994) THEN
  WriteString("<"); WriteLn;
ELSE
  WriteString(">="); WriteLn;
END;
...

```

```

NOTES
It is better only to use this function for years from -7 to 1582!

```

```

BUGS
No known bugs.

```

SEE ALSO

```

GregorianDaySmaller()
,
HeisDaySmaller()

```

1.42 Date/JulianDiffDate

```

NAME
JulianDiffDate -- Returns the date for a diff to another date. (V33)

```

```

SYNOPSIS
JulianDiffDate(day,month,year,diffdays,dday,dmonth,dyear);

```

```

PROCEDURE JulianDiffDate(day,month : SHORTCARD; year,days : INTEGER;
  VAR dday,dmonth : SHORTCARD; VAR dyear : INTEGER);

```

```

FUNCTION
Returns the date wich lies diffdays before/after the specified date.

```

```

INPUTS
day      - day of the date
month    - month of the date
year     - year of the date
diffdays - difference to the date in days

```

```

RESULT
dday     - Destination day

```

dmonth - Destination month
 dyear - Destination year

EXAMPLE

```
...
JulianDiffDate(23,1,1994,7,dday,dmonth,dyear);
...
```

NOTES

It is better to use this function only from -7 to 1582!

BUGS

unknown.

SEE ALSO

```
GregorianDiffDate()
,
HeisDiffDate()
,
JulianDayDiff()
```

1.43 Date/JulianLeapYear

NAME

JulianLeapYear -- Checks if a year is a leap year. (V33)

SYNOPSIS

```
leapyear := JulianLeapYear(year);
```

```
PROCEDURE JulianLeapYear(year : INTEGER) : BOOLEAN;
```

FUNCTION

JulianLeapYear checks if a year is a leap year in the julian calendar
 For years after Chr. it checks if the year is devideable by 4.
 For years before Chr. a leap year must have a modulo 4 value of 1

INPUTS

year - The year which should be checked (from -32768 to 32767)
 I think only values from -7 to 1582 are valid, because of
 the variant that was done on -8 by Augustus and other things!

RESULT

leapyear - TRUE if the year is a leap year, otherwise false.

EXAMPLE

```
...
IF JulianLeapYear(1994) THEN
  WriteString("leap year!");
ELSE
  WriteString("no leap year!");
END;
WriteLn;
...
```

NOTES

A year is 365.25 days long!

Use this function only for values from -7 to 1582!

BUGS

No known bugs.

SEE ALSO

```
GregorianLeapYear()
,
HeisLeapYear()
```

1.44 Date/JulianMonthDays

NAME

JulianMonthDays -- Gives back the number of days of a month. (V33)

SYNOPSIS

```
days := JulianMonthDays(month,year);
```

```
PROCEDURE JulianMonthDays(month : SHORTCARD;
```

```
year : INTEGER) : SHORTCARD;
```

FUNCTION

JulianMonthDays gives you back the number of days a month in a specified year has.

INPUTS

month - The month from wich you want to get the number of days.

year - The year in which the month is.

RESULT

days - The number of days the month uses, or 0 if you use a wrong month.

EXAMPLE

```
...
days := JulianMonthDays(1,1994);
WriteString("Days of January 1994 : ");
WriteCard(days,2); WriteLn;
...
```

NOTES

It is better only to use this function for years from -7 to 09.1582!

BUGS

No known bugs.

SEE ALSO

```
JulianLeapYear()
,
```

```
GregorianMonthDays()  
,  
HeisMonthDays()
```

1.45 Date/JulianToJD

NAME

JulianToJD -- Returns the JD for a date. (V33)

SYNOPSIS

```
jd := JulianToJD(day,month,year);
```

```
PROCEDURE JulianToJD(day,month : SHORTCARD;  
    year : INTEGER) : LONGCARD;
```

FUNCTION

Returns the JD for a Julian date.

INPUTS

```
day      - day of the date to convert  
month    - month of the date to convert  
year     - year of the date to convert
```

RESULT

jd - This is the JD

EXAMPLE

```
...  
jd := JulianToJD(23,1,1994);  
...
```

NOTES

It is better to use this function only from -7 to 1582!

BUGS

unknown.

SEE ALSO

```
GregorianToJD()  
,  
HeisToJD()  
,  
JSYearToJD()  
,  
JYearToScaliger()  
,  
JulianDayDiff()
```

1.46 Date/JulianWeek

NAME

JulianWeek -- Gets the weeknumber of a specified date. (V33)

SYNOPSIS

```
weeknr := JulianWeek(day,month,year);
```

```
PROCEDURE JulianWeek(day,month : SHORTCARD;  
    year : INTEGER) : SHORTCARD;
```

FUNCTION

JulianWeek gets the weeknumber for a specified date.

INPUTS

day - day of the date
month - month of the date
year - year of the date

RESULT

week - This is the number of the week the specified date lies in.
If the first day in a new year is a Friday, Saturday or Sunday, this would be the last week of the last year!
If the 29.12. is a Monday, the 30.12. is a Monday or a Tuesday, the 31.12. is a Monday, Tuesday or a Wednesday this is the first week of the next year!

EXAMPLE

```
...  
weeknr := JulianWeek(4,10,1582);  
...
```

NOTES

It is better only to use this function for years from 0 to 1582!

BUGS

For years < 0 errors could occur.

SEE ALSO

```
GregorianWeek()  
,  
HeisWeek()  
,  
JulianWeekday()  
,  
JulianDaySmaller()  
,  
JulianDayDiff()
```

1.47 Date/JulianWeekday


```

NAME
JulianWeekday -- Gets the weekday of a specified date. (V33)

SYNOPSIS
weekday := JulianWeekday(day,month,year);

PROCEDURE JulianWeekday(day,month : SHORTCARD;
    year : INTEGER) : Weekday;

FUNCTION
JulianWeekday gets the weekday for a specified date.

INPUTS
day - day of the date
month - month of the date
year - year of the date

RESULT
weekday - This result is of type:
    Weekdays := (dayerr,Monday,Tuesday,Wednesday,Thursday,Friday,
        Saturday,Sunday);
    dayerr will show you, that an error occurs!

EXAMPLE
...
weekday := JulianWeekday(4,10,1582);
IF weekday = dayerr THEN
...
END;
...

NOTES
It is better only to use this function for years from 0 to 1582!
In this version no dayerr will occur!

BUGS
For years < 0 errors could occur, or systemcrashes(?).

SEE ALSO

```

```

GregorianWeekday()
,
HeisWeekday()

```

1.48 Date/JulianYearDays

```

NAME
JulianYearDays -- Gives back the number of days in a year. (V33)

SYNOPSIS
days := JulianYearDays(year);

PROCEDURE JulianYearDays(year : INTEGER) : CARDINAL;

```

FUNCTION
 JulianYearDays gives you back the number of days in
 a specified year.

INPUTS
 year - The year in which to count the days.

RESULT
 days - The number of days the year uses.

EXAMPLE
 ...
 days := JulianYearDays(1994);
 WriteString("Days of 1994 : ");
 WriteCard(days,3); WriteLn;
 ...

NOTES
 It is better only to use this function for years from -7 to 1581!

BUGS
 No known bugs.

SEE ALSO

JulianMonthDays()
 ,
 GregorianYearDays()
 ,
 HeisYearDays()

1.49 Date/JYearToScaliger

NAME
 JYearToScaliger -- Returns the year as Scaliger year. (V33)

SYNOPSIS
 syear := JYearToScaliger(year);

PROCEDURE JYearToScaliger(year : INTEGER) : CARDINAL;

FUNCTION
 Returns the Scaliger year.

INPUTS
 year - Julian year

RESULT
 syear - The Scaliger year

EXAMPLE
 ...
 syear := JYearToScaliger(1582);

...

NOTES

It is better to use this function only from -7 to 1582!

BUGS

unknown.

SEE ALSO

```
GYearToScaliger()
',
HYearToScaliger()
```

1.50 Date/LMT

NAME

LMT -- Calculates your local time in your timezone (V33)

SYNOPSIS

```
secs := LMT(secs,meridian,pos);
```

```
PROCEDURE LMT(secs : LONGCARD; meridiandegree,
               posdegree : REAL) : LONGINT;
```

FUNCTION

Calculates your Local Mean Time of you place!

INPUTS

```
secs      - Seconds of the running day (hours*3600+min*60+sec)
meridian  - Degrees of your timezone-meridian
pos       - Degrees of your place
```

RESULT

secs - Local seconds of the running day

EXAMPLE

...

```
secs := LMT(76080,15.0,8.923055556);
```

...

NOTES

none

BUGS

No errorcheck, if you put in valid degrees (-180 to +180)

SEE ALSO

1.51 Date/MJDtoJD

```
NAME
MJDtoJD -- Switches from MJD to JD. (V33)

SYNOPSIS
jd := MJDtoJD(mjd);

PROCEDURE MJDtoJD(mjd : LONGCARD) : LONGCARD;

FUNCTION
Returns the Julianday of a Modified Julianday.

INPUTS
mjd - Modified Julianday

RESULT
jd - The Julianday

EXAMPLE
...
jd := JDtoMJD(49353);
...

NOTES
none

BUGS
unknown.

SEE ALSO
MJDtoJD()
```

1.52 Date/ScaligerYearToG

```
NAME
ScaligerYearToG -- Returns the Scaliger year as Gregorian year. (V33)

SYNOPSIS
year := ScaligerYearToG(syear);

PROCEDURE ScaligerYearToG(syear : CARDINAL) : INTEGER;

FUNCTION
Returns the Gregorian year of a Scaliger year.

INPUTS
syear - Scaliger year

RESULT
year - The Gregorian year

EXAMPLE
...
year := ScaligerYearToG(6400);
...
```

NOTES

It is better to use this function only from 4707 to 7981!

BUGS

unknown.

SEE ALSO

```
ScaligerYearToJ()  
,  
ScaligerYearToH()
```

1.53 Date/ScaligerYearToH

NAME

ScaligerYearToH -- Returns the Scaliger year as Heis year. (V33)

SYNOPSIS

```
year := ScaligerYearToH(syear);
```

```
PROCEDURE ScaligerYearToH(syear : CARDINAL) : INTEGER;
```

FUNCTION

Returns the Heis year of a Scaliger year.

INPUTS

syear - Scaliger year

RESULT

year - The Heis year

EXAMPLE

```
...  
year := ScaligerYearToH(7000);  
...
```

NOTES

It is better to use this function only from 4707 to 7981!

BUGS

unknown.

SEE ALSO

```
ScaligerYearToJ()  
,  
ScaligerYearToG()
```

1.54 Date/ScaligerYearToJ

NAME
ScaligerYearToJ -- Returns the Scaliger year as Julian year. (V33)

SYNOPSIS
year := ScaligerYearToJ(syear);

PROCEDURE ScaligerYearToJ(syear : CARDINAL) : INTEGER;

FUNCTION
Returns the Julian year of a Scaliger year.

INPUTS
syear - Scaliger year

RESULT
year - The Julian year

EXAMPLE
...
year := ScaligerYearToJ(4800);
...

NOTES
It is better to use this function only from 4707 to 6295!

BUGS
unknown.

SEE ALSO

ScaligerYearToG()
,
ScaligerYearToH()

1.55 Date/SecToTime

NAME
SecToTime -- Returns the time from seconds (V33)

SYNOPSIS
SecToTime(secs, hour, min, sec);

PROCEDURE SecToTime(secs : LONGCARD; VAR hour, min, sec : SHORTCARD);

FUNCTION
Gives you back the time from the specified seconds

INPUTS
secs - Time in seconds

RESULT
hour - hours (0-23)
min - minutes (0-59)

sec - seconds (0-59)

EXAMPLE

```
...  
SecToTime(76860, hour, min, sec);  
...
```

NOTES

Don't forget to convert 24h time to AM/PM time if needed!

BUGS

No errorcheck, if you use a valid time

SEE ALSO

TimeToSec()

1.56 Date/TimeToJD

NAME

TimeToJD -- Returns the JD for a time. (V33)

SYNOPSIS

```
jd := TimeToJD(hour, min, sec);
```

```
PROCEDURE TimeToJD(hour, min, sec : SHORTCARD) : REAL;
```

FUNCTION

Returns the JD for a specified time.

INPUTS

hour - hour of the time to convert
min - minute of the time to convert
sec - sec. of the time to convert

RESULT

jd - This is the JD time

EXAMPLE

```
...  
jd := TimeToJD(16, 33, 0);  
...
```

NOTES

none

BUGS

There is no check, if the specified time is a valid time!

SEE ALSO

JDTToTime()

1.57 Date/TimeToSec

NAME

TimeToSec -- Returns the time in seconds (V33)

SYNOPSIS

```
secs := TimeToSec(hour,min,sec);
```

```
PROCEDURE TimeToSec(hour,min,sec : SHORTCARD) : LONGCARD;
```

FUNCTION

Gives you back the time in seconds

INPUTS

```
hour - hours you want (0-23)
min  - minutes you want (0-59)
sec  - seconds you want (0-59)
```

RESULT

secs - Time in seconds

EXAMPLE

```
...
secs := TimeToSec(21,15,00);
...
```

NOTES

Don't forget to convert AM/PM time to 24h time!

BUGS

No errorcheck, if you use a valid time

SEE ALSO

SecToTime()

1.58 Date/TimeZoneFactor

NAME

TimeZoneFactor -- Returns the value you have to add to GMT time (V33)

SYNOPSIS

```
addhours := TimeZoneFactor(degrees);
```

```
PROCEDURE TimeZoneFactor(degree : SHORTINT) : SHORTINT;
```

FUNCTION

This gives you the hours you have to add to GMT time, specified on the fact, that a timezone is 15 degrees and that GMT is centered on 0 degrees!

INPUTS

```
degrees - Position of timezone you live in (from -180 to +180)
```

RESULT

addhours - Time to add to GMT time to get your locale zone time
(-12 to +12)

EXAMPLE

```
...  
addhours := TimeZoneFactor(-8);  
...
```

NOTES

none

BUGS

No errorcheck, if you put in valid degrees (-180 to +180).
Only full degrees are supportet, keep sure that you
round in the right way for 0.x degree places
I am not sure about the correct +/- behaviour!!!

SEE ALSO