

guienvsupport

COLLABORATORS

	<i>TITLE :</i> guienvsupport		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		March 24, 2022	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	guienvsupport	1
1.1	GUIEnvironment/GUIEnvironment Support Module Guide	1
1.2	Screen Support	1
1.3	Gadget Support	2
1.4	Font Support	2
1.5	rsc	2

Chapter 1

guienvsupport

1.1 GUIEnvironment/GUIEnvironment Support Module Guide

GUIEnvironment

Support Module Guide

```
=====
© 1994   Carsten Ziegeler
          Augustin-Wibbelt-Str.7
          D-33106 Paderborn
          Germany
=====
```

The GUIEnvironment support module simplifies some handling methods:

Screen support

Gadget support

Font support

1.2 Screen Support

GUIEnvSupport exports some predefined display IDs:

```
GES_HiresPalID, GES_HiresID, GES_LoresPalID, GES_LoresID.
```

Using this instead of the ones defined in graphics, often makes importing graphics needless.

1.3 Gadget Support

GUIEnvSupport offers the GADDESC and the GADOBJS makros which calculate the tag value for the belonging gadget description tags !

The GEHUpdateEntryGadgetAHook function is a callback hook which can be used for gadtools entry text gadgets (STRING_KIND, INTEGER_KIND). If you set the up function to this hook (using the GEG_UpAHook tag), everytime a IDCMP_GADGETUP message for this gadget arrives, the belonging variable will get the new value of the gadget !

(But only of course if notification was set for this gadget !)

1.4 Font Support

The TopazAttr() function returns a pointer to an initialized TextAttr structure for the topaz 8 font !

1.5 rcs

\$RCSfile: GUIEnvSupport.guide \$

\$Revision: 1.5 \$

\$Date: 1994/11/03 15:51:36 \$

GUIEnvironment Support Module Guide

Copyright © 1994, Carsten Ziegeler

Augustin-Wibbelt-Str.7, 33106 Paderborn, Germany
